Hung Ta / PRODUCT CATALOGUE

HT-2101

Electro-Hydraulic Servo Universal Testing Machine

Versatile hydraulic testing for metals, polymers, and construction materials.



Product overview

With wide range of function and application, suitable for research, inspection, and testing in the field of metal, rubber, plastic, leather, cable and wire, textile, fiber, paper, PE, construction materials, electric appliance, petrochemical, transportation, automobile, package, polymer, aerospace and more. FDC55 high strength casting material with driving screws and high stiffness axle materials for strong structure, high stability, and long durability. High accuracy loadcell with accuracy of load reaching ±0.005%, force accuracy reaches ±0.5 class. Standardized jaw holder specification for economic, convenient, and speedy replacement. Multi-purpose application test program for tensile, compression, shear, peeling, and displacement measurement.

Technical specifications

Capacity	300 ~ 2,000 kN
Load Accuracy	Class 1 ±1% (optional Class 0.5 ±0.5%)
Force Resolution	1/200,000 (Hung Ta Interface Card)
Drive System	Electro-hydraulic servo
Tests	Tensile, compression, bending, shear, peeling
Loading Speed	=100 max. (60 Hz)
Crosshead Speed	150 ~ 300 mm/min
Optional	Bending fixture, compression, extensometer, wire-rope jig, furnace

Typical applications

Metal manufacturers / Construction materials / R&D laboratories / Automotive / Petrochemical

Referenced standards

ASTM E4 / ASTM E8-04 / ISO 7500-1-2004 / ISO 6892-1 / GB/T 228-2010 / DIN 5122 / JIS B7721

Configuration & quotation

Send the specimen material and dimensions, required force range, test method and factory location. Confirm the supplied machine, fixtures and accessories in the quotation.

Specifications are reference values for configuration review. Contact Hung Ta Instrument for the current supplied configuration.