

Functional Programming

Lecture 14: Foldable and Traversable

Twan van Laarhoven

20 December 2021

Outline

- Foldable containers
- Traversable containers
- Ad hoc traversals
- Lenses

Foldable

Containers - again

What is a (finite) container?

- A container holds some number of 'values'
- It supports `fmap` (Functor)



Containers - again

What is a (finite) container?

- A container holds some number of 'values'
- It supports `fmap` (Functor)
- We can `fold` over the values in the container



What is a fold?

Left and right folds

`foldr` :: (a → b → b) → b → [a] → b

`foldl` :: (b → a → b) → b → [a] → b

For lists: `foldr` matches structure.

`foldr` (\otimes) z (1 : (2 : (3 : []))) = (1 \otimes (2 \otimes (3 \otimes z)))



```
class Monoid m where
  mempty  :: m
  (<math>\langle \diamond \rangle</math>) :: m → m → m
```

What is a fold?

Left and right folds

`foldr` :: (a → b → b) → b → [a] → b

`foldl` :: (b → a → b) → b → [a] → b

For lists: `foldr` matches structure.

`foldr` (\otimes) z (1 : (2 : (3 : []))) = (1 \otimes (2 \otimes (3 \otimes z)))

Tree structured folds

`fold` :: (Monoid m) ⇒ [m] → m

Often combined with a map

`foldMap` :: (Monoid m) ⇒ (a → m) → [a] → m

```
class Monoid m where
  mempty :: m
  (<)    :: m -> m -> m
```

fold/foldMap for lists

Collapsing a list of values into a single value:

```
fold :: Monoid m => [m] -> m
fold [ ]      = mempty
fold (x : xs) = x < fold xs
```

Is the same as

```
fold = foldr (<) mempty
```

Combining fold with map

```
foldMap :: Monoid m => (a -> m) -> [a] -> m
foldMap f [ ]      = mempty
foldMap f (x : xs) = f x < foldMap f xs
```



foldMap examples

With the `Sum` monoid

```
newtype Sum a = Sum { getSum :: a }  
instance Num a => Monoid (Sum a) where  
    mempty = Sum 0  
    Sum x <+ Sum y = Sum (x + y)
```

We can implement

```
sum :: Num a => [a] -> a  
sum = getSum . foldMap Sum
```

and

```
length :: [a] -> Int  
length = getSum . foldMap (\_ -> Sum 1)
```



Foldable containers

Generalize fold to any container type

```
class Foldable t where
  foldr    :: (a → b → b) → b → t a → b
  foldl    :: (b → a → b) → b → t a → b
  fold     :: Monoid m ⇒ t m → m
  foldMap  :: Monoid m ⇒ (a → m) → t a → m
```

Foldable includes default implementations, defining either `foldr` or `foldMap` is sufficient.



Foldable containers

```
data Tree a = Leaf a | Node (Tree a) (Tree a)
```

```
instance Foldable Tree where
```

```
  foldMap :: Monoid m => (a -> m) -> Tree a -> m
```

```
  foldMap f (Leaf x)    = f x
```

```
  foldMap f (Node l r) = foldMap f l <math>\diamond</math> foldMap f r
```

foldMap follows tree structure:

```
foldMap f (Node (Node (Leaf 1) (Leaf 2)) (Node (Leaf 3) (Leaf 4)))  
    = (f 1 <math>\diamond</math> f 2) <math>\diamond</math> (f 3 <math>\diamond</math> f 4)
```

And is much easier to implement than foldr



Other primitives

What primitives can we define for Foldable containers?

```
toList  :: (Foldable t) => t a -> [a]
null    :: (Foldable t) => t a -> Bool
length  :: (Foldable t) => t a -> Int
elem     :: (Foldable t, Eq a) => a -> t a -> Bool
maximum :: (Foldable t, Ord a) => t a -> a
```

Exercise: define these functions in terms of `foldr` or `foldMap`.



Defining foldMap using foldr and vice-versa

foldMap from foldr

```
foldMap :: Monoid m => (a -> m) -> t a -> m  
foldMap f = foldr (\a m -> f a < m) mempty
```



Defining foldMap using foldr and vice-versa

foldMap from foldr

```
foldMap :: Monoid m => (a -> m) -> t a -> m
foldMap f = foldr (\a m -> f a < m) mempty
```

foldr from foldMap

```
foldr :: (a -> b -> b) -> b -> t a -> b
foldr f e x = appEndo (foldMap (Endo . f) x) e
```



Endo explained

Functions in the same type ($a \rightarrow a$) are a monoid (endomorphisms)

```
newtype Endo a = Endo { appEndo :: a  $\rightarrow$  a }
```

```
instance Monoid (Endo a) where
```

```
  mempty = Endo id
```

```
  Endo f  $\diamond$  Endo g = Endo (f . g)
```

For example

```
  foldr f e [1,2,3]
= (appEndo (foldMap (Endo . f) [1,2,3])) e
= (appEndo (Endo (f 1)  $\diamond$  Endo (f 2)  $\diamond$  Endo (f 3)  $\diamond$  Endo id)) e
= (f 1 . f 2 . f 3 . id) e
= f 1 (f 2 (f 3 e))
```



Traversable containers

Traversable

Mapping a function that may fail over a list

```
traverse :: (a → Maybe b) → [a] → Maybe [b]
traverse f [] = pure []
traverse f (x : xs) = pure (:) <*> f x <*> traverse f xs
```

Generalize to

- any applicative f instead of **Maybe** (seen before as **mapM**).
- any container t instead of list

Gives

```
class (Functor t, Foldable t) ⇒ Traversable t where
  traverse :: Applicative f ⇒ (a → f b) → t a → f (t b)
```



Traversable: examples

Instance for lists:

```
instance Traversable [] where
  traverse :: Applicative f => (a -> f b) -> [a] -> f [b]
  traverse g [ ]      = pure [ ]
  traverse g (x : xs) = pure (:) <*> g x <*> traverse g xs
```

Instance for trees:

```
instance Traversable Tree where
  traverse :: Applicative f => (a -> f b) -> Tree a -> f (Tree b)
  traverse g (Leaf x)    = pure Leaf <*> g x
  traverse g (Node l r) = pure Node <*> traverse g l <*> traverse g r
```



Traverse generalizes mapM

Apply an action to every element of a list

```
askUser :: String → IO Bool
```

```
twoQuestions :: IO [Bool]
```

```
twoQuestions = mapM askUser  
    ["Do you like cake?",  
     "Are you still here?"]
```



Traverse generalizes mapM

Apply an action to every element of a container

```
askUser :: String → IO Bool
```

```
twoQuestions :: IO [Bool]
```

```
twoQuestions = traverse askUser  
              ["Do you like cake?",  
               "Are you still here?"]
```

```
optQuestion :: Maybe String → IO (Maybe Bool)
```

```
optQuestion = traverse askUser
```



Traverse generalizes map

Recall: identity functor

```
newtype Id a = Id { getId :: a }  
instance Functor Id where  
    fmap f (Id x) = Id (f x)  
instance Applicative Id where  
    pure = Id  
    Id f <*> Id x = Id (f x)
```

Then

```
amap :: Traversable f => (a -> b) -> f a -> f b  
amap f = getId . traverse (Id . f)
```

So Traversable containers are Functors



Traverse generalizes fold

The constant functor

```
newtype Const c a = Const { getConst :: c }  
instance Functor (Const c) where  
  fmap _ (Const x) = Const x  
instance Monoid c  $\Rightarrow$  Applicative (Const c) where  
  pure _ = Const mempty  
  Const x <*> Const y = Const (x  $\diamond$  y)
```

Gives

```
afoldMap :: (Traversable f, Monoid m)  $\Rightarrow$  (a  $\rightarrow$  m)  $\rightarrow$  f a  $\rightarrow$  m  
afoldMap f = getConst . traverse (Const . f)
```

So **Traversable** containers are **Foldable**



Ad hoc traversals

Lenses

Ad hoc traversals

Traversable is about visiting all elements in a container

traverse :: (**Traversable** t, **Applicative** f) \Rightarrow (a \rightarrow f a) \rightarrow t a \rightarrow f (t a)

We can also traverse all literals in an expression

lits :: **Applicative** f \Rightarrow (**Integer** \rightarrow f **Integer**) \rightarrow **Expr** \rightarrow f **Expr**

lits f (**Lit** x) = **Lit** <\$> f x

lits f (**Add** x y) = **Add** <\$> **lits** f x <*> **lits** f y

lits f (**Mul** x y) = **Mul** <\$> **lits** f x <*> **lits** f y

Or the first element of a pair

fst' :: **Applicative** f \Rightarrow (a \rightarrow f a) \rightarrow (a,b) \rightarrow f (a,b)

fst' f (x,y) = (\x' \rightarrow (x',y)) <\$> f x



Using ad hoc traversals

Sum of all literals in an expression

```
sumLits :: Expr → Integer  
sumLits = getSum . getConst . lits (Const . Sum)
```

Count number of literals

```
countLits :: Expr → Int  
countLits = getSum . getConst . lits (\_ → Const (Sum 1))
```

```
>>> sumLits (Add (Lit 1) (Mul (Lit 3) (Lit 3)))
```

```
7
```

```
>>> countLits (Add (Lit 1) (Mul (Lit 3) (Lit 3)))
```

```
3
```

Look familiar? Compare `fold` from `traverse`; `sum` and `length` from `fold`.



Using ad hoc traversals as folds

Let's give this a name

```
type Traversal s a = forall f. Applicative f => (a -> f a) -> (s -> f s)
```

```
lits :: Traversal Expr Integer
```

```
lits = — as before
```

```
foldMapOf :: Monoid m => Traversal s a -> (a -> m) -> (s -> m)
```

```
foldMapOf trav f = getConst . trav (Const . f)
```

```
lengthOf :: Traversal s a -> s -> Int
```

```
lengthOf trav = getSum . foldMapOf trav (\_ -> Sum 1)
```

Now

```
length = lengthOf traverse
```

```
countLits = lengthOf lits
```

Using ad hoc traversals as maps

Also

```
type Traversal s a = forall f. Applicative f => (a -> f a) -> (s -> f s)
mapOf :: Traversal s a -> (a -> a) -> (s -> s)
mapOf trav f = getId . trav (Id . f)  — sometimes called over
```

Now

```
fmap = mapOf traverse
```

Example

```
>>> mapOf lits (*2) (Add (Lit 1) (Mul (Lit 3) (Lit 3)))
(Add (Lit 2) (Mul (Lit 6) (Lit 6)))
```



More traversals

Traversing all items in a container

```
each :: Traversable t => Traversal (t a) a  
each = traverse
```

Traversing a single item in a list

```
at :: Applicative f => Int -> (a -> f a) -> [a] -> f [a]  
at 0 f (x:xs) = (:xs) <$> f x  
at n f (x:xs) = (x:) <$> at (n-1) xs  
at _ f _ = error "index out of range"
```



More traversals – examples

```
>>> foldMapOf (at 2) return "hello"  
"1"
```

```
>>> mapOf each toUpper "hello"  
"HELLO"
```

```
>>> mapOf (at 2) toUpper "hello"  
"heLlo"
```



Odd and even

```
>>> mapOf evens toUpper "hello world"
"HeLlO WoRlD"
```

Where

— *Traverse the even positions*

`evens :: Applicative f => (a -> f a) -> [a] -> f [a]` — *Traversal [a] a*

`evens _ [] = pure []`

`evens f (x:xs) = (:) <$> f x <*> odds f xs`

— *Traverse the odd positions*

`odds :: Applicative f => (a -> f a) -> [a] -> f [a]`

`odds _ [] = pure []`

`odds f (x:xs) = (x:) <$> evens f xs` — *don't apply f to x*



Lenses

If the function is used exactly once, then Functor is enough

$\text{fst}' :: \text{Functor } f \Rightarrow (a_1 \rightarrow f\ a_1) \rightarrow (a_1, b) \rightarrow f\ (a_2, b)$
 $\text{fst}'\ f\ (x_1, y) = (\backslash x_2 \rightarrow (x_2, y)) <\$> f\ x_1$

Such a traversal is called a *lens*.

$\text{type Lens } s\ a = \text{forall } f. \text{Functor } f \Rightarrow (a \rightarrow f\ a) \rightarrow (s \rightarrow f\ s)$

Compare

$\text{type Traversal } s\ a = \text{forall } f. \text{Applicative } f \Rightarrow (a \rightarrow f\ a) \rightarrow (s \rightarrow f\ s)$



Viewing through a lens

`Const` c is only an Applicative functor if c is a `Monoid`.

`foldOf` $:: \text{Monoid } m \Rightarrow \text{Traversal } s \ m \rightarrow s \rightarrow m$
`foldOf` = `foldMapOf` `id`

But `Const` c is always a *functor* even if c is not a `Monoid`, so

`view` $:: \text{Lens } s \ a \rightarrow s \rightarrow a$
`view` `lens` = `getConst` . `lens` `Const`

Also

`modify` $:: \text{Lens } s \ a \rightarrow (a \rightarrow a) \rightarrow s \rightarrow s$
`modify` = `mapOf`
`set` $:: \text{Lens } s \ a \rightarrow a \rightarrow s \rightarrow s$
`set` `lens` x = `modify` (`const` x)



Lens examples

```
>>> view (at 2) [1,2,3,4]
```

```
3
```

```
>>> modify (at 2) negate [1,2,3,4]  
[1,2,-3,4]
```

```
>>> view fst ' (123,"hello")  
123
```

```
>>> set fst ' 456 (123,"hello")  
(456,"hello")
```

Composing traversals

Visit the even elements, and for each of those visit the third element

```
evens . at 2 :: Traversal [[a]] a
```

So

```
>>> foldMapOf (evens . at 2) return ["hello", "world", "where", "I", "live"]  
"lev"
```

```
>>> mapOf (each . each) (+1) [Just 2, Nothing, Just 3]  
[Just 3, Nothing, Just 4]
```

Composing two lenses gives a lens

```
>>> view (fst' . snd') (('a', 3), "thing")  
3
```



Conditional traversal

Visit a value if a condition holds

`when` :: (a → Bool) → Traversal a a

`when` pred f x

| pred x = f x

| otherwise = pure x

```
>>> mapOf (each . when (> 0)) succ [1,3,-4,2,0]  
[2,4,-4,3,0]
```



Traversing children

Traverse direct children of an expression

```
children :: Traversal Expr Expr  
children f (Lit x)   = pure (Lit x)  
children f (Add x y) = Add <$> f x <*> f y  
children f (Mul x y) = Mul <$> f x <*> f y
```

Use as a default


```
flipMul :: Expr → Expr  
flipMul (Mul x y) = Mul (flipMul y) (flipMul x)  
flipMul expr      = mapOf children flipMul expr
```

Flips arguments to all **Mul** constructors



Take away

The container-like class hierarchy



Summary

- Foldable generalizes folds to other containers
- Traversable generalizes `mapM`.
- Ad-hoc traversals can view and modify parts of a data structure

