



**Verified Carbon
Standard**

INSTALLATION OF HIGH EFFICIENCY WOOD BURNING COOKSTOVES IN INDONESIA 1

Document Prepared by

C-Quest Capital Stoves Asia Limited

Project Title	Installation of high efficiency wood burning cookstoves in Indonesia 1
Version	02
Date of Issue	16-August-2022
Prepared By	C-Quest Capital Stoves Asia Limited
Contact	Address: C-Quest Capital Stoves Asia Limited, Brumby Centre, Lot 42, Jalan Muhibbah, 87000 Labuan F. T., Malaysia, Telephone: +6 087 593828 Email: cqc-operations@cquestcapital.com Website: www.cquestcapital.com

CONTENTS

1	PROJECT DETAILS.....	4
1.1	Summary Description of the Project	4
1.2	Sectoral Scope and Project Type	4
1.3	Project Eligibility	5
1.4	Project Design	5
1.5	Project Proponent	6
1.6	Other Entities Involved in the Project	7
1.7	Ownership.....	7
1.8	Project Start Date	7
1.9	Project Crediting Period	7
1.10	Project Scale and Estimated GHG Emission Reductions or Removals	7
1.11	Description of the Project Activity	8
1.12	Project Location	10
1.13	Conditions Prior to Project Initiation	11
1.14	Compliance with Laws, Statutes and Other Regulatory Frameworks.....	12
1.15	Participation under Other GHG Programs	12
1.16	Other Forms of Credit.....	12
1.17	Sustainable Development Contributions	12
1.18	Additional Information Relevant to the Project	13
2	SAFEGUARDS	14
2.1	No Net Harm	14
2.2	Local Stakeholder Consultation	14
2.3	Environmental Impact	14
2.4	Public Comments	14
2.5	AFOLU-Specific Safeguards	14
3	APPLICATION OF METHODOLOGY.....	14
3.1	Title and Reference of Methodology	14
3.2	Applicability of Methodology	14
3.3	Project Boundary	16
3.4	Baseline Scenario	18

3.5	Additionality	18
3.6	Methodology Deviations	19
4	QUANTIFICATION OF GHG EMISSION REDUCTIONS AND REMOVALS	19
4.1	Baseline Emissions	19
4.2	Project Emissions	19
4.3	Leakage.....	19
4.4	Net GHG Emission Reductions and Removals	19
5	MONITORING	27
5.1	Data and Parameters Available at Validation	27
5.2	Data and Parameters Monitored.....	29
5.3	Monitoring Plan	33

1 PROJECT DETAILS

1.1 Summary Description of the Project

A summary description of the technologies/ measures to be implemented by the project.

The project status is under development. The project involves distribution of fuel-efficient improved cookstoves (ICS) in Indonesia. The ICS disseminated through this project will replace the baseline cookstoves.

Through this project, the distribution and installation of approximately 500,000 ICS will be undertaken for households in Indonesia. It is intended that under this project two types of single pot portable stove will be distributed, which are SSM S32-X stove and Baldwin stove. Each household will receive up to 2 ICS per household, it could comprise of same or different types of ICS. The ICS will burn wood more efficiently thereby improving thermal transfer to pots, hence saving fuel. Not only will this halt the rapidly progressing deforestation in Indonesia but will also reduce health hazards from indoor smoke pollution and women and children will have to spend less time collecting firewood.

The end user will be informed in advance that the use of ICS generates carbon finance which in turn is used for subsidising the price of ICS and for recovering project implementation costs.

The location of the project.

The project will take place in Indonesia. The details of the project location are provided in Section 1.12.

An explanation of how the project is expected to generate GHG emission reductions or removals.

The ICS will substitute the current cooking practices of using the three stone fired stoves or a conventional device with no improved combustion air supply or flue gas ventilation, that is without a grate or a chimney. The ICS burns wood more efficiently thereby improving thermal transfer to pots, hence saving fuel and lowering greenhouse gas emissions.

A brief description of the scenario existing prior to the implementation of the project.

The baseline scenario is the continued use of three stone fired or a conventional cook stove without a grate or a chimney by the target population burning non-renewable wood fuel to meet similar thermal energy needs in the absence of project activity.

An estimate of annual average and total GHG emission reductions and removals.

The average annual GHG emission reduction from the project is expected to be 3,263,178 t CO₂e. Total GHG emission reduction from the project is expected to be 32,631,780 tCO₂e over the entire crediting period of 10 years.

1.2 Sectoral Scope and Project Type

The project is categorised under type/category as below:

a) **Sectoral scope:** 03 - Energy demand

b) **Type:** II – Energy efficiency improvement projects

The project is a grouped project.

1.3 Project Eligibility

The project involves energy efficient cookstove distribution which falls under the category of efficiency improvements in thermal applications, therefore it is eligible under the scope of VCS Program.

1.4 Project Design

- ☐ The project includes a single location or installation only
- ☐ The project includes multiple locations or project activity instances, but is not being developed as a grouped project
- ☒ The project is a grouped project

Eligibility Criteria

For the inclusion of new project activity instances (each SSM-S32-X Stove or Baldwin Stove), the project proponent shall ensure that it meets the eligibility criteria below.

No.	Criterion	How the new project activity instances to comply
1	Meet the applicability conditions set out in the methodology applied to the project	New project activity instances (each SSM-S32-X Stove or Baldwin Stove) will meet the applicability conditions set out in Section 3.2 where the target of the end-user is household and the ICS deployed is at least 25% of thermal efficiency.
2	Use the technologies or measures specified in the project description.	SSM-S32-X Stoves and Baldwin Stoves to be adopted in the project,
3	Apply the technologies or measures in the same manner as specified in the project description.	SSM-S32-X Stoves and Baldwin Stoves to be adopted in the project and it will replace traditional cookstoves in household
4	Are subject to the baseline scenario determined in the project description for the specified project activity and geographic area.	The new project activity instances (each ICS) will be distributed within Indonesia only and subject to the same baseline scenario determined in Section 3.4.
5	Have characteristics with respect to additionality that are consistent with the initial instances for the specified project activity and geographic area.	All new project activity instances will use the activity method for demonstration of additionality.

		Step 1: Regulatory Surplus There is no mandated government programme or policy in host country of this project ensuring the distribution of new project activity instances. Step 2: Positive List The inclusion of new project activity instances will comply with positive list as it satisfies criterion 1 where it meets all the applicability conditions of the methodology.
6	Where a capacity limit applies to a project activity included in the project, no project activity instance shall exceed such limit. Further, no single cluster of project activity instances shall exceed the capacity limit, determined as follows: 1) Each project activity instance that exceeds one percent of the capacity limit shall be identified. 2) Such instances shall be divided into clusters, whereby each cluster is comprised of any system of instances such that each instance is within one kilometer of at least one other instance in the cluster. Instances that are not within one kilometer of any other instance shall not be assigned to clusters. 3) None of the clusters shall exceed the capacity limit and no further project activity instances shall be added to the project that would cause any of the clusters to exceed the capacity limit.	No project activity instance shall exceed the applicable limit, which is 180 GWh_{th}/y. The expected annual energy saving for each project activity instance is approximately 0.03 GWh_{th}/y or 0.017% of the limit. As the annual energy saving is below 1% of the limit, therefore no project activity instance is identified and divided into clusters.

1.5 Project Proponent

Organization name	C-Quest Capital Stoves Asia Limited
Contact person	Ken Newcombe

Title	Director
Address	Brumby Centre, Lot 42, Jalan Muhibbah, 87000 Labuan, Malaysia.
Telephone	+6 087 423828
Email	cqc-operations@cquestcapital.com

1.6 Other Entities Involved in the Project

At the present, C-Quest Capital Stoves Asia Limited is the sole entity involved in the project.

1.7 Ownership

The project ownership is with C-Quest Capital Stoves Asia Limited.

Further, Registration certificate cum consent deed signed by end user (stove owner) to PP during the registration process includes the statutory clause *“Acknowledgement and Carbon Rights Waiver – My household hereby transfers and waives all and any rights in connection with the improved cookstove or project and greenhouse gas emission reductions or other environmental or social attributes generated by the installation and use of the improved cookstove to C-Quest Capital Stoves Asia Ltd and we understand that C-Quest Capital Stoves Asia Ltd may, at any time, transfer those rights to an affiliate without further notice or consent”*.

This is in line with clause 5 of section 3.6.1. of VCS project standard version 04.2.

1.8 Project Start Date

01-July-2022 (The estimated date of distribution of first ICS under this grouped project)

1.9 Project Crediting Period

01-July-2022 to 30-June-2032, 10 years fixed crediting period

1.10 Project Scale and Estimated GHG Emission Reductions or Removals

The estimated annual GHG emission reductions/removals of the project are:

- ☐ <20,000 tCO₂e/year
- ☐ 20,000 – 100,000 tCO₂e/year
- ☐ 100,001 – 1,000,000 tCO₂e/year
- ☒ >1,000,000 tCO₂e/year

Project Scale	
Project	
Large project	√

Year	Estimated GHG emission reductions or removals (tCO ₂ e)
Year 2022-2023	6,160,396
Year 2023-2024	5,474,781
Year 2024-2025	4,805,245
Year 2025-2026	4,151,552
Year 2026-2027	3,513,467
Year 2027-2028	2,890,759
Year 2028-2029	2,283,200
Year 2029-2030	1,690,565
Year 2030-2031	1,112,632
Year 2031-2032	549,183
Total estimated ERs	32,631,780
Total number of crediting years	10
Average annual ERs	3,263,178

1.11 Description of the Project Activity

The project involves distribution of fuel-efficient improved cookstoves (ICS) to replace the baseline cookstoves in households.


The ICS to be deployed under this project are SSM S32-X stove and Baldwin stove which substantially reduce fuel consumption and emissions for conducting cooking and water heating tasks in homes.



SSM S32-X stove with pot skirt

Table 1: Technical description of SSM S32-X stove with pot skirt

No	Parameter	Value
1	Thermal Efficiency	52.68% (with pot skirt)
2	Dimensions	25.5 cm height, 32 cm diameter
3	Material	- Stove Body: Stainless Steel - Pot Rest: Cast Iron - Pot Skirt: Stainless Steel - Burning Chamber: Stainless Steel and Ceramic - Fuel Feeding Door: Stainless Steel - Inner Fuel Shelf: Stainless Steel - Outer Fuel Shelf: Powder-coated steel
4	Life Span	10 years



Baldwin stove

Table 2: Technical description of Baldwin stove

No	Parameter	Value
1	Thermal Efficiency	52.07%
2	Dimensions	27.0 cm height; 23.0 cm to 30.0 cm adjustable diameter
3	Material	▪ Stove Body: Stainless Steel ▪ Pot Rest: Cast Iron ▪ Door frame: Stainless Steel ▪ Pot Rest: Steel ▪ Legs: Steel ▪ Inner Fuel Shelf: Cast Iron
4	Life Span	10 years

Data collection of ICS end-user

Project proponent will gather the necessary information to identify households using its ICS during the course of the project. To facilitate this process, each ICS will be assigned a unique serial number. This number will be recorded during the registration process together with the following information (as appropriate and as available):


- Name of ICS user or head of the household
- Address / GPS of ICS household
- Phone number of ICS user or household, where available.
- Stove model
- Date of distribution/installation
- ICS serial number
- Retailer/distributor information

The information collected will be stored in the electronic database which will serve as project database for project monitoring and sampling purposes.

1.12 Project Location

The project location will be the geographical boundary of Republic of Indonesia with coordinates 0° 47' 21.4" S latitude and 113° 55.28' E longitude.¹

¹ <https://www.geodatos.net/en/coordinates/indonesia>



Indonesia map²



Map of project area (See KML file attached)

1.13 Conditions Prior to Project Initiation

The conditions prior to project initiation is the continued use of non-renewable wood fuel (firewood) by the target population to meet similar thermal energy needs as provided by project cookstoves in absence of project activity. The pre-project devices are inefficient three-stone fires

² <http://www.freeworldmaps.net/asia/indonesia/indonesia-provinces-map.jpg>

or conventional systems with no improved combustion air supply mechanism and flue gas ventilation system i.e., traditional stoves.

1.14 Compliance with Laws, Statutes and Other Regulatory Frameworks

There are no laws and regulations governing the use of improved cookstoves in Indonesia households. The project is a voluntary effort by the project proponent.

A review is made on Indonesia environmental laws and regulations as below:

- a) Environmental Protection and Management (Law No. 32/2009)
- b) Waste Management (Law No. 18/2008)

There is no negative concern made on improved cookstoves project from the above laws and regulations.

1.15 Participation under Other GHG Programs

1.15.1 Projects Registered (or seeking registration) under Other GHG Program(s)

The project has not been registered, nor is it seeking registration under any other GHG program.

1.15.2 Projects Rejected by Other GHG Programs

The project has not been rejected by any other GHG program.

1.16 Other Forms of Credit

1.16.1 Emissions Trading Programs and Other Binding Limits

Does the project reduce GHG emissions from activities that are included in an emissions trading program or any other mechanism that includes GHG allowance trading?

☐ Yes ☒ No

1.16.2 Other Forms of Environmental Credit

Has the project sought or received another form of GHG-related credit, including renewable energy certificates?

☐ Yes ☒ No

1.17 Sustainable Development Contributions

The project contributes to sustainable development in a number of ways:

a) Environmental Sustainability

- The project will help significantly reduce greenhouse gas emissions over its lifetime.
- The project will help reduce the use of non-renewable biomass from forests, thus assist in conserving existing forest stock and the protection of natural forest eco-systems and wildlife habitats.

b) Social Sustainability

- Considerably less time need to be spent collecting wood fuel for the family home thereby reducing the work burden on rural families and presenting alternative opportunities for economic development.
- The amount of indoor pollutants from the burning of biomass in the family home will be reduced. Less carbon dioxide, carbon monoxide and particulates will be emitted due to the decrease in total biomass burned and an increase in the temperature of combustion.
- The stove provides a safer method for combusting biomass for cooking, helping to reduce burn injuries, especially for children, in the family home.

c) Economic Sustainability

- The project will help develop a section of the local economy, in the distribution, local assembly, maintenance and monitoring activities.
- Household expenditures on cooking fuel will be reduced through the use of the ICS.
- Saved household labour can be diverted to more productive economic activities.
- The project will create local employment opportunities in operational and management roles, as well as future assembly and/or manufacturing initiatives.

Project will be pursued for SD Vista labeling, so detail of SDG achieved by the project activity will be provided in the SD Vista PD.

1.18 Additional Information Relevant to the Project

Leakage Management

Not applicable as the project adopts a net gross adjustment factor of 95% to account for leakage.

Commercially Sensitive Information

No commercially sensitive information has been excluded from the public version of the project description.

Further Information

Not applicable.

2 SAFEGUARDS

2.1 No Net Harm

The project will only bring positive impacts on environmental and socio-economic aspects as elaborated in Section 1.17. No potential negative environmental or socio-economic impacts have been identified for the project.

2.2 Local Stakeholder Consultation

This section is not applicable as the project is listed under development. Local Stakeholder Consultation details will be updated later at the time of VVB validation process.

2.3 Environmental Impact

No negative environmental impacts have been identified from the project and environmental impact assessment (EIA) is not required for the project.

2.4 Public Comments

This section is not applicable as the project is not listed under VERRA yet.

2.5 AFOLU-Specific Safeguards

This section is not applicable as the project is a non-AFOLU project.

3 APPLICATION OF METHODOLOGY

3.1 Title and Reference of Methodology

VMR0006: Methodology for Installation of High Efficiency Firewood Cookstoves, Version 1.1³

3.2 Applicability of Methodology

Applicability criterion	How the project complies
-------------------------	--------------------------

³ <https://verra.org/wp-content/uploads/2021/07/VMR0006-Methodology-for-Installation-of-High-Efficiency-Firewood-Cookstoves-v1.1.pdf>

Project activities shall be implemented in domestic premises or in community-based kitchen	The proposed project involves deployment of ICS only in households.
The project stove shall have specified high-power thermal efficiency of at least 25% per the manufacturer's specifications and shall exclusively use woody biomass and can be single pot or multi-pot;	SSM S32-X stove and Baldwin stove are planned to be distributed under this project are single pot wood cookstoves that have efficiency of 52.68% and 52.07% respectively as per the manufacturer's specifications.
Non-renewable biomass has been used in the project region since 31 December 1989, using survey methods or referring to published literature, official reports or statistics;	Non-renewable biomass has been used since 31 December 1989 in Indonesia as demonstrated below.
For the specific case of biomass residues processed as a fuel (e.g. briquettes, wood chips	Not applicable. The ICS is introduced as energy efficiency measure to replace baseline stoves and reduce the use of non-renewable biomass for combustion.
The CDM-PDD or CDM-PoA-DD/CPA-DD shall explain the proposed method for distribution of project devices including the method to avoid double counting of emission reductions such as unique identifications of product and end-user locations (e.g. programme logo).	The project proponent will ensure that every cookstove that will be distributed within the project area will have a unique ID comprising of a combination of customer name, geographical location as well as a serial number to identify the ICS end users of this project activity. In addition, the project will be cross checked against other CDM project activity operating in the country using the UNFCCC, the Gold Standard, and other relevant voluntary carbon schemes to ensure that the ICS is not included in any other CDM project activity or voluntary project activity. Also, the approach adopted for distribution of cookstoves will be elaborately described in the monitoring report.
The CDM-PDD or CDM-PoA-DD/CPA-DD shall also explain how the proposed procedures prevent double counting of emission reductions, for example to avoid that project stove manufacturers, wholesale providers or	An undertaking will be taken by all the beneficiaries, i.e., the end-users indicating that the ownership of the current project solely lies with C-Quest Capital Stoves Asia Limited. The beneficiaries are completely

others claim credit for emission reductions from the project devices.	dependent on our experts and field staff who provide capacity building and required training to the community to use the ICS. To further ensure that the ownership rights of the project are reserved with CQC, all the stakeholders relevant, i.e., manufacturers/wholesale providers will be signing an undertaking which will clearly state that the project proponent or an entity authorized by it shall be the sole owner of the VCU's arising from the project.
---	--

Evidence that the non-renewable biomass has been in use since 1989

Non-renewable biomass has been in use since 31 December 1989 as evidenced by various FAO statistical data. The Global Forest Resources Assessment 2010⁴ (FAO) indicates that forest areas decline yearly. Between years 1990 and 2000, Indonesia lost on average of 1.913,600 hectares of forest per year. This amounts to an average annual deforestation rate of 1.61%. Between years 2000 and 2010, the rate of forest loss is 5% or 0.50% per annum. In total, between 1990 and 2010, Indonesia lost 20.3% of its forest cover, or around 24,113,000 hectares.

Decline in forest area between 1990 – 2010

FRA 2010 categories	Area (1000 hectares)			
	1990	2000	2005	2010
Forest	118,545	99,409	97,857	94,432
Other wooded land	n.a.	22,627	22,206	21,003
Other land	62,612	59,121	61,094	65,722
...of which with tree cover	n.a.	n.a.	n.a.	n.a.
Inland water bodies	9,300	9,300	9,300	9,300
TOTAL	190,457	190,457	190,457	190,457

Thus, it can be concluded that losses have been reported in forest areas from before 1989 thereby hinting that fuelwood used across Indonesia comes from non-renewable sources.


3.3 Project Boundary

Source		Gas	Included?	Justification/Explanation
Baseline	Emission from use of non-renewable	CO ₂	Yes	Major source
		CH ₄	Yes	Major source

⁴ FAO, Global Forest Resources Assessment 2010, Country Report, Indonesia, page 10
<https://www.fao.org/docrep/013/al531E/al531E.pdf>

Project	biomass/Fossil fuel	N ₂ O	Yes	Major source
		Other	No	No other source identified
	Emission from use of non-renewable biomass	CO ₂	Yes	Major source
		CH ₄	Yes	Major source
		N ₂ O	Yes	Major source
		Other	No	No other source identified

A representation of the baseline scenario and project scenario boundaries are given as below.



3.4 Baseline Scenario

The baseline scenario is the continued use of three stone fired cookstoves or a conventional device with no improved combustion air supply or flue gas ventilation (that is without a grate or a chimney) by the target population by burning non-renewable woody biomass to meet the thermal energy needs. The project cookstoves (ICS) will be deployed substituting the less efficient baseline stoves.

The baseline cookstoves are three-stone fires or conventional systems, which lacks efficient combustion chambers/air supply mechanism and flue gas ventilation system, leading to more wood fuel use and higher GHG emissions. While the project stoves continue to use the same wood fuel, due to higher efficiency, it reduces the need (saves) to burn more wood fuel for the same purposes (household cooking).

It is a common and traditional practice in the project area to use three stone fired stoves or a conventional device with no improved combustion air supply or flue gas ventilation, that is without a grate or a chimney. Hence, the applicable efficiency fraction for three stones fired or conventional stoves which stands at 0.1 (default) as per the applied methodology⁵ is considered in the baseline estimations.

Baseline scenario can also be verified from the registration cum consent deed signed by the registered stove user at the time of distribution of the project device (ICS), which confirms that, registered user voluntarily adopting the project stove and was using the three stone fire or conventional device (without a grate or a chimney) before switching to the project stove.

3.5 Additionality

The methodology uses activity method for the demonstration of additionality.

Activity Method

Step 1: Regulatory Surplus

There is no mandated government programme or policy in host country of this project ensuring the distribution of domestic fuel-efficient cookstoves. The project is not mandated by any law, statute or other regulatory framework, or for UNFCCC non-Annex I countries, any systematically enforced law, statute or other regulatory framework.

Households may only participate voluntarily in this project. It is hereby confirmed that the proposed project is a voluntary coordinated action by CQC.

Step 2: Positive List

⁵ Pg.19, section 9.2, VMR0006, Methodology for Installation of High Efficiency Firewood Cookstoves

As per Section 3.2, the project meets the applicability conditions of the methodology which represent the positive list.

The project installs the ICS at zero cost to the household and has no other source of revenue other than the sale of GHG credits.

The project is not implemented as part of government schemes or supported by multilateral funds.

Conclusion: As the project fulfills the conditions above, it is deemed additional.

Step 3: Project Method

This step is not applicable under project activity because the stoves are provided at zero cost to the end-users.

3.6 Methodology Deviations

The project did not apply any methodology deviations.

4 QUANTIFICATION OF GHG EMISSION REDUCTIONS AND REMOVALS

4.1 Baseline Emissions

The methodology does not account for baseline emissions separately, but instead quantifies net emission reductions achieved by the project. Please refer to Section 4.4

4.2 Project Emissions

The methodology does not account for project emissions separately, but instead quantifies net emission reductions achieved by the project. Please refer to Section 4.4.

4.3 Leakage

Leakage shall be considered as default 0.95 in accordance with methodology.

4.4 Net GHG Emission Reductions and Removals

The improved cookstove is introduced as energy efficiency measure in the project, therefore equations 1 and 2 of the methodology will be applied to calculate the net GHG emission reductions.

$$ER_y = \sum_i \sum_j ER_{y,i,j} \quad \text{Equation (1)}$$

Where:

- i = Indices for the situation where more than one type/model of improved cookstove is introduced to replace three-stone fire
- j = Indices for the situation where there is more than one batch of improved cookstove of type i
- ER_y = Emission reductions during year y in t CO₂e
- $ER_{y,i,j}$ = Emission reductions by improved cookstove of type i and batch j during year y in t CO₂e

$$ER_{y,i,j} = B_{y,savings,i,j} \times NCV_{wood\ fuel} \times f_{NRB,y} \times (EF_{wf,CO_2} + EF_{wf,non\ CO_2}) \times N_{y,i,j} \times 0.95 \quad \text{Equation (2)}$$

Where:

- $B_{y,savings,i,j}$ = Quantity of woody biomass that is saved in tonnes per improved cookstove of type i and batch j during year y
- $f_{NRB,y}$ = Fraction of woody biomass that can be established as non-renewable biomass (fNRB)⁶
- $NCV_{wood\ fuel}$ = Net calorific value of the non-renewable woody biomass that is substituted or reduced (IPCC default for wood fuel, 0.0156 TJ/tonne)⁷
- EF_{wf,CO_2} = CO₂ emission factor for the use of wood fuel in baseline scenario (IPCC default for wood fuel, 112 tCO₂/TJ)⁸
- $EF_{wf,non\ CO_2}$ = Non-CO₂ emission factor for the use of wood fuel in baseline scenario (IPCC default for wood fuel, 26.23 tCO₂/TJ)⁹
- $N_{y,i,j}$ = Number of improved cookstoves of type i and batch j operating during year y
- 0.95 = Discount factor to account for leakage

⁶ Default values endorsed by designated national authorities and approved by the Board are available at <https://cdm.unfccc.int/DNA/fNRB/index.html>

⁷ 2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 1 Introduction

⁸ 2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 2 Stationary Combustion

⁹ 2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 2 Stationary Combustion

The quantify of woody biomass saved due to implementation of improved cookstoves to be estimated using equation below:

$$B_{y,savings,i,j} = B_{y=1,new,i,survey} \times \left(\frac{\eta_{new,y,i,j}}{\eta_{old}} - 1 \right) \quad \text{Equation (3)}$$

where

- η_{old} = Efficiency of baseline cookstove
- $\eta_{new,y,i,j}$ = Efficiency of the improved cookstove type i and batch j determined through water boiling test (WBT) during year y
Alternatively, efficiency may be determined using Equation 4.
- $B_{y=1,new,i,j,survey}$ = Annual quantity of woody biomass used by improved cookstoves in tonnes per device of type i and batch j , determined in the first year of the implementation of the project through a sample survey.

$$\eta_{new,y,i,j} = \eta_p \times (DF_n)^{y-1} \times 0.94 \quad \text{Equation (4)}$$

where

- η_p = Efficiency of project stove (fraction) at the start of project activity.
- $(DF_n)^{y-1}$ = Discount factor to account for efficiency loss of project cookstove per year of operation (fraction). This value may be based on actual monitoring or based on manufacturer's declaration on expected loss in efficiency or through publicly available literature on relevant industry standards. Alternatively default value of 0.99 efficiency loss per year can be considered.
- 0.94 = Adjustment factor to account for uncertainty related to project cookstove efficiency test.

For ex-ante calculation purpose, the assumption below is applied.

- 1) It is assumed that the 500,000 ICS to be distributed under SSM S32-X stove and Baldwin stove with estimated proportion of 50:50.
- 2) Annual stove loss rate is estimated at 10% for SSM S32-X stove and 10% for Baldwin stove.
- 3) $B_{y=1,new,i,j,survey}$ is assumed as 1.83 tonnes / device / year

Determination of number of ICS operating during year y

$$N_{y,i,j} = 250,000 \times [1 - (y-1) \times 10\%]$$

Example of calculation:

If $y = 2$,

$$N_{y,i,j} = 250,000 \times [1 - (2-1) \times 10\%]$$

$$= 250,000 \times 90\%$$

$$= 225,000$$

Hence, the number of ICS operating during year y is as below:

	SSM S32-X stove	Baldwin Stove
Year (y)	$N_{y,i,j}$	$N_{y,i,j}$
1	250,000	250,000
2	225,000	225,000
3	200,000	200,000
4	175,000	175,000
5	150,000	150,000
6	125,000	125,000
7	100,000	100,000
8	75,000	75,000
9	50,000	50,000
10	25,000	25,000

Determination of efficiency of ICS during year y

$$\eta_{new,y,i,j} = \eta_p \times (DF_n)^{y-1} \times 0.94$$

Where

$$\eta_p = 52.68\%$$

$$DF_n = 0.99$$

Example of calculation:

If y= 2

$$\eta_{new,y,i,j} = 52.68\% \times (0.99)^{2-1} \times 0.94$$

$$= 49.02\%$$

Hence the efficiency of ICS during year y is as below:

	SSM S32-X stove	Baldwin Stove
Year (y)	$\eta_{new,y,i,j}$	$\eta_{new,y,i,j}$
1	49.52%	48.95%
2	49.02%	48.46%
3	48.53%	47.97%
4	48.05%	47.49%
5	47.57%	47.02%
6	47.09%	46.55%
7	46.62%	46.08%
8	46.16%	45.62%
9	45.69%	45.16%
10	45.24%	44.71%

Determination of quantity of woody biomass that is saved in tonnes per ICS during year y

$$B_{y,savings,i,j} = B_{y=1,new,i,survey} \times \left(\frac{\eta_{new,y,i,j}}{\eta_{old}} - 1 \right)$$

Example of calculation:

If y= 2,

$$B_{y,savings,i,j} = 1.83 \times [(0.4902/0.1) - 1]$$

= 7.1219 tonnes

			SSM S32-X stove	Baldwin Stove	SSM S32-X stove	Baldwin Stove
Year (y)	$B_{y=1,new,i,survey}$	η_{old}	$\eta_{new,y,i,j}$	$\eta_{new,y,i,j}$	$B_{y,savings,i,j}$	$B_{y,savings,i,j}$
1	1.83	0.1	49.52%	48.95%	7.2123	7.1076
2	1.83	0.1	49.02%	48.46%	7.1219	7.0183
3	1.83	0.1	48.53%	47.97%	7.0324	6.9298
4	1.83	0.1	48.05%	47.49%	6.9438	6.8423

5	1.83	0.1	47.57%	47.02%	6.8562	6.7556
6	1.83	0.1	47.09%	46.55%	6.7693	6.6698
7	1.83	0.1	46.62%	46.08%	6.6834	6.5849
8	1.83	0.1	46.16%	45.62%	6.5983	6.5008
9	1.83	0.1	45.69%	45.16%	6.5141	6.4175
10	1.83	0.1	45.24%	44.71%	6.4307	6.3351

Determination of emission reductions by ICS of batch 1 during year y

$$ER_{y,i,j} = B_{y,savings,i,j} \times NCV_{wood\ fuel} \times f_{NRB,y} \times (EF_{wf,CO_2} + EF_{wf,non\ CO_2}) \times N_{y,i,j} \times 0.95$$

Where

$$NCV_{wood\ fuel} = 0.0156 \text{ TJ/tonne}$$

$$f_{NRB,y} = 0.84$$

$$EF_{wf,CO_2} + EF_{wf,non\ CO_2} = 112 + 26.23 = 138.23 \text{ tCO}_2/\text{TJ}$$

Example of calculation:

SSM S32-X stove

If y=2,

$$ER_{y,i,j} = 7.1219 \times 0.0156 \times 0.84 \times 138.23 \times 225,000 \times 0.95$$

$$= 2,757,446.26 \text{ tCO}_2$$

Year	$B_{y,savings,i,j}$	$NCV_{wood\ fuel}$	$f_{NRB,y}$	$EF_{wf,CO_2} + EF_{wf,non\ CO_2}$	$N_{y,i,j}$	$ER_{y,i,j}$
1	7.2123	0.0156	0.84	138.23	250,000	3,102,707.39
2	7.1219	0.0156	0.84	138.23	225,000	2,757,446.26
3	7.0324	0.0156	0.84	138.23	200,000	2,420,271.79
4	6.9438	0.0156	0.84	138.23	175,000	2,091,064.64
5	6.8562	0.0156	0.84	138.23	150,000	1,769,707.03
6	6.7693	0.0156	0.84	138.23	125,000	1,456,082.73
7	6.6834	0.0156	0.84	138.23	100,000	1,150,077.07

8	6.5983	0.0156	0.84	138.23	75,000	851,576.88
9	6.5141	0.0156	0.84	138.23	50,000	560,470.51
10	6.4307	0.0156	0.84	138.23	25,000	276,647.79

Example of calculation:

Baldwin stove

If $y=2$,

$$ER_{y,i,j} = 7.0183 \times 0.0156 \times 0.84 \times 138.23 \times 225,000 \times 0.95$$

$$= 2,717,334.83 \text{ tCO}_2$$

Year	$B_{y,savings,i,j}$	$NCV_{wood\ fuel}$	$f_{NRB,y}$	$EF_{wf,CO2}$ + $EF_{wf,non\ CO2}$	$N_{y,i,j}$	$ER_{y,i,j}$
1	7.1076	0.0156	0.84	138.23	250,000	3,057,688.95
2	7.0183	0.0156	0.84	138.23	225,000	2,717,334.83
3	6.9298	0.0156	0.84	138.23	200,000	2,384,973.74
4	6.8423	0.0156	0.84	138.23	175,000	2,060,487.71
5	6.7556	0.0156	0.84	138.23	150,000	1,743,760.31
6	6.6698	0.0156	0.84	138.23	125,000	1,434,676.69
7	6.5849	0.0156	0.84	138.23	100,000	1,133,123.48
8	6.5008	0.0156	0.84	138.23	75,000	838,988.84
9	6.4175	0.0156	0.84	138.23	50,000	552,162.41
10	6.3351	0.0156	0.84	138.23	25,000	272,535.28

	SSM S32-X stove	Baldwin stove	Total (round down)
Year	$ER_{y,i,j}$	$ER_{y,i,j}$	tCO ₂
1	3,102,707.39	3,057,688.95	6,160,396
2	2,757,446.26	2,717,334.83	5,474,781

3	2,420,271.79	2,384,973.74	4,805,245
4	2,091,064.64	2,060,487.71	4,151,552
5	1,769,707.03	1,743,760.31	3,513,467
6	1,456,082.73	1,434,676.69	2,890,759
7	1,150,077.07	1,133,123.48	2,283,200
8	851,576.88	838,988.84	1,690,565
9	560,470.51	552,162.41	1,112,632
10	276,647.79	272,535.28	549,183

Year	Estimated baseline emissions or removals (tCO ₂ e)	Estimated project emissions or removals (tCO ₂ e)	Estimated leakage emissions (tCO ₂ e)	Estimated net GHG emission reductions or removals (tCO ₂ e)
Year 2022-2023	6,160,396	0	0	6,160,396
Year 2023-2024	5,474,781	0	0	5,474,781
Year 2024-2025	4,805,245	0	0	4,805,245
Year 2025-2026	4,151,552	0	0	4,151,552
Year 2026-2027	3,513,467	0	0	3,513,467
Year 2027-2028	2,890,759	0	0	2,890,759
Year 2028-2029	2,283,200	0	0	2,283,200
Year 2029-2030	1,690,565	0	0	1,690,565
Year 2030-2031	1,112,632	0	0	1,112,632
Year 2031-2032	549,183	0	0	549,183
Total	32,631,780	0	0	32,631,780

5 MONITORING

5.1 Data and Parameters Available at Validation

Data / Parameter	$f_{NRB,y}$
Data unit	Fraction
Description	Fraction of woody biomass saved by the project activity during year y that can be established as non-renewable biomass
Source of data	Value determined from survey methods
Value applied	0.84
Justification of choice of data or description of measurement methods and procedures applied	This parameter shall be determined ex-ante. C4 EcoSolutions (Pty) Ltd was appointed as third party to study and derive the f_{NRB} value for Indonesia.
Purpose of Data	Calculation of emission reductions
Comments	The report of f_{NRB} will be made available to VVB during the validation.

Data / Parameter	$NCV_{wood\ fuel}$
Data unit	TJ/tonne
Description	Net calorific value of the non-renewable woody biomass that is substituted or reduced
Source of data	2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 1 Introduction
Value applied	0.0156
Justification of choice of data or description of measurement methods and procedures applied	IPCC default value
Purpose of Data	Calculation of emission reductions
Comments	-

Data / Parameter	EF_{wf,CO_2}
Data unit	tCO ₂ /TJ
Description	CO ₂ emission factor for the use of wood fuel in baseline scenario
Source of data	2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 2 Stationary Combustion
Value applied	112
Justification of choice of data or description of measurement methods and procedures applied	IPCC default value
Purpose of Data	Calculation of emission reductions
Comments	-

Data / Parameter	$EF_{wf,non\ CO_2}$
Data unit	tCO ₂ /TJ
Description	Non-CO ₂ emission factor for the use of wood fuel in baseline scenario
Source of data	2006 IPCC Guidelines for National Greenhouse Gas Inventories; Volume 2 Energy, Chapter 2 Stationary Combustion
Value applied	26.23
Justification of choice of data or description of measurement methods and procedures applied	IPCC default value
Purpose of Data	Calculation of emission reductions
Comments	-

Data / Parameter	η_{old}
Data unit	Fraction
Description	Efficiency of baseline cookstove

Source of data	Methodological default value
Value applied	0.1
Justification of choice of data or description of measurement methods and procedures applied	A default value of 0.1 shall be used if baseline device is a three-stone fire using firewood (not charcoal), or a conventional device with no improved combustion air supply or flue gas ventilation, that is without a grate or a chimney.
Purpose of Data	Calculation of emission reductions
Comments	-

Data / Parameter	η_p
Data unit	Fraction
Description	Efficiency of project stove at the start of project activity.
Source of data	Manufacturer's specification
Value applied	SSM S32-X stove: 52.68% Baldwin stove: 52.07%
Justification of choice of data or description of measurement methods and procedures applied	This parameter shall be determined ex-ante
Purpose of Data	Calculation of $\eta_{new,y,i,j}$
Comments	-

5.2 Data and Parameters Monitored

Data / Parameter	$N_{y,i,j}$
Data unit	Number
Description	Number of project devices of type I and batch j operating during year y
Source of data	Monitoring

Description of measurement methods and procedures to be applied	Measured directly or based on a representative sample. Sampling standard shall be used for determining the sample size to achieve 90/10 confidence precision according to the latest version of Standard for sampling and surveys for CDM project activities and programme of activities.
Frequency of monitoring/recording	At least once every two years
Value applied	For ex-ante emission reduction calculation, it is assumed that the project will distribute up to 500,000 ICS with proportion of 50:50 between SSM S32-X stove and Baldwin stove.
Monitoring equipment	Monitoring survey
QA/QC procedures to be applied	Sampling standard “sampling and surveys for CDM project activities and programme of activities” version 9 will be used for determining the sample size to achieve 90/10 confidence precision.
Purpose of data	Calculation of emission reductions
Calculation method	Proportion of operational stoves obtained from the survey is multiplied by the total commissioned stoves to arrive at this value
Comments	No Comments

Data / Parameter	$\eta_{new,y,i,j}$				
Data unit	Fraction				
Description	Efficiency of the improved cookstove type i and batch j determined through water boiling test (WBT) during year y				
Source of data	Calculation				
Description of measurement methods and procedures to be applied	To adopt Option V given in the methodology: “Efficiency of the improved cookstoves to be estimated using equation 5 above where loss in efficiency per year is calculated, and therefore this parameter does not need to be monitored”				
Frequency of monitoring/recording	Annually				
Value applied	For ex-ante calculation, the value below is applied. SSM S32-X <table border="1"> <tr> <th>Year (y)</th><th>$\eta_{new,y,i,j}$</th></tr> <tr> <td>1</td><td>49.52%</td></tr> </table>	Year (y)	$\eta_{new,y,i,j}$	1	49.52%
Year (y)	$\eta_{new,y,i,j}$				
1	49.52%				

		<table><tr><td>2</td><td>49.02%</td></tr><tr><td>3</td><td>48.53%</td></tr><tr><td>4</td><td>48.05%</td></tr><tr><td>5</td><td>47.57%</td></tr><tr><td>6</td><td>47.09%</td></tr><tr><td>7</td><td>46.62%</td></tr><tr><td>8</td><td>46.16%</td></tr><tr><td>9</td><td>45.69%</td></tr><tr><td>10</td><td>45.24%</td></tr></table>	2	49.02%	3	48.53%	4	48.05%	5	47.57%	6	47.09%	7	46.62%	8	46.16%	9	45.69%	10	45.24%				
	2	49.02%																						
	3	48.53%																						
	4	48.05%																						
	5	47.57%																						
	6	47.09%																						
	7	46.62%																						
	8	46.16%																						
	9	45.69%																						
	10	45.24%																						
	Baldwin stove																							
	<table><tr><td>Year (y)</td><td>$\eta_{new,y,i,j}$</td></tr><tr><td>1</td><td>48.95%</td></tr><tr><td>2</td><td>48.46%</td></tr><tr><td>3</td><td>47.97%</td></tr><tr><td>4</td><td>47.49%</td></tr><tr><td>5</td><td>47.02%</td></tr><tr><td>6</td><td>46.55%</td></tr><tr><td>7</td><td>46.08%</td></tr><tr><td>8</td><td>45.62%</td></tr><tr><td>9</td><td>45.16%</td></tr><tr><td>10</td><td>44.71%</td></tr></table>	Year (y)	$\eta_{new,y,i,j}$	1	48.95%	2	48.46%	3	47.97%	4	47.49%	5	47.02%	6	46.55%	7	46.08%	8	45.62%	9	45.16%	10	44.71%	
Year (y)	$\eta_{new,y,i,j}$																							
1	48.95%																							
2	48.46%																							
3	47.97%																							
4	47.49%																							
5	47.02%																							
6	46.55%																							
7	46.08%																							
8	45.62%																							
9	45.16%																							
10	44.71%																							
Monitoring equipment	Calculated value (No Monitoring equipment used)																							
QA/QC procedures to be applied	This parameter will be calculated using equation 5 of the applied methodology.																							
Purpose of data	Calculation of emission reductions																							
Calculation method	Calculation to be performed using equation below: $\eta_{new,y,i,j} = \eta_p \times (DF_n)^{y-1} \times 0.94$																							

Comments	No Comments
----------	-------------

Data / Parameter	$B_{y=1,new,i,j,survey}$
Data unit	Tonnes
Description	Annual quantity of woody biomass used by improved cookstoves in tonnes per device of type i and batch j, determined in the first year of the implementation of the project through a sample survey
Source of data	Monitoring survey
Description of measurement methods and procedures to be applied	Minimum sample size of each type i and batch j should be in line with the latest version of Standard for sampling and surveys for CDM project activities and programme of activities or guidelines provided in methodology Section 8.4 option (b). Determined in the first year of the introduction of the devices (e.g. during the first year of the crediting period, $y=1$) through measurement campaigns at representative households and/or sample survey. Sample surveys to estimate this parameter, that are solely based on questionnaires or interviews (i.e. that do not implement measurement campaigns) may only be used if the following conditions are satisfied. (i) Baseline cookstoves have been completely decommissioned and only improved cookstoves are exclusively used in the project households; (ii) If multiple devices are used in the project, it is possible from the results of the survey questions to clearly differentiate the quantity of firewood being used by each device. In other words, if more than one device, or another device that consumes firewood, are in use in project households, then the sample survey needs to distinguish the quantity of firewood used by the project device and the other devices that use firewood.
Frequency of monitoring/recording	Determined in the first year of project implementation
Value applied	For ex-ante calculation, the value is assumed as 5 kg/device/day or equal to 1.83 tonnes/device/year.
Monitoring equipment	Weighing Scales to be used for measuring quantity of fuel wood
QA/QC procedures to be applied	Calibration of weighing scales to be used for measuring the fuel wood will get done before start using on site
Purpose of data	Calculation of emission reductions
Calculation method	Not Applicable. This is monitored value.

Comments	No Comments
----------	-------------

Data / Parameter	Life Span
Data unit	Number of years
Description	The operating lifetime of the project device. The life span should be reported if the methodology equation 5 is adopted to determine the project stove efficiency
Source of data	Manufacturer's specification
Description of measurement methods and procedures to be applied	Technical specification as declared by the manufacturer and wherever possible supported by third party report.
Frequency of monitoring/recording	Once at the time of project stove installation
Value applied	SSM S32-X stove: 10 years Baldwin stove: 10 years
Monitoring equipment	No equipment is required to monitor this parameter
QA/QC procedures to be applied	This parameter will be referred from the Manufacturer's specification
Purpose of data	Calculation of emission reductions
Calculation method	No calculation used for this parameter
Comments	If the life span of project devices is less than the crediting period, it shall be demonstrated that the devices shall be replaced after the life span has ended. In such cases, if it cannot be demonstrated that the project devices will be replaced with new devices, no emission reductions can be claimed beyond the life span of the project devices.

5.3 Monitoring Plan

Sampling Plan

As per the *Guideline for Sampling and Surveys for CDM Project Activities and Programme of Activities, version 04.0*, the sampling plan is the following:

(a) Sampling design

Due to the large number of ICS envisioned to be distributed under the project, it is not economically feasible to monitor each individual ICS unit distributed. Therefore, representative sampling shall be

undertaken for each batch of ICS. The sampling plan to be designed in line with the requirements of the *Standard for Sampling and Surveys for CDM Project Activities and Programme of Activities, version 09.0*.

Samples will be drawn from ICS recorded in the project database administered by the project proponent. A detailed explanation of this database is found in Section 1.11 of project description.

Objectives and Reliability Requirements

The objective is to obtain an unbiased and reliable estimate of the proportion or mean value of the following key variables over the course of the crediting period. As per CDM Methodology AMS-II.G, 90/10 confidence/precision shall be applied for annual sampling requirement and 95/10 for biennial sampling inspection. As per *Standard for Sampling and Surveys for CDM Project Activities and Programme of Activities*, 90/10 confidence/precision to be adopted for small-scale project and 95/10 for large-scale project. Given that the size of the project is under the category of large projects, hence 95/10 confidence/precision shall be adopted for all parameters unless the average annual emission reductions of the project below the threshold.

Monitored Parameters:

The project involves introduction of improved cook stoves as energy efficiency measure:

No.	Monitoring parameters	Sampling parameters	Parameter type	Monitoring frequency
1	$N_{y,i,j}$ Number of project devices of type i and batch j operating during year y	Proportion of ICS still in operation	Proportion	Biennially
2	$\eta_{\text{new},y,i,j}$ Efficiency of the device of each type i and batch j implemented as part of the project activity	Thermal Efficiency of operational ICS	Mean value	Annually (The project opts to determine the efficiency using the equation given by methodology, therefore it is not required to monitor this parameter via sampling survey.)
3	$B_{y=1,\text{new},i,j,\text{survey}}$ Quantity of woody biomass used by project devices in tonnes per device of type i . and batch j	Daily consumption of woody biomass per ICS	Mean value	Determined in the first year of project implementation

Target Population

The target population will be the complete set of appliances (ICS) deployed under the project.

Sampling Method

The project involves distribution of ICS throughout the project area thereby replacing traditional cooking devices. The population is heterogeneous in nature i.e. common technology with similar operating characteristics but dispersed i.e. distribution of ICS is spread across different states/province of the country. The population consists of sub-populations which are homogeneous called as Strata. The characteristics of population (for example quantity of biomass consumed) are more similar within the stratum (ICS of same type, vintage and location in which they are operating) than across the strata. Therefore, Stratified Sampling technique will be used to conduct sampling survey among ICS batches.

The populations of each batch will be combined together, the sample size is determined, and a single survey will be undertaken to collect data. To ensure the survey result is representative of the entire population, the dissimilarity (such as ICS type, vintage and location in which they are operating) within the included CPAs will be taken into account in the sample size calculation. The ICS of same type, vintage and location in which they are operating will be grouped in the same strata. Samples will be drawn by using the random number generator.

To determine the parameters, sampling will involve the following approaches (outcome in brackets):

$N_{y,i,j}$	Visual inspection of the premises to see if ICS is operational and in use. Interview with end user if required to verify that ICS is still in use (Yes/No)
$B_{y=1,new,i,j,survey}$	Interview with end user and estimate the daily consumption of woody biomass of ICS (Daily consumption of woody biomass)

Sample Size

The procedure to determine the sample of households will ensure that they adequately represent the broader project population, minimizing sampling error. Using, a 90 or 95 per cent confidence level, and a 10 per cent margin of error, a random sample will be selected from each strata.

In order to calculate the required sample size estimates, values for the proportions, mean values, and standard deviations are required. As per *Guideline for Sampling and surveys for CDM project activities and programmes of activities, version 04.0*, there are different ways available to obtain the estimates of the parameter of interest:

- (a) Refer to the result of previous studies and use these results;

- (b) In a situation where information from previous studies is not available, a preliminary sample as a pilot could be conducted and use that sample is used to provide the estimates;
- (c) Use best guesses based on the researcher's own experiences.

Proportion parameter

To estimate the sample size for proportion parameters, the following equation¹⁰ is used:

$$n \geq \frac{1.96^2 NV}{(N-1) \times 0.1^2 + 1.96^2 \times V}$$

Where¹¹:

$$V = \left(\frac{SD}{p} \right)^2$$

n = Sample size

N = Population size (Total number of households or ICS)

p = Weighted overall expected proportion

SD^2 = Weighted overall expected variance

1.96 = Represents the 95% confidence required

(In the case of 90% confidence, 1.645 shall be used)

0.1 = Represents the 10% relative precision

The overall variance and proportion are calculated using equation below:

$$p = \frac{(g_a \times p_a) + (g_b \times p_b) + (g_c \times p_c) + \dots + (g_k \times p_k)}{N}$$

$$SD^2 = \frac{(g_a \times p_a(1 - p_a)) + (g_b \times p_b(1 - p_b)) + (g_c \times p_c(1 - p_c)) + \dots + (g_k \times p_k(1 - p_k))}{N}$$

Where

¹⁰ Equation 1 of Appendix 3, *Guidelines for Sampling and Surveys for CDM Project Activities and Programme of Activities (Version 04.0)*

¹¹ Equation 2 of Appendix 3, *Guidelines for Sampling and Surveys for CDM Project Activities and Programme of Activities (Version 04.0)*

g_i = Size of the i^{th} strata where $i = a, \dots, k$

p_i = Proportion of the i^{th} strata where $i = a, \dots, k$

Sample size for each strata

$$n_i = \frac{g_i}{N} \times n$$

Where:

n_i = Sample size of the i^{th} strata where $i = a, \dots, k$

Mean value parameter

To estimate the sample size for mean value parameter, the following equation¹² is used:

$$n \geq \frac{1.96^2 NV}{(N-1) \times 0.1^2 + 1.96^2 \times V}$$

Where¹³:

$$V = \left(\frac{SD}{m} \right)^2$$

n = Sample size

N = Population size (Total number of households or ICS)

m = Weighted overall expected mean

SD^2 = Weighted overall expected variance

1.96 = Represents the 95% confidence required

(In the case of 90% confidence, 1.645 shall be used)

0.1 = Represents the 10% relative precision

The overall variance and mean are calculated using equation below:

¹² Equation 19 of Appendix 3, *Guidelines for Sampling and Surveys in CDM Project Activities and Programme of Activities* (version 04.0)

¹³ Equation 20 of Appendix 3, *Guidelines for Sampling and Surveys in CDM Project Activities and Programme of Activities* (version 04.0)

$$m = \frac{(g_a \times m_a) + (g_b \times m_b) + (g_c \times m_c) + \dots + (g_k \times m_k)}{N}$$

$$SD^2 = \frac{(g_a \times SD_a^2) + (g_b \times SD_b^2) + (g_c \times SD_c^2) + \dots + (g_k \times SD_k^2)}{N}$$

Where

g_i = Size of the i^{th} strata where $i = a, \dots, k$

m_i = Mean of the i^{th} strata where $i = a, \dots, k$

Sample size for each strata

$$n_i = \frac{g_i}{N} \times n$$

Where:

n_i = Sample size of the i^{th} strata where $i = a, \dots, k$

If the resulting sample size based on the above equation is smaller than 30 ICS, then as the parameter of interest is a numeric mean value (i.e. not a proportion or percentage) the Student's t-distribution shall be used.

The sample size for mean value parameter is referred to the equation below¹⁴:

$$n = \left(\frac{t_{n-1} \times SD}{0.1 \times mean} \right)^2$$

Where t_{n-1} is the value of the t-distribution for 95% confidence when the sample size is n. Since the sample size is not known yet, the first step is to use the value for 95% confidence when the sample is large, i.e. 1.96 and then redefine the calculation.

The calculation now need to repeat using t-value for 95% confidence. The process should be iterated until there is no change to the value of n.

The project proponent may choose to use the same sample to monitor more than one parameter. According to the Standard for sampling and surveys for CDM project activities and programme of activities, if there is more than one parameter to be estimated, then a sample size calculation should be done for each of them. Then either the largest number for the sample size is chosen as sampling effort with one common survey, or separate sampling efforts and surveys are

¹⁴ Paragraph 102, *Guidelines for Sampling and Surveys in CDM Project Activities and Programme of Activities* (version 04.0)

undertaken for each parameter. For instance, the project proponent may sample separately $N_{y,ij}$ and $B_{y=1,new,ij,survey}$ –or a combination of two parameters in the same sample. Sampling more than one parameter within the same sample (household) helps reduce travel needs for monitoring and the associated costs. At the same time this approach ensures the random selection of samples for every parameter.

Oversampling is strongly encouraged, not only to compensate for any attrition, outliers or non-response associated with the sample, but also to prevent a situation at the analysis stage where the required reliability is not achieved and additional sampling efforts would be required. The sample size shown above will be adjusted upwards to account for non-responses, Project proponent shall determine the appropriate non-responses rate based on previous experience.

Sampling Frame

Separate samples shall be taken for each batch. The sampling frames shall be defined as per below. In overall, a batch of ICS will have same group of end users which is household users, thus it is expected that the geographical locations do not have influence on the parameter of interest. Therefore, all monitoring parameters can be assumed to be highly homogeneous for each ICS model regardless of how the end user group and distribution/installation location is defined.

To formulate sample frame, all ICS operating under the batch will be combined together. The number of project devices operating may vary with ICS type and location where they are located & efficiency of the ICS depends on the ICS type and ICS age group. Therefore, ICS can be sub-grouped into strata based on ICS batch, ICS type and location where they are located.

	Batch j				
Number of ICS Operating	250,000				
Location/Region	A	B	C	D	E
ICS Type	X	X	X	X	X
Number of ICS / strata	50,000	50,000	50,000	50,000	50,000
Strata	1	2	3	4	5
	Sampling frame				

(b) Data to be collected:

(i) Field Measurements:

The table below summarizes field measurement data requirements

Parameter	Timing (indicative)	Frequency as required by methodology	Methods to be applied	Comments on seasonal fluctuation
$N_{y,i,j}$	Monitoring will likely occur every 12 to 24 months	Biennially	Visits to the premises, visual inspection and interview with ICS end-user.	Not due to any seasonal fluctuation.
$B_{y=1,new,i,j,survey}$	Monitoring will likely occur within the first year after installation	First year of installation	Visits to the premises, visual inspection and interview with ICS end-user.	Not due to any seasonal fluctuation.

Hard copies of the surveys will be kept and the database will have back up. Original stove purchase contracts, information collected from the registration or other means of acceptance by the users will be stored in the project office. A back-up of the project database will also be stored on an electric medium. All data monitored and required for verification and issuance will be kept for two years after the end of the crediting period or the last issuance of credits for the project activity, whichever is later.

(ii) Quality Assurance/Quality Control

The project proponent will apply measures to ensure the required confidence/precision for each sampled parameter is met, allowing for non-response and the possible removal of outliers from the sample, as part of a Quality Control/Quality Assurance system. The choice of measure applied to each parameter will depend on the cost of each data collection approach and logistics required. The project proponent will determine the most effective measure for each parameter from the following list:

- Oversampling: Randomly draw a sample more than the calculated number (say 20%) and collect data from each
- Buffer Group: Randomly draw additional samples (say 20%) and collect data from only for minimum numbers of ICS as per sample size calculation. If this would not result in the required sample size data would be collected from the additional ICS that were selected in the sample.
- If precision required is not achieved by reliability check, use the lower bound or upper bound of estimates of the parameter.

The sampling plan has the following procedures in place to ensure good quality data. The project proponent will ensure that field personnel have reviewed, understand and have agreed to follow the monitoring plan procedures, including provisions for maximizing response rates, documenting out-of-population cases, refusals and other sources of non-response. A quality control and assurance strategy will be documented. Quality control and assurance strategies include

addressing non-sampling errors, such as non-response or bias from interviewer. The project proponent or a competent third party designated by the project proponent with the proper skills will train the monitoring personnel on how to properly survey households to prevent bias from interviewer. In the case a household refuses to participate, another household will be chosen at random. To reduce interviewer bias, good questionnaire design and well-tested questionnaires will be used.

The sample data for mean value parameter is continuous and therefore the presence of outliers is possible. To identify and address outliers for the parameter, outliers will be defined as those data points with values greater than three standard deviations from the mean of the sample. Data points identified as outliers will be examined further to correct for possible transcription and data entry errors but will be omitted from the analysis if no such administrative errors exist.

(iii) Analysis

The project proponent will manage a project database that includes the following data that can be directly attributable to each batch within the project, thereby allowing unambiguous determination of the emission reductions attributable to each project:

- A list of households participating in each batch / project, including name, community/location, distribution/installation date and unique serial number;
- Testing to ensure that the stoves are still operating above the minimum 25% efficiency required by the methodology, by the project proponent or a third party certified by a national standards body or an appropriate certifying agency recognized by it.
- Where replacements are made, assurance that the efficiency of the new ICS is similar to the specified.

Data obtained from the samples will be used to estimate proportions and mean values for the parameters described above. The values will then be factored into the emissions reduction calculations and result in the request for issuance of VERs. The parameters are applied for emission reduction calculations. The stoves that are not in use will be excluded from emissions reductions calculations and will not be counted towards the total number of ICS in operation during the monitoring period.

(c) Implementation

Sampling for the purpose of emission reduction calculation and elaboration of the monitoring report will occur at the end of each monitoring period. This sampling will be conducted by trained personal from project proponent or an experienced third-party entity. The credentials and/or training materials for the sampling personal will be provided to the VVB at verification. The maximum length of one monitoring period will be two years (duration, not calendar years), with option for annual or bi-annual monitoring. The project proponent will be responsible for managing household data collection and entry into the project database. Field personnel will receive training on how to properly deal with surveying techniques and reduce errors and sign a document certifying that there is no conflict of interest of those involved in data collection and analysis. If there is conflict of interest, the personnel will not be allowed to participate in data collection and

analysis. The project database will record the start and end dates of each monitoring period and record the emission reductions attributable to each monitoring period. Appropriate record keeping procedures will be implemented to ensure that each monitoring period data set can be transparently attributed to its corresponding batch/project, preventing any occurrences of double counting. An internal review of the project database will be able to determine the current status of each batch — the duration of previous monitoring periods, the households delivering monitoring data, and current verification activities.

(i) Assessment for Leakage

The methodology provides a net to gross adjustment factor of 0.95 to account for leakages, hence the surveys are not required to determine leakage.

The other source of leakage occurs if equipment currently being utilized is transferred from outside the boundary to the project activity. All ICS in the project will be newly manufactured/assembled before distribution.

(ii) Disposal of Low Efficiency Appliances and Use of Baseline Stoves

When an ICS is distributed, the end user receives information explaining that conventional open fire appliance must no longer be used. Follow-up meetings with end users will ensure that those who have received an ICS are using it properly and that the conventional open fire is no longer in use. If it is determined that the conventional open fire is still in use along with the operating ICS, a survey will be conducted, and discount will be applied to ER formulae for emission reduction adjustment.

(iii) Monitoring Reporting

The project proponent will assess all monitoring data and produce a monitoring report for the VVB to verify corresponding to the preceding monitoring period. This report will present the data relating to the emission reductions generated by those batches during the monitoring period.