# **CUSTOMER SERVICE BULLETIN**

### Radio Shack CUSTOMER SERVICE BULLETIN

Bulletin No. 1559-Ø6

Description Manuf. Inv. Control

Model Model I

Stock No. 26-1559 All Prior 3.0

Date Dec. 22, 1981

Page 1 of 2

400 Atrium—One Tandy Center, Fort Worth, Texas 76102

#### **Problem**

It has been found that a problem can occur in Finish Good Maintenance which causes the machine to lock up when updating the files if more than 300 raw materials are in the finished good.

### Solution

The problem is corrected by following the steps listed below.

- Backup the diskette(s) and make the changes on the Backup copy of the program.
- In BASIC load the program by typing LOAD"FGMAINT"
- Make the following corrections:

CHANGES (Retype the line or refer to the Edit section of the owners manual)

Old Line:4 DEFINTI-K,F,R,W-Z:DIMW,WS,WL,WD,PT,X,Y,F1\$(8,5,4),F(7),IX\$(128), FR(1,61 $\emptyset$ ),J(3),FG\$(25,3),FG(25),P\$(63),Q\$(63)

New Line:4 DEFINTI-K,F,R,W-Z:DIMW,WS,WL,WD,PT,X,Y,F1\$(8,5,4),F(7),IX\$(128), FR(1,61 $\emptyset$ ),J(4),FG\$(25,3),FG(25),P\$(63),Q\$(63)

Old Line:851 $\emptyset$  J(1)=VARPTR(IX(1)):J(2)=VARPTR(FR( $\emptyset$ ,1)):J(3)=RQ

New Line:851 $\emptyset$  J(1)=VARPTR(IX(1)):J(2)=VARPTR(FR( $\emptyset$ ,1)):J(3)=RQ:J(4)=HR

Old Line:10090 FIELD1\*146ASUS\$:GET1\*285:SR\$=US\$:RETURN

New Line:10090 FIELD1\*149ASUS\$:GET1\*285:SR\$=US\$:RETURN

# CUSTOMER SERVICE BULLETIN

Subject .

MANUFACTURING INVENTORY CONTROL 1559-Ø6

Page \_\_\_\_ Of 2\_\_\_\_

#### \*ALSO MAKE THE FOLLOWING CHANGES TO "MFGINIT" (INITALIZATION DISK)

Old Line:16000 SR\$=STRING\$(146,32):FORX=1TO146:READY:MID\$(SR\$,X,1)=CHR\$(Y): NEXT

New Line:16000 SR\$=STRING\$(149,32):FORX=1TO149:READY:MID\$(SR\$,X,1)=CHR\$ (Y):NEXT

Old Line:16010 FIELD1,146ASQS\$:LSETQS\$=SR\$:PUT1,285:SR\$="":RETURN

New Line:16010 FIELD1,149ASQS\$:LSETQS\$=SR\$:PUT1,285:SR\$="":RETURN

#### REPLACE LINES 16030 THROUGH 16120 WITH THESE LINES:

16Ø3Ø DATA 2Ø5,127,1Ø,94,35,86,213,221,225,35,94,35,86,213,253

16040 DATA 225,35,94,35,86,35,78,35,70,3,19,197,213,209,193

16Ø5Ø DATA 11,121,176,2ØØ,197,221,35,221,35,213,253,229,225,1,4

16Ø6Ø DATA Ø,27,122,179,4Ø,67,213,221,126,Ø,19Ø,35,32,69,221

16Ø7Ø DATA 126,1,19Ø,32,63,2Ø9,43,94,35,86,213,35,94,35,86

16Ø8Ø DATA 213,229,2Ø9,43,62,4,245,197,213,229,237,184,225,2Ø9,193

16Ø9Ø DATA 241,61,32,243,2Ø9,253,114,3,253,115,2,2Ø9,253,114,1

16100 DATA 253,115,0,253,229,225,17,4,0,25,229,253,225,209,27

1611Ø DATA 122,179,213,32,159,2Ø9,193,2Ø1,17,3,Ø,25,229,197,225

1612Ø DATA 19,25,229,193,225,209,27,122,179,40,138,213,24,159

- 4. Type SAVE "FGMAINT" to save the changes in the program.
- 5. At TRSDOS Ready, make a backup copy of the corrected diskette.