Hawaii Framework Reference Documentation

Marcel Overdijk

Version 2.0.0.BUILD-SNAPSHOT

Table of Contents

1. Introduction to Hawaii	
1.1. Spring Boot	2
2. Getting Started with Hawaii	3
3. Hawaii Features	4
3.1. Environments	4
3.2. Configuration properties	4
3.3. Hawaii Time	4
3.4. Resource Assembler	
3.5. Validation	6
4. Hawaii Starters	
4.1. hawaii-starter	7
4.2. hawaii-starter-rest	
4.3. hawaii-starter-test	
5. Deployment	8
Appendices	9
Appendix A: Hawaii application properties	9

kūlia i ka nu'u. Strive to reach the highest.	

Chapter 1. Introduction to Hawaii

The Hawaii Framework is a Java framework for developing Spring based applications.

It provides production-ready features and integrations based best practices and experience to boost projects.

The Hawaii Framework is developed internally at QNH and is used in projects for medium and large enterprise customers.

1.1. Spring Boot

Combining Spring Boot and the Hawaii production-ready features and auto configuration brings even more power and simplicity to developers, without sacrificing flexibility.

The Hawaii Framework also provides various Spring Boot Starters to automatically include the needed dependencies and trigger the auto configuration of the Hawaii production-ready features.

But it is important to mention that most of the Hawaii features can also used without using Spring Boot. In that case the desired features need to be configured manually by defining the appropriate Spring beans inside the application's context.

Chapter 2. Getting Started with Hawaii

Chapter 3. Hawaii Features

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

3.1. Environments

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

3.2. Configuration properties

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

3.3. Hawaii Time

HawaiiTime is not merely a convenient wrapper to instantiate new java.time date and time objects. It provides an application wide java.time.Clock reference which is particular useful for unit testing.

It is similar to Joda's DateTimeUtils which also allows setting a fixed current time. However it is important to note that Joda's DateTimeUtils uses a static variable to store the current time. HawaiiTime does not take this approach. Instead the HawaiiTime bean needs to be injected in any class that needs to instantiate new date and time objects. This approach is more flexible and e.g. has the benefit that unit tests can be run in parallel. See example usage below.

```
public class MyClass {
   private HawaiiTime hawaiiTime;
   this.hawaiiTime = hawaiiTime;
   }
   public void doSomethingWithDate() {
       ZonedDateTime dateTime = this.hawaiiTime.zonedDateTime(); ②
       // ...
   }
}
public class MyClassTests {
   @Test
   public void testDoSomethingWithDate() {
       long millis = System.currentTimeMillis();
       HawaiiTime hawaiiTime = new HawaiiTime();
       hawaiiTime.useFixedClock(millis); 3
       MyClass myClass = new MyClass(hawaiiTime);
       myClass.doSomethingWithDate();
       // ...
   }
}
```

- 1 Inject the HawaiiTime bean.
- ② Use the injected HawaiiTime bean to instantiate new date and time objects.
- ③ In unit tests a fixed clock can be used to manipulate and predict the exact current time.

Another benefit of using HawaiiTime is that a fixed time can be used in a running application to test how it behaves on a given date or time.



Third-party libraries being used by the application do not use HawaiiTime and probably instantiate date and time objects based on the System time.

Hawaii uses UTC as default timezone but this can be changed by setting the hawaii.time.timezone configuration property. The provided value will be parsed by java.time.ZoneId#of(String zoneId) and supports different timezone formats like UTC, Europe/Amsterdam and GMT+1.

The creation of the HawaiiTime bean can also be disabled by setting hawaii.time.enabled to false.

3.4. Resource Assembler

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet

auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

3.5. Validation

Chapter 4. Hawaii Starters

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

4.1. hawaii-starter

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

4.2. hawaii-starter-rest

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hendrerit ipsum quis est elementum, ut lacinia metus fringilla. Aliquam ullamcorper a enim sed luctus. Aliquam cursus dolor nec aliquet auctor. Vestibulum eget lectus posuere, ullamcorper arcu at, lobortis erat. Aenean feugiat enim enim, et ultrices lacus ornare sagittis. Nunc quis odio sed felis semper semper bibendum pulvinar tortor. Duis sollicitudin aliquet ligula, a suscipit leo pulvinar a. Praesent enim sem, fringilla eget purus vel, auctor ornare nisl. In eu malesuada lorem, vel sodales nulla. Aenean suscipit, est eget mattis congue, leo ex laoreet purus, quis fringilla ante mi a massa.

4.3. hawaii-starter-test

Chapter 5. Deployment

Appendices

Appendix A: Hawaii application properties

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent neque mi, lobortis non sagittis vitae, porttitor ac dolor. Morbi facilisis porta vestibulum. Donec id risus scelerisque, dictum leo et, mattis ante. Praesent ac viverra nisi, ac cursus lectus. Ut vel tellus sit amet libero efficitur tristique. Aenean id massa pulvinar, imperdiet sapien et, tempus dui. Sed imperdiet porttitor iaculis. Vivamus mattis sit amet nisi nec dictum.

```
# HAWAII PROPERTIES
# This sample file is provided as a guideline. Do NOT copy it in its
# entirety to your own application.
# HAWAII SPRING BOOT DEFAULTS
spring:
 jackson:
   date-format: com.fasterxml.jackson.databind.util.ISO8601DateFormat
   property-naming-strategy: CAMEL_CASE_TO_LOWER_CASE_WITH_UNDERSCORES
   serialization:
     indent-output: false
     write-dates-as-timestamps: false
     write-date-timestamps-as-nanoseconds: false
logging:
 file: log/hawaii.log
 level:
     org.hawaiiframework: INFO
     org.springframework: INFO
# HAWAII TIME
hawaii:
 time:
   enabled: true # Enable creation of the 'HawaiiTime' bean.
   timezone: UTC # The timezone to use like 'UTC', 'Europe/Amsterdam' or 'GMT+1'.
spring:
 profiles: dev
 jackson:
   serialization.indent-output: true
logging:
 level:
   org.hawaiiframework: DEBUG
spring:
 profiles: test
spring:
 profiles: prod
```