

# Decomposition-based Successive Approximation Methods for Global Optimization

Ivo Nowak<sup>1,a)</sup> and Pavlo Muts<sup>1,b)</sup>

<sup>1</sup>*Hamburg University of Applied Sciences, Berliner Tor 21, 20099 Hamburg, Germany*

<sup>a)</sup>Corresponding author: ivo.nowak@haw-hamburg.de

<sup>b)</sup>pavlo.muts@haw-hamburg.de

**Abstract.** Traditional deterministic global optimization methods are often based on a Branch-and-Bound (BB) search tree, which may grow rapidly, preventing the method to find a good solution. Motivated by decomposition-based inner approximation (column generation) methods for solving transport scheduling problems with over 100 million variables, we present two new deterministic decomposition-based successive approximation methods for general modular and/or sparse MINLPs. The first algorithm, called DECOA, is a successive MIP-outer-approximation algorithm based on refining nonconvex polyhedral underestimators of nonlinear functions. The second algorithm, called DIOR, is based on successively improving inner and outer approximations by solving column and cut generation sub-problems using DECOA. Both algorithms are part of Decogo, a new parallel MINLP solver. We describe the basic ideas of both algorithms, and present numerical results with Decogo for instances of the MINLPlib2.

## INTRODUCTION

We assume that a MINLP is reformulated as a *block-separable* optimization problem, of the form

$$\min c^T x \quad \text{s. t.} \quad x \in P, \quad x_k \in G_k, \quad k \in K \quad (1)$$

with

$$P := \{x \in [\underline{x}, \bar{x}] : a_j^T x \leq b_j, j \in J\} \quad \text{and} \quad G_k := G_k^{NLP} \cap G_k^{LP} \cap G_k^{INT}$$

where the  $n$  variables are partitioned into  $|K|$  blocks of dimension  $n_k$ , and  $x_k \in \mathbb{R}^{n_k}$  denotes the variables of the  $k$ -th block. The constraints defining  $G_k$  are called *local*, and the constraints defining  $P$  are called *global*. The linear objective function is defined by  $c \in \mathbb{R}^n$ , and the global linear constraints are defined by  $a_j \in \mathbb{R}^n$  and  $b_j \in \mathbb{R}$  for  $j \in J$ . The nonlinear, linear and mixed-integer local constraint sets are defined by  $G_k^{NLP} := \{y \in \mathbb{R}^{n_k} : g_{kj}(y) \leq 0, j \in [m_k]\}$  with  $g_{kj} : \mathbb{R}^{n_k} \rightarrow \mathbb{R}$ ,  $G_k^{LP} := \{y \in [\underline{x}_k, \bar{x}_k] : a_{kj}^T y \leq b_{kj}, j \in J_k\}$ , with  $a_{kj} \in \mathbb{R}^{n_k}$ ,  $b_{kj} \in \mathbb{R}$ , and  $G_k^{INT} := \mathbb{R}^{n_{k1}} \times \mathbb{Z}^{n_{k2}}$ , respectively. The vectors  $\underline{x}_k, \bar{x}_k \in \mathbb{R}^{n_k}$  determine the lower and upper bounds on the variables. Note that if some variable bounds are not finite and  $G_k$  is bounded, finite lower and upper bounds  $\underline{x}_k, \bar{x}_k \in \mathbb{R}^{n_k}$  can be computed. The restriction to inequality constraints is only for notational simplicity. Furthermore, we use the notation  $G := \prod_{k \in K} G_k$ .

Most exact algorithms for solving the MINLP (1) are based on the spatial branch-and-bound approach and variants like branch-cut-and-price [5] or branch-decompose-and-cut [10], see [4, 3] for an overview of MINLP-solvers. A main difficulty of this approach is a possibly rapidly growing branch-and-bound tree, which makes it difficult to solve large-scale models in reasonable time.

Motivated by the excellent performance of the Column Generation (CG) based Rapid Branching (RB) approach [2, 8] for solving huge network optimization problems with small duality gaps, the Decomposition-based Inner and Outer Refinement (DIOR) algorithm was proposed in [9], which does not use a single potentially large BB search tree. In this paper, a variant of this approach is presented. It uses the new Decomposition-based Outer Approximation (DECOA) algorithm for quickly solving MINLP sub-problems, in order to compute solution candidates, generate cuts and reduce the duality gap.

## THE MIP OUTER APPROXIMATION PROBLEM

DECOA successively refines a MIP Outer Approximation (MIPOA) problem by adding cuts and refining nonconvex polyhedral underestimators, presented in [9], of nonlinear functions. A MIPOA is defined by

$$\min c^T x \quad \text{s. t.} \quad x \in \check{P} \cap \check{G}, \quad (2)$$

where  $\check{P}$  and  $\check{G} := \prod_{k \in K} \check{G}_k$  are convex and nonconvex polyhedral approximations, respectively, defined by

$$\check{P} := \{x \in [\underline{x}, \bar{x}] : A_j x \leq b_j, j \in \check{J}\} \quad \text{and} \quad \check{G}_k := \{y \in G_k^{INT} \cap \check{G}_k^{LP} : \check{g}_{kj}(y) \leq 0, j \in J_k\}$$

with  $\check{G}_k^{LP} := \{y \in [\underline{x}_k, \bar{x}_k] : a_{kj}^T y \leq b_{kj}, j \in \check{J}_k\}$ ,  $\check{J} \supseteq J$ ,  $\check{J}_k \supseteq J_k$ , and  $\check{g}_{kj}$  denotes a piecewise linear underestimator of the nonlinear function  $g_{kj}$ , which is constructed using the DC formulation (Difference of Convex functions)

$$g_{kj}(x) = h_{kj}(x) - \sigma_{kj} \sum_{i \in I_{kj}} q_{ki}(x),$$

defined by the convexified nonlinear and quadratic functions

$$h_{kj}(y) := g_{kj}(y) + \sigma_{kj} \sum_{i \in [n_k]} q_{ki}(y_i) \quad \text{and} \quad q_{ki}(y_i) := (y_i - \underline{x}_{ki})(y_i - \bar{x}_{ki}). \quad (3)$$

The convexification parameters are computed by  $\sigma_{kj} = \max\{0, -v_{kj}\}$  and  $v_{kj}$  is a lower bound of the optimal value of the nonlinear eigenvalue problem

$$\min y^T H_{kj}(x) y \quad \text{s. t.} \quad x \in [\underline{x}_k, \bar{x}_k], y \in \mathbb{R}^{n_k}, \|y\|^2 = 1 \quad (4)$$

with  $H_{kj} = \nabla^2 g_{kj}$ .

A convex polyhedral underestimator of  $h_{kj}$  is defined by

$$\check{h}_{kj}(y) = \max_{\hat{y} \in T_k} \bar{h}_{kj,\hat{y}}(y), \quad \text{where} \quad \bar{h}_{kj,\hat{y}}(y) := h_{kj}(\hat{y}) + \nabla h_{kj}(\hat{y})^T (y - \hat{y}), \quad (5)$$

regarding a sample set  $T_k \subset \check{G}_k^{LP}$ . A piecewise linear overestimator of  $q_{ki}$  is defined by

$$\check{q}_{ki}(y) := q_{ki}(\hat{y}_{ki,v}) \frac{\hat{y}_{ki,v+1} - y}{\hat{y}_{ki,v+1} - \hat{y}_{ki,v}} + q_{ki}(\hat{y}_{ki,v+1}) \frac{y - \hat{y}_{ki,v}}{\hat{y}_{ki,v+1} - \hat{y}_{ki,v}}$$

for  $y \in [\hat{y}_{ki,v}, \hat{y}_{ki,v+1}]$ ,  $v \in \{1, \dots, |B_{ki}| - 1\}$ , regarding breakpoints  $B_{ki} := \{\hat{y}_{ki,1}, \dots, \hat{y}_{ki,|B_{ki}|}\}$ . Then a nonconvex polyhedral underestimator  $\check{g}_{kj}$  of  $g_{kj}$  is given by

$$\check{g}_{kj}(x) := \check{h}_{kj}(x) - \sigma_{kj} \sum_{i \in I_{kj}} \check{q}_{ki}(x).$$

## THE DECOMPOSITION-BASED OUTER APPROXIMATION (DECOA) ALGORITHM

Algorithm 1 describes DECOA in a simplified form. Given an initial upper bound  $\bar{v}$  on the optimal value of (1), and an initial MIPOA problem (2), defined by  $\check{P}$  and  $\check{G}$ , it solves the MINLP (1) by successively refining the MIPOA using *decomposition-based* cut and breakpoint generation, see methods `ADD_CUTS_POINTS` and `ADD_BLOCK_REFINE_CUTS_POINTS`.

The method `INIT_CUTS_POINTS` computes an initial polyhedral relaxation  $\check{G}$ , a first solution candidate  $x^*$ , an upper bound  $\bar{v}$  of the optimal value of the MINLP, and a solution  $\hat{x}$  of the MIPOA. The method `ADD_CUTS_POINTS` computes for  $k \in K$  a solution  $\hat{y}_k$  of the  $k$ -th projection problem

$$\min \|y - \hat{x}_k\|^2 \quad \text{s. t.} \quad y \in G_k^{NLP} \cap \check{G}_k^{LP},$$

and  $\check{G}_k$  is refined by cuts and breakpoints at  $\hat{y}_k$ . For  $k \in K$ , the method `ADD_BLOCK_REFINE_CUTS_POINTS` first computes a solution  $\hat{x}_k$  of the  $k$ -th partly fixed MIPOA regarding a solution candidate  $x^*$

$$\min c^T x \quad \text{s. t.} \quad x \in P \cap \check{G}, \quad x_m = x_m^*, \quad m \in K \setminus \{k\},$$

then calls `ADD_CUTS_POINTS` for generating cuts and breakpoints regarding  $\hat{x}_k$ , and repeats both steps until there is no improvement. The method `ADD_NLP_CUTS` fixes all integer variables of the MINLP (1) using the solution  $\hat{x}$  of the MIPOA. Then a solution  $x^*$  of the resulting NLP is computed, and  $\check{G}_k$  is refined by cuts and points at  $x_k^*$ . Furthermore, the method `TIGHTEN_BOUNDS` adds the cut  $c^T x \leq \bar{v} = c^T x^*$  to  $\check{P}$ , and reduces the intervals  $[\underline{x}_{ki}, \bar{x}_{ki}]$  by *optimality based bound tightening*, similar as in [7].

---

**Algorithm 1** Decomposition-based MIP outer approximation method DECOA

---

```

1: function OASOLVE( $\bar{v}, \check{P}, \check{G}$ )
2:   ( $x^*, \hat{x}, \bar{v}, \check{G}$ )  $\leftarrow$  INITCUTPOINTS( $\bar{v}, \check{P}, \check{G}$ )                                # init the MIPOA
3:   repeat
4:     if  $|\hat{x} - x^*|$  is not reducing then
5:       ( $x^*, \check{G}$ )  $\leftarrow$  ADDFIXEDNLP_CUTS_POINTS( $\hat{x}, \check{G}$ )                                # compute solution
6:       if  $c^T x^* < \bar{v}$  then
7:          $\bar{v} \leftarrow c^T x^*$ 
8:         ( $\check{P}, \check{G}$ )  $\leftarrow$  TIGHTEN_BOUNDS( $x^*, \check{P}, \check{G}$ )                                # reduce  $[\underline{x}, \bar{x}]$ 
9:         ( $\hat{x}, \check{G}$ )  $\leftarrow$  ADDBLOCKREFINECUTPOINTS( $x^*, \check{G}$ )    # gen. cuts and points by block-refine
10:    repeat
11:      ( $\hat{x}, \check{G}$ )  $\leftarrow$  ADDCUTPOINTS( $\hat{x}, x^*, \check{G}$ )                                # gen. cuts and points by projection
12:    until stopping criterion
13:  until  $\bar{v} - c^T \hat{x} < \epsilon$ 
14:  return ( $\bar{v}, \hat{x}, x^*, \check{P}, \check{G}$ )

```

---

## THE DECOMPOSITION-BASED INNER AND OUTER REFINEMENT (DIOR) ALGORITHM

Algorithm 2 describes DIOR, a decomposition algorithm for solving a general MINLP. It uses the methods `AUTO_DECOMP` for transforming the given MINLP into the form (1), `CALC_CURVATURE` for calculating the convexification parameters  $\sigma$  as in (4), `INIT_OA` for initializing  $\check{G}$ , computing the first solution candidate  $x^*$  and the related upper bound  $\bar{v}$ , and a solution  $\hat{x}$  of the MIPOA, `COL_GEN_START` for computing initial inner approximation points  $S$  and refining  $\check{G}$ , `ADD_OPT_CUT` for cutting off a solution candidate  $x^*$ , and `ADD_COL_GEN_CUTS` for reducing the duality gap by adding CG-based cuts. CG and cut generation subproblems are solved by a simplified version of the DECOA Algorithm 1.

---

**Algorithm 2** Decomposition-based Inner- and Outer-Refinement

---

```

1: function DIOR
2:   AUTODECOMP
3:   ( $\bar{v}, \hat{x}, x^*, \check{G}$ )  $\leftarrow$  INIT_OA                                # init. MIPOA and first solution using DECOA
4:   ( $S, \check{G}$ )  $\leftarrow$  COL_GEN_START( $\check{G}$ )                                # init. inner and outer approximation
5:    $\check{P} \leftarrow P$ 
6:   repeat
7:     ( $\check{P}, \check{G}$ )  $\leftarrow$  OPT_CUT( $x^*, S, \check{P}, \check{G}$ )                                # cut off solution
8:     ( $S, \check{G}$ )  $\leftarrow$  ADD_COL_GEN_CUTS( $\hat{x}, S, \check{P}, \check{G}$ )                                # reduce duality gap
9:     ( $\bar{v}, \hat{x}, x^*, \check{P}, \check{G}$ )  $\leftarrow$  OASOLVE( $\bar{v}, \check{P}, \check{G}$ )                                # compute new solution using DECOA
10:  until  $\bar{v} - c^T \hat{x} < \epsilon$  or stopping criterion
11:  return  $x^*$ 

```

---

## NUMERICAL EXPERIMENTS USING DECOGO

A preliminary version of Algorithms 1 and 2 were implemented in Python/Pyomo [6] as part of a new MINLP-solver, called Decogo (Decomposition-based Global Optimizer). The MINLP and MIP subproblems are solved using SCIP

[1, 12], and the LP and NLP subproblems are solved using Ipopt [13]. The global MINLP solver is only used during preprocessing for computing the convexification parameters  $\sigma_{kj}$  by solving (4). After preprocessing, only MIP, LP and NLP subproblems are solved.

Since the implementation of Decogo is not finished, we present only results for convex MINLPs using DECOA. The numerical experiments were performed using 91 instances of the MINLPlib2 [11] with a maximum and average number of 1400 and 230 variables, respectively. The experiments show that the current version of DECOA needs on average 15 MIPOA solutions to solve these MINLP instances. Switching off the decomposition-based cut and point generation methods `ADDCUTSPOINTS` and `ADDBLOCKREFINECUTSPOINTS` significantly increases the number of MIPOA solutions.

## ACKNOWLEDGMENTS

This work was funded by grant 03ET4053B of the German Federal Ministry for Economic Affairs and Energy.

## REFERENCES

- [1] T. Achterberg. SCIP: solving constraint integer programs. *Mathematical Programming Computation*, 1(1):1–41, Jul 2009.
- [2] R. Borndörfer, A. Löbel, M. Reuther, T. Schlechte, and S. Weider. Rapid branching. *Public Transport*, 5:3–23, 2013.
- [3] S. Burer and A. Letchford. Non-convex mixed-integer nonlinear programming: A survey. *Surveys in Operations Research and Management Science*, 17 (2):97–106, 2012.
- [4] M. R. Bussieck and S. Vigerske. *MINLP Solver Software*. [www.math.hu-berlin.de/stefan/minlpsoft.pdf](http://www.math.hu-berlin.de/stefan/minlpsoft.pdf), 2014.
- [5] J. Desrosiers and M. Lübbecke. Branch-price-and-cut algorithms. In J. Cochran, L. Cox, P. Keskinocak, J. Kharoufeh, and J. Smith, editors, *Wiley Encyclopedia of Operations Research and Management Science*. John Wiley & Sons, Inc., 2010.
- [6] W. Hart, C. Laird, J. Watson, and D. Woodruff. *Pyomo—optimization modeling in python*, volume 67. Springer Science & Business Media, 2012.
- [7] H. Nagarajan, M. Lu, S. Wang, R. Bent, and K. Sundar. *An Adaptive, Multivariate Partitioning Algorithm for Global Optimization of Nonconvex Programs*. <https://arxiv.org/abs/1707.02514>, 2017.
- [8] I. Nowak. *Parallel Decomposition Methods for Nonconvex Optimization - Recent Advances and New Directions*, 2014. Proceedings of MAGO.
- [9] I. Nowak, N. Breittfeld, E. M. T. Hendrix, and G. Njacheun-Njanzoua. Decomposition-based inner- and outer-refinement algorithms for global optimization. *Journal of Global Optimization*, 2018.
- [10] T. Ralphs and M. Galati. Decomposition and dynamic cut generation in integer linear programming. *Mathematical Programming*, 106(2):261–285, 2006.
- [11] S. Vigerske. *MINLP Library 2*. <http://www.gamsworld.org/minlp/minlplib2/html>, 2017.
- [12] S. Vigerske and A. Gleixner. SCIP: global optimization of mixed-integer nonlinear programs in a branch-and-cut framework. *Optimization Methods and Software*, 33(3):563–593, 2018.
- [13] A. Wächter. *An Interior Point Algorithm for Large-Scale Nonlinear Optimization with Applications in Process Engineering*. PhD thesis, Carnegie Mellon University, Pittsburgh, USA, <http://researcher.watson.ibm.com/researcher/files/us-andreasw/thesis.pdf>, 2002.