

## Day 16 Task: Docker for DevOps Engineers.



### Docker

Docker is a platform and technology for building, shipping, and running distributed applications, whether on laptops, datacentre VMs, or the cloud. It allows developers to package their applications and dependencies into a portable container, which can then be run on any system with the Docker runtime installed. This makes it easy to deploy and run applications consistently across different environments, and helps to ensure that the application will run correctly regardless of the underlying infrastructure. Docker also provides tools for managing and orchestrating multiple containers, making it a popular choice for building and deploying microservices-based applications.

Docker also provides a tool called Docker Compose, which allows developers to define and run multi-container applications. It uses a YAML file to configure the application's services and networks, and it can spin up and tear down entire environments with a single command.

### Follow the below steps to setup docker

Steps 1 : Create a Ec2 instance in AWS.

Steps 2 : Install Docker in instance.

Commands:

- `sudo yum update -y`

- `sudo amazon-linux-extras install docker`
- `sudo service docker start`
- `sudo systemctl enable docker`
- `sudo usermod -a -G docker ec2-user`
- Log out and log back in again to pick up the new docker group permissions. You can accomplish this by closing your current SSH terminal window and reconnecting to your instance in a new one. Your new SSH session will have the appropriate docker group permissions.
- `docker info`

### Steps 3 : Create a Docker image

Commands :

- `docker pull <image_name>`
- `docker run -d --name <container-name> -p <port mapping> <image_name:tag>`

## Tasks

- Use the `docker run` command to start a new container and interact with it through the command line. [Hint: `docker run hello-world`]

```
ubuntu@ip-172-31-90-202:~$ docker run hello-world
Unable to find image 'hello-world:latest' locally
latest: Pulling from library/hello-world
2db29710123e: Pull complete
Digest: sha256:aa0cc8055b82dc2509bed2e19b275c8f463506616377219d9642221ab53cf9fe
Status: Downloaded newer image for hello-world:latest

Hello from Docker!
This message shows that your installation appears to be working correctly.

To generate this message, Docker took the following steps:
 1. The Docker client contacted the Docker daemon.
 2. The Docker daemon pulled the "hello-world" image from the Docker Hub.
    (amd64)
 3. The Docker daemon created a new container from that image which runs the
    executable that produces the output you are currently reading.
 4. The Docker daemon streamed that output to the Docker client, which sent it
    to your terminal.

To try something more ambitious, you can run an Ubuntu container with:
$ docker run -it ubuntu bash

Share images, automate workflows, and more with a free Docker ID:
https://hub.docker.com/

For more examples and ideas, visit:
https://docs.docker.com/get-started/
```

- Use the `docker inspect` command to view detailed information about a container or image.

```
ubuntu@ip-172-31-90-202:~$ docker run -d --name jenkins-server-dpcker -p 8080:8080
jenkins/jenkins:latest
7f282ca71d2b839070aa53e90c3aa6c03a6388ed2e8c58ad74df2381591440db
ubuntu@ip-172-31-90-202:~$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
7f282ca71d2b	jenkins/jenkins:latest	"/usr/bin/tini -- /u..."	11 seconds ago	Up 10 seconds	0.0.0.0:8080->8080/tcp, :::8080->8080/tcp, 50000/tcp	jenkins-server-dpcker

```
ubuntu@ip-172-31-90-202:~$ docker run -d --name jenkins-server-dpcker -p 8080:8080
jenkins/jenkins:latest
7f282ca71d2b839070aa53e90c3aa6c03a6388ed2e8c58ad74df2381591440db
ubuntu@ip-172-31-90-202:~$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
7f282ca71d2b	jenkins/jenkins:latest	"/usr/bin/tini -- /u..."	11 seconds ago	Up 10 seconds	0.0.0.0:8080->8080/tcp, :::8080->8080/tcp, 50000/tcp	jenkins-server-dpcker

```
ubuntu@ip-172-31-90-202:~$ docker inspect 7f282ca71d2b
```

```
[
  {
    "Id": "7f282ca71d2b839070aa53e90c3aa6c03a6388ed2e8c58ad74df2381591440db",
    "Created": "2023-01-21T08:56:25.034148774Z",
    "Path": "/usr/bin/tini",
    "Args": [
```

```
7bafa292da30be54188",
    "Gateway": "172.17.0.1",
    "IPAddress": "172.17.0.2",
    "IPPrefixLen": 16,
    "IPv6Gateway": "",
    "GlobalIPv6Address": "",
    "GlobalIPv6PrefixLen": 0,
    "MacAddress": "02:42:ac:11:00:02",
    "DriverOpts": null
  }
]
ubuntu@ip-172-31-90-202:~$
```

- Use the `docker port` command to list the port mappings for a container.

```
ubuntu@ip-172-31-90-202:~$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
7f282ca71d2b	jenkins/jenkins:latest	"/usr/bin/tini -- /u..."	7 minutes ago	Up 7 minutes	0.0.0.0:8080->8080/tcp, :::8080->8080/tcp, 50000/tcp	jenkins-server-dpcker

```
ubuntu@ip-172-31-90-202:~$ docker stats 7f282ca71d2b
```

```
Error response from daemon: No such container: 7f282ca71d2d
```

```
ubuntu@ip-172-31-90-202:~$ docker stats 7f282ca71d2b
```

CONTAINER ID	NAME	CPU %	MEM USAGE / LIMIT	MEM %	NET I/O	BLOCK I/O	PIDS
7f282ca71d2b	jenkins-server-dpcker	4.07%	290.5MiB / 966.2MiB	30.07%	5.56MB / 29KB	168MB / 128MB	38

CONTAINER ID	NAME	CPU %	MEM USAGE / LIMIT	MEM %	NET I/O	BLOCK I/O	PIDS
7f282ca71d2b	jenkins-server-dpcker	0.39%	288.5MiB / 966.2MiB	29.86%	5.56MB / 29KB	168MB / 128MB	38

```
ubuntu@ip-172-31-90-202:~$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
7f282ca71d2b	jenkins/jenkins:latest	"/usr/bin/tini -- /u..."	4 minutes ago	Up 4 minutes

```
ubuntu@ip-172-31-90-202:~$ docker port 7f282ca71d2b
```

```
8080/tcp -> 0.0.0.0:8080
8080/tcp -> :::8080
```

- Use the `docker stats` command to view resource usage statistics for one or more containers.

CONTAINER ID	NAME	CPU %	MEM USAGE / LIMIT	MEM %	NET I/O	BLOCK I/O	PIDS
7f282ca71d2b	jenkins-server-dpcker	0.29%	288.5MiB / 966.2MiB	29.86%	5.56MB / 29kB	168MB / 128MB	38

- Use the `docker top` command to view the processes running inside a container.

```
ubuntu@ip-172-31-90-202:~$ docker ps
CONTAINER ID   IMAGE             COMMAND                  CREATED        STATUS        PORTS
7f282ca71d2b   jenkins/jenkins:latest  "/usr/bin/tini -- /u..." 11 minutes ago Up 11 minutes 0.0.0.0:8080->8080/tcp, :::8080->8080/tcp, 50000/tcp
jenkins-server-dpcker
ubuntu@ip-172-31-90-202:~$ docker top 7f282ca71d2b
CONTAINER ID   PID      PPID      CPU      TIME      TTY      TIME      CMD
7f282ca71d2b   1577     1556      0%       08:56     ?        00:00:00  /usr/bin/tini --
7f282ca71d2b   1577     1556      0%       08:56     ?        00:00:00  java -Duser.home=/var/jenkins_home -Djenkins.model.Jenkins.slaveAgentPort=50000 -Dhudson.lifecycle=
hudson.lifecycle.ExitLifecycle -jar /usr/share/jenkins/jenkins.war
```

- Use the `docker save` command to save an image to a tar archive.

```
ubuntu@ip-172-31-90-202:~$ docker ps
CONTAINER ID   IMAGE             COMMAND                  CREATED        STATUS        PORTS
7f282ca71d2b   jenkins/jenkins:latest  "/usr/bin/tini -- /u..." About an hour ago Up About an hour 0.0.0.0:8080->8080/tcp, :::8080->8080/tcp
jenkins-server-dpcker
ubuntu@ip-172-31-90-202:~$ docker save jenkins/jenkins > jenkins_jenkins.tar
ubuntu@ip-172-31-90-202:~$
```

- Use the `docker load` command to load an image from a tar archive.

```
ubuntu@ip-172-31-90-202:~$ docker save jenkins/jenkins > jenkins_jenkins.tar
ubuntu@ip-172-31-90-202:~$ docker load -i jenkins_jenkins.tar
Loaded image: jenkins/jenkins:latest
ubuntu@ip-172-31-90-202:~$
```