



Présentation CCP Développeur Web & Web mobile Partie Back End

20/11/2025

Sommaire

1. Résumé du projet
2. Contexte du projet
3. Outils
4. Architecture globale
5. Méthode Merise
6. Sécurité
7. Extrait de code
8. Performances
9. Tests
10. Crates
11. Déploiement
12. Compétences couvertes
13. Conclusion




Contexte du projet : Introduction



PokeRNCP est une API REST de type Pokédex, elle permet aux utilisateurs de créer un compte et de collectionner les Pokémon des 6 premières générations.

Contexte du projet : Equipe




Xabi Martinez

32 ans

Holberton C#24

Bordeaux

Contexte du projet : Contraintes



Temps



Organisation



Compétences


Contexte du projet : Utilisation

- CRUD de compte
- Capture de Pokémon
- Data sur un Pokémon capturé
- Possibilité de trouver une Pokémon spécifique

Gestion du projet : Outils




Architecture globale



Methode Merise

- MCD : Users, Pokémon, User_Pokemon
- Relation $N \leq N$ capturée
- Attribut dérivé caught
- Contraintes UNIQUE + cascade
- Modèle stable & normalisé

MCD



MPD

USERS			
uuid	id	PK	
string	username		UNIQUE, NOT NULL
string	email		UNIQUE, NULLABLE
string	password		NOT NULL
timestampz	created_at		

POKEMON			
int	id	PK	
string	name		UNIQUE, NOT NULL
string	type1		NOT NULL
string	type2		NULLABLE
int	base_hp		
int	base_attack		
int	base_defense		
int	base_sp_attack		
int	base_sp_defense		
int	base_speed		
int	dex_no		
string	image_url		
double	height_m		
double	weight_kg		
text	description		

attrape (one-to-many)

est attrapé par (one-to-many)

USER_POKEMON			
int	id	PK	
uuid	user_id	FK	
int	pokemon_id	FK	
string	nickname		
timestampz	discovered_at		UNIQUE(user_id, pokemon_id)

Initialisation DB

```
init_db

-- Requis pour gen_random_uuid()
CREATE EXTENSION IF NOT EXISTS pgcrypto;

-- ===== TABLE USERS =====
CREATE TABLE IF NOT EXISTS users (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    username VARCHAR(50) UNIQUE NOT NULL,
    email VARCHAR(100) UNIQUE,
    password TEXT NOT NULL,
    created_at TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-- ===== TABLE POKEMON =====
CREATE TABLE IF NOT EXISTS pokemon (
    id SERIAL PRIMARY KEY,
    name VARCHAR(100) UNIQUE NOT NULL,
    type1 VARCHAR(20) NOT NULL,
    type2 VARCHAR(20),
    base_hp INTEGER,
    base_attack INTEGER,
    base_defense INTEGER,
    base_sp_attack INTEGER,
    base_sp_defense INTEGER,
    base_speed INTEGER
);

-- ===== TABLE ASSOCIATIVE USER_POKEMON =====
CREATE TABLE IF NOT EXISTS user_pokemon (
    id SERIAL PRIMARY KEY,
    user_id UUID NOT NULL REFERENCES users(id) ON DELETE CASCADE,
    pokemon_id INTEGER NOT NULL REFERENCES pokemon(id),
    nickname VARCHAR(50),
    discovered_at TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    UNIQUE(user_id, pokemon_id)
);

-- ===== INDEX =====
CREATE INDEX IF NOT EXISTS idx_user_pokemon_user_id ON user_pokemon(user_id);
CREATE INDEX IF NOT EXISTS idx_user_pokemon_pokemon_id ON user_pokemon(pokemon_id);
```

Migration DB

```
migration

-- Migration: add_pokemon_image_and_number (UP)
-- Ajoute des colonnes pour stocker le numéro du Pokédex et l'URL de l'image

ALTER TABLE pokemon
  ADD COLUMN IF NOT EXISTS dex_no INTEGER,
  ADD COLUMN IF NOT EXISTS image_url TEXT;
```

```
migration

-- Drop weaknesses column and add description to pokemon
ALTER TABLE pokemon
  DROP COLUMN IF EXISTS weaknesses,
  ADD COLUMN IF NOT EXISTS description TEXT;
```

```
migration

-- Migration: add_pokemon_measurements_and_weaknesses (UP)
-- Ajoute taille/poids (en unités SI) et faiblesses

ALTER TABLE pokemon
  ADD COLUMN IF NOT EXISTS height_m DOUBLE PRECISION,
  ADD COLUMN IF NOT EXISTS weight_kg DOUBLE PRECISION,
  ADD COLUMN IF NOT EXISTS weaknesses TEXT[];
```

Sécurité de l'API

- JWT access court / refresh long
- Cookies HttpOnly, SameSite Lax/Strict
- Argon2 pour les mots de passe
- Middlewares Axum
- Mitigation CSRF (cookies + header)

Flux applicatifs

- Login : validation + tokens
- Refresh automatique
- Listing Pokémon
- Capture (idempotente)
- Vérifications & permissions

Extraits de code

```
catch function

pub async fn catch(
    CurrentUser(user_id): CurrentUser,
    State(pool): State<PgPool>,
    Json(payload): Json<CatchByNamePayload>,
) → ApiResult<(axum::http::StatusCode, String)> {
    let pokemon_id = sqlx::query_scalar::<_, i32>(r#"SELECT id FROM pokemon WHERE name = $1"#)
        .bind(&payload.name)
        .fetch_optional(&pool)
        .await
        .map_err(to_500)?
        .ok_or_else(|| not_found("Pokémon introuvable."))?;

    let _ = sqlx::query(
        r#"
        INSERT INTO user_pokemon (user_id, pokemon_id, nickname)
        VALUES ($1, $2, $3)
        ON CONFLICT (user_id, pokemon_id) DO NOTHING
        "#,
    )
        .bind(user_id)
        .bind(pokemon_id)
        .bind(payload.nickname)
        .execute(&pool)
        .await
        .map_err(to_500)?;

    created("Pokémon marqué comme capturé.")
}
```

```
list_all function

pub async fn list_all(
    CurrentUser(user_id): CurrentUser,
    State(pool): State<PgPool>,
) → ApiResult<Json<Vec<PokemonWithCaught>>> {
    let rows = sqlx::query_as::<_, PokemonWithCaught>(
        r#"
        SELECT
            p.id          AS id,
            p.name        AS name,
            p.type1       AS type1,
            p.type2       AS type2,
            p.dex_no      AS dex_no,
            p.image_url   AS image_url,
            EXISTS (
                SELECT 1 FROM user_pokemon up
                WHERE up.user_id = $1 AND up.pokemon_id = p.id
            )             AS caught
        FROM pokemon p
        ORDER BY p.id
        "#,
    )
        .bind(user_id)
        .fetch_all(&pool)
        .await
        .map_err(to_500)?;

    Ok(Json(rows))
}
```

Performance et optimisations

- Rust + Tokio
- Requêtes compilées SQLx
- Démarrage : retry DB
- Idempotence et LIMIT
- Calcul dynamique caught

Qualité et tests

- Tests d'intégration (reqwest)
- nextest : exécution rapide
- Linter clippy
- Séparation clean du code
- Documentation claire

Tests

```
db_test function

#[tokio::test]
async fn la_base_de_donnees_repond() {
    let pool = common::test_pool().await;
    let one: i32 = sqlx::query_scalar("SELECT 1")
        .fetch_one(pool)
        .await
        .unwrap();
    assert_eq!(one, 1);
}
```

```
unique_user_test function

#[tokio::test]
async fn create_user_201_et_conflict_409() {
    let (base, handle) = start_server().await;
    let client = request::Client::new();
    let unique = uuid::Uuid::new_v4().to_string();
    let username = format!("user_{}", unique);
    let email = format!("{}", unique, "@example.com");
    let res = client
        .post(format!("{}/api/users", base))
        .json(&json!({
            "username": username,
            "email": email,
            "password": "Password123!"
        }))
        .send()
        .await
        .unwrap();
    assert_eq!(res.status(), StatusCode::CREATED);

    let res = client
        .post(format!("{}/api/users", base))
        .json(&json!({
            "username": username,
            "email": email,
            "password": "Password123!"
        }))
        .send()
        .await
        .unwrap();
    assert_eq!(res.status(), StatusCode::CONFLICT);

    handle.abort();
    delete_user(&username).await;
}
```

Tests

```
Nexttest run ID 30847ad9-3b4b-483a-a030-82761db22e59 with nextest profile: default
Starting 17 tests across 8 binaries
PASS [ 0.709s] pokedex_rncp_backend::health_test get_root_retourne_bienvenue
PASS [ 0.710s] pokedex_rncp_backend::db_test la_base_de_donnees_repond
PASS [ 0.718s] pokedex_rncp_backend::auth logout_definit_cookies_expirants
PASS [ 0.712s] pokedex_rncp_backend::health_test path_inconnu_retourne_404
PASS [ 0.727s] pokedex_rncp_backend::pokemon list_requiert_auth
PASS [ 0.744s] pokedex_rncp_backend::auth me_requiert_authentification
PASS [ 0.741s] pokedex_rncp_backend::auth tokens_invalides_donnent_401
PASS [ 1.503s] pokedex_rncp_backend::auth me_ok_avec_bearer
PASS [ 1.542s] pokedex_rncp_backend::auth me_ok_avec_cookie_auth
PASS [ 1.554s] pokedex_rncp_backend::auth refresh_token_ok_avec_cookie_refresh
PASS [ 1.555s] pokedex_rncp_backend::auth refresh_token_requiert_bearer_et_definit_cookie
PASS [ 1.130s] pokedex_rncp_backend::pokemon list_search_catch_get
PASS [ 1.172s] pokedex_rncp_backend::user delete_user_soi_meme
PASS [ 1.604s] pokedex_rncp_backend::user create_user_201_et_conflit_409
PASS [ 1.890s] pokedex_rncp_backend::user update_user_refuse_si_different
PASS [ 2.219s] pokedex_rncp_backend::user update_user_soi_meme_modifie_username_email_et_password
PASS [ 3.182s] pokedex_rncp_backend::auth reset_mot_de_passe_retourne_token_et_confirmation_mise_a_jour
```

Crates utilisés

Tokio

A runtime for writing reliable, asynchronous, and slim applications with the Rust programming language. It is:

- **Fast:** Tokio's zero-cost abstractions give you bare-metal performance.
- **Reliable:** Tokio leverages Rust's ownership, type system, and concurrency model to reduce bugs and ensure thread safety.
- **Scalable:** Tokio has a minimal footprint, and handles backpressure and cancellation naturally.

crates.io v1.48.0 license MIT CI passing chat 2k online

[Website](#) | [Guides](#) | [API Docs](#) | [Chat](#)

Overview

Tokio is an event-driven, non-blocking I/O platform for writing asynchronous applications with the Rust programming language. At a high level, it provides a few major components:

- A multithreaded, work-stealing based task [scheduler](#).
- A reactor backed by the operating system's event queue (epoll, kqueue, IOCP, etc.).
- Asynchronous [TCP and UDP](#) sockets.

These components provide the runtime components necessary for building an asynchronous application.

RustCrypto: Argon2

 docs passing argon2 no status license Apache2.0/MIT rustc 1.65+
zulip join chat

Pure Rust implementation of the [Argon2](#) password hashing function.

[Documentation](#)

About

Argon2 is a memory-hard [key derivation function](#) chosen as the winner of the [Password Hashing Competition](#) in July 2015.

It implements the following three algorithmic variants:

- **Argon2d:** maximizes resistance to GPU cracking attacks
- **Argon2i:** optimized to resist side-channel attacks
- **Argon2id:** (default) hybrid version combining both Argon2i and Argon2d

Support is provided for embedded (i.e. `no_std`) environments, including ones without `alloc` support.

Déploiement professionnel

- Docker multi-stage Rust
- docker-compose (API + DB)
- Images légères
- Variables d'environnement
- Tunnel HTTPS possible

Compétences RNCP couvertes

- Modélisation Merise & SQL relationnel
- Développement d'API REST sécurisée
- Sécurité : hachage, JWT, cookies
- Tests, conteneurisation, déploiement

Conclusion



Travail fourni

- Système de connexion
- Système de capture dynamique
- Projet complet & opérationnel



Apprentissage

- Découverte d'Axum
- Approche professionnelle
- Sécurité approfondie



Futur

- Ajout d'une CI/CD
- Ajout des features