



WATERCOLOR



Bashundhara
Exercise Book
Write Your Future

Computer Graphics (CSE - 4201) TMM

Naima Islam Nodi

13.01.19

Ref. Book :

Computer Graphics (C version) 4th edition

- Donald Thearn, M. Pauline
Baker

— X —

STB

and friends

Author

Editor

Illustrator

Designer

Photographer

Printer

Publisher

Editor-in-Chief

Editorial Assistant

Editorial Advisor

Editorial Consultant

Editorial Manager

Editorial Producer

Editorial Supervisor

Editorial Writer

Editorial Associate

Editorial Intern

Editorial Fellow

Editorial Graduate




14.01.19

CRT

Intended (i)

Random Scan Displays

Colors CRT:



LCD°

3D:


Creates different image in different eyes.

— X —

16.01.19.

2.4

* Coordinate Representations:



→ Local / Modeling coordinate.

Graphics Functions:

Primitive

Geometric Transformations

Viewing Transformations

—x—

"Chapter - 3"

* Points & Lines:

line drawing algorithms:

$$y = mx + c$$


$$m = \frac{y_2 - y_1}{x_2 - x_1}$$

$$b = y_1 - mx_1$$

$$\Delta y = m \Delta x$$

$$\Delta x = \frac{\Delta y}{m}$$

DDA:



$$m = \frac{9-5}{9-4} = \frac{4}{5} = 0.8$$

x	y	Nearest integer
4	5	5
5	5.8	6
6	6.6	7
7	7.4	7
8	8.2	8
9	9	9

$(4, 5), (9, 10)$

$$\Rightarrow m = \frac{10 - 5}{9 - 4} = \frac{5}{5} = 1$$

$(4, 5), (9, 11)$

$$\Rightarrow m = \frac{6}{5} = 1.2 > 1$$

calculate x here,
with respect to y
as the change of
 y is greater.

$$\text{Now, } \frac{1}{1.2} = 0.8 \left(\frac{1}{m} \text{ if } m > 1 \right)$$

y	x	nearest integer
5	4	4
6	4.8	5
7	5.6	6
8	6.4	6
9	7.2	7
10	8	8
11	8.8	9


equ. 3.6, 3.7

$(5, 6), (10, 15)$

$$m = \frac{15 - 6}{10 - 5} = 1.8$$


$(1/m)$
Now, $\frac{1}{1.8} = 0.5$

y	x	nearest integer
6	5	5
7	5.6	6
8	6.2	6
9	6.8	7
10	7.4	7
11	8	8
12	8.6	9
13	9.2	9
14	9.8	10
15	10.4	10




21.01.19.

Bresenham's Algorithm



x_k, y_k

$x_{k+1}, y_k / y_{k+1}$



$$\Delta x = 4$$

$$\Delta y = 2$$

$$2 \Delta y = 4$$

$$2 \Delta y - 2 \Delta x = 4 - 8 = -4$$

$$P_0 = 2 \Delta y - \Delta x = 4 - 4 = 0$$

P = Decision Parameter

$$P = 4 - 8 = -4$$

$$\rightarrow (5, 6), (10, 15)$$

$$\Delta x = 5$$

$$\Delta y = 9$$

$$2\Delta y = 18$$

$$2\Delta y - 2\Delta x = 8$$

$$P_0 = 2\Delta y - \Delta x = 18 - 5 = 13$$

$$\rightarrow (4, 5), (9, 9).$$

$$\boxed{\Delta x = 5}$$

$$\Delta y = 4$$

$$2\Delta y = 8$$

$$2\Delta y - 2\Delta x = 8 - 10 = -2$$


$$P_0 = 2\Delta y - \Delta x = 8 - 5 = 3$$

$$P_{k+1} = 3 + 2\Delta y - 2\Delta x$$

$$= 3 + 8 - 10 = 1$$

$$\cancel{P_{k+1} = 1 + 8 - 10 = -1}$$

$$\cancel{P_{k+1} = -1 + 8 - 10 = -3}$$



$$(-20, 10), (30, 18)$$


$$P_{k+1} = 1 + 8 - 10 = -1$$

$$\begin{aligned} P_{k+1} &= P_k + 2\Delta y = -1 + 8 \\ &= 7 \end{aligned}$$

$$P_{k+1} = P_k + 2\Delta y - 2\Delta x$$

$$= 7 + 8 - 10$$

$$= 5$$



$$\Rightarrow (-20, 10), (30, 18)$$

$$\Delta x = 10$$

$$\Delta y = 8$$

$$2\Delta y = 16$$

$$2\Delta y - 2\Delta x = 16 - 20 = -4$$

$$P_{k+1} = P_k + 2\Delta y$$

$$P_0 = 2\Delta y - \Delta x = 16 - 10 = 6$$

$$(20, 10) \quad (21, 11)$$

$$P_{K+1} = P_K + 2\Delta y - 2\Delta x$$

$$= 6 + 16 - \cancel{20}$$

$$= 2$$

(22, 12)

$$P_{K+1} = 2 + 16 - 20$$

$$= -2$$

(23, 12)

$$P_{K+1} = P_K + 2\Delta y$$

$$= -2 + 16$$

$$= 14$$

(23, 12) (24, 13)

$$P_{K+1} = P_K + 2\Delta y - 2\Delta x$$

$$= 14 + 16 - 20$$

$$= 10$$

(24, 13) (25, 14)

$$P_{k+1} = 10 + 16 - 20 \\ = 6$$

~~(25, 14)~~ (26, 15)

$$P_{k+1} = 6 + 16 - 20 \\ = 2$$

~~(26, 15)~~ (27, 16)

$$P_{k+1} = 2 + 16 - 20 \\ = -2$$

~~26, 15~~ ~~(27, 15)~~ (28, 16)

$$P_{k+1} = P_k + 2 \Delta y \\ = -2 + 16 \\ = 14$$

~~(28, 16)~~ (29, 17)

$$P_{k+1} = 14 + 16 - 20 = 10$$

~~(29, 17)~~ (30, 18)

$$P_{k+1} = 10 + 16 - 20$$

≥ 6

$$(30, 18)$$

Calculation:


23.01.19

$$(x_i + 1), (y_i)$$

$$(x_i + 1), (y_i + 1)$$

$$d_1 = \delta - g_1$$

$$d_2 = (y+1) - y$$



$$\therefore d_1 = m(x_0 + 1) + b - y_0$$

$$y = m(x_1 + 1) + b$$

$$d_2 = (y_i + 1) - y = y_i + 1 - m(x_i + 1) - b$$

$$d_1 - d_2 = 2m(x_i + 1) - 2y_i + 2b - 1$$

if $d_1 - d_2 < 0$ then $y_{i+1} \leftarrow y_i$

(more floating point calculation)

if $d_1 - d_2 > 0$ then $y_{i+1} \leftarrow y_i + 1$

CT-1 : (27.01.19) → 10:50 am.

CRT, LCD → How it works?

DDA, Bresenham's algorithm.


→ x

"LAB"

23.01.19

→ 800 pixels

600 ↓
y



800, 600

int main()

{ int gd=DETECT, gm;

initgraph(&gd, &gm, " ");

line (150, 150, 450, 150);

line (150, 200, 450, 200);


line (150, 250, 450, 250);

getch();

closegraph();


}

→ x



27.01.19.

Parallel Line Algorithm:



* divide the line into some predefined segments & define their starting & ending for each segment. Then use line drawing algorithm for every segment with two or more processors parallelly.

Circle - Generating algorithm:

$$x^2 + y^2 = r^2 \quad [\text{if the center is at } (0,0)] .$$



$$\Rightarrow y^2 = r^2 - x^2$$

$$x^2 + y^2 = r^2$$

(when the center of a circle is at $(0,0)$)

If not, then,

$$(x - x')^2 + (y - y')^2 = r^2$$





* If first square then, square root. So an expensive algorithm.

* If the center is not at $(0,0)$, then


$$(x - x_c)^2 + (y - y_c)^2 = r^2$$

$$\left. \begin{array}{l} x = x_c + r \cos \theta \\ y = y_c + r \sin \theta \end{array} \right\}$$
 still the algorithm is slow



28.01.19


(i)




$$\text{always } x = x + 1$$

$$y = y \text{ or } y - 1$$

If $x^2 + y^2 > r^2$ then the point is out of the circle, if $x^2 + y^2 < r^2$ then the point is in the circle.



$$x^2 + y^2 < r^2$$



$$x^2 + y^2 > r^2$$

$$(x, y) = (2, 10) \quad r = 10$$

$$P_0 = 1 - r = 1 - 10 = -9$$

$$2x_0 = 0$$


$$2y_0 = 0$$

— X —

30.01.19

1. $f(x, y) = 0 \rightarrow$ The point lies on the circle
2. $f(x, y) < 0 \rightarrow$ The point lies within "
3. $f(x, y) > 0 \rightarrow$ The " " outside "

$$f(x, y) = (x - x_c)^2 + (y - y_c)^2 - r^2$$



Midpoint circle Algorithm:


$$P_k = f(x_k + 1, y_k - \frac{1}{2})$$

$$= (x_k + 1)^2 + (y_k - \frac{1}{2})^2 - r^2$$


— x —

03.02.19.

Ellipse - generating Algorithm:



$$d_1 + d_2 = \text{constant} \quad (\text{for every point } P)$$



$$x = x_c + r_n \cos \theta$$

$$y = y_c + r_n \sin \theta$$

Ellipse \rightarrow H.C.G.

(Algorithm + derivation)

For computer screen ($x, y_{\max} - y$)

$\xrightarrow{\hspace{1cm}} x \xleftarrow{\hspace{1cm}}$

04.02.19


CT-1.

—x—

06.02.19

Pixel Addressing and object geometry:

* use Inside part of a closed area




outside the
boundary


—x—

"LAB"

06.02.19.




$$\begin{aligned}
 & x = 1 - 200 \\
 & d = 450 - 600
 \end{aligned}$$





DDA Algorithm


put pixel (x, y , ~~start color~~)



60



$$\begin{aligned}
 & 450 - 500 \rightarrow x \\
 & 100 - 150 \rightarrow y
 \end{aligned}$$




11.02.19.

Inside-Outside Test:

* Odd-Even Rule: (If direction is not given)

If intersects odd lines \rightarrow inside area

If intersects even lines \rightarrow outside area.



* Nonzero-Winding-Numbers Rule: (If direction $\theta = 0$ given)

If right to left $\rightarrow +1$ ($v = 0+1$)


elseif left to right $\rightarrow -1$

After loop, Output zero \rightarrow outside area

Output Nonzero \rightarrow Inside area

Curve lines :

Boundary fill Algorithm :



17.02.19

18.02.19

Flood fill :

Font

Sherif, Sans Sherif

"Chapter-4"

* Line Attribute:

butt caps

round caps

projecting square caps

miter join

Round join

bevel join



Single line

width increase

Multiple line

width increase

* Line Gap:

Pen and brush options:

CT-2

Till now

Wednesday - 27.02.19.

2nd period.

—x—

20.02.19.

Curve Attributes:

* Color & Grayscale level:

$$\text{intensity} = 0.5 (\min(r, g, b) + \max(r, g, b))$$

* Area fill Attributes:

Marker Attributes:

Anti Aliasing:

$$f_s = 2 f_{\text{max}}$$

$$\Delta x_0 = \frac{\Delta x_{\text{cycle}}}{2}$$

Used to reduce stairy line.

Super Sampling

$$\text{pixel color} = (5 \cdot \text{red} + 4 \cdot \text{blue}) / 9$$

1	2	1
-2	4	2
1	2	1

"LAB"

20.02.19

24.02.19

"Chapterb - 5"

Basic Transformations:

Translation :

$$x' = x + t_x,$$

$$y' = y + t_y.$$

(t_x, t_y) translation vector.



25.02.19

Rotation

Scaling

27.02.19.

3x3 Matrix:

$$\begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$\begin{bmatrix} x' \\ y' \\ z \end{bmatrix} = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \cdot \begin{bmatrix} x \\ y \\ z \end{bmatrix}$$

Translation

$$P' = T(t_x, t_y) \cdot P$$

$$\begin{bmatrix} x' \\ y' \\ z \end{bmatrix} = \begin{bmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \cdot \begin{bmatrix} x \\ y \\ z \end{bmatrix}$$

Rotation

* Translation:

$$P = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \quad P' = \begin{bmatrix} x'_1 \\ x'_2 \end{bmatrix} \quad T = \begin{bmatrix} t_x \\ t_y \end{bmatrix}$$

* Rotation:

$$R = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$$

* Scaling:

$$\begin{bmatrix} x' \\ y \end{bmatrix} = \begin{bmatrix} s_x & 0 \\ 0 & s_y \end{bmatrix} \cdot \begin{bmatrix} x \\ y \end{bmatrix}$$

$$P' = S \cdot P$$

General Pivot - Point Rotations:

$$\begin{bmatrix} \cos\theta & -\sin\theta & x_n(1-\cos\theta) \\ \sin\theta & \cos\theta & - \\ 0 & 0 & 1 \end{bmatrix}$$

$$A \cdot B \cdot C = (A \cdot B) \cdot C = A \cdot (B \cdot C)$$

In case of Rotation & scaling \rightarrow order should be maintained.

* Reflection:

$$\begin{bmatrix} 1 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \text{ Reflect with respect to } x\text{-axis.}$$


$$\begin{bmatrix} -1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Reflected
with respect to y-axis

$$\begin{bmatrix} -1 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Reflect with respect to both
x and y - axis

* Shearing



$$\begin{bmatrix} 1 & sh_x & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$x' = x + sh_x \cdot y$$

$$y' = y$$

Shear with respect to x-axis.

— x —