

# Software Requirements Specification (SRS)

## ADC (Analog To Digital Converter)

**Authors:** Burners Team (Ahmed Salah, Basem Moufreh, Hassan El Gabass , Hazem El Morshedi , Mohamed Safwat).

**Customer:** NTI

**Instructor:** Mahmoud Ali, Ahmed Abd El Reheem.

### Table Of Content

<b>1 Introduction .....</b>	<b>2</b>
<b>1.1 Purpose: .....</b>	<b>2</b>
<b>1.2 Scope.....</b>	<b>2</b>
<b>1.3 Definitions, Acronyms, and Abbreviations:.....</b>	<b>2</b>
<b>2 System overview .....</b>	<b>3</b>
<b>2.1 Description .....</b>	<b>3</b>
<b>2.2 System Context .....</b>	<b>4</b>
<b>3 Functional Requirements.....</b>	<b>4</b>
<b>3.1 Configuration: .....</b>	<b>4</b>
<b>3.2 Synchronous Conversion .....</b>	<b>4</b>
<b>3.3 Asynchronous Conversion .....</b>	<b>4</b>
<b>3.4 Multiple conversions .....</b>	<b>5</b>
<b>4 Non-functional Requirements .....</b>	<b>5</b>
<b>4.1 Usability: .....</b>	<b>5</b>
<b>4.2 Reliability: .....</b>	<b>5</b>
<b>4.3 Power consumption: .....</b>	<b>5</b>

# 1 Introduction

This document contains the Software Requirements Specification (SRS) for the ADC software driver.

**1.1 Purpose:** The purpose of this document is to define the requirements for the software system that interacts with an ADC (Analog to Digital converter).

**1.2 Scope** This document covers the functional and non-functional requirements of the ADC software system.

## 1.3 Definitions, Acronyms, and Abbreviations:

ADC: Analog to Digital Converter.


SAR: Successive approximation register

## 2 System overview

### 2.1 Description

An analog-to-digital converter (ADC) is a device that converts an analog signal, such as a voltage or current, into a digital signal. This allows the signal to be processed and stored by a Microprocessor or other digital device.

## 2.2 System Context



## 3 Functional Requirements

### 3.1 Configuration:

To be able to choose the voltage reference and the left hand adjustment and the prescaler.

### 3.2 Synchronous Conversion

Waiting until the Sensor data is read from a specific channel and the ADC Complete the conversion.

### 3.3 Asynchronous Conversion

Don't wait until the Sensor data is read from a specific channel and the ADC Complete the conversion and use interrupt to be able to do any required actions.

### 3.4 Multiple conversions

Being able to perform a multiple conversions from different channels on the ADC.

## 4 Non-functional Requirements

### 4.1 Usability:

Define the usability requirements, including user interface guidelines, intuitive navigation, and clear readability.

### 4.2 Reliability:

It is important that the ADC is reliable and durable for any application.

### 4.3 Power consumption:

The ADC should consume as little power as possible. Power consumption is typically measured in mill watts (mW).

## 5 State Machine

