

Software Requirements Specification (SRS)

Clear Timer on Compare (CTC) Mode for Timer2

Authors: Burners Team (Ahmed Salah, Basem Moufreh,
Hassan El Gabass , Hazem El Morshedi , Mohamed Safwat).

Customer: NTI

Instructor: Mahmoud Ali, Ahmed Abd El Reheem

Contents

1. System Overview	2
2. Functional Requirements.....	2
2.1 Timer2 Initialization.....	2
2.2 Timer Start/Stop.....	2
2.3 Output Compare Interrupt	2
2.4 Read Timer Value	2
2.5 Timer2 Counter Behavior	2
3. Non-Functional Requirements.....	3
3.1 Performance.....	3
3.2 Reliability.....	3
3.3 Precision	3

1. System Overview

The Timer2 module in the AVR ATmega32 microcontroller shall be configured to operate in the Clear Timer on Compare (CTC) Mode. In this mode, Timer2 will count up from an initial value of 0 to a user-defined compare value, triggering an output compare match interrupt when the counts match. This mode is suitable for generating precise time intervals and periodic events.

2. Functional Requirements

2.1 Timer2 Initialization

- The system shall provide a function to initialize Timer2 in CTC Mode.
- The user shall be able to specify the initial value (preload value) for Timer2.
- The user shall be able to set the compare value for generating interrupts.

2.2 Timer2 Start/Stop

- The system shall offer functions to start and stop Timer.
- Starting the timer shall initiate the counting process from the specified initial value.
- Stopping the timer shall freeze the count.

2.3 Output Compare Interrupt

- The system shall allow enabling and disabling of the Timer2 output compare interrupt.
- When enabled, Timer2 shall generate an interrupt when the count matches the specified compare value.
- The system shall provide a user-defined interrupt service routine (ISR) that will be executed upon compare match.

2.4 Read Timer Value

- The system shall provide functions to read the current value of Timer2.
- Reading the timer shall return the current count value.

2.5 Timer2 Counter Behavior

- Timer2 shall increment from the initial value to the user-defined compare value.

- When the count matches the compare value, it shall trigger the output compare interrupt.
- The timer shall stop counting when the output compare interrupt is triggered.

3. Non-Functional Requirements

3.1 Performance

- Timer2 shall operate accurately at the specified clock frequency.
- The software shall be optimized for minimal CPU usage, ensuring it does not introduce significant overhead on the system.

3.2 Reliability

- Timer2 shall operate reliably without unintended resets or malfunctions.
- The interrupt handling for the Timer2 output compare match shall not disrupt the normal operation of the system.

3.3 Precision

- The system shall provide precise control over timing intervals with minimal deviation from the specified compare value.