Efficient Implementation Strategies for Block Ciphers on ARMv8

Bachelorarbeit

Bastian Engel

April 3, 2023

Abstract

Lorem ipsum dolor [1] sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Declaration

I hereby declare that ...

Contents

Chapter 1

Introduction

1.1 Notation

1.2 Block ciphers

Securing communication channels between different parties has been a long-term subject of study for cryptographers and engineers which is essential to our modern world to cope with ever-increasing amounts of devices producing and sharing data. The main way to facilitate high-throughput, confidential communications nowadays is through the use of symmetric cryptography in which two parties share a common secret, called a key, which allows them to encrypt, share and subsequently decrypt messages to achieve confidentiality against third parties. Ciphers can be divided into two categories; block ciphers, which always encrypt fixed-sized messages called blocks, and stream ciphers, which continuously provide encryption for an arbitrarily long, constant stream of data.

A block cipher can be defined as a bijection between the input block (the message) and the output block (the ciphertext). For any block cipher with block size n, we denote the key-dependent encryption and decryption functions as $E_K, D_K : \mathbb{F}_2^n \to \mathbb{F}_2^n$. The simplest way to characterize this bijection is through a lookup table which yields the highest possible performance as each block can be encrypted by one simple lookup depending on the key and the message. This is not practical though due to most ciphers working with block and key sizes $n, |K| \geq 64$. For a block cipher with $n = 64, |K| = 128$, a space of $2^{64}2^{128}64 = 2^{198}$ is necessary. Considering modern consumer hard

disks being able to store data in the order of 2^{40}, it is easy to see that a lookup table is wholly impractical. We therefore describe block ciphers algorithmically which opens up possibilities for different tradeoffs and security concerns.

1.2.1 GIFT

`GIFT`[1], first presented in the *CHES 2017* cryptographic hardware and embedded systems conference, is a lightweight block cipher based on a previous design called `PRESENT`, developed in 2007. Its goal is to offer maximum security while being extremely light on resources. Modern battery-powered devices like RFID tags or low-latency operations like on-the-fly disc encryption present strong hardware and power constraints. GIFT aims to be a simple, low-energy cipher suited for these kinds of applications.

`GIFT` comes in two variants; `GIFT-64` working with 64-bit blocks and `GIFT-128` working with 128-bit blocks. In both cases, the key is 128 bits long. The design is a very simple, round-based substitution-permutation network (SPN). One round consists in a sequential application of the confusion layer by means of 4-bit S-boxes and subsequent diffusion through bit permutation. After the bit permutation, a round key is added to the cipher state and the single round is complete. `GIFT-64` uses 28 rounds while `GIFT-128` uses 40 rounds.



Figure 1.1: Two rounds of GIFT-64

Substitution layer

The input of `GIFT` is split into 4-bit nibbles which are then fed into 16 S-boxes for `GIFT-64` and 32 S-boxes for `GIFT-128`. The S-box $S : \mathbb{F}_2^4 \to \mathbb{F}_2^4$ is defined as follows:

x	0	1	2	3	4	5	6	7	8	9	a	b	c	d	e	f
$S(x)$	1	a	4	c	6	f	3	9	2	d	b	7	5	0	8	e

Permutation layer

The permutation P works on individual bits and maps bit b_i to $b_{P(i)}, i \in \{0, 1, \ldots, n-1\}$. The different permutations for `GIFT-64` and `GIFT-128` can be expressed by:

$$P_{64}(i) = 4\left\lfloor \frac{i}{16} \right\rfloor + 16\left(\left(3\left\lfloor \frac{i \bmod 16}{4} \right\rfloor + (i \bmod 4)\right) \bmod 4\right) + (i \bmod 4)$$

$$P_{128}(i) = 4\left\lfloor \frac{i}{16} \right\rfloor + 32\left(\left(3\left\lfloor \frac{i \bmod 16}{4} \right\rfloor + (i \bmod 4)\right) \bmod 4\right) + (i \bmod 4)$$

Round key addition

The last step of each round consists in XORing a round key R_i to the cipher state. The new cipher state s_{i+1} after each full round is therefore given by

$$s_{i+1} = P(S(s_i)) \oplus R_i$$

Round key extraction and key schedule

Round key extraction differs for `GIFT-64` and `GIFT-128`. Let $K = k7||k6||\ldots||k0$ denote the 128-bit key state.

GIFT-64 . We extract two 16-bit words $U||V = k_1||k_0$ from the key state. u_i and v_i are XORed to r_{4i+1} and r_{4i} of the round key R respectively.

GIFT-128 . We extract two 32-bit words $U||V = k_5||k4||k1||k_0$ from the key state. u_i and v_i are XORed to r_{4i+2} and b_{4i+1} of the round key R respectively.

In both cases, we additionally XOR a round constant $C = c_5c_4c_3c_2c_1c_0$ to bit positions $n - 1, 23, 19, 15, 11, 7, 3$. The round constants are generated using a 6-bit affine linear-feedback shift register and have the following values:

Rounds	Constants
1 - 16	`01,03,07,0F,1F,3E,3D,3B,37,2F,1E,3C,39,33,27,0E`
17 - 32	`1D,3A,35,2B,16,2C,18,30,21,02,05,0B,17,2E,1C,38`
33 - 48	`31,23,06,0D,1B,36,2D,1A,34,29,12,24,08,11,22,04`

The key state is then updated by setting $k_1 \leftarrow k_1 \ggg 2$, $k_0 \leftarrow k_0 \ggg 12$ and rotating the new state 32 bits to the right:

$$k_7||k_6||\dots||k_1||k_0 \leftarrow k_1 \ggg 2||k_0 \ggg 12||k_7||k_6||\dots||k_3||k_2$$

1.2.2 Camellia

1.3 The ARMv8 platform

With small devices, embedded processors and ASICs becoming ever more ubiquitous and essential in areas like medicine or automotive design, the need for ...

Chapter 2

Implementation strategies

Due to the structural differences of SPN- and Feistel network-based ciphers, we shall analyze these two separately.

2.1 Strategies for SPN

Three implementation strategies for substitution-permutation networks are introduced by [2]:

- Table-based implementations
- `vperm` implementations
- Bitslice implementations

2.1.1 Table-based

Table-driven programming is a simple way to increase performance of operations by tabulating the results, therefore requiring only a single memory access to acquire the result. This approach is obviously limited to manageable table sizes, so while tabulating a function like the AES S-box $S_{AES} : \mathbb{F}_2^8 \to \mathbb{F}_2^8$ requires only 2^{11} space, tabulating the `GIFT` permutation layer $P_{GIFT} : \mathbb{F}_2^{64} \to \mathbb{F}_2^{64}$ would require 2^{70} space, which is totally unfeasible.

A common approach is to tabulate the output of each S-box, including the diffusion layer, and then XORing the results together. Let n denote the internal cipher state size and s the size of a single S-box in bits. For

each S-box $S_i, i \in \{0, \ldots, \frac{n}{s}\}$, we can construct a mapping $T_i : \mathbb{F}_2^s \to \mathbb{F}_2^n$ representing substitution with subsequent permutation of that single S-box. The cipher state before round key addition is then given by $\bigoplus_{i=0}^{\frac{n}{s}-1} T_i(m_i)$ for each s-bit message chunk m_i. This approach requires space of $\frac{n}{s}|\mathbb{F}_2^s|n = \frac{n^2 2^s}{s}$ bits, which, for `GIFT-64`, results in a manageable size of $\frac{64^2 2^4}{4} = 2^{14}$ bits which equals 16 KiB.

Constructing the tables

For `GIFT-64`, table construction is relatively straightforward and can be done as follows:

Listing 2.1: Table construction algorithm

```
1    tables <- [][]
2    for sbox_index from 0 to 15 do
3        for sbox_input from 0 to 15 do
4            output <- sbox(sbox_input)
5            output <- permute(output << (4 * sbox_index))
6            tables[sbox_index][sbox_input] <- output
```

Implementing this algorithm gives us the following table representing the first and second S-box.

x	$T_0(x)$	$T_1(x)$	...
$0x0$	$0x1$	$0x1000000000000$	...
$0x1$	$0x8000000020000$	$0x800000002$	...
$0x2$	$0x400000000$	$0x40000$	...
$0x3$	$0x8000400000000$	$0x800040000$	...
$0x4$	$0x400020000$	$0x40002$	...
$0x5$	$0x8000400020001$	$0x1000800040002$	...
$0x6$	$0x20001$	$0x1000000000002$	...
$0x7$	$0x8000000000001$	$0x1000800000000$	...
$0x8$	$0x20000$	$0x2$	...
$0x9$	$0x8000400000001$	$0x1000800040000$	...
$0xa$	$0x8000000020001$	$0x1000800000002$	...
$0xb$	$0x400020001$	$0x1000000040002$	...
$0xc$	$0x400000001$	$0x1000000040000$	...
$0xd$	$0x0$	$0x0$	...
$0xe$	$0x8000000000000$	$0x800000000$	...
$0xf$	$0x8000400020000$	$0x800040002$	...

The tables for `GIFT-128` can be generated in a similar way by looping through all 32 S-boxes instead of 16 on line 3.

2.1.2 Using `vperm`

Nowadays, most instructions set architectures support single-instruction, multiple-data processing. The idea of such an SIMD system is to work on multiple data stored in vectors at once to speed up calculations. For A64, two types of vector processing are available:

1. Advanced SIMD, known as NEON
2. Scalable Vector Extension (SVE)

We will take a look at NEON as this is the type of vector processing supported by the Cortex-A73 processor.

ARM Neon

The register file of the NEON unit is made up of 32 quad-word (128-bit) registers `V[0-31]`, each extending the standard 64-bit floating-point registers `D[0-31]`. These registers are divided into equally sized lanes on which the vector instructions operate. Valid ways to interpret for example the register `V0` are:



Figure 2.1: Divisions of the V0 register

NEON instructions interpret their operands' layouts (i.e. lane count and width) through the use of suffixes such as `.4S` or `.8H`. For example, adding

eight 16-bit halfwords from register `V1` and `V2` together and storing the result in `V0` can be done as follows:

```
ADD V0.8H, V1.8H, V2.8H
```



Figure 2.2: Addition of two vector registers

The plenitude of different processing instructions allow flexible ways to further speed up algorithms having reached their optimizational limit on non-SIMD platforms. `vperm`, a general term standing for *vector permute*, is a common instruction on SIMD machines. Called `TBL` on NEON, it is used for parallel table lookups and arbitrary permutations. It takes two inputs to perform a lanewise lookup:

1. A register with lookup values
2. One or more registers containing data

S-box lookup

This instruction can be used to implement S-box lookup of all 16 S-boxes in a single instruction. We do this by packing our 64-bit cipher state $s = s_{15}||s_{14}||\ldots||s_0$ into a vector register V_0. Because we can only operate on whole bytes, we put each 4-bit S-box into an 8-bit lane which neatly fits into the 128-bit registers. We then put the S-box itself into register V_1 which will be used as the data register for the table lookup.

The confusion layer can now be performed through one `TBL` instruction:

```
TBL V0.16B, V1.16B, V0.16B
```



Figure 2.3: Performing the S-Box lookup in parallel

2.1.3 Bitslicing

Bitslicing refers to the technique of splitting up n bits into m slices to achieve a more efficient representation to operate on. The structure of `GIFT` naturally offers possibilities for bitslicing. We split the cipher state bits $b_{63}b_{62}\dots b_0$ into four slices $S_i, i \in \{0,1,2,3\}$ such that the i-th slice contains all i-th bits of the individual S-boxes. This is equivalent to transposing the bit matrix.

$$S = \begin{bmatrix} S_0 \\ S_1 \\ S_2 \\ S_3 \end{bmatrix} = \begin{bmatrix} b_{60}b_{56}b_{52}\dots b_0 \\ b_{61}b_{57}b_{53}\dots b_1 \\ b_{62}b_{58}b_{54}\dots b_2 \\ b_{63}b_{59}b_{55}\dots b_3 \end{bmatrix}$$

Parallel S-Boxes

This representation offers multiple advantages. We first note that computation of the S-box can be executed in parallel, similar to the `vperm` technique above. This can be done by finding an algorithmic way to apply the S-box which has already been proposed by the original `GIFT` authors:

$$
\begin{aligned}
S_1 &\leftarrow S_1 \oplus (S_0 \wedge S_2) \\
t &\leftarrow S_0 \oplus (S_1 \wedge S_3) \\
S_2 &\leftarrow S_2 \oplus (t \vee S_1) \\
S_0 &\leftarrow S_3 \oplus S_2 \\
S_1 &\leftarrow S_1 \oplus S_0 \\
S_0 &\leftarrow \neg S_0 \\
S_2 &\leftarrow S_2 \oplus (t \wedge S_1) \\
S_3 &\leftarrow t
\end{aligned}
$$

This is very efficient as it only requires six XOR-, three AND and one OR operation.

An important property of the permutation is the fact that bits always stay in their slice. This means we can decompose the permutation P into four permutations $P_i, i \in \{0, 1, 2, 3\}$ and apply these permutations separately to each slice. One possible way to implement a permutation P_i in software is to mask off all bits individually, shift them to their correct position and OR them together:

$$P_i(S_i) = \bigvee_{k=0}^{15} (S_i \wedge m_i) \ll s_i$$

This approach requires 47 operations, meaning all four permutations require over 150 operations which would present a major bottleneck to the round function. We can improve on this by working on multiple message blocks at once and using the aforementioned `vperm` instruction to implement the bit shuffling. We then need only four instructions for the complete diffusion layer.

Using `vperm` for slice permutation

We cannot use the `TBL` instruction directly as we need to shuffle individual bits, but the smallest data we can operate on are bytes. We therefore encrypt $8n$ messages at once which allows us to create bytewise groupings. These messages are put into $4m$ registers with register R_{4i} containing S_0, register R_{4i+1} containing S_1 and so forth. With block size BS and register size RS, the following must hold:

$$8n \cdot BS = 4m \cdot RS$$

In the case of `GIFT-64` with $BS = 64$ and ARM NEON with $RS = 128$, we get

$$8n \cdot 64 = 4m \cdot 128 \Leftrightarrow n = m$$

$n = m = 1$ would be a valid choice which yields eight messages divided into four registers. We choose $n = m = 2$ so we can directly utilize the algorithm for bit packing presented by the original GIFT authors, although it is simple to adapt this algorithm to only four registers and eight messages by adjusting the `SWAPMOVE` shift and mask values.

Packing the data into bitslice format

Let $a, b, \ldots, p$ be sixteen messages of length 64 with subscripts denoting individual bits. We first put these messages into eight SIMD registers $V_0, V_1, \ldots, V_7$:

$$\begin{aligned} V_0 &= b||a & V_4 &= j||\,i \\ V_1 &= d||c & V_5 &= l||\,k \\ V_2 &= f||e & V_6 &= n||m \\ V_3 &= h||g & V_7 &= p||\,o \end{aligned}$$

We then use the `SWAPMOVE` technique to bring the data into bitslice format. This operation operates on two registers A, B using mask M and shift value N. It swaps bits in A masked by $(M \ll N)$ with bits in B masked by M in using only three XOR-, one AND- and two shift operations.

$$\begin{aligned} &\text{SWAPMOVE}(A, B, M, N) : \\ &\quad T = ((A \gg N) \oplus B) \wedge M \\ &\quad B = B \oplus T \\ &\quad A = A \oplus (T \ll N) \end{aligned}$$

One caveat of this approach is the fact that NEON registers cannot be shifted in their entirety due to the fact bits are not able to cross lanes. This

leads to the problem of being able to shift at most two lanes of 64 bits at once. We thus need to implement the `shr(V,n)` and `shl(V,n)` operations on our own. This can be done by first extracting the 64-bit lanes a, b out of $V = b||a$, shifting the lanes individually and finally shifting and ORing the crossing bits back into the other lane.

$$\begin{aligned}\text{shl}(V, n) :& \\ a, b &= V[0], V[1] \\ c &= (a \gg (64 - n)) \\ V[0] &= (a \ll n) \\ V[1] &= (b \ll n) \vee c\end{aligned}$$

The following operations group all i-th bits of the messages $a, c, \ldots, o$ into bytes and puts these into the lower half of the registers $V_{i \bmod 8}$. The same is done for messages $b, d, \ldots, p$, only differing in that the bytes are put into the upper half of the registers.

$$\begin{array}{ll}
\text{SWAPMOVE}(V_0, V_1, 0x5555\ldots55, 1) & \text{SWAPMOVE}(V_4, V_5, 0x5555\ldots55, 1) \\
\text{SWAPMOVE}(V_2, V_3, 0x5555\ldots55, 1) & \text{SWAPMOVE}(V_6, V_7, 0x5555\ldots55, 1) \\
\text{SWAPMOVE}(V_0, V_2, 0x3333\ldots33, 2) & \text{SWAPMOVE}(V_4, V_6, 0x3333\ldots33, 2) \\
\text{SWAPMOVE}(V_1, V_3, 0x3333\ldots33, 2) & \text{SWAPMOVE}(V_5, V_7, 0x3333\ldots33, 2) \\
\text{SWAPMOVE}(V_0, V_4, 0x0f0f\ldots0f, 4) & \text{SWAPMOVE}(V_1, V_5, 0x0f0f\ldots0f, 4) \\
\text{SWAPMOVE}(V_2, V_6, 0x0f0f\ldots0f, 4) & \text{SWAPMOVE}(V_3, V_7, 0x0f0f\ldots0f, 4)
\end{array}$$

With $Ax = o_x m_x k_x j_x g_x e_x c_x a_x$ and $Bx = p_x n_x l_x i_x h_x f_x d_x b_x$ denoting byte groups, our data now has the following permutation-friendly format:

n	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
V_0	$B56$	$B48$	$B40$	$B32$	$B24$	$B16$	$B8$	$B0$	$A56$	$A48$	$A40$	$A32$	$A24$	$A16$	$A8$	$A0$
V_1	$B57$	$B49$	$B41$	$B33$	$B25$	$B17$	$B9$	$B1$	$A57$	$A49$	$A41$	$A33$	$A25$	$A17$	$A9$	$A1$
V_2	$B58$	$B50$	$B42$	$B34$	$B26$	$B18$	$B10$	$B2$	$A58$	$A50$	$A42$	$A34$	$A26$	$A18$	$A10$	$A2$
V_3	$B59$	$B51$	$B43$	$B35$	$B27$	$B19$	$B11$	$B3$	$A59$	$A51$	$A43$	$A35$	$A27$	$A19$	$A11$	$A3$
V_4	$B60$	$B52$	$B44$	$B36$	$B28$	$B20$	$B12$	$B4$	$A60$	$A52$	$A44$	$A36$	$A28$	$A20$	$A12$	$A4$
V_5	$B61$	$B53$	$B45$	$B37$	$B29$	$B21$	$B13$	$B5$	$A61$	$A53$	$A45$	$A37$	$A29$	$A21$	$A13$	$A5$
V_6	$B62$	$B54$	$B46$	$B38$	$B30$	$B22$	$B14$	$B6$	$A62$	$A54$	$A46$	$A38$	$A30$	$A22$	$A14$	$A6$
V_7	$B63$	$B55$	$B47$	$B39$	$B31$	$B23$	$B15$	$B7$	$A63$	$A55$	$A47$	$A39$	$A31$	$A23$	$A15$	$A7$

Although this would already work, we prefer to have only bits of the same messages in each register - otherwise the permutation would need to operate on two source registers with the added requirement of storing the pre-permutation values for the first four registers, slowing down the round function through superfluous load/stores. This transformation is trivial by use of TBL with two data source operands. The final data format we operate on is as follows:

n	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
V_0	$A60$	$A56$	$A52$	$A48$	$A44$	$A40$	$A36$	$A32$	$A28$	$A24$	$A20$	$A16$	$A12$	$A8$	$A4$	$A0$
V_1	$A61$	$A57$	$A53$	$A49$	$A45$	$A41$	$A37$	$A33$	$A29$	$A25$	$A21$	$A17$	$A13$	$A9$	$A5$	$A1$
V_2	$A62$	$A58$	$A54$	$A50$	$A46$	$A42$	$A38$	$A34$	$A30$	$A26$	$A22$	$A18$	$A14$	$A10$	$A6$	$A2$
V_3	$A63$	$A59$	$A55$	$A51$	$A47$	$A43$	$A39$	$A35$	$A31$	$A27$	$A23$	$A19$	$A15$	$A11$	$A7$	$A3$
V_4	$B60$	$B56$	$B52$	$B48$	$B44$	$B40$	$B36$	$B32$	$B28$	$B24$	$B20$	$B16$	$B12$	$B8$	$B4$	$B0$
V_5	$B61$	$B57$	$B53$	$B49$	$B45$	$B41$	$B37$	$B33$	$B29$	$B25$	$B21$	$B17$	$B13$	$B9$	$B5$	$B1$
V_6	$B62$	$B58$	$B54$	$B50$	$B46$	$B42$	$B38$	$B34$	$B30$	$B26$	$B22$	$B18$	$B14$	$B10$	$B6$	$B2$
V_7	$B63$	$B59$	$B55$	$B51$	$B47$	$B43$	$B39$	$B35$	$B31$	$B27$	$B23$	$B19$	$B15$	$B11$	$B7$	$B3$

We can now create permutation tables using the specification of the individual slice permutations P_i which are then applied to V_i and V_{i+4} respectively:

j	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
$P_0(j)$	0	12	8	4	1	13	9	5	2	14	10	6	3	15	11	7
$P_1(j)$	4	0	12	8	5	1	13	9	6	2	14	10	7	3	15	11
$P_2(j)$	8	4	0	12	9	5	1	13	10	6	2	14	11	7	3	15
$P_3(j)$	12	8	4	0	13	9	5	1	14	10	6	2	15	11	7	3

One thing to take note of is the original permutation values only show where a given byte should land, not which byte belongs to a certain position - i.e. for P_0, byte 1 should land in position 12, but the byte belonging to position 1 is byte 4. Because TBL works in the latter way, we have to do some trivial rearrangements.

Assuming the correct permutation values are put into registers V_8, V_9, V_{10}, V_{11}, this now allows us to compute the permutation layer for all 16 blocks in only eight permutation instructions.

```
TBL V0, V0, V8    TBL V1, V1, V9
TBL V4, V4, V8    TBL V5, V5, V9
TBL V2, V2, V10   TBL V3, V3, V11
TBL V6, V6, V10   TBL V7, V7, V11
```

Round key function

In contrast to packing and unpacking of data which is only done once in the beginning and end, a round key is derived for every round, so the round key derivation function needs to be as fast as possible. A simple but naive approach for one round would be to generate a single round key, copy it 15 times and pack the resulting registers similar to how we proceed with the messages. Due to the cost of packing the messages, this is prohibitivly expensive. Because we know where each byte group ends up after packing, we can directly XOR the round key bits to the correct position. Extending these bits to bytes can then be done simply by repeatedly shifting and ORing the registers together.

2.2 Implementation

Implementations in the C programming language for the presented strategies can be found in Appendix A. Although directly writing Assembler code could result in a small performance benefit, this generally increases the work necessary by an order of magnitude for only limited results. Instruction-level optimization and in particular register allocation is left to the compiler.

2.2.1 NEON intrinsics

The header file `<arm_neon.h>` provides ARM-specific data and function definitions including vector data types and C functions for working with these vectors. These functions are known as NEON intrinsics [3] and give the programmer a high-level interface to most NEON instructions. Major advantages of this approach include the ease of development as the compiler takes over register allocation and load/store operations as well as performance benefits through compiler optimizations.

Standard vector data types have the format `uintnxm_t` with lane width n in bits and and lane count m. Array types of the format `uintnxmxc_t`, $c \in \{2, 3, 4\}$ are also defined which are used in operations requiring multiple parameters like `TBL` or pairwise load/stores. Intrinsics include the operation name and lane data format as well as an optional `q` suffix to indicate operation on a 128-bit register. Multiplying eight pairs of 16-bit numbers `a,b` for example can be done via the following:

```
uint16x8_t result = vmulq_u16(a, b);
```

In this case, the compiler allocates vector registers for `a`, `b` and `result` and assembles the intrinsic to `MUL Vr.8H, Va.8H, Vb.8H`. Necessary loads and stores for the result and parameters are also handled automatically. Of special interest to us are the following intrinsics, each existing in different variants with different lane widths and also array types:

Intrinsic		Description
`uint8x16_t`	`vreinterpretq_u8_u64(uint64x2_t)`	Explicit casting
`uint64_t`	`vgetq_lane_u64(void)`	Extract a single lane
`void`	`vsetq_lane_u64(uint64_t)`	Insert a single lane
`uint64x2_t`	`vdupq_n_u64(uint64_t)`	Initialize all lanes to same value
`void`	`vst1q_u64(uint64_t*, uint64x2_t)`	Store from register to memory
`uint64x2_t`	`vld1q_u64(uint64_t*, uint64x2_t)`	Load from memory to register
`uint8x16_t`	`veorq_u8(uint8x16_t, uint8x16_t)`	bitwise XOR
`uint8x16_t`	`vandq_u8(uint8x16_t, uint8x16_t)`	bitwise AND
`uint8x16_t`	`vorrq_u8(uint8x16_t, uint8x16_t)`	bitwise OR
`uint8x16_t`	`vmvnq_u8(uint8x16_t)`	bitwise NOT
`uint8x16_t`	`vqtbl2q_u8(uint8x16_t, uint8x16_t)`	permutation (`TBL`)

Table 2.1: Common NEON intrinsics

2.3 Strategies for Camellia

Chapter 3

Evaluation

In this chapter, we will evaluate the strategies through performance measurements and discuss advantages, disadvantages and possible use cases.

3.1 Benchmarks

Performance measurements were taken for each strategy as well as for naive reference implementations and are presented in cycles per byte (c/B) as well as constant throughput in MiB/s of the entire encryption strategy.

The AArch64 defines system registers in addition to general-purpose registers which are used for system configuration and monitoring. One of these registers is the performance monitor cycle count register `PMCCNTR` which counts processor clock cycles. Access from userspace is disabled by default and can be activated through a custom Linux kernel module by setting `PMUSERENR.EN` to 1. To minimize interference and because the cycle count register is core-local, we isolate one of the cores from the rest of the system for exclusive benchmarking use.

3.1.1 GIFT

3.1.2 Camellia

Strategy	Function	Latency (c/B)	Total throughput (MiB/s)
Naive `GIFT-64`	`round_keys`	191.17	throughput
	`subcells`	2.74	
	`permute`	21.96	
	`encrypt`	995.36	
Naive `GIFT-128`	`round_keys`	166.73	throughput
	`subcells`	2.72	
	`permute`	61.28	
	`encrypt`	2786.88	
Table-driven	`round_keys`	190.42	throughput
	`subperm`	3.88	
	`encrypt`	312.97	
`vperm` S-box	`round_keys`	271.35	throughput
	`subcells`	1.12	
	`permute`	14.98	
	`encrypt`	761.18	
Bitsliced	`round_keys`	7.69	throughput
	`subcells`	0.28	
	`permute`	0.11	
	`encrypt`	21.38	

Table 3.1: Benchmarks for `GIFT`

Acknowledgements

I want to thank ...

Appendix A

C implementations

A.1 Implementations for SPN

A.1.1 Table-based

Listing A.1: `gift_table.h`

```
#ifndef GIFT_TABLE_H
#define GIFT_TABLE_H

#include <stdint.h>

#define ROUNDS_GIFT_64 28

void gift_64_table_generate_round_keys(uint64_t rks[restrict ROUNDS_GIFT_64],
                                       const uint64_t key[restrict 2]);

uint64_t gift_64_table_subperm(const uint64_t cipher_state);

// can only encrypt using table technique!
uint64_t gift_64_table_encrypt(const uint64_t m, const uint64_t key[restrict 2]);

#endif
```

Listing A.2: `gift_table.c`

```
#include "gift_table.h"

#include <stdlib.h>
#include <string.h>

static const int round_const[] = {
        // rounds 0-15
        0x01, 0x03, 0x07, 0x0F, 0x1F, 0x3E, 0x3D, 0x3B,
        0x37, 0x2F, 0x1E, 0x3C, 0x39, 0x33, 0x27, 0x0E,
```

```
10          // rounds 16-31
11          0x1D, 0x3A, 0x35, 0x2B, 0x16, 0x2C, 0x18, 0x30,
12          0x21, 0x02, 0x05, 0x0B, 0x17, 0x2E, 0x1C, 0x38,
13          // rounds 32-47
14          0x31, 0x23, 0x06, 0x0D, 0x1B, 0x36, 0x2D, 0x1A,
15          0x34, 0x29, 0x12, 0x24, 0x08, 0x11, 0x22, 0x04
16  };
17
18  static const uint64_t tables[16][16] = {
19          { 0x0000000000000001UL, 0x0008000000020000UL, 0x0000000400000000UL, 0
                x0008000400000000UL, 0x0000000400020000UL, 0x0008000400020001UL, 0
                x0000000000020001UL, 0x0008000000000001UL, 0x0000000000020000UL, 0
                x0008000400000001UL, 0x0008000000020001UL, 0x0000000400020001UL, 0
                x0000000400000001UL, 0x0000000000000000UL, 0x0008000000000000UL, 0
                x0008000400020000UL },
20          { 0x0001000000000000UL, 0x0000000800000002UL, 0x0000000000040000UL, 0
                x0000000800040000UL, 0x0000000000040002UL, 0x0001000800040002UL, 0
                x0001000000000002UL, 0x0001000800000000UL, 0x0000000000000002UL, 0
                x0001000800040000UL, 0x0001000800000002UL, 0x0001000000040002UL, 0
                x0001000000040000UL, 0x0000000000000000UL, 0x0000000800000000UL, 0
                x0000000800040002UL },
21          { 0x0000000100000000UL, 0x0002000000080000UL, 0x0000000000000004UL, 0
                x0000000000080004UL, 0x0002000000000004UL, 0x0002000100080004UL, 0
                x0002000100000000UL, 0x0000000100080000UL, 0x0002000000000000UL, 0
                x0000000100080004UL, 0x0002000100080000UL, 0x0002000100000004UL, 0
                x0000000100000004UL, 0x0000000000000000UL, 0x0000000000080000UL, 0
                x0002000000080004UL },
22          { 0x0000000000010000UL, 0x0000000200000008UL, 0x0004000000000000UL, 0
                x0004000000000008UL, 0x0004000200000000UL, 0x0004000200010008UL, 0
                x0000000200010000UL, 0x0000000000010008UL, 0x0000000200000000UL, 0
                x0004000000010008UL, 0x0000000200010008UL, 0x0004000200010000UL, 0
                x0004000000010000UL, 0x0000000000000000UL, 0x0000000000000008UL, 0
                x0004000200000008UL },
23          { 0x0000000000000010UL, 0x0080000000200000UL, 0x0000004000000000UL, 0
                x0080004000000000UL, 0x0000004000200000UL, 0x0080004000200010UL, 0
                x0000000000200010UL, 0x0080000000000010UL, 0x0000000000200000UL, 0
                x0080004000000010UL, 0x0080000000200010UL, 0x0000004000200010UL, 0
                x0000004000000010UL, 0x0000000000000000UL, 0x0080000000000000UL, 0
                x0080004000200000UL },
24          { 0x0010000000000000UL, 0x0000008000000020UL, 0x0000000000400000UL, 0
                x0000008000400000UL, 0x0000000000400020UL, 0x0010008000400020UL, 0
                x0010000000000020UL, 0x0010008000000000UL, 0x0000000000000020UL, 0
                x0010008000400000UL, 0x0010008000000020UL, 0x0010000000400020UL, 0
                x0010000000400000UL, 0x0000000000000000UL, 0x0000008000000000UL, 0
                x0000008000400020UL },
25          { 0x0000001000000000UL, 0x0020000000800000UL, 0x0000000000000040UL, 0
                x0000000000800040UL, 0x0020000000000040UL, 0x0020001000800040UL, 0
                x0020001000000000UL, 0x0000001000800000UL, 0x0020000000000000UL, 0
                x0000001000800040UL, 0x0020001000800000UL, 0x0020001000000040UL, 0
                x0000001000000040UL, 0x0000000000000000UL, 0x0000000000800000UL, 0
                x0020000000800040UL },
26          { 0x0000000000100000UL, 0x0000002000000080UL, 0x0040000000000000UL, 0
                x0040000000000080UL, 0x0040002000000000UL, 0x0040002000100080UL, 0
                x0000002000100000UL, 0x0000000000100080UL, 0x0000002000000000UL, 0
                x0040000000100080UL, 0x0000002000100080UL, 0x0040002000100000UL, 0
                x0040000000100000UL, 0x0000000000000000UL, 0x0000000000000080UL, 0
                x0040002000000080UL },
```

```
27          { 0x0000000000000100UL, 0x0800000002000000UL, 0x0000040000000000UL, 0
                x0800040000000000UL, 0x0000040002000000UL, 0x0800040002000100UL, 0
                x0000000002000100UL, 0x0800000000000100UL, 0x0000000002000000UL, 0
                x0800040000000100UL, 0x0800000002000100UL, 0x0000040002000100UL, 0
                x0000040000000100UL, 0x0000000000000000UL, 0x0800000000000000UL, 0
                x0800040002000000UL },
28          { 0x0100000000000000UL, 0x0000080000000200UL, 0x0000000004000000UL, 0
                x0000800004000000UL, 0x0000000004000200UL, 0x0100080004000200UL, 0
                x0100000000000200UL, 0x0100080000000000UL, 0x0000000000000200UL, 0
                x0100080004000000UL, 0x0100080000000200UL, 0x0100000004000200UL, 0
                x0100000004000000UL, 0x0000000000000000UL, 0x0000080000000000UL, 0
                x0000080004000200UL },
29          { 0x0000010000000000UL, 0x0200000008000000UL, 0x0000000000000400UL, 0
                x0000000008000400UL, 0x0200000000000400UL, 0x0200010008000400UL, 0
                x0200010000000000UL, 0x0000010008000000UL, 0x0200000000000000UL, 0
                x0000010008000400UL, 0x0200010008000000UL, 0x0200010000000400UL, 0
                x0000010000000400UL, 0x0000000000000000UL, 0x0000000008000000UL, 0
                x0200000008000400UL },
30          { 0x0000000001000000UL, 0x0000020000000800UL, 0x0400000000000000UL, 0
                x0400000000000800UL, 0x0400020000000000UL, 0x0400020001000800UL, 0
                x0000020001000000UL, 0x0000000001000800UL, 0x0000020000000000UL, 0
                x0400000001000800UL, 0x0000020001000800UL, 0x0400020001000000UL, 0
                x0400000001000000UL, 0x0000000000000000UL, 0x0000000000000800UL, 0
                x0400020000000800UL },
31          { 0x0000000000001000UL, 0x8000000020000000UL, 0x0000400000000000UL, 0
                x8000400000000000UL, 0x0000400020000000UL, 0x8000400020001000UL, 0
                x0000000020001000UL, 0x8000000000001000UL, 0x0000000020000000UL, 0
                x8000400000001000UL, 0x0000000020001000UL, 0x0000400020001000UL, 0
                x0000400000001000UL, 0x0000000000000000UL, 0x8000000000000000UL, 0
                x8000400020000000UL },
32          { 0x1000000000000000UL, 0x0000800000002000UL, 0x0000000040000000UL, 0
                x0000800040000000UL, 0x0000000040002000UL, 0x1000800040002000UL, 0
                x1000000000002000UL, 0x1000800000000000UL, 0x0000000000002000UL, 0
                x1000800040000000UL, 0x1000800000002000UL, 0x1000000040002000UL, 0
                x1000000040000000UL, 0x0000000000000000UL, 0x0000800000000000UL, 0
                x0000800040002000UL },
33          { 0x0000100000000000UL, 0x2000000080000000UL, 0x0000000000004000UL, 0
                x0000000080004000UL, 0x2000000000004000UL, 0x2000100080004000UL, 0
                x2000100000000000UL, 0x0000100080000000UL, 0x2000000000000000UL, 0
                x0000100080004000UL, 0x2000100080000000UL, 0x2000100000004000UL, 0
                x0000100000004000UL, 0x0000000000000000UL, 0x0000000080000000UL, 0
                x2000000080004000UL },
34          { 0x0000000010000000UL, 0x0000200000008000UL, 0x4000000000000000UL, 0
                x4000000000008000UL, 0x4000200000000000UL, 0x4000200010008000UL, 0
                x0000200010000000UL, 0x0000000010008000UL, 0x0000200000000000UL, 0
                x4000000010008000UL, 0x0000200010008000UL, 0x4000200010000000UL, 0
                x4000000010000000UL, 0x0000000000000000UL, 0x0000000000008000UL, 0
                x4000200000008000UL }
35  };
36
37  void gift_64_table_generate_round_keys(uint64_t rks[restrict ROUNDS_GIFT_64],
38                                         const uint64_t key[restrict 2])
39  {
40          uint64_t key_state[] = {key[0], key[1]};
41          for (int round = 0; round < ROUNDS_GIFT_64; round++) {
42                  int v = (key_state[0] >> 0 ) & 0xffff;
43                  int u = (key_state[0] >> 16) & 0xffff;
```

```
44
45                  // add round key (RK=U||V)
46                  rks[round] = 0UL;
47                  for (size_t i = 0; i < 16; i++) {
48                          int key_bit_v   = (v >> i)  & 0x1;
49                          int key_bit_u   = (u >> i)  & 0x1;
50                          rks[round] ^= (uint64_t)key_bit_v << (i * 4 + 0);
51                          rks[round] ^= (uint64_t)key_bit_u << (i * 4 + 1);
52                  }
53
54                  // add single bit
55                  rks[round] ^= 1UL << 63;
56
57                  // add round constants
58                  rks[round] ^= ((round_const[round] >> 0) & 0x1) << 3;
59                  rks[round] ^= ((round_const[round] >> 1) & 0x1) << 7;
60                  rks[round] ^= ((round_const[round] >> 2) & 0x1) << 11;
61                  rks[round] ^= ((round_const[round] >> 3) & 0x1) << 15;
62                  rks[round] ^= ((round_const[round] >> 4) & 0x1) << 19;
63                  rks[round] ^= ((round_const[round] >> 5) & 0x1) << 23;
64
65                  // update key state
66                  int k0 = (key_state[0] >> 0 ) & 0xffffUL;
67                  int k1 = (key_state[0] >> 16) & 0xffffUL;
68                  k0 = (k0 >> 12) | ((k0 & 0xfff) << 4);
69                  k1 = (k1 >> 2 ) | ((k1 & 0x3  ) << 14);
70                  key_state[0] >>= 32;
71                  key_state[0] |= (key_state[1] & 0xffffffffUL) << 32;
72                  key_state[1] >>= 32;
73                  key_state[1] |= ((uint64_t)k0 << 32) | ((uint64_t)k1 << 48);
74          }
75  }
76
77  uint64_t gift_64_table_subperm(const uint64_t cipher_state)
78  {
79          uint64_t new_cipher_state = 0;
80
81          for (size_t i = 0; i < 16; i++) {
82                  int nibble = (cipher_state >> (i * 4)) & 0xf;
83                  new_cipher_state ^= tables[i][nibble];
84          }
85
86          return new_cipher_state;
87  }
88
89  uint64_t gift_64_table_encrypt(const uint64_t m, const uint64_t key[restrict 2])
90  {
91          uint64_t c = m;
92
93          // generate round keys
94          uint64_t rks[ROUNDS_GIFT_64];
95          gift_64_table_generate_round_keys(rks, key);
96
97          // round loop
98          for (int round = 0; round < ROUNDS_GIFT_64; round++) {
99                  c = gift_64_table_subperm(c);
100                 c ^= rks[round];
```

```
101         }
102
103         return c;
104 }
```

A.1.2 Using `vperm`

Listing A.3: `gift_vec_sbox.h`

```
1  #ifndef GIFT_VEC_SBOX_H
2  #define GIFT_VEC_SBOX_H
3
4  #include <stdint.h>
5  #include <arm_neon.h>
6
7  #define ROUNDS_GIFT_64 28
8
9  // expose for benchmarking
10 uint8x16_t gift_64_vec_sbox_subcells(const uint8x16_t cipher_state);
11 uint8x16_t gift_64_vec_sbox_subcells_inv(const uint8x16_t cipher_state);
12 uint8x16_t gift_64_vec_sbox_permute(const uint8x16_t cipher_state);
13 uint8x16_t gift_64_vec_sbox_permute_inv(const uint8x16_t cipher_state);
14 void       gift_64_vec_sbox_generate_round_keys(uint8x16_t rks[ROUNDS_GIFT_64],
15                                                 const uint64_t key[2]);
16
17 // construct tables
18 void gift_64_vec_sbox_init(void);
19
20 uint64_t gift_64_vec_sbox_encrypt(const uint64_t m, const uint64_t key[2]);
21 uint64_t gift_64_vec_sbox_decrypt(const uint64_t c, const uint64_t key[2]);
22
23 #endif
```

Listing A.4: `gift_vec_sbox.c`

```
1  #include "gift_vec_sbox.h"
2
3  #include <stdint.h>
4  #include <arm_neon.h>
5  #include <string.h>
6
7  static uint64_t sbox_vec_u64[2] = {
8          0x09030f060c040a01UL, 0x0e080005070b0d02UL
9  };
10
11 static uint64_t sbox_vec_inv_u64[2] = {
12 0x0b040c020608000dUL, 0x050f09030a01070eUL
13 };
14
15 static uint8x16_t sbox_vec;
16 static uint8x16_t sbox_vec_inv;
17
18 #define U64_TO_V128(V,M)\
```

```
19          V = vsetq_lane_u64(\
20          (uint64_t)((M >> 4 * 0) & 0xf) << 8 * 0 |\
21          (uint64_t)((M >> 4 * 1) & 0xf) << 8 * 1 |\
22          (uint64_t)((M >> 4 * 2) & 0xf) << 8 * 2 |\
23          (uint64_t)((M >> 4 * 3) & 0xf) << 8 * 3 |\
24          (uint64_t)((M >> 4 * 4) & 0xf) << 8 * 4 |\
25          (uint64_t)((M >> 4 * 5) & 0xf) << 8 * 5 |\
26          (uint64_t)((M >> 4 * 6) & 0xf) << 8 * 6 |\
27          (uint64_t)((M >> 4 * 7) & 0xf) << 8 * 7,\
28          V, 0);\
29          V = vsetq_lane_u64(\
30          (uint64_t)((M >> 4 * 8)  & 0xf) << 8 * 0 |\
31          (uint64_t)((M >> 4 * 9)  & 0xf) << 8 * 1 |\
32          (uint64_t)((M >> 4 * 10) & 0xf) << 8 * 2 |\
33          (uint64_t)((M >> 4 * 11) & 0xf) << 8 * 3 |\
34          (uint64_t)((M >> 4 * 12) & 0xf) << 8 * 4 |\
35          (uint64_t)((M >> 4 * 13) & 0xf) << 8 * 5 |\
36          (uint64_t)((M >> 4 * 14) & 0xf) << 8 * 6 |\
37          (uint64_t)((M >> 4 * 15) & 0xf) << 8 * 7,\
38          V, 1);
39
40  static const size_t perm_64[] = {
41          0, 17, 34, 51, 48, 1, 18, 35, 32, 49, 2, 19, 16, 33, 50, 3,
42          4, 21, 38, 55, 52, 5, 22, 39, 36, 53, 6, 23, 20, 37, 54, 7,
43          8, 25, 42, 59, 56, 9, 26, 43, 40, 57, 10, 27, 24, 41, 58, 11,
44          12, 29, 46, 63, 60, 13, 30, 47, 44, 61, 14, 31, 28, 45, 62, 15
45  };
46
47  static const size_t perm_64_inv[] = {
48          0, 5, 10, 15, 16, 21, 26, 31, 32, 37, 42, 47, 48, 53, 58, 63,
49          12, 1, 6, 11, 28, 17, 22, 27, 44, 33, 38, 43, 60, 49, 54, 59,
50          8, 13, 2, 7, 24, 29, 18, 23, 40, 45, 34, 39, 56, 61, 50, 55,
51          4, 9, 14, 3, 20, 25, 30, 19, 36, 41, 46, 35, 52, 57, 62, 51
52  };
53
54  static const int round_const[] = {
55          // rounds 0-15
56          0x01, 0x03, 0x07, 0x0F, 0x1F, 0x3E, 0x3D, 0x3B, 0x37, 0x2F, 0x1E, 0x3C, 0
                x39, 0x33, 0x27, 0x0E,
57          // rounds 16-31
58          0x1D, 0x3A, 0x35, 0x2B, 0x16, 0x2C, 0x18, 0x30, 0x21, 0x02, 0x05, 0x0B, 0
                x17, 0x2E, 0x1C, 0x38,
59          // rounds 32-47
60          0x31, 0x23, 0x06, 0x0D, 0x1B, 0x36, 0x2D, 0x1A, 0x34, 0x29, 0x12, 0x24, 0
                x08, 0x11, 0x22, 0x04
61  };
62
63  uint8x16_t gift_64_vec_sbox_subcells(const uint8x16_t cipher_state)
64  {
65          return vqtbl1q_u8(sbox_vec, cipher_state);
66  }
67
68  uint8x16_t gift_64_vec_sbox_subcells_inv(const uint8x16_t cipher_state)
69  {
70          return vqtbl1q_u8(sbox_vec_inv, cipher_state);
71  }
72
```

```
73  uint8x16_t gift_64_vec_sbox_permute(const uint8x16_t cipher_state)
74  {
75          // collect into 64-bit register (faster)
76          uint64_t new_cipher_state = 0UL;
77
78          // S-box 0-7
79          uint64_t boxes[2];
80          vst1q_u64(boxes, cipher_state);
81          for (size_t box = 0; box < 8; box++) {
82                  for (size_t i = 0; i < 4; i++) {
83                          int bit = (boxes[0] >> (box * 8 + i)) & 0x1;
84                          new_cipher_state |= (uint64_t)bit << perm_64[box * 4 + i
                                ];
85                  }
86          }
87
88          // S-box 8-15
89          for (size_t box = 0; box < 8; box++) {
90                  for (size_t i = 0; i < 4; i++) {
91                          int bit = (boxes[1] >> (box * 8 + i)) & 0x1;
92                          new_cipher_state |= (uint64_t)bit << perm_64[(box + 8) *
                                4 + i];
93                  }
94          }
95
96          uint8x16_t ret;
97          U64_TO_V128(ret, new_cipher_state);
98
99          return ret;
100 }
101
102 uint8x16_t gift_64_vec_sbox_permute_inv(const uint8x16_t cipher_state)
103 {
104         // collect into 64-bit register (faster)
105         uint64_t new_cipher_state = 0;
106
107         // S-box 0-7
108         uint64_t boxes = vgetq_lane_u64(cipher_state, 0);
109         for (size_t box = 0; box < 8; box++) {
110                 for (size_t i = 0; i < 4; i++) {
111                         int bit = (boxes >> (box * 8 + i)) & 0x1;
112                         new_cipher_state |= (uint64_t)bit << perm_64_inv[box * 4
                                + i];
113                 }
114         }
115
116         // S-box 8-15
117         boxes = vgetq_lane_u64(cipher_state, 1);
118         for (size_t box = 0; box < 8; box++) {
119                 for (size_t i = 0; i < 4; i++) {
120                         int bit = (boxes >> (box * 8 + i)) & 0x1;
121                         new_cipher_state |= (uint64_t)bit << perm_64_inv[(box +
                                8) * 4 + i];
122                 }
123         }
124
125         uint8x16_t ret;
```

```
126         U64_TO_V128(ret, new_cipher_state);
127
128         return ret;
129 }
130
131 void gift_64_vec_sbox_generate_round_keys(uint8x16_t rks[ROUNDS_GIFT_64],
132                                           const uint64_t key[2])
133 {
134         uint64_t key_state[] = {key[0], key[1]};
135         for (int round = 0; round < ROUNDS_GIFT_64; round++) {
136                 int v = (key_state[0] >> 0 ) & 0xffff;
137                 int u = (key_state[0] >> 16) & 0xffff;
138
139                 // add round key (RK=U||V)
140                 uint64_t round_key = 0UL;
141                 for (size_t i = 0; i < 16; i++) {
142                         int key_bit_v   = (v >> i)  & 0x1;
143                         int key_bit_u   = (u >> i)  & 0x1;
144                         round_key ^= (uint64_t)key_bit_v << (i * 4 + 0);
145                         round_key ^= (uint64_t)key_bit_u << (i * 4 + 1);
146                 }
147
148                 // add single bit
149                 round_key ^= 1UL << 63;
150
151                 // add round constants
152                 round_key ^= ((round_const[round] >> 0) & 0x1) << 3;
153                 round_key ^= ((round_const[round] >> 1) & 0x1) << 7;
154                 round_key ^= ((round_const[round] >> 2) & 0x1) << 11;
155                 round_key ^= ((round_const[round] >> 3) & 0x1) << 15;
156                 round_key ^= ((round_const[round] >> 4) & 0x1) << 19;
157                 round_key ^= ((round_const[round] >> 5) & 0x1) << 23;
158
159                 // pack into vector register
160                 U64_TO_V128(rks[round], round_key)
161
162                 // update key state
163                 int k0 = (key_state[0] >> 0 ) & 0xffffUL;
164                 int k1 = (key_state[0] >> 16) & 0xffffUL;
165                 k0 = (k0 >> 12) | ((k0 & 0xfff) << 4);
166                 k1 = (k1 >> 2 ) | ((k1 & 0x3  ) << 14);
167                 key_state[0] >>= 32;
168                 key_state[0] |= (key_state[1] & 0xffffffffUL) << 32;
169                 key_state[1] >>= 32;
170                 key_state[1] |= ((uint64_t)k0 << 32) | ((uint64_t)k1 << 48);
171         }
172 }
173
174 void gift_64_vec_sbox_init(void)
175 {
176         // construct sbox_vec
177         sbox_vec = vld1q_u64(sbox_vec_u64);
178
179         // construct sbox_vec_inv
180         sbox_vec_inv = vld1q_u64(sbox_vec_inv_u64);
181 }
182
```

```
183 uint64_t gift_64_vec_sbox_encrypt(const uint64_t m, const uint64_t key[2])
184 {
185         // pack into vector register
186         uint8x16_t c;
187         U64_TO_V128(c, m);
188 
189         // generate round keys
190         uint8x16_t rks[ROUNDS_GIFT_64];
191         gift_64_vec_sbox_generate_round_keys(rks, key);
192 
193         // round loop
194         for (int round = 0; round < ROUNDS_GIFT_64; round++) {
195                 c = gift_64_vec_sbox_subcells(c);
196                 c = gift_64_vec_sbox_permute(c);
197                 c = veorq_u8(c, rks[round]);
198         }
199 
200         // unpack
201         uint64_t ret = 0UL;
202         ret |= (uint64_t)vgetq_lane_u8(c, 0) << 4 * 0;
203         ret |= (uint64_t)vgetq_lane_u8(c, 1) << 4 * 1;
204         ret |= (uint64_t)vgetq_lane_u8(c, 2) << 4 * 2;
205         ret |= (uint64_t)vgetq_lane_u8(c, 3) << 4 * 3;
206         ret |= (uint64_t)vgetq_lane_u8(c, 4) << 4 * 4;
207         ret |= (uint64_t)vgetq_lane_u8(c, 5) << 4 * 5;
208         ret |= (uint64_t)vgetq_lane_u8(c, 6) << 4 * 6;
209         ret |= (uint64_t)vgetq_lane_u8(c, 7) << 4 * 7;
210         ret |= (uint64_t)vgetq_lane_u8(c, 8) << 4 * 8;
211         ret |= (uint64_t)vgetq_lane_u8(c, 9) << 4 * 9;
212         ret |= (uint64_t)vgetq_lane_u8(c, 10) << 4 * 10;
213         ret |= (uint64_t)vgetq_lane_u8(c, 11) << 4 * 11;
214         ret |= (uint64_t)vgetq_lane_u8(c, 12) << 4 * 12;
215         ret |= (uint64_t)vgetq_lane_u8(c, 13) << 4 * 13;
216         ret |= (uint64_t)vgetq_lane_u8(c, 14) << 4 * 14;
217         ret |= (uint64_t)vgetq_lane_u8(c, 15) << 4 * 15;
218 
219         return ret;
220 }
221 
222 uint64_t gift_64_vec_sbox_decrypt(const uint64_t c, const uint64_t key[2])
223 {
224         // pack into vector register
225         uint8x16_t m;
226         U64_TO_V128(m, c);
227 
228         // generate round keys
229         uint8x16_t rks[ROUNDS_GIFT_64];
230         gift_64_vec_sbox_generate_round_keys(rks, key);
231 
232         // round loop (in reverse)
233         for (int round = ROUNDS_GIFT_64 - 1; round >= 0; round--) {
234                 m = veorq_u8(m, rks[round]);
235                 m = gift_64_vec_sbox_permute_inv(m);
236                 m = gift_64_vec_sbox_subcells_inv(m);
237         }
238 
239         // unpack
```

```
240         uint64_t ret = 0UL;
241         ret |= (uint64_t)vgetq_lane_u8(m, 0) << 4 * 0;
242         ret |= (uint64_t)vgetq_lane_u8(m, 1) << 4 * 1;
243         ret |= (uint64_t)vgetq_lane_u8(m, 2) << 4 * 2;
244         ret |= (uint64_t)vgetq_lane_u8(m, 3) << 4 * 3;
245         ret |= (uint64_t)vgetq_lane_u8(m, 4) << 4 * 4;
246         ret |= (uint64_t)vgetq_lane_u8(m, 5) << 4 * 5;
247         ret |= (uint64_t)vgetq_lane_u8(m, 6) << 4 * 6;
248         ret |= (uint64_t)vgetq_lane_u8(m, 7) << 4 * 7;
249         ret |= (uint64_t)vgetq_lane_u8(m, 8) << 4 * 8;
250         ret |= (uint64_t)vgetq_lane_u8(m, 9) << 4 * 9;
251         ret |= (uint64_t)vgetq_lane_u8(m, 10) << 4 * 10;
252         ret |= (uint64_t)vgetq_lane_u8(m, 11) << 4 * 11;
253         ret |= (uint64_t)vgetq_lane_u8(m, 12) << 4 * 12;
254         ret |= (uint64_t)vgetq_lane_u8(m, 13) << 4 * 13;
255         ret |= (uint64_t)vgetq_lane_u8(m, 14) << 4 * 14;
256         ret |= (uint64_t)vgetq_lane_u8(m, 15) << 4 * 15;
257
258         return ret;
259 }
```

A.1.3 Bitslicing

Listing A.5: `gift_vec_sliced.h`

```
1  #ifndef GIFT_VEC_SLICED_H
2  #define GIFT_VEC_SLICED_H
3
4  #include <stdint.h>
5  #include <arm_neon.h>
6
7  #define ROUNDS_GIFT_64 28
8
9  // expose for benchmarking
10 uint8x16_t shl(uint8x16_t v, int n);
11 uint8x16_t shr(uint8x16_t v, int n);
12 void gift_64_vec_sliced_swapmove(uint8x16_t *restrict a, uint8x16_t *restrict b,
       uint8x16_t m, int n);
13 void gift_64_vec_sliced_bits_pack(uint8x16x4_t m[restrict 2]);
14 void gift_64_vec_sliced_bits_unpack(uint8x16x4_t m[restrict 2]);
15
16 void gift_64_vec_sliced_subcells(uint8x16x4_t cipher_state[restrict 2]);
17 void gift_64_vec_sliced_subcells_inv(uint8x16x4_t cipher_state[restrict 2]);
18 void gift_64_vec_sliced_permute(uint8x16x4_t cipher_state[restrict 2]);
19 void gift_64_vec_sliced_permute_inv(uint8x16x4_t cipher_state[2]);
20 void gift_64_vec_sliced_generate_round_keys(uint8x16x4_t rks[restrict
       ROUNDS_GIFT_64][2],
21                                             const uint64_t key[restrict 2]);
22
23 void gift_64_vec_sliced_init(void);
24
25 void gift_64_vec_sliced_encrypt(uint64_t c[restrict 16],
26                                 const uint64_t m[restrict 16],
27                                 const uint64_t key[restrict 2]);
```

```
28 void gift_64_vec_sliced_decrypt(uint64_t m[restrict 16],
29                                 const uint64_t c[restrict 16],
30                                 const uint64_t key[restrict 2]);
31
32 #endif
```

Listing A.6: `gift_vec_sliced.c`

```
1  #include "gift_vec_sliced.h"
2
3  #include <stddef.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  static uint64_t pack_shf_u64[4] = {
8          0x1303120211011000UL, 0x1707160615051404UL, // S0/S1/S2/S3
9          0x1b0b1a0a19091808UL, 0x1f0f1e0e1d0d1c0cUL, // S4/S5/S6/S7
10 };
11
12 static uint64_t pack_shf_inv_u64[4] = {
13         0x0e0c0a0806040200UL, 0x1e1c1a1816141210UL, // S0/S1/S2/S3
14         0x0f0d0b0907050301UL, 0x1f1d1b1917151311UL, // S4/S5/S6/S7
15 };
16
17 static uint64_t perm_u64[8] = {
18         0x0f0b07030c080400UL, 0x0d0905010e0a0602UL, // S0/S4
19         0x0c0804000d090501UL, 0x0e0a06020f0b0703UL, // S1/S5
20         0x0d0905010e0a0602UL, 0x0f0b07030c080400UL, // S2/S6
21         0x0e0a06020f0b0703UL, 0x0c0804000d090501UL  // S3/S7
22 };
23
24
25 static uint64_t perm_inv_u64[8] = {
26         0x05090d0104080c00UL, 0x070b0f03060a0e02UL, // S0/S4
27         0x090d0105080c0004UL, 0x0b0f03070a0e0206UL, // S1/S5
28         0x0d0105090c000408UL, 0x0f03070b0e02060aUL, // S2/S6
29         0x0105090d0004080cUL, 0x03070b0f02060a0eUL  // S3/S7
30 };
31
32 static uint8x16x2_t pack_shf;
33 static uint8x16x2_t pack_shf_inv;
34 static uint8x16x4_t perm;
35 static uint8x16x4_t perm_inv;
36
37 static uint8x16_t pack_mask_0;
38 static uint8x16_t pack_mask_1;
39 static uint8x16_t pack_mask_2;
40
41 static const int round_const[] = {
42         // rounds 0-15
43         0x01, 0x03, 0x07, 0x0F, 0x1F, 0x3E, 0x3D, 0x3B, 0x37, 0x2F, 0x1E, 0x3C, 0
               x39, 0x33, 0x27, 0x0E,
44         // rounds 16-31
45         0x1D, 0x3A, 0x35, 0x2B, 0x16, 0x2C, 0x18, 0x30, 0x21, 0x02, 0x05, 0x0B, 0
               x17, 0x2E, 0x1C, 0x38,
46         // rounds 32-47
```

```
47          0x31, 0x23, 0x06, 0x0D, 0x1B, 0x36, 0x2D, 0x1A, 0x34, 0x29, 0x12, 0x24, 0
                x08, 0x11, 0x22, 0x04
48  };
49
50  uint8x16_t shl(uint8x16_t v, int n)
51  {
52          uint64_t l[2];
53          vst1q_u64(l, v);
54          l[1] = (l[1] << n) | (l[0] >> (64 - n));
55          l[0] <<= n;
56          return vreinterpretq_u8_u64(vld1q_u64(l));
57  }
58
59  uint8x16_t shr(uint8x16_t v, int n)
60  {
61          uint64_t l[2];
62          vst1q_u64(l, v);
63          l[0] = l[0] >> n | (((l[1] << (64 - n)) >> (64 - n)) << (64 - n));
64          l[1] >>= n;
65          return vreinterpretq_u8_u64(vld1q_u64(l));
66  }
67
68  void gift_64_vec_sliced_swapmove(uint8x16_t *restrict a, uint8x16_t *restrict b,
        uint8x16_t m, int n)
69  {
70
71          uint8x16_t t = vandq_u8(veorq_u8(shr(*a, n), *b), m);
72          *b = veorq_u8(*b, t);
73          *a = veorq_u8(*a, shl(t, n));
74  }
75
76  void gift_64_vec_sliced_bits_pack(uint8x16x4_t m[restrict 2])
77  {
78          // take care not to shift mask bits out of the register
79          gift_64_vec_sliced_swapmove(&m[0].val[0], &m[0].val[1], pack_mask_0, 1);
80          gift_64_vec_sliced_swapmove(&m[0].val[2], &m[0].val[3], pack_mask_0, 1);
81          gift_64_vec_sliced_swapmove(&m[1].val[0], &m[1].val[1], pack_mask_0, 1);
82          gift_64_vec_sliced_swapmove(&m[1].val[2], &m[1].val[3], pack_mask_0, 1);
83
84          gift_64_vec_sliced_swapmove(&m[0].val[0], &m[0].val[2], pack_mask_1, 2);
85          gift_64_vec_sliced_swapmove(&m[0].val[1], &m[0].val[3], pack_mask_1, 2);
86          gift_64_vec_sliced_swapmove(&m[1].val[0], &m[1].val[2], pack_mask_1, 2);
87          gift_64_vec_sliced_swapmove(&m[1].val[1], &m[1].val[3], pack_mask_1, 2);
88
89          // make bytes (a0 b0 c0 d0 a4 b4 c4 d4 -> a0 b0 c0 d0 e0 f0 g0 h0)
90          gift_64_vec_sliced_swapmove(&m[0].val[0], &m[1].val[0], pack_mask_2, 4);
91          gift_64_vec_sliced_swapmove(&m[0].val[2], &m[1].val[2], pack_mask_2, 4);
92          gift_64_vec_sliced_swapmove(&m[0].val[1], &m[1].val[1], pack_mask_2, 4);
93          gift_64_vec_sliced_swapmove(&m[0].val[3], &m[1].val[3], pack_mask_2, 4);
94
95          // same plaintext slice bits into same register (so we only have to do
96          // what we are doing here once instead of every round)
97          uint8x16x2_t pairs[4] = {
98                  { .val = { m[0].val[0], m[1].val[0] }},
99                  { .val = { m[0].val[1], m[1].val[1] }},
100                 { .val = { m[0].val[2], m[1].val[2] }},
101                 { .val = { m[0].val[3], m[1].val[3] }},
```

```
102         };
103
104         m[0].val[0] = vqtbl2q_u8(pairs[0], pack_shf.val[0]);
105         m[0].val[1] = vqtbl2q_u8(pairs[1], pack_shf.val[0]);
106         m[0].val[2] = vqtbl2q_u8(pairs[2], pack_shf.val[0]);
107         m[0].val[3] = vqtbl2q_u8(pairs[3], pack_shf.val[0]);
108
109         m[1].val[0] = vqtbl2q_u8(pairs[0], pack_shf.val[1]);
110         m[1].val[1] = vqtbl2q_u8(pairs[1], pack_shf.val[1]);
111         m[1].val[2] = vqtbl2q_u8(pairs[2], pack_shf.val[1]);
112         m[1].val[3] = vqtbl2q_u8(pairs[3], pack_shf.val[1]);
113 }
114
115 void gift_64_vec_sliced_bits_unpack(uint8x16x4_t m[restrict 2])
116 {
117         uint8x16x2_t pairs[4] = {
118                 { .val = { m[0].val[0], m[1].val[0] }},
119                 { .val = { m[0].val[1], m[1].val[1] }},
120                 { .val = { m[0].val[2], m[1].val[2] }},
121                 { .val = { m[0].val[3], m[1].val[3] }},
122         };
123
124         m[0].val[0] = vqtbl2q_u8(pairs[0], pack_shf_inv.val[0]);
125         m[0].val[1] = vqtbl2q_u8(pairs[1], pack_shf_inv.val[0]);
126         m[0].val[2] = vqtbl2q_u8(pairs[2], pack_shf_inv.val[0]);
127         m[0].val[3] = vqtbl2q_u8(pairs[3], pack_shf_inv.val[0]);
128
129         m[1].val[0] = vqtbl2q_u8(pairs[0], pack_shf_inv.val[1]);
130         m[1].val[1] = vqtbl2q_u8(pairs[1], pack_shf_inv.val[1]);
131         m[1].val[2] = vqtbl2q_u8(pairs[2], pack_shf_inv.val[1]);
132         m[1].val[3] = vqtbl2q_u8(pairs[3], pack_shf_inv.val[1]);
133
134         // take care not to shift mask bits out of the register
135         gift_64_vec_sliced_swapmove(&m[0].val[0], &m[0].val[1], pack_mask_0, 1);
136         gift_64_vec_sliced_swapmove(&m[0].val[2], &m[0].val[3], pack_mask_0, 1);
137         gift_64_vec_sliced_swapmove(&m[1].val[0], &m[1].val[1], pack_mask_0, 1);
138         gift_64_vec_sliced_swapmove(&m[1].val[2], &m[1].val[3], pack_mask_0, 1);
139
140         gift_64_vec_sliced_swapmove(&m[0].val[0], &m[0].val[2], pack_mask_1, 2);
141         gift_64_vec_sliced_swapmove(&m[0].val[1], &m[0].val[3], pack_mask_1, 2);
142         gift_64_vec_sliced_swapmove(&m[1].val[0], &m[1].val[2], pack_mask_1, 2);
143         gift_64_vec_sliced_swapmove(&m[1].val[1], &m[1].val[3], pack_mask_1, 2);
144
145         // make bytes (a0 b0 c0 d0 a4 b4 c4 d4 -> a0 b0 c0 d0 e0 f0 g0 h0)
146         gift_64_vec_sliced_swapmove(&m[0].val[0], &m[1].val[0], pack_mask_2, 4);
147         gift_64_vec_sliced_swapmove(&m[0].val[2], &m[1].val[2], pack_mask_2, 4);
148         gift_64_vec_sliced_swapmove(&m[0].val[1], &m[1].val[1], pack_mask_2, 4);
149         gift_64_vec_sliced_swapmove(&m[0].val[3], &m[1].val[3], pack_mask_2, 4);
150 }
151
152 void gift_64_vec_sliced_subcells(uint8x16x4_t cs[restrict 2])
153 {
154         cs[0].val[1] = veorq_u8(cs[0].val[1],
155                                 vandq_u8(cs[0].val[0], cs[0].val[2]));
156         uint8x16_t t = veorq_u8(cs[0].val[0],
157                                 vandq_u8(cs[0].val[1], cs[0].val[3]));
158         cs[0].val[2] = veorq_u8(cs[0].val[2], vorrq_u8(t, cs[0].val[1]));
```

```
159         cs[0].val[0] = veorq_u8(cs[0].val[3], cs[0].val[2]);
160         cs[0].val[1] = veorq_u8(cs[0].val[1], cs[0].val[0]);
161         cs[0].val[0] = vmvnq_u8(cs[0].val[0]);
162         cs[0].val[2] = veorq_u8(cs[0].val[2], vandq_u8(t, cs[0].val[1]));
163         cs[0].val[3] = t;
164
165         cs[1].val[1] = veorq_u8(cs[1].val[1],
166                                 vandq_u8(cs[1].val[0], cs[1].val[2]));
167         t            = veorq_u8(cs[1].val[0],
168                                 vandq_u8(cs[1].val[1], cs[1].val[3]));
169         cs[1].val[2] = veorq_u8(cs[1].val[2], vorrq_u8(t, cs[1].val[1]));
170         cs[1].val[0] = veorq_u8(cs[1].val[3], cs[1].val[2]);
171         cs[1].val[1] = veorq_u8(cs[1].val[1], cs[1].val[0]);
172         cs[1].val[0] = vmvnq_u8(cs[1].val[0]);
173         cs[1].val[2] = veorq_u8(cs[1].val[2], vandq_u8(t, cs[1].val[1]));
174         cs[1].val[3] = t;
175 }
176
177 void gift_64_vec_sliced_subcells_inv(uint8x16x4_t cs[restrict 2])
178 {
179         uint8x16_t t = cs[0].val[3];
180         cs[0].val[2] = veorq_u8(cs[0].val[2], vandq_u8(t, cs[0].val[1]));
181         cs[0].val[0] = vmvnq_u8(cs[0].val[0]);
182         cs[0].val[1] = veorq_u8(cs[0].val[1], cs[0].val[0]);
183         cs[0].val[3] = veorq_u8(cs[0].val[0], cs[0].val[2]);
184         cs[0].val[2] = veorq_u8(cs[0].val[2], vorrq_u8(t, cs[0].val[1]));
185         cs[0].val[0] = veorq_u8(t, vandq_u8(cs[0].val[1], cs[0].val[3]));
186         cs[0].val[1] = veorq_u8(cs[0].val[1],
187                                 vandq_u8(cs[0].val[0], cs[0].val[2]));
188
189         t            = cs[1].val[3];
190         cs[1].val[2] = veorq_u8(cs[1].val[2], vandq_u8(t, cs[1].val[1]));
191         cs[1].val[0] = vmvnq_u8(cs[1].val[0]);
192         cs[1].val[1] = veorq_u8(cs[1].val[1], cs[1].val[0]);
193         cs[1].val[3] = veorq_u8(cs[1].val[0], cs[1].val[2]);
194         cs[1].val[2] = veorq_u8(cs[1].val[2], vorrq_u8(t, cs[1].val[1]));
195         cs[1].val[0] = veorq_u8(t, vandq_u8(cs[1].val[1], cs[1].val[3]));
196         cs[1].val[1] = veorq_u8(cs[1].val[1],
197                                 vandq_u8(cs[1].val[0], cs[1].val[2]));
198 }
199
200 void gift_64_vec_sliced_permute(uint8x16x4_t cs[restrict 2])
201 {
202         cs[0].val[0] = vqtbl1q_u8(cs[0].val[0], perm.val[0]);
203         cs[0].val[1] = vqtbl1q_u8(cs[0].val[1], perm.val[1]);
204         cs[0].val[2] = vqtbl1q_u8(cs[0].val[2], perm.val[2]);
205         cs[0].val[3] = vqtbl1q_u8(cs[0].val[3], perm.val[3]);
206
207         cs[1].val[0] = vqtbl1q_u8(cs[1].val[0], perm.val[0]);
208         cs[1].val[1] = vqtbl1q_u8(cs[1].val[1], perm.val[1]);
209         cs[1].val[2] = vqtbl1q_u8(cs[1].val[2], perm.val[2]);
210         cs[1].val[3] = vqtbl1q_u8(cs[1].val[3], perm.val[3]);
211 }
212
213 void gift_64_vec_sliced_permute_inv(uint8x16x4_t cs[restrict 2])
214 {
215         cs[0].val[0] = vqtbl1q_u8(cs[0].val[0], perm_inv.val[0]);
```

```
216         cs[0].val[1] = vqtbl1q_u8(cs[0].val[1], perm_inv.val[1]);
217         cs[0].val[2] = vqtbl1q_u8(cs[0].val[2], perm_inv.val[2]);
218         cs[0].val[3] = vqtbl1q_u8(cs[0].val[3], perm_inv.val[3]);
219 
220         cs[1].val[0] = vqtbl1q_u8(cs[1].val[0], perm_inv.val[0]);
221         cs[1].val[1] = vqtbl1q_u8(cs[1].val[1], perm_inv.val[1]);
222         cs[1].val[2] = vqtbl1q_u8(cs[1].val[2], perm_inv.val[2]);
223         cs[1].val[3] = vqtbl1q_u8(cs[1].val[3], perm_inv.val[3]);
224 }
225 
226 void gift_64_vec_sliced_generate_round_keys(uint8x16x4_t rks[restrict
        ROUNDS_GIFT_64][2],
227                                             const uint64_t key[restrict 2])
228 {
229         uint64_t key_state[] = {key[0], key[1]};
230         for (int round = 0; round < ROUNDS_GIFT_64; round++) {
231                 int v = (key_state[0] >> 0 ) & 0xffff;
232                 int u = (key_state[0] >> 16) & 0xffff;
233 
234                 // add round key (RK=U||V)
235                 // (slice 2 stays unused)
236                 uint64_t rk[6] = { 0x0UL };
237                 for (size_t i = 0; i < 8; i++) {
238                         int key_bit_v   = (v >> (i + 0)) & 0x1;
239                         int key_bit_u   = (u >> (i + 0)) & 0x1;
240                         rk[0]           ^= (uint64_t)key_bit_v << (i * 8);
241                         rk[2]           ^= (uint64_t)key_bit_u << (i * 8);
242 
243                         key_bit_v       = (v >> (i + 8)) & 0x1;
244                         key_bit_u       = (u >> (i + 8)) & 0x1;
245                         rk[1]           ^= (uint64_t)key_bit_v << (i * 8);
246                         rk[3]           ^= (uint64_t)key_bit_u << (i * 8);
247                 }
248 
249                 // add single bit
250                 rk[5] ^= 1UL << (7 * 8);
251 
252                 // add round constants
253                 rk[4] ^= ((uint64_t)(round_const[round] >> 0) & 0x1) << (0 * 8);
254                 rk[4] ^= ((uint64_t)(round_const[round] >> 1) & 0x1) << (1 * 8);
255                 rk[4] ^= ((uint64_t)(round_const[round] >> 2) & 0x1) << (2 * 8);
256                 rk[4] ^= ((uint64_t)(round_const[round] >> 3) & 0x1) << (3 * 8);
257                 rk[4] ^= ((uint64_t)(round_const[round] >> 4) & 0x1) << (4 * 8);
258                 rk[4] ^= ((uint64_t)(round_const[round] >> 5) & 0x1) << (5 * 8);
259 
260                 // extend bits to bytes
261                 for (size_t i = 0; i < 6; i++) {
262                         rk[i] |= rk[i] << 1;
263                         rk[i] |= rk[i] << 2;
264                         rk[i] |= rk[i] << 4;
265                 }
266 
267                 rks[round][0].val[0] = vsetq_lane_u64(rk[0], rks[round][0].val
                        [0], 0);
268                 rks[round][0].val[0] = vsetq_lane_u64(rk[1], rks[round][0].val
                        [0], 0);
269                 rks[round][0].val[1] = vsetq_lane_u64(rk[2], rks[round][0].val
```

```
                    [1], 0);
270                 rks[round][0].val[1] = vsetq_lane_u64(rk[3], rks[round][0].val
                        [1], 0);
271                 rks[round][0].val[2] = vdupq_n_u8(0);
272                 rks[round][0].val[3] = vsetq_lane_u64(rk[4], rks[round][0].val
                        [3], 0);
273                 rks[round][0].val[3] = vsetq_lane_u64(rk[5], rks[round][0].val
                        [3], 0);
274                 rks[round][1]        = rks[round][0];
275
276                 // update key state
277                 int k0 = (key_state[0] >> 0 ) & 0xffffUL;
278                 int k1 = (key_state[0] >> 16) & 0xffffUL;
279                 k0 = (k0 >> 12) | ((k0 & 0xfff) << 4);
280                 k1 = (k1 >> 2 ) | ((k1 & 0x3  ) << 14);
281                 key_state[0] >>= 32;
282                 key_state[0] |= (key_state[1] & 0xffffffffUL) << 32;
283                 key_state[1] >>= 32;
284                 key_state[1] |= ((uint64_t)k0 << 32) | ((uint64_t)k1 << 48);
285         }
286 }
287
288 void gift_64_vec_sliced_init(void)
289 {
290         // bit packing shuffle
291         pack_shf = vld1q_u8_x2((uint8_t*)&pack_shf_u64[0]);
292
293         // inverse bit packing shuffle
294         pack_shf_inv = vld1q_u8_x2((uint8_t*)&pack_shf_inv_u64[0]);
295
296         // permutations
297         perm = vld1q_u8_x4((uint8_t*)&perm_u64[0]);
298
299         // inverse permutations
300         perm_inv = vld1q_u8_x4((uint8_t*)&perm_inv_u64[0]);
301
302         // packing masks
303         pack_mask_0 = vdupq_n_u8(0x55);
304         pack_mask_1 = vdupq_n_u8(0x33);
305         pack_mask_2 = vdupq_n_u8(0x0f);
306 }
307
308 void gift_64_vec_sliced_encrypt(uint64_t c[restrict 16],
309                                 const uint64_t m[restrict 16],
310                                 const uint64_t key[restrict 2])
311 {
312         uint8x16x4_t s[2];
313         s[0] = vld1q_u8_x4((uint8_t*)&m[0]);
314         s[1] = vld1q_u8_x4((uint8_t*)&m[8]);
315         gift_64_vec_sliced_bits_pack(s);
316
317         uint8x16x4_t rks[ROUNDS_GIFT_64][2];
318         gift_64_vec_sliced_generate_round_keys(rks, key);
319
320         for (int round = 0; round < ROUNDS_GIFT_64; round++) {
321                 gift_64_vec_sliced_subcells(s);
322                 gift_64_vec_sliced_permute(s);
```

```
323
324                 s[0].val[0] = veorq_u8(s[0].val[0], rks[round][0].val[0]);
325                 s[0].val[1] = veorq_u8(s[0].val[1], rks[round][0].val[1]);
326                 s[0].val[2] = veorq_u8(s[0].val[2], rks[round][0].val[2]);
327                 s[0].val[3] = veorq_u8(s[0].val[3], rks[round][0].val[3]);
328                 s[1].val[0] = veorq_u8(s[1].val[0], rks[round][1].val[0]);
329                 s[1].val[1] = veorq_u8(s[1].val[1], rks[round][1].val[1]);
330                 s[1].val[2] = veorq_u8(s[1].val[2], rks[round][1].val[2]);
331                 s[1].val[3] = veorq_u8(s[1].val[3], rks[round][1].val[3]);
332         }
333
334         gift_64_vec_sliced_bits_unpack(s);
335         vst1q_u8_x4((uint8_t*)&c[0], s[0]);
336         vst1q_u8_x4((uint8_t*)&c[8], s[1]);
337 }
338
339 void gift_64_vec_sliced_decrypt(uint64_t m[restrict 16],
340                                 const uint64_t c[restrict 16],
341                                 const uint64_t key[restrict 2])
342 {
343         uint8x16x4_t s[2];
344         s[0] = vld1q_u8_x4((uint8_t*)&c[0]);
345         s[1] = vld1q_u8_x4((uint8_t*)&c[8]);
346         gift_64_vec_sliced_bits_pack(s);
347
348         uint8x16x4_t rks[ROUNDS_GIFT_64][2];
349         gift_64_vec_sliced_generate_round_keys(rks, key);
350
351         for (int round = ROUNDS_GIFT_64 - 1; round >= 0; round--) {
352                 s[0].val[0] = veorq_u8(s[0].val[0], rks[round][0].val[0]);
353                 s[0].val[1] = veorq_u8(s[0].val[1], rks[round][0].val[1]);
354                 s[0].val[2] = veorq_u8(s[0].val[2], rks[round][0].val[2]);
355                 s[0].val[3] = veorq_u8(s[0].val[3], rks[round][0].val[3]);
356                 s[1].val[0] = veorq_u8(s[1].val[0], rks[round][1].val[0]);
357                 s[1].val[1] = veorq_u8(s[1].val[1], rks[round][1].val[1]);
358                 s[1].val[2] = veorq_u8(s[1].val[2], rks[round][1].val[2]);
359                 s[1].val[3] = veorq_u8(s[1].val[3], rks[round][1].val[3]);
360
361                 gift_64_vec_sliced_permute_inv(s);
362                 gift_64_vec_sliced_subcells_inv(s);
363         }
364
365         gift_64_vec_sliced_bits_unpack(s);
366         vst1q_u8_x4((uint8_t*)&m[0], s[0]);
367         vst1q_u8_x4((uint8_t*)&m[8], s[1]);
368 }
```

Appendix B

Lorem dolor

Bibliography

[1] Subhadeep Banik et al. "GIFT: A Small Present". In: Aug. 2017, pp. 321–345. ISBN: 978-3-319-66786-7. DOI: 10.1007/978-3-319-66787-4_16.

[2] Ryad Benadjila et al. "Implementing Lightweight Block Ciphers on x86 Architectures". In: Selected Areas in Cryptography – SAC 2013. Ed. by Tanja Lange, Kristin Lauter, and Petr Lisoněk. Berlin, Heidelberg: Springer Berlin Heidelberg, 2014, pp. 324–351. ISBN: 978-3-662-43414-7.

[3] ARM Limited. Arm Neon Intrinsics Reference. 2022.