

# Board Questions

Seventh Session, Oct 17, 2016

## 1 Chain Rule for Entropy

Prove the chain rule for entropy, namely that  $H(X, Y) = H(X|Y) + H(Y)$ .

## 2 Data Compression

For the rest of today, we are studying the problem of *data compression*. Assume we have a source of information which emits four different symbols  $a, b, c, d$  with probabilities  $1/2, 1/4, 1/8, 1/8$ , respectively. We model our source as iid realisation of a categorical random variable  $X$  with distribution  $P_X$ . A typical sequence of symbols from this source could look like this: *bababcbdbbaabadbaaaa*. Our task is to *compress* such sequences as much as possible. Formally, we would like to map every source symbol to a binary string such that the average code length is minimal.

### 2.1 Codes

The following are four (binary symbol) codes  $C, D, E, F$  for the categorical random variable  $X$ , with  $\mathcal{X} = \{a, b, c, d\}$ :

| $x$ | $P(X = x)$ | $C(x)$ | $D(x)$ | $E(x)$ | $F(x)$ |
|-----|------------|--------|--------|--------|--------|
| $a$ | $1/2$      | 0      | 0      | 0      | 00     |
| $b$ | $1/4$      | 10     | 010    | 01     | 01     |
| $c$ | $1/8$      | 110    | 01     | 011    | 10     |
| $d$ | $1/8$      | 111    | 10     | 111    | 11     |

These codes can be used to encode strings of symbols by concatenation. For instance, the encoding of string "adba" under code  $E$  is

$$E(adba) = E(a)E(d)E(b)E(a) = 0\ 111\ 01\ 0 = 0111010$$

1. What is the encoding of *adba* under codes  $C, D$  and  $F$ ?
2. What is the decoding of 001001110 under code  $C$ ?
3. What is the decoding of 0100100 under code  $D$ ? Is it unique?
4. What is the decoding of 001111 under code  $E$ ? Is it unique? What happens if you learn that the next bit is 1 (so you have to decode 0011111 under  $E$ )?
5. Can you prove that arbitrary concatenations of codewords of  $C$  are uniquely decodable? What about concatenations of codewords of  $E$  or  $F$ ?
6. Which of the above codes is the most convenient to work with in terms of encoding and decoding? Why?

## 2.2 Code Length

The *average code length* of a binary symbol code is defined as follows. Let  $\ell(s)$  denote the length of a string  $s \in \{0, 1\}^*$ . The (average) length of a code  $C$  for a source  $X$  is defined as

$$\ell_C(X) := \mathbb{E}[\ell(C(X))] = \sum_{x \in \text{supp}(X)} P(X = x) \ell(C(x)).$$

1. Compute  $\ell_C(X)$ ,  $\ell_D(X)$ ,  $\ell_E(X)$ ,  $\ell_F(X)$  for the codes of the previous section.
2. Compute the entropy  $H(X)$  for the distribution  $P_X$  above and compare both the obtained values and the way you have obtained them.

In the Information Theory course, we will prove Shannon's source-coding theorem:

**Theorem 1.** Let  $P_X$  be a distribution and  $\ell_{\min}(X) := \min_C \ell_C(X)$  the minimal average codeword length among all uniquely decodable codes. Then,

$$H(X) \leq \ell_{\min}(X) \leq H(X) + 1.$$

In other words, the Shannon entropy pretty much determines the optimal average codeword length.

## 2.3 Optimal Codes

1. Show that code  $C$  from Section 2.1 is optimal in terms of average coding length.
2. Construct an optimal symbol code for the following distribution:

|            |     |     |     |     |     |      |      |
|------------|-----|-----|-----|-----|-----|------|------|
| $y$        | $a$ | $b$ | $c$ | $d$ | $e$ | $f$  | $g$  |
| $P(Y = y)$ | 1/4 | 1/4 | 1/8 | 1/8 | 1/8 | 1/16 | 1/16 |

**Hint:** Should symbols with high probability to occur receive long or short codewords?

3. Prove that the code you found is optimal!
4. Look up on the internet what [Huffman coding](#) is and use it to find an optimal binary symbol code for the following distribution:

|            |      |      |     |      |      |
|------------|------|------|-----|------|------|
| $z$        | $a$  | $b$  | $c$ | $d$  | $e$  |
| $P(Z = z)$ | 0.25 | 0.25 | 0.2 | 0.15 | 0.15 |

## 2.4 Randomness-Efficient Sampling

Let's consider a different problem, namely how to efficiently sample iid from a distribution  $P_X$ . Explain how to repeatedly sample from  $P_X$  given an optimal binary code and access to uniformly distributed random bits. How many random bits per sampled symbol do you need on average?