On Combiners for Verifiable Random Functions

Basil Rohner (brohner@ethz.ch)
Bachelor's Thesis, ETH Zürich
April 11, 2026

Research Question

Can we *combine* multiple instances of verifiable random function (VRFs) into a single VRF that is secure as long as *enough* of the instances are?

- How do we *combine* the candidate schemes?
- What are *enough* candidates to combine?

Can we combine *k* out of *n* VRF instances in a *black-box* fashion?

Verifiable Functions

Definition (Verifiable Function)

A *verifiable function* (VF) VF is a triple of the following efficient algorithms:

- $\mathsf{Gen}_{\mathsf{VF}}(1^\lambda) = (\mathsf{sk}, \mathsf{pk})$ generates a key-pair
- $\mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x) = (y, \pi)$ evaluates points to an image-proof pair
- $\mathsf{Vfy}_{\mathsf{VF}}(\mathsf{pk}, x, y, \pi) = b$ verifies evaluations

A VF is a purely syntactic object, we define security properties on top of it.

Properties of Verifiable Functions

ε-Correctness

Honestly generated image-proof pairs verify with probability at least ε:

$$\Pr\left[\begin{array}{c}(\mathsf{sk},\mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VF}}(1^{\lambda}) \\ x \leftarrow_{\$} \{0,1\}^{\lambda} \quad : \mathsf{Vfy}_{\mathsf{VF}}(\mathsf{pk},x,y,\pi) = 1 \\ (y,\pi) \leftarrow \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk},x)\end{array}\right] \geq \varepsilon(\lambda)$$

VF is *correct* if it is 1-correct and *statistically correct* if it is $(1-\varepsilon)$-correct and $\varepsilon \in \mathsf{negl}(\lambda)$.

Properties of Verifiable Functions

Unique Provability

For every pk and every x, at most one image y is provable:

$$\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y_0, \pi_0) = \mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y_1, \pi_1) = 1 \implies y_0 = y_1.$$

Properties of Verifiable Functions

$(\varepsilon, \mathfrak{t})$-Pseudorandom

For any adversary $\mathcal{A}$ running in time at most $\mathfrak{t}$, playing the prf experiment $\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$:
The advantage $\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ is bounded from above by

$$\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

Properties of Verifiable Functions

$(\varepsilon, \mathfrak{t})$-Unpredictability

For any adversary $\mathcal{A}$ running in time at most $\mathfrak{t}$, playing the prf experiment $\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$: The advantage $\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ is bounded from above by

$$\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

Properties of Verifiable Functions

$(\varepsilon, \mathfrak{t})$-Weak Pseudorandomness

For any adversary $\mathcal{A}$ running in time at most $\mathfrak{t}$, playing the prf experiment $\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$:
The advantage $\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ is bounded from above by

$$\mathbf{Adv}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathsf{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

Verifiable Random Functions

Verifiable Random Function

A *verifiable random function* (VRF) is a VF that is:

- Correct
- Uniquely Provable
- Pseudorandom

Robust Black-Box Combiners

Definition (Robust $(n; k)$ Black-Box P-Combiner)

A ppt. oracle Turing machine Π_P that, given oracle access to n candidates $\mathcal{O}_1, \ldots, \mathcal{O}_n$, implements primitive P securely whenever at least k of the candidates do s.t. computational security properties hold against inefficient adversaries.

- **Black-box:** the combiner queries candidates as oracles — it cannot inspect or modify their code.
- We require security against adversaries with access to a **PSPACE oracle**, forcing the combiner to derive its security from the candidates.
- Known results: simple $(n; 1)$ black-box combiners exist for PRFs, OWFs, PKE, key agreement, … — but **not known for VRFs**.

Robust Black-Box DAG Combiners

We consider robust black-box combiners in a DAG normal form.

- Dedicated **source** s (the input) and **sink** t (the output).
- Every other vertex v carries
  - a label $\ell(v) = (i, j)$ specifying *which candidate's* j-th oracle is queried, and
  - a ppt. Turing machine f^v that computes the query input from the responses of the predecessors $\mathcal{N}_{\mathcal{G}}^{-}(v)$.
- Execution traces the DAG in topological order: at each v, build $\mathbf{q}_v \leftarrow f^v(\{\mathbf{x}_w\}_{w \in \mathcal{N}_{\mathcal{G}}^{-}(v)})$ and set $\mathbf{x}_v \leftarrow \mathcal{O}_{\ell(v)}(\mathbf{q}_v)$. The sink's Turing machine f^t produces the final output.

Equivalence. Every robust $(n; k)$ black-box combiner has a *computationally equivalent* DAG combiner — the DAG form is a convenient normal form for our proofs.

Equivalence

- Robust $(n; k)$ black-box DAG combiners are robust $(n; k)$ black-box combiners
- Robust $(n; k)$ black-box combiners can be converted into robust $(n; k)$ black-box DAG combiner

By induction over the number of oracle queries, bounded from above by $p(\lambda) \in \text{poly}$. $p(\lambda)$ layers. At every vertex v in layer l simulate the combiner Π_{VRF}

The 1-out-of-2 Combiner

- Simplest non-trivial case, only two candidates
- Construction extends to robust $(n-1)$-out-of-n black-box combiner
- Impossibility extends to robust $\lfloor n/2 \rfloor$-out-of-n black-box combiner

Impossibility Proof Overview

Given any robust $(2; 1)$ black-box DAG VRF-combiner Π_{VRF} we find oracles $\mathcal{O}_1, \mathcal{O}_2$ such that at least one of them implements a VRF but $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ doesn't implement a VRF.

- Let $\mathcal{O}_{vrf}$ be a VF candidate implementing a secure VRF
- Let $\mathcal{O}_{uppc}$ be a VF candidate implementing a uniquely provable and correct VF
- Let $\mathcal{A}$ be the adversary defined as follows

Impossibility of Robust (2; 1) Black-Box DAG VRF-Combiners

Impossibility of Robust $(n; \lfloor n/2 \rfloor)$ Black-Box DAG VRF-Combiners

Impossibility of Robust $(n; n-1)$ Black-Box DAG VRF-Combiners

What We Showed

Theorem. Impossibility 1-out-of-2 combiner.

There is **no** robust $(2; 1)$ black-box VRF-combiner.

Corollary. Impossibility $\lfloor n/2 \rfloor$-out-of-n combiner.

There is **no** robust $(n; \lfloor n/2 \rfloor)$ black-box VRF-combiner.

Generalizing to $(n-1)$-out-of-n Combiner

Conjecture. Impossibility $(n-1)$-out-of-n combiner.

There is **no** robust $(n; n-1)$ black-box VRF-combiner.

Where the Proof breaks down

- In the 1-out-of-2 case we rely on the fact that for one candidate we can always guess the responses perfectly, and for the other the obscure queries are mutually irrelevant in the sense that under the correct secret key the image y stays the same. That means that for all tests on the correct secret keys sk^* the output remains consistent through all runs. For any $n > 2$ and $k = n - 1$ we have at least two candidate whose outputs we cannot predict perfectly. While mutual independence holds for

Beyond Impossibility

Let assume *unique provability* for all *n* candidates:

- *Then a parallel combiner for PRF is applicable*

Too strong of an assumption?

- No, unique provability is an information theoretic property and typically proven.

Open Questions

Conjecture: $(n; n-1)$ is also impossible

There exists no robust $(n; n-1)$ black-box VRF-combiner.

That is, it is *not* enough for all-but-one candidates to be secure — any robust black-box VRF-combiner needs strictly more than a constant number of insecure candidates to tolerate.

Why it is hard. Our $(2; 1)$ impossibility proof exploits a specific structural argument about obscure queries and verification traces. Extending it to $n-1$ adversarial candidates would require reasoning about the simultaneous freedom on many oracles, and the current technique does not directly generalize.

Other open directions.

- Closing the gap between $(n; \lfloor n/2 \rfloor)$ (impossible) and $(n; n-1)$ (conjectured impossible).
- Finding the weakest candidate assumptions under which *some* robust black-box

Summary

Summary

- Introduced Robust $(n; k)$ Black-Box DAG Combiner for more principled analysis
- Established impossibility for robust $(n; \lfloor n/2 \rfloor)$ black-box VRF-combiner
- Conjectured impossibility for robust $(n; n-1)$ black-box VRF-combiner
- Assuming unique provability for all candidates allows for rboust $(n; 1)$ black-box VRF-combiner