ETH
Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

On Combiners for Verifiable Random Functions

Bachelor Thesis

Basil Rohner

March 17, 2026

Advisors: Prof. Dr. D. Hofheinz, N. Brandt, X. Duan
Department of Computer Science, ETH Zürich

Acknowledgments

I would like to thank my supervisors Nicholas Brandt and Xiaoqi Duan for their continuous support and patience. I also want to thank Professor Dennis Hofheinz for the opportunity to write my thesis at his group. Finally, I would like to thank my family and friends for their endless support and encouragement.

"The wise man does at once what the fool does finally."

— Niccolò Machiavelli

Abstract

Verifiable random functions (VRFs) are an extension of pseudorandom functions (PRFs), one can evaluate the function using a secret key to obtain random-looking images and corresponding proofs. Given the corresponding public key one can verify whether a given image was generated from an input if given a suitable proof.

In this thesis we study ways to combine multiple instances of VRFs in a black-box fashion. Specifically we study the existence of robust black-box VRF-combiners, constructions which are given oracle access to a set of candidate schemes, of which a sufficiently large (unknown) subest implements the VRF securely, and implements a secure VRF.

While there exist simple constructions of such robust black-box combiners for the related PRF primitive even if only one candidate implements a secure PRF, we show that there exists no robust black-box VRF-combiners if not at least half of the candidate schemes are secure, even if we relax the required security properties from the combiner.

Contents

Contents **iv**

1 Introduction **1**
1.1 Motivation and Previous Work 1
1.2 PRF Combiners 3
1.3 Our Contribution 4

2 Notation and Preliminaries **7**
2.1 Notation 7
2.2 Verifiable Functions 8
2.3 Robust Combiners 11

3 Results **13**
3.1 Robust Black-Box DAG Combiner 13
3.2 Impossibility of Robust Black-Box VRF-Combiner 18
3.3 Strong Robust Black-Box Combiners 37
3.4 Discussion 39

4 Conclusion **41**

Bibliography **42**

Appendix **43**
The Difference Lemma 43
Conjecture 43

Chapter 1

Introduction

1.1 Motivation and Previous Work

Pseudorandom Functions. A pseudorandom function (PRF) [GGM86] is a deterministic algorithm that takes as input a secret key k and a point x to produce an output y that looks random in the sense that no efficient adversary, modeled by a probabilistic polynomial time (ppt.) Turing machine can distringuish the output y from a random bitstring r of the same length. This must hold even if the adversary has access to a polynoial number of point evaluations (x, y) before distinguishing the output. PRFs are fundamental to modern cryptography and used to construct ....

Verifiable Functions. A verifiable function (VF) is a public-key primitive that allows the holder of a secret key sk to evaluate points x to obtain image-proof pairs (y, π) such that any party holding the public key pk can verify that y was indeed computed correctly from x if given the proof π. We require correctness and unique provability from the verification which state that correctly generated image-proof pairs (y, π) always (or except with negligible probability) is accepted by the verification algorithm and that at most one image can be proven respectively.

In this work we primarily study extensions of VRs, primarily the verifiable random function (VRF) introduced by Micali, Rabin and Vadhan in [MRV99] that additionally requires the outputs y to be pseudorandom to efficient adversaries without access to the corresponding proof. Similar to the pseudorandomness definition for PRFs we require that no efficient adversary can distinguish the images y from random outputs r, even if the adversary gets to see polynomially many evaluations of x with their corresponding proof. VRFs can be seen as a public-key analogoue of PRFs with verifiability requirements.

In practice VRFs are used to implement signatures with strong verifiability guarantees [**?**], resettable zero-knowledge proofs [**?**], lottery and e-cash systems [**?**] and they play a big role in distributed leader election protocols that runs many Proof-of-Stake blockchain systems [**?**].

Additionally we study VFs satisfying weaker notions of pseudorandomness such as weak pseudorandomness and unpredictability which give rise to verifiable unpredictable functions (VUFs) [**?**] and weak verifiable random functions (wVRFs) [**?**] respectively. VUFs additionally require that the evaluation of the VF on a fresh evaluation point cannot be predicted by efficient adversaries except with negligible probability and wVRFs require that pseudorandomness holds, but only on uniformly random evaluation points x, instead of a point chosen by the adversary.

add stronger notions cVRF, khVRF, aggVRF, unbiasVRF if time

Robust Combiners. In cryptography we often take a reductionist approach when constructing new cryptographic primitives, in general constructions satisfying computational security properties rely on cryptographic hardness assumptions. To hedge against the breakdown of cryptographic hardness assumptions, and thus the subsequence failure of the construction we may want to base the security of systems on multiple hardness assumptions. Robust combiners [**?**] are constructions that combine n candidate schemes, concrete instances of the same primitive, and implement a secure instance of that primitive if a large enough subset of those candidate is secure. The notion of combiners has gained traction with the rise of post-quantum and hybrid-cryptography areas

Stronger version of robust combiners are robust black-box combiners [**?**] which are only given query access to the candidate schemes as oracles, i.e. cannot inspect the Turing machine of the candidate scheme. The motivation of a robust black-box combiner is to have a combiner that can implement a secure scheme only with access to sub-schemes with the underlying code of the candidate schemes are not accessible to the combiner. We wish for the combiner to derive its security from the evaluation of the secure subset of oracles, not by making any modifications to the candidates or simply implementing a secure instance of the primitive himself. For that reason we additionally require robust black-box combiners to implement the secure instance relative to a PSPACE complete oracle, that is guarantee the security against adversaries with access to a PSPACE oracle.

Robust black-box combiners have been considered for a variety of cryptographic primitives such as oblivious transfer [**?**], non-interactive zero-knowledge proofs (NIZK) [**?**], non-interactive witness-indistinguishable arguments (NIWI) [**?**], indistinguishability obvuscation (iO) [**?**] and signature schemes [**?**]. Additionally many folklore constructions exist for PRF, key exchange protocols . While there exist VRF constructions rely on PRFs and

add some

NIWIs, for both of which combiners have been studied, black-box combiners for VRFs have, to the best of our knowledge, not been studied.

1.2 PRF Combiners

VRF can be considered as an extension of PRFs to the public-key setting with the additional requirements of verifiability. Simple robust black-box PRF combiners exist. One combiner works by evaluating the evaluation point x with every candidate scheme to obtain images y_1, y_2 and returning the XOR of the two images $y = y_1 \oplus y_2$. Pseudorandomness of the combined scheme can be shown with a reductionist approach. Specifically we show that given an adversary against the combined scheme, we can construct an adversary against every candidate scheme running in the same time with the same advantage. By contraposition, assuming that at least one candidate scheme is pseudorandom and there exists no efficient combiner with non-negligible advantage against the candidate we show that there exists no efficient adversary against the combined scheme with non-negligible advantage. We illustrate the construction of a robuts $(2;1)$ black-box PRF-combiner in Section 1.2.

$\underline{\mathsf{Eval}_{\mathsf{PRF}}^{\mathcal{O}_1,\mathcal{O}_2}(k,x)}$

1 : $y_1 \leftarrow \mathcal{O}_1(k,x)$
2 : $y_2 \leftarrow \mathcal{O}_2(k,x)$
3 : **return** $y_1 \oplus y_2$

Figure 1.1: Robust $(2;1)$ Black-Box PRF-combiner.

We outline the reduction and refer to the appendix for the formal proof. The reduction against candidate scheme $\mathcal{O}_i$ relies on the pseudorandomness oracle $\mathcal{O}_{eval}$ and simulates the other candidate $\mathcal{O}_{2-i}$ himself to answer queries of the combiners adversary with $\mathcal{O}_{eval}(x) \oplus \mathcal{O}_{2-i}(k,x)$. The adversary against the combined scheme then guesses the hidden bit b, trying to distinguish the random world from the real world which the reduction then uses to guess its own hidden bit b'. If the hidden bit $b' = 0$ then the adversary $\mathcal{A}$ is simulated perfectly in the sense that the reduction wins the security experiment with the same advantage of $\mathcal{A}$ while for bit $b' = 1$ the answers to the queries of the adversary are still uniformly random bitstrings and therefore the reduction also wins with the same probability.

Note that the existance of a robust $(2;1)$ black-box PRF-combiner naturally leads to a robust $(n;1)$ black-box VRF-combiner for any natural number n by iteratively applying the construction on the construction and a new candidate. Since there exists a robust $(n;1)$ black-box PRF-combiner one could hope

for a similar construction to work for VRFs. This is however not the case, as we will show in Theorem 3.19 there exist no robust $(n; \lfloor n/2 \rfloor)$ black-box combiner for VRFs.

1.3 Our Contribution

Robust Black-Box DAG Combiner. We introduce the notion of robust black-box DAG combiners, formally defined in Definition 3.1, DAG combiners for short. DAG combiners are black-box combiners which are defined by directed acyclic graphs (DAGs) for every implemented algorithm. The implemented algorithms are specified through computation that runs along the DAG starting from a designated source vertex and ending in a target vertex. In the execution vertices correspond to queries to implementation functions of candidate oracles on an input computed from all preceding vertices by a ppt. Turing machine (without oracle access to the candidates). DAG combiners make the structure of the black-box combiner more explicit by structuring it into interleaved oracle queries to the candidats and intermediate computation, that we model with Turing machines without oracle access to the candidates. We illustrate this concept in Figure 1.2 on the example of the simple robust black-box PRF-combiner in Section 1.2.

To connect DAG combiners and general black-box combiners we show that the notions are indeed equivalent, that is, that for every general black-box combiner we can construct a DAG combiner that behaves identically in the sense that the algorithms defined by the combiners are equivalent. We state this result formally in Theorem 3.2. The concept of a robust black-box DAG combiner allows us to reason over a more structured representation of robust black-box combiners, more similar to a circuit in structure simplifying the proofs later on.

Robust Black-Box VRF-Combiner. Following the introduction of a robust black-box DAG combiner, we study the simplest robust black-box VRF-combiner, robust $(2;1)$ black-box VRF-combiners. We answer the question on whether there is a construction that combines two candidates, of which only at least one is secure, negatively. Specifically we show impossibility of robust $(2;1)$ black-box VRF-combiners in **??**.

Since we can naturally use a robust $(n; \lfloor n/2 \rfloor)$ black-box VRF-combiner to construct a $(2;1)$ combiner by simply initializing half the candidates with $\mathcal{O}_1$ and the other half with $\mathcal{O}_2$ we get an impossibility result for robust $(n; \lfloor n/2 \rfloor)$ black-box VRF-combiner by contraposition. Next we inspect robust black-box combiners with additional assumptions on the candidate schemes and relaxed requirements on the construction in the hopes of finding combiner constructions. We show that even if we only require unpredictability, sta-




Figure 1.2: Robust $(2;1)$ Black-Box DAG PRF-combiner. Note that for every node we first combine the output of all predecessors using a ppt. Turing machine f^v_{Eval}. The output $\mathbf{w}_v$ of f^v_{Eval} is then queried to the corresponding oracle $\mathcal{O}_{\ell(v)}$. The source vertex doesn't compute anything but simply outputs the inputs while the sink t doesn't query any oracle and simply combines its inputs. In the formal definition the intermediate Turing machines f^v_{Eval} would take as input sets of tuples with a labling of the vertex and the corresponding output, e.g. $(v, \mathbf{x}_v)$, for the sake of simplicity we simply list the outputs in the arguments.

tistical correctness and statistical unique provability from the construction, the impossibility holds Theorem 3.19, this gives two corollaries excluding the possibility of robust $(n; \lfloor n/2 \rfloor)$ black-box combiners for wVRF and VUF in Corollary 3.20 and Corollary 3.21. By strengthening the assumptions on the candidates for all candidates to implement pseudorandomness is also insufficient to find constructions Theorem 3.19.

unclear

We show that if we assume all candidates to be uniquely provable and perfectly correct, the combination of the candidates works in a very similar fashion to the combiner on the PRF primitive. Note that since unique provability and perfect correctness are generally information theoretic properties, this means that for most VRF constructions, e.g. LatticeVRF [**?**] and ECVRF [**?**], those properties are typically proven mathematically. Arguable combiners are only interesting for combining computational security properties that rely on hardness assumptions.

Having strengthened the assumptions on the candidates we can now consider more advanced notions of VRFs. We'll show that with simple extensions we can construct combiners for constrainable VRFs, key-homomorphic VRFs and aggregable VRFs if all candidates are guaranteed to be uniquely provable and perfectly correct. Finally we consider unbiasable VRFs for which we provide a combiner that relies on collision resistant hash functions and deterministic 2-source randomness extractors.

Chapter 2

Notation and Preliminaries

2.1 Notation

For a positive integeger n define $[n] = \{1, \ldots, n\}$. We use $\lambda \in \mathbb{N}$ exclusively to denote the security parameter. We use $\mathsf{poly}(\lambda)$ to denote the set of functions that are polynomial in λ in the sense of Definition 2.1 and $\mathsf{negl}(\lambda)$ to denote the set of functions that are negligible in λ in the sense of Definition 2.2. We call a function f *overwhelming* if $1 - f(\lambda) \in \mathsf{negl}(\lambda)$. We use $\leftarrow$ for simple assignment. For a set S we write $s \leftarrow_\$ S$ to indicate that the value s is sampled uniformly at random from set S and for a probabilistic algorithm $\mathcal{A}$ we write $y \leftarrow_\$ \mathcal{A}(x)$ to denote assigning to y the output of $\mathcal{A}$ on input x. We use ppt. to abbreviate probabilistic polynomial time in the context of Turing machines. Finally, we use bold letters, e.g. $\mathbf{x}$, to indicate that $\mathbf{x}$ consists of multiple values such as tuples or vectors.

maybe change

Definition 2.1 (Polynomial Functions) *We say that a function $p : \mathbb{N} \to \mathbb{R}$ is polynomial if the folowing holds*

$$\exists d \in \mathbb{N}, \exists n_0 \in \mathbb{N}, \forall n > n_0, p(n) \leq n^d$$

Definition 2.2 (Negligible Functions) *We say that a function $\varepsilon : \mathbb{N} \to \mathbb{R}$ is negligible if the following holds*

$$\forall p \in \mathsf{poly}(\lambda), \exists n_0 \in \mathbb{N}, \forall n > n_0, |\varepsilon(n)| < \frac{1}{p(n)}$$

2.2 Verifiable Functions

A verifiable function (VF) VF is a cryptographic primitive that implements algorithms $\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}$ and $\mathsf{Vfy}_{\mathsf{VF}}$. A user can generate key-pairs $(\mathsf{sk}, \mathsf{pk})$ using $\mathsf{Gen}_{\mathsf{VF}}$ consisting of a secret key sk and a public key pk, use the secret key sk to make evaluate arbitrary points $x \in \{0,1\}^\lambda$ using $\mathsf{Eval}_{\mathsf{VRF}}$ and use the public key pk to verify a triple (x, y, π) using $\mathsf{Vfy}_{\mathsf{VRF}}$. We give a formal definition in Definition 2.3, the definition takes inspiration of the definition of a VRF in [**?**]. To reduce redundancy we define additional security properties such as pseudorandomness and unpredictability seperately.

Definition 2.3 (Verifiable Function) *A verifiable function (VF)* VF *is a triple of efficient (ppt.) algorithms* $(\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$ *with the syntax*

this is less elegant now

- $\mathsf{Gen}_{\mathsf{VF}}$*: The key-generation algorithm takes as input the unary encoding of the security parameter and produces a pair* $(\mathsf{sk}, \mathsf{pk}) \in \mathcal{SK} \times \mathcal{PK}$ *containing a secret and a public key respectivley.*
- $\mathsf{Eval}_{\mathsf{VF}}$*: The evaluation algorithm takes as input a tuple* (sk, x) *containing a secret key* $\mathsf{sk} \in \mathcal{SK}$ *and an evaluation point* $x \in \{0,1\}^\lambda$ *and produces an tuple* (y, π) *containing an image* $y \in \mathcal{Y}$ *and a proof* $\pi \in \mathcal{P}$*.*
- $\mathsf{Vfy}_{\mathsf{VF}}$*: The verification algorithm takes as input a tuple* (pk, x, y, π) *containing a public key* $\mathsf{pk} \in \mathcal{PK}$*, an evaluation point* $x \in \{0,1\}^\lambda$*, an image* $y \in \mathcal{Y}$ *and a proof* $\pi \in \mathcal{P}$ *and returns a bit b denoting acceptance or rejection.*

can evaluation or verification be randomized, probably vfy can be probabilistic

Note that a VF is a purely syntactical concept. For a VF we define various properties to arrive to arrive at specific cryptographic primitives, e.g. VRFs. First of all we define ε-correctness, a property that guarantes that over random key-pairs and evaluation points, the verification algorithm accepts a correctly computed image-proof pair with probability at least ε.

Definition 2.4 (ε-Correctness, [?]) *A verifiable function* $\mathsf{VF} = (\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$ *is ε-correct, if for all security parameters $\lambda \in \mathbb{N}$ we have that*

$$\Pr\left[\mathsf{Vfy}_{\mathsf{VF}}(\mathsf{pk}, x, y, \pi) = 1 : \begin{array}{c}(\mathsf{sk}, \mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VF}}(1^\lambda) \\ x \leftarrow_{\$} \{0,1\}^\lambda \\ (y, \pi) \leftarrow \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x)\end{array}\right] \geq \varepsilon(\lambda)$$

We define a VF VF *to be perfectly correct, or just correct, if it is* 1*-correct and statistically correct if ε is an overwhelming function.*

Intuitively a correct VF states that honestly generated image-proof pairs are accepted by the verification algorithm. Next we define unique provability. A VF is uniquely provable if not more than one image can be proven, even for maliciously crafted public keys.

Definition 2.5 (Unique Provability, [?]) *A verifiable function* VF*, with algorithms* $(\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$*, is defined to be uniquely provable if for all evaluation points* $x \in \{0,1\}^\lambda$*, all public-keys* $\mathsf{pk} \in \mathcal{PK}$ *and any two images-proof pairs* $(y_0, \pi_0), (y_1, \pi_1) \in \mathcal{Y} \times \mathcal{PK}$ *we have:*

$$\mathsf{Vfy}_{\mathsf{VF}}(\mathsf{pk}, x, y_0, \pi_0) = 1 \wedge \mathsf{Vfy}_{\mathsf{VF}}(\mathsf{pk}, x, y_1, \pi_1) = 1 \implies y_0 = y_1$$

maybe comment why no statistical notion

Correctness and unique provability are information theoretic. We define pseudorandomness of a VF which is a computational property, stating that no efficient adversary $\mathcal{A}$ can distinguish images y corresponding to evaluation of x, chosen by $\mathcal{A}$, from a uniformly random output $y^* \leftarrow_\$ \mathcal{Y}$. This needs to hold even if the adversary gets to see the evaluation of a polynoial number of points $x \neq x^*$.

Definition 2.6 ((t,ε)-Pseudorandomness, [?]) *A VF* $(\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$ *is defined to be* (t,ε)*-pseudorandom if for all security parameters* $\lambda \in \mathbb{N}$*, for all stateful adversaries* $\mathcal{A}$*, running in time at most* $t(\lambda)$*, the advantage of* $\mathcal{A}$ *in the prf security experiment outlined in Figure 2.1 is at most* $\varepsilon(\lambda)$*, i.e. if*

$$\mathbf{Adv}^{\mathrm{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathrm{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

We say that a VF is pseudorandom, if it is (t,ε)*-pseudorandom with* ε *being a negligible function and* t *being a polynomial, i.e.* $\varepsilon \in \mathsf{negl}(\lambda), t \in \mathsf{poly}(\lambda)$*.*

Next we define two weaker notions of pseudorandomness. While (strong) pseudorandomness required the evaluation of adverserially chosen points to be indistinguishable from uniformly random elements $y^* \in \mathcal{Y}$ we can relax this requirement by requiring computational indistinguishability for uniformly random challenges $x^* \leftarrow_\$ \{0,1\}^\lambda$. We call this notion weak pseudorandomness.

Definition 2.7 ((t,ε)-Weak Pseudorandomness, [?]) *A VF* $(\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$ *is defined to be* (t,ε)*-weakly pseudorandom if for all security parameters* $\lambda \in \mathbb{N}$*, for all stateful adversaries* $\mathcal{A}$*, running in time at most* $t(\lambda)$*, the advantage of* $\mathcal{A}$ *in the wprf security experiment outlined in Figure 2.1 is at most* $\varepsilon(\lambda)$*, i.e. if*

$$\mathbf{Adv}^{\mathrm{wprf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathrm{wprf}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

We say that a VF is weakly pseudorandom, if it is (t,ε)*-weakly pseudorandom with* ε *being a negligible function and* t *being a polynomial, i.e.* $\varepsilon \in \mathsf{negl}(\lambda), t \in \mathsf{poly}(\lambda)$*.*

Alternatively a VF can be unpredictable. A VF is unpredictable if no adversary can predict the image y of the evaluation of a challenge x chosen by the adversary. This property needs to hold even if the adversary sees the evaluation of a polynomial number of points $x \neq x^*$. Note that if the adversary can predict the output of evaluation on x^* he can also distinguish the output from a random output $y^* \leftarrow_{\$} \{0,1\}$ with non-negligible probability making unpredictability is a weaker property than pseudorandomness.

Definition 2.8 ((ε, t)-Unpredictability, [?]) *A VF $(\mathsf{Gen}_{\mathsf{VF}}, \mathsf{Eval}_{\mathsf{VF}}, \mathsf{Vfy}_{\mathsf{VF}})$ is defined to be (t, ε)-unpredictable if for all security parameters $\lambda \in \mathbb{N}$, for all stateful adversaries $\mathcal{A}$, running in time at most $t(\lambda)$, the advantage of $\mathcal{A}$ in the up security experiment outlined in Figure 2.1 is at most $\varepsilon(\lambda)$, i.e. if*

$$\mathbf{Adv}^{\mathrm{up}}_{\mathsf{VF}}(\lambda, \mathcal{A}) := 2 \cdot \left| \Pr\left[\mathbf{Exp}^{\mathrm{up}}_{\mathsf{VF}}(\lambda, \mathcal{A}) = 1\right] - \frac{1}{2} \right| \leq \varepsilon(\lambda)$$

We say that a VF is unpredictable, if it is (t, ε)-unpredictable with ε being a negligible function and t being a polynomial, i.e. $\varepsilon \in \mathsf{negl}(\lambda), t \in \mathsf{poly}(\lambda)$.

We now define the notions of a verifiable random function (VRF), verifiable unpredictable function (VUF) and weak verifiable random function (WVRF), which are correct, uniquely provable and pseudorandom, unpredictable and weakly pseudorandom VFs respectivly. We formally define the primitives.

Definition 2.9 (Verifiable Random Functions) *A verifiable random function $\mathsf{VRF} = (\mathsf{Gen}_{\mathsf{VRF}}, \mathsf{Eval}_{\mathsf{VRF}}, \mathsf{Vfy}_{\mathsf{VRF}})$ is a VF that satisfies perfect correctness in the sense of Definition 2.4, unique provability in the sense of Definition 2.5 and pseudorandomness in the sense of Definition 2.6.*

Definition 2.10 (Weak Verifiable Random Functions) *A weak verifiable unpredictable function $\mathsf{WVRF} = (\mathsf{Gen}_{\mathsf{WVRF}}, \mathsf{Eval}_{\mathsf{WVRF}}, \mathsf{Vfy}_{\mathsf{WVRF}})$ is a VF that satisfies perfect correctness in the sense of Definition 2.4, unique provability in the sense of Definition 2.5 and weak pseudorandomness in the sense of Definition 2.7.*

Definition 2.11 (Verifiable Unpredictable Functions) *A verifiable unpredictable function $\mathsf{VUF} = (\mathsf{Gen}_{\mathsf{VUF}}, \mathsf{Eval}_{\mathsf{VUF}}, \mathsf{Vfy}_{\mathsf{VUF}})$ is a VF that satisfies perfect correctness in the sense of Definition 2.4, unique provability in the sense of Definition 2.5 and unpredictability in the sense of Definition 2.8.*

Experiment $\mathbf{Exp}^{\text{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$

1 : $b \leftarrow_{\$} \{0,1\}$
2 : $(\mathsf{sk}, \mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VF}}(1^{\lambda})$
3 : $S \leftarrow \varnothing$
4 : $(x^*, \sigma) \leftarrow_{\$} \mathcal{A}^{\mathcal{O}_{\text{eval}}}(1^{\lambda}, \mathsf{pk})$
5 : $(y_0, \pi_0) \leftarrow \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x^*)$
6 : $y_1 \leftarrow_{\$} \mathcal{Y}$
7 : $b' \leftarrow_{\$} \mathcal{A}(1^{\lambda}, x^*, \sigma, y_b)$
8 : **return** $b = b' \wedge x^* \notin S$

Experiment $\mathbf{Exp}^{\text{wprf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$

1 : $b \leftarrow_{\$} \{0,1\}$
2 : $(\mathsf{sk}, \mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VF}}(1^{\lambda})$
3 : $S \leftarrow \varnothing$
4 : $\sigma \leftarrow_{\$} \mathcal{A}^{\mathcal{O}_{\text{eval}}}(1^{\lambda}, \mathsf{pk})$
5 : $x^* \leftarrow_{\$} \{0,1\}^{\lambda}$
6 : $(y_0, \pi_0) \leftarrow \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x^*)$
7 : $y_1 \leftarrow_{\$} \mathcal{Y}$
8 : $b' \leftarrow_{\$} \mathcal{A}^{\mathcal{O}_{\text{eval}}}(1^{\lambda}, x^*, \sigma, y_b)$
9 : **return** $b = b' \wedge x^* \notin S$

Experiment $\mathbf{Exp}^{\text{up}}_{\mathsf{VF}}(\lambda, \mathcal{A})$

1 : $(\mathsf{sk}, \mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VF}}(1^{\lambda})$
2 : $S \leftarrow \varnothing$
3 : $(x^*, y^*) \leftarrow_{\$} \mathcal{A}^{\mathcal{O}_{\text{eval}}}(1^{\lambda}, \mathsf{pk})$
4 : $(y, \pi) \leftarrow \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x^*)$
5 : **return** $y^* = y \wedge x^* \notin S$

Oracle $\mathcal{O}_{\text{eval}}(x)$

1 : $S \leftarrow S \cup \{x\}$
2 : $(y, \pi) \leftarrow_{\$} \mathsf{Eval}_{\mathsf{VF}}(\mathsf{sk}, x)$
3 : **return** y

Figure 2.1: The pseudorandomness security experiment $\mathbf{Exp}^{\text{prf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ used in Definition 2.6, the weak pseudorandomness security experiment $\mathbf{Exp}^{\text{wprf}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ used in Definition 2.7 and the unpredictability security experiment $\mathbf{Exp}^{\text{up}}_{\mathsf{VF}}(\lambda, \mathcal{A})$ used in Definition 2.8. The main changes between the pseudorandomness security experiment and the weak pseudorandomness security experiment are highlighted in grey.

2.3 Robust Combiners

For two natural numbers n, k we define the robust $(n;k)$ black-box combiner, or robust black-box combiner for short. A robust $(n;k)$ black-box combiner for a primitive P is a construction Π_{P}, to be precise a ppt. oracle Turing machine, that is given query access to n oracles, the candidate schemes $\mathcal{O}_1, \ldots, \mathcal{O}_n$. If at least k candidate schemes implement the primitive P, then the combiner $\Pi^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{P}}$ securely implements P. The idea behind a robust black-box combiner is that the construction extracts the security properties from the subset of correct candidates, even if some candidate schemes are not secure instances. However now note the following problem in the current definition:

If there exists a secure instance of P there always exists robust $(n;0)$ black-box combiner that simply ignores its candidates and implements P. This robust black-box combiner meets all the requirements of the definition. Showing

that there exists no specific robust black-box combiner therefore requires to show that no secure instance of the primitive P exists, which is often a difficult complexity theoretic statement.

To circumvent this problem we want to explicitly force the combiner to derive its security from the subset of secure candidate schemes. To do this, we require the security properties of the combiner to hold relative to a PSPACE complete oracle. Firstly we want to note that this means that the adversary against the combiner can efficiently check whether an element is a member of a PSPACE complete language, enabling the adversary to generally break computational hardness assumptions but limiting the adversary still to a polynomial number of oracle queries. Secondly we want to note that this notion of a combiner still doesnt solve the issue if the security of the cryptographic primitive are *all* information theoretic.

Very unhappy with this definition

TODO state contrapositive of the definition below here.

Definition 2.12 (Robust $(n;k)$ Black-Box P-Combiner) *A robust $(n;k)$ black-box combiner for primitive* P *with k algorithms is a tuple of ppt. oracle Turing machines $\Pi_{\mathsf{P}} = (\mathsf{Alg}_{\mathsf{P}}^1, \ldots, \mathsf{Alg}_{\mathsf{P}}^k)$ such that if there exists an ppt. adversary $\mathcal{A}^{\mathcal{O}_1,\ldots,\mathcal{O}_n,\mathsf{PSPACE}}$ that against $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ then there exist $n-k+1$ ppt. adversaries $\mathcal{B}_1^{\mathcal{O}_{\ell(1)}}, \ldots, \mathcal{B}_{n-k+1}^{\mathcal{O}_{\ell(n-k+1)}}$ and an injective function $\ell : [n-k+1] \to [n]$ such that for any $i \in [n-k+1]$ the adversary $\mathcal{B}_i^{\mathcal{O}_{\ell(i)}}$ breaks the security of the candidate $\mathcal{O}_{\ell(i)}$.*

Remark. If P defines composite security properties, as is the case for VRFs for instance, we say that an adversary breaks the security of P if it breaks one of the required security properties. For computational security properties such as pseudorandomness this typically means that the adversary wins the corresponding security experiment with non-negligible advantage. For information theoretic or statistical properties such as unique provability or correctness this means that the property doesn't hold (we can think of this as the adversary $\mathcal{A}$ being arbitrary, breaking the security).

Chapter 3

Results

3.1 Robust Black-Box DAG Combiner

Intuitively, a robust black-box combiner operates on n candidate schemes by adaptively interleaving calls to the candidates oracles with ppt. processing to combine the candidates outputs in a way such that security properties of the secure subset of oracles are preserved if there are sufficiently many of them. For certain arguments it can be helpful to model the combiners structure more explicitly, we do so by modeling every algorithm implemented by the combiner with a directed acyclic graph (DAG) reflecting the computation.

In addition to the DAG we specify dedicate source and sink vertices s and t, a vertex labling $\ell : V(\mathcal{G}) \setminus \{s,t\} \to [n] \times [|\mathsf{P}|]$ mapping every non-source and non-sink vertex to a tuple (i,j) indicating which candidate is queried on which oracle and ppt. Turing machines f^v for every vertex $v \in V(\mathcal{G})$ that compute the query input to the candidate and oracle $\ell(v)$ given the oracle response of the predecessors $\mathcal{N}_{\mathcal{G}}^{-}(v)$. The source vertex s simply corresponds to the input $\mathbf{x}$ to the algorithm while the target is associated with a single ppt. Turing machine f^t that computes the final output of the combiner $\mathbf{y}$.

A robust black-box DAG combiner algorithm, is then executed by tracing the computation through the corresponding DAG $\mathcal{G}$. The input to every oracle query is computed from the response of the oracles at the preceding vertices using the Turing machine f^v associated with the respective vertex $v \in V(\mathcal{G})$. The output of the algorithm is given by the output of f^t on the respective inputs. We assume that the random tape of the intermediate Turing machines are initialized identically to the random tape of the combiner Turing machine . A robust black-box DAG combiner has to satisfy that the algorithm induced by the DAG description needs to be a robust black-box combiner. We formally define robust black-box DAG combiners as follows, we use $|\mathsf{P}|$ for primitive P to denote the number of implemented algorithms and generically name them $(\mathsf{Alg}_{\mathsf{P}}^1, \ldots, \mathsf{Alg}_{\mathsf{P}}^p)$ if $|\mathsf{P}| = p$.

argue

Definition 3.1 (Robust $(n;k)$ Black-Box DAG P-Combiner) *A roubst $(n;k)$ black-box DAG combiner for primitive P is a robust $(n;k)$ black-box algorithm Π_{P} in the sense of Definition 2.12, i.e. a tuple algorithms $(\mathsf{Alg}^1_{\mathsf{P}}, \ldots, \mathsf{Alg}^p_{\mathsf{P}})$ where every algorithm $\mathsf{Alg}^i_{\mathsf{P}}$ is specified by a tuple of the following shape*

$$\left(\mathcal{G}_p, s_p, t_p, \ell_p, \{f_p^v\}_{v \in V(\mathcal{G}_p) \setminus \{s_p\}}\right)$$

Such that for all $p \in \mathsf{P}$, $\mathcal{G}_p$ is a DAG, s_p and t_p are vertices in $V(\mathcal{G}_p)$ such that s_p has no ingoing edges and t_p has no outgoing edges, $\ell_p : V(\mathcal{G}_p) \to [n] \times \mathsf{P}$ is a vertex labling and $\{f_p^v\}_{v \in V(\mathcal{G}_p) \setminus \{s_p\}}$ are pt. Turing machines. Where, given the tuple, the algorithm $\mathsf{Alg}^p_{\mathsf{P}}$ is defined as shown in Figure 3.1.

Algorithm $\mathsf{Alg}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{P}}(\mathbf{x})$

$\mathbf{x}_s \leftarrow \mathbf{x}$
for $v \in \mathsf{topo}(V(\mathcal{G}_p) \setminus \{s_p, t_p\})$ **do**
  // Compute the query $\mathbf{q}_v$ to the oracle
  $\mathbf{q}_v \leftarrow f_p^v(\{(w, \mathbf{x}_w)\}_{w \in \mathcal{N}^-_{\mathcal{G}_p}(v)})$
  // Evaluate the oracle on $\mathbf{q}_v$
  $\mathbf{x}_v \leftarrow \mathcal{O}_{\ell(v)}(\mathbf{q}_v)$
return $f_p^t(\{w, \mathbf{x}_w\}_{w \in \mathcal{N}^-_{\mathcal{G}_p}(t)})$

Figure 3.1: Definition of the robust black-box DAG combiner algorithm $\Pi^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{P}}.\mathsf{Alg}_{\mathsf{P}}$ initialized with candidates $\mathcal{O}_1, \ldots, \mathcal{O}_n$. We use topo to denote an algorithm returning the vertices in $V(\mathcal{G}_p)$ in a fixed topological ordering. We use the notation $\mathcal{O}_{c(v)}$ for $c(v) = (i, j)$ to denote the oracle j or the i'th candidate $\mathcal{O}_i$, i.e. $\mathcal{O}_i.\mathsf{Alg}_{\mathsf{P},\mathsf{j}}$.

By definition, a robust black-box DAG combiner corresponds to a robust black-box combiner. We also show that for every robust black-box combiner there exists a canonical robust black-box DAG combiner which is *computationally equivalent* in the sense that the algorithms implemented realize equivalent functions. We state this result in the following theorem, which we will be using to lead our impossibility proofs over robust black-box DAG combiners instead of robust black-box combiners.

computational equivalence more def?

Theorem 3.2 (Robust $(n;k)$ Black-Box DAG Combiners) *For every robust $(n;k)$ black-box combiner in the sense of Definition 2.12 there exists a computationally equivalent robust $(n;k)$ black-box DAG combiner in the sense of Definition 3.1.*

Intuition. The idea behind the proof is to take an arbitrary robust $(n;k)$ black-box combiner Π_{P} and unroll its computation in a graph consisting of $T(n,\lambda)$ layers where each vertex on a layer k is connected to all vertices of the preceding layers $i < k$. Each layer k consisting of $n|\mathsf{P}|$ vertices corresponding

to the different oracles which can be queried as the k'th query. At every layer k for every vertex the combiner then simulates the Turing machine of Π_{P} until the $k+1$'the oracle query. Since the Turing machine f^v can however not make any oracle query itself it relies on the previous connected vertices to obtain the answer to those oracle queries. For the i'th query the Turing machine simply uses the output of the correct vertex on layer i to simulate the oracle query. Once we reach the k'th query and the query would be to oracle $\mathcal{O}_{(i,j)}$ then we distinguish the case when we are at the correct vertex or not. If the current vertex satisfies $c(v) = (i,j)$ then we simply return the query $\mathbf{q}_v$ resulting in the correct query being made, otherwise if $c(v) \neq (i,j)$ then we simply return an arbitrary query that meets the expected input format of $\mathcal{O}_{c(v)}$. An important nuance is that we need to fix the random tape of the Turing machines ρ since otherwise between simulating the oracle queries at a later point the executions may diverge.

maybe cover more explicitly

Proof (Theorem 3.2) Let Π_{P} be a fixed robust $(n;k)$ black-box combiner for primitive P and let $\mathsf{Alg}_{\mathsf{P}}$ be an arbitrary algorithm implemented by P. We label the candidate schemes with $\mathcal{O}_1, \ldots, \mathcal{O}_n$. We construct a robust $(n;k)$ black-box DAG combiner $\widetilde{\Pi}_{\mathsf{P}}$ that is computationally equivalent to Π_{P} to prove the theorem.

Since Π_{P} is a robust $(n;k)$ black-box combiner it is a ppt. Turing machine and the number of oracle queries made by Π_{P} can therefore be bounded from above by $Q(\lambda, n)$, a polynomial in λ and n. We construct the DAG $\mathcal{G}_{\mathsf{Alg}_{\mathsf{P}}} = (V_{\mathsf{Alg}_{\mathsf{P}}}, E_{\mathsf{Alg}_{\mathsf{P}}})$ as follows:

$$V_{\mathsf{Alg}_{\mathsf{P}}} = \{s_{\mathsf{Alg}_{\mathsf{P}}}, t_{\mathsf{Alg}_{\mathsf{P}}}\} \cup [Q(\lambda,n)] \times [n] \times [|\mathsf{P}|] \tag{3.1}$$

$$E_{\mathsf{Alg}_{\mathsf{P}}} = \{((d_1,i_1,j_1),(d_2,i_2,j_2)) \in [Q(\lambda,n)] \times [n] \times [|\mathsf{P}|] : d_1 < d_2\} \tag{3.2}$$

$$\cup \{s_{\mathsf{Alg}_{\mathsf{P}}}\} \times [Q(\lambda,n)] \times [n] \times [|\mathsf{P}|] \tag{3.3}$$

$$\cup [Q(\lambda,n)] \times [n] \times [|\mathsf{P}|] \times \{t_{\mathsf{Alg}_{\mathsf{P}}}\} \tag{3.4}$$

We define a vertex labling $\ell_{\mathsf{Alg}_{\mathsf{P}}}(d,i,j) = (i,j)$ and the ppt. Turing machines $\{f^v_{\mathsf{Alg}_{\mathsf{P}}}\}_{v \in V_{\mathsf{Alg}_{\mathsf{P}}}}$ as follows: On input $\{(w, \mathbf{x}_w)\}_{w \in \mathcal{N}_{\mathcal{G}}^-}$ simulate the Turing machine $\Pi_{\mathsf{P}}.\mathsf{Alg}_{\mathsf{P}}$ on input $\mathbf{x}$. For every q'th query made to the oracle (i,j) it looks up the value of $\mathbf{x}_{(q,i,j)}$ and continues its execution with that oracle response. For the k'th query if the query is to oracle $c(v)$ then simply return the result, otherwise if the query is to an oracle $(i,j) \neq c(v)$ then return an element in the domain of the oracle (i,j) (that oracle query will not further be considered in the execution). For $f^t_{\mathsf{Alg}_{\mathsf{P}}}$ simulate the entire execution of $\Pi_{\mathsf{P}}.\mathsf{Alg}_{\mathsf{P}}$ and proceed analogously but since no more query will be made we just return the result. To show that $\widetilde{\Pi}_{\mathsf{P}}$ is a robust $(n;k)$ black-box DAG combiner we need to show that the algorithm $\mathsf{Alg}_{\mathsf{P}}$ specified by $(\mathcal{G}_{\mathsf{Alg}_{\mathsf{P}}}, s_{\mathsf{Alg}_{\mathsf{P}}}, t_{\mathsf{Alg}_{\mathsf{P}}}, \ell_{\mathsf{Alg}_{\mathsf{P}}}, \{f^v_{\mathsf{Alg}_{\mathsf{P}}}\}_{v \in V(\mathcal{G}_{\mathsf{Alg}_{\mathsf{P}}})})$ is computationally equivalent to $\Pi_{\mathsf{P}}.\mathsf{Alg}_{\mathsf{P}}$ and runs in time polynomial in λ, n. We first show that the algorithm is computationally equivalent, for that consider the following claim.

how to best define

Claim 3.3 *Let Π_{P} be a robust $(n;k)$ black-box combiner for primitive in the sense of Definition 2.12 and let $\widetilde{\Pi}_{\mathsf{P}}$ be the algorithm obtained by applying the procedure above, then we have for for all candidates $\mathcal{O}_1,\ldots,\mathcal{O}_n$ and every algorithm $\mathsf{Alg}^i_{\mathsf{P}}$ implemented by P the following holds.*

$$\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Alg}^i_{\mathsf{P}} = \widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Alg}^i_{\mathsf{P}}$$

Proof (Claim 3.3) Fix a robust $(n;k)$ black-box P-combiner Π_{P}, candidate schemes $\mathcal{O}_1,\ldots,\mathcal{O}_n$, an algorithm implemented by Π_{P}, let $\widetilde{\Pi}_{\mathsf{P}}$ be the robust $(n;k)$ black-box DAG P-combiner constructed as specified above and let $\mathbf{x}$ be an arbitrary input to the algorithm $\mathsf{Alg}_{\mathsf{P}}$. We show that

$$\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Alg}^i_{\mathsf{P}}(\mathbf{x}) = \widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Alg}^i_{\mathsf{P}}(\mathbf{x})$$

By induction over the number of queries made by the Π_{P} combiner. We say that an vertex v on layer $d \in [Q(\lambda,n)]$ is *correct* if in the execution of $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Alg}^i_{\mathsf{P}}(\mathbf{x})$ the d'th oracle query is made to the oracle $c(v)$ and we say that its *incorrect* otherwise. Formally we show that for every $d \in [Q(\lambda,n)]$ the output of the d'th query of the robust black-box combiner $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ and the output of the d'th query of the robust black-box DAG combiner $\widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ agree.

Base case: If $d = 1$ then the output of the robust black-box DAG combiner $\widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ is computed by simulating the evaluation of $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ until the first oracle query and then making the correct oracle query itself at the correct vertex. Therefore the base case holds.

Inductive step: We assume that for every $d' < d$ the output of the query at the correct vertex v at layer d' is equivalent to the output of the d''th oracle query output are the same. Since therefore the execution of the algorithm of $\widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ is perfectly simulated it computes the exact same input and queries by correctness of the vertex the correct oracle on the same input, resulting in the same output. □

what about randomized oracles

Claim 3.4 *Let Π_{P} be a robust $(n;k)$ black-box combiner for primitive in the sense of Definition 2.12 and let $\widetilde{\Pi}_{\mathsf{P}}$ be the algorithm obtained by applying the procedure above, then we have for for all candidates $\mathcal{O}_1,\ldots,\mathcal{O}_n$ and every algorithm $\mathsf{Alg}^i_{\mathsf{P}}$ runs in polynomial time.*

Proof (Claim 3.4) By construction the DAG $\mathcal{G}_{\mathsf{Alg}^i_{\mathsf{P}}}$ has $2 + n|\mathsf{P}|Q(\lambda,n)$ vertices. At each vertex $v \in V(\mathcal{G}^i_{\mathsf{Alg}_{\mathsf{P}}})$ the Turing machine $f^v_{\mathsf{Alg}^i_{\mathsf{P}}}$ simulates $\Pi_{\mathsf{P}}.\mathsf{Alg}_{\mathsf{P}}$ where every oracle query is answered with a constant-time lookup along predecessor outputs, i.e. runs in time a polynomial $T(n,\lambda)$. Hence the overall running time is bounded by

$$|V(\mathcal{G}_{\mathsf{Alg}_{\mathsf{P}}})|T(\lambda,n) \in \mathsf{poly}(\lambda,n)$$

Concluding the proof. □

It remains to show that $\widetilde{\Pi}_{\mathsf{P}}$ is indeed a robust $(n;k)$ black-box combiner. By Claim 3.3 the algorithms implemented by $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ and $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ are equivalent. In particular, any adversary $\mathcal{A}^{\mathcal{O}_1,\ldots,\mathcal{O}_n,\mathsf{PSPACE}}$ against $\widetilde{\Pi}_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ is also an adversary against $\Pi_{\mathsf{P}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ with the same advantage. By Definition 2.12 this means that there exist $n-k+1$ ppt. adversaries $\mathcal{B}_1^{\mathcal{O}_{\ell(1)}},\ldots,\mathcal{B}_{n-k+1}^{\mathcal{O}_{\ell(n-k+1)}}$ and an injective function $\ell : [n-k+1] \to [n]$ such that for any $i \in [n-k+1]$ the adversary $\mathcal{B}_i^{\mathcal{O}_{\ell(i)}}$ breaks the security of the candidate $\mathcal{O}_{\ell(i)}$. Hence $\widetilde{\Pi}_{\mathsf{P}}$ is a robust $(n;k)$ black-box combiner. □

Example. For an example consider of a robust $(2;1)$ black-box DAG combiner for the PRF primitive see Figure 1.2. Note that the construction shown in Figure 1.2 doesn't correspond to the robust $(2;1)$ black-box DAG PRF-combiner one would obtain by following the procedure used in the proof of Theorem 3.2.

3.2 Impossibility of Robust Black-Box VRF-Combiner

We consider the possibility of combining VRFs in a black-box fashion. Specifically, we study the possibilities of combining two candidates, at least one of them implementing a secure VRF. Such robust $(2;1)$ black-box combiners are the simplest robust black-box combiner construction. However the existence of robust $(2;1)$ black-box combiners immediately give rise to the robust $(n;1)$ black-box combiners, while an impossibility implies that there exists no robuts $(n;\lfloor n/2 \rfloor)$ black-box combiner. Consequently, settling the $(2;1)$ case in either direction extends to a seemingly stronger result.

In this section we present a proof of the impossibility of robust $(2;1)$ black-box VRF-combiners. At a high level, the proof exploits the fact that the oracles outputs must be used to produce a pseudorandom output but at the same time cannot influence the output distribution "too much" since otherwise if the candidate were the malleable candidate he could allow for two distinct images to be produced without the verifier being able to tell the difference. In the proof we make the simplifying assumption that the secret key space of all candidates is given by $\mathcal{SK}_i = \{0,1\}^{s_i(\lambda)}$ for a function $s_i \in \mathsf{poly}(\lambda)$. We state the formal statement in the following theorem.

Theorem 3.5 (Robust (2;1) Black-Box VRF Combiner) *There exists no robust $(2;1)$ black-box combiner as defined in Definition 2.12 for the VRF primitive as defined in Definition 2.9.*

Intuition. Instead of showing the impossibility for the robust $(2;1)$ black-box combiner, we show an impossibility for robust $(2;1)$ black-box DAG combiners. The impossibility of a robust $(2;1)$ black-box VRF-combiner then follows directly from the equivalence of robust black-box combiners and robust black-box DAG combiners in Theorem 3.2.

Now suppose, for a contradiction, that there exists a robust $(2;1)$ black-box DAG VRF-combiner Π_{VRF}. Let $\mathcal{O}_1, \mathcal{O}_2$ be candidate schemes, at least one of which implementing a secure VRF. By Definition 2.12, $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ must implement a secure VRF. In particular, since $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ implements a secure VRF, it must be perfectly correct and uniquely provable. We derive a contradiction by initializing $\mathcal{O}_1, \mathcal{O}_2$ with specific candidate schemes of which at least one implements a secure VRF, and then constructing an adversary $\mathcal{A}^{\mathsf{PSPACE},\mathcal{O}_1,\mathcal{O}_2}$ that breaks the pseudorandomness of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ with non-negligible advantage.

The adversary works by iteratively narrowing down the set of candidate secret keys in the pseudorandomness experiment, starting with the secret key space $\mathcal{SK}$, by relying on its PSPACE complete oracle PSPACE. The filtering works as follows: $\mathcal{A}$ samples a polynomial number of evaluation points $x_1, \ldots, x_{2s(\lambda)}$ u.a.r. from $\{0,1\}^\lambda$. Then uses the evaluation oracle $\mathcal{O}_{eval}$ in the prf security

experiment to evaluate the points under the games secret key sk^* to obtain image-proof pairs $(y_1, \pi_1), \ldots, (y_{2s(\lambda)}, \pi_{2s(\lambda)})$. Using the games public key pk^* the adversary now computes the trace of the combiners verification algorithm on the tuples $(\mathsf{pk}^*, x_1, y_1, \pi_1), \ldots, (\mathsf{pk}^*, x_{2s(\lambda)}, y_{2s(\lambda)}, \pi_{2s(\lambda)})$ to obtain $\tau_1, \ldots, \tau_{2s(\lambda)}$. The key ingredient is a ppt. Turing machine $\mathsf{EvalSim}_{\mathsf{VRF}}$ that takes as input a tuple $(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i)$ and returns either $\top$ or $\bot$, satisfying the following properties:

- $\mathsf{EvalSim}_{\mathsf{VRF}}$ makes no oracle queries to the candidates $\mathcal{O}_1, \ldots, \mathcal{O}_n$
- If $\mathsf{sk} = \mathsf{sk}^*$ then $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i) = \top$
- If $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}^{y}(\mathsf{sk}, x_i) \neq y_i$ then $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i) = \bot$

Before elaborating on the construction of $\mathsf{EvalSim}_{\mathsf{VRF}}$ we first explain how the adversary can use this ppt. Turing machine to break pseudorandomness of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$. Recall that we require the security properties of the combiner to hold relative to a PSPACE complete oracle precisely because we want the combiner to derive its security from the candidate oracles (and not implement it itself). Now, $\mathsf{EvalSim}_{\mathsf{VRF}}$ makes no oracle queries yet still only returns $\top$ if a secret key candidate $\mathsf{sk} \in \mathcal{SK}$ *agrees* with the games secret key sk^* in the sense that on x_i they evaluate to the same image. Using its PSPACE complete oracle PSPACE the adversary can now enumerate the entire secret key space $\mathcal{SK}$ and discard any secret key candidate for which there exists a tuple $(x_i, y_i, \pi_i, \tau_i)$ such that $\mathsf{EvalSim}_{\mathsf{VRF}}$ returns $\bot$ (strictly speaking, the PSPACE oracle decides membership queries for PSPACE languages, we defer these technicalities to the formal proof). Note that sk^* is never eliminated since $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}^*, x_i, y_i, \pi_i, \tau_i) = \top$ always and that all other survivors satisfy that they evaluate to the same image as sk^* under $x_1, \ldots, x_{2s(\lambda)}$. There are two possible cases that can happen after the narrowing has taken place:

If for sufficiently many tuples $(x_i, y_i, \pi_i, \tau_i)$ the number of eliminated candidate secret keys is sufficiently large then after $2s(\lambda)$ iterations of filtering we end up with a polynomially sized set $\mathcal{SK}_{cand}$ containing sk^*. The adversary can then sample a uniformly random secret key $\mathsf{sk}_{cand} \in \mathcal{SK}_{cand}$, winning the security experiment if $\mathsf{sk}^* = \mathsf{sk}_{cand}$. This happens with non-negligible probability.

On the other hand if only for a small number of tuples $(x_i, y_i, \pi_i, \tau_i)$ the size of the set of candidate keys decreases significantly this means that for many of the remaining secret key candidates, the probability of evaluating to the same image than the experiments secret key on uniformly random evaluation points is non-negligible. In this scenario the adversary proceeds analogously, he samples a uniformly random secret key candidate and evaluates the challenge pre-image x^* to compare with the challenge image y^*. Since sk_{cand} agrees with the expeirments secret key sk^* with non-negligible probability the adversary wins the game with non-negligible advantage.

We now describe the construction of $\mathsf{EvalSim}_{\mathsf{VRF}}$ algorithm. The algorithm simulates the evaluation of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ by iterating over the the vertices in $V(\mathcal{G}_{\mathsf{Eval}_{\mathsf{VRF}}})$ in a fixed but arbitrary topological ordering. At every vertex v it simulates the associated Turing machine f_{eval}^{v} on the corresponding inputs to obtain $\mathbf{q}_v$. Oracle queries to $\mathcal{O}_1$ are answered trivially with a fixed response, this is the case as we will later initialize this oracle with a trivial, uniquely provable and perfectly correct oracle that returns fixed values for key generation and evaluation and verifies exactly the fixed image. For oracle queries to $\mathcal{O}_2$ we distinguish *exposed* queries, which are contained in the verification trace τ_i, and *obscure* queries, which are not contained in the verification trace. The simulator answers the exposed queries with the response contained in τ_i. Thus the only queries that cannot perfectly be answered are the obscure queries to $\mathcal{O}_2$.

For every obscure query to $\mathcal{O}_2$ the adversary branches its execution for every well-formed responses of the query (e.g. all possible values in $\mathcal{Y} \times \mathcal{P}$ if the query is to $\mathcal{O}_2$s evaluation algorithm) and continues the execution for every branch. Finally if for all branches the evaluation of the combiner is y_i $\mathsf{EvalSim}_{\mathsf{VRF}}$ returns $\top$, otherwise it returns $\bot$. We illustrate the algorithm $\mathsf{EvalSim}_{\mathsf{VRF}}$ in **??**.

!

Its easy to see that the first and third requirements for the $\mathsf{EvalSim}_{\mathsf{VRF}}$ algorithm are met. By construction $\mathsf{EvalSim}_{\mathsf{VRF}}$ makes no oracle queries to candidates. Assuming that $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}^{y}(\mathsf{sk}, x_i) \neq y_i$ then, since we answer all queries to $\mathcal{O}_1$ and the exposed queries to $\mathcal{O}_2$ truthfully, there must exits a well-formed assignment of oracle responses to obscure queries to candidate $\mathcal{O}_2$ such that the execution of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}^{y}(\mathsf{sk}, x_i)$ is simulated perfectly and therefore the output is not y_i, thus we have $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i) = \bot$.

For the second property, we argue that for the security experiments secret key sk^* any assignment of responses to obscure queries to candidate $\mathcal{O}_2$ does not change the image produced by the combiner simulation. Suppose for a contradiction that there exists two different assignments of oracle responses that result in two different images $\tilde{y} \neq \hat{y}$. We derive a contradiction in three steps. First, we may assume without loss of generality that in the evaluation of the robust black-box DAG combiners evaluation algorithm every specific oracle is queried on a specific input at most once (Claim 3.6). Secondly, we construct two oracles $\widehat{\mathcal{O}}_2, \widetilde{\mathcal{O}}_2$, possibly not uniquely provable or perfectly correct, which are the oracle $\mathcal{O}_2$ remapped on the obscure queries to the two assignments that produce different images $\hat{y} \neq \tilde{y}$ respectively. Third, we turn $\mathcal{O}_1$ into a full VRF by remapping all but a small subset of evaluation points to agree with the secure VRF $\mathcal{O}_2$ (Lemma 3.7). Since $\widehat{\mathcal{O}}_2, \widetilde{\mathcal{O}}_2$ produce different images but only differ on obscure queries not contained in the verification trace they are indistinguishable for the combiners verification algorithm. This forces the combiner to violate either unique provability or perfect correctness.

We show the description of the full adversary $\mathcal{A}$ in Figure 3.2.

Proof (Theorem 3.5) □ replace

Proof of Theorem 3.5. Let Π_{VRF} be an arbitrary robust $(2;1)$ black-box DAG combiner for the VRF primitive. Let $\mathcal{O}_{vrf}$ be a VF oracle implementing a secure VRF and let $\mathcal{O}_{uppc}$ be an oracle implementing a trivial, uniquely provable and perfectly correct VF such that the key generation algorithm always returns $(\mathsf{sk}_{def}, \mathsf{pk}_{def})$, the evaluation algorithm returns (y_{def}, π_{def}) for every input and the verification algorithm accepts a tuple (pk, x, y, π) if and only if $y = y_{def}$. First, we show two important results that central to the proof stated in Claim 3.6 and Lemma 3.7.

We claim that we can assume without loss of generality, that the robust black-box DAG combiner for the VRF primitive, during the execution of its evaluation algorithm on arbitrary inputs, queries every oracle algorithm on any given input at most once.

Claim 3.6 *Let Π_{VRF} be a robust $(n;k)$ black-box DAG VRF-combiner in the sense of Definition 3.1. There exists a robust $(n;k)$ black-box DAG VRF-combiner $\widetilde{\Pi}_{\mathsf{VRF}}$ such that in the execution of the evaluation algorithm it queries any oracle algorithm on any given input at most once.*

Proof (Claim 3.6) Let Π_{VRF} be a robust $(n;k)$ black-box DAG VRF-combiner. We obtain $\widetilde{\Pi}_{\mathsf{VRF}}$ by modifying Π_{VRF} in the following way: At every vertex $v \in V(\mathcal{G}_{eval})$ the Turing machine $\tilde{f}^{v}_{eval}$ that maintains a table T_v of mappings from previous oracle queries $\mathbf{q}_w$ for $w \in \mathcal{N}^{-}_{\mathcal{G}_{eval}}(v)$ to oracle responses $\mathbf{x}_w$ of the same oracle algorithm $\ell_{eval}(v)$. $\widetilde{f}^{v}_{eval}$ then simulates the Turing machine f^{v}_{eval} until it returns the query $\mathbf{q}_v$. Then $\widetilde{f}^{v}_{eval}$ checks whether $\mathbf{q}_w$ is contained in the table T_v. If that is not the case we issue the query $\mathbf{q}_w$ to $\mathcal{O}_{\ell_{eval}}(\mathbf{q}_w)$, otherwise we issue a fresh query $\widetilde{\mathbf{q}}_w$ not in the table. If the oracle is queried on $\widetilde{\mathbf{q}}_w$ subsequent Turing machines f^{u}_{eval} with $(v,u) \in E(\mathcal{G}_{eval})$, will then simply find the first query to the oracle $c(v)$ with the same input if they are also incident to u. To ensure this we will again simply draw an edge from the source to every other vertex, from every vertex (d,i,j) to any vertex (d',i',j') if $d < d'$ and from every vertex to the sink.

To show that $\widetilde{\Pi}_{\mathsf{VRF}}$ is indeed a valid robust $(n;k)$ black-box DAG VRF-combiner it is sufficient to show that for any tuple of n candidate schemes $\mathcal{O}_1, \ldots, \mathcal{O}_n$ of which at least k implement a secure VRF. The algorithms implemented by $\Pi^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{VRF}}$ and $\widetilde{\Pi}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{VRF}}$ are equivalent. Since we dont modify the algorithms $\mathsf{Gen}_{\mathsf{VRF}}$ and $\mathsf{Vfy}_{\mathsf{VRF}}$ we only need to show that equivalence holds for $\mathsf{Eval}_{\mathsf{VRF}}$.

Assume towards a contradiction that this is not the case, i.e. that there exists an input $(\mathsf{sk}, x) \in \mathcal{SK} \times \{0,1\}^{\lambda}$ such that $\Pi^{\mathcal{O}_1,\ldots,\mathcal{O}_n}_{\mathsf{VRF}}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x) = y_1$ and

$\widetilde{\Pi}_{\mathsf{VRF}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk},x) = y_2$ with $y_1 \neq y_2$. Since the Turing machine around the oracle calls are simulated the same way in both this either means that f_{eval}^t is probabilistic which or that an oracle query is answered differently and thus not deterministic. In both cases we have that both y_1, y_2 could also have been produced by $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$. By perfect correctness both y_1, y_2 must be verifiable but by unique provability only at most one of y_1, y_2 can be verifiable. A contradiction. We conclude that therefore the algorithm $\mathsf{Eval}_{\mathsf{VRF}}$ of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ and $\widetilde{\Pi}_{\mathsf{VRF}}^{\mathcal{O}_1,\ldots,\mathcal{O}_2}$ are functionally equivalent.

To show a polynomial runtime bound on $\widetilde{\Pi}_{\mathsf{VRF}}^{\mathcal{O}_1,\ldots,\mathcal{O}_n}$ we □ …

From now on we will assume that for every input to the combiners evaluation algorithm, and oracle is queried on any given input at most once. That is, if we remap the output of an oracle on a single point, then at most one oracle query differs in the execution of the evaluation algorithm for every input.

Next, let $\widetilde{\mathcal{SK}} \subseteq \mathcal{SK}$ and $\widetilde{\mathcal{PK}} \subseteq \mathcal{PK}$ be sets with size bounded by a polynomial, i.e. $|\widetilde{\mathcal{SK}}|, |\widetilde{\mathcal{PK}}| \in \mathsf{poly}(\lambda)$. We can construct an oracle $\widetilde{\mathcal{O}}_{uppc}$ from $\mathcal{O}_{vrf}$ and $\mathcal{O}_{uppc}$ such that $\widetilde{\mathcal{O}}_{uppc}$ implements a secure VRF and $\widetilde{\mathcal{O}}_{uppc}$ agrees with $\mathcal{O}_{uppc}$ on the outputs of the evaluation algorithm on all points $\widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}$ and on the verification algorithm on all points $\widetilde{\mathsf{pk}} \in \widetilde{\mathcal{PK}}$. Formally stated in the following lemma.

Lemma 3.7 *Let $\mathcal{O}_{vrf}$ be a VRF oracle in the sense of Definition 2.9 and $\mathcal{O}_{uppc}$ a VF oracle that is perfectly correct in the sense of Definition 2.4 and uniquely provable in the sense of Definition 2.5. Let $\widetilde{\mathcal{SK}} \subseteq \mathcal{SK}$ and $\widetilde{\mathcal{PK}} \subseteq \mathcal{PK}$ be polynomially bounded sets, i.e. $|\widetilde{\mathcal{SK}}|, |\widetilde{\mathcal{PK}}| \in \mathsf{poly}(\lambda)$. There exists an oracle $\widetilde{\mathcal{O}}_{uppc}$ satisfying the following properties.*

1. *The evaluation algorithm of $\widetilde{\mathcal{O}}_{uppc}$ agrees with the evaluation algorithm of $\mathcal{O}_{uppc}$ on all secret keys $\widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}$, i.e. we have that*

$$\forall \widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}, \widetilde{\mathcal{O}}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk},\cdot) = \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk},\cdot)$$

2. *The verification algorithm of $\widetilde{\mathcal{O}}_{uppc}$ agrees with the evaluation algorithm of $\widetilde{\mathcal{O}}_{uppc}$ on all public keys $\widetilde{\mathsf{pk}} \in \widetilde{\mathcal{PK}}$, i.e. we have that*

$$\forall \widetilde{\mathsf{pk}} \in \widetilde{\mathcal{PK}}, \widetilde{\mathcal{O}}_{uppc}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk},\cdot,\cdot,\cdot) = \mathcal{O}_{uppc}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk},\cdot,\cdot,\cdot)$$

3. *The oracle $\widetilde{\mathcal{O}}_{uppc}$ implements a secure VRF in the sense of Definition 2.9.*

A too simple idea would be to replace the mapping of $\mathcal{O}_{vrf}.\mathsf{Eval}_{\mathsf{VRF}}$ on all inputs (sk,x) with $\mathsf{sk} \in \widetilde{\mathcal{SK}}$ and similarly modify the mapping of $\mathcal{O}_{vrf}.\mathsf{Vfy}_{\mathsf{VRF}}$ on all inputs (pk,x,y,π) with $\mathsf{pk} \in \widetilde{\mathcal{PK}}$. However, the resulting oracle doesn't

necessarily need to be uniquely provable or perfectly correct anymore. For instance, imagine the scenario where a secret key $\widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}$ is remapped but the corresponding public key pk does not itself belong to $\widetilde{\mathcal{PK}}$. In that case the verification algorithm on pk is left unchanged while the evaluation algortihm on $\widetilde{\mathsf{sk}}$ is modified. This can result in correctly computed image-proof pairs to be rejected by the verification algorithm, violating perfect correctness.

Proof (Lemma 3.7) We begin by introducing a two relations $\sim_{\mathcal{SK}} \subseteq \mathcal{SK}^2$ and $\sim_{\mathcal{PK}} \subseteq \mathcal{PK}^2$. Intuitively, these relations capture whether two secret or public keys have a counterpart which could have been sampled with both keys. Formally we define the relations $\sim_{\mathcal{SK}}, \sim_{\mathcal{PK}}$ as follows:

$$\mathsf{sk}_1 \sim_{\mathcal{SK}} \mathsf{sk}_2 \iff \exists \mathsf{pk} \in \mathcal{PK}, \Pr\left[\begin{matrix}(\mathsf{sk}_1, \mathsf{pk}) \leftarrow_{\$} \mathcal{O}_{uppc}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda) \wedge \\ (\mathsf{sk}_2, \mathsf{pk}) \leftarrow_{\$} \mathcal{O}_{uppc}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)\end{matrix}\right] > 0 \tag{3.5}$$

$$\mathsf{pk}_1 \sim_{\mathcal{PK}} \mathsf{pk}_2 \iff \vee \exists \mathsf{sk} \in \mathcal{SK}, \Pr\left[\begin{matrix}(\mathsf{sk}, \mathsf{pk}_1) \leftarrow_{\$} \mathcal{O}_{uppc}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda) \wedge \\ (\mathsf{sk}, \mathsf{pk}_2) \leftarrow_{\$} \mathcal{O}_{uppc}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)\end{matrix}\right] > 0 \tag{3.6}$$

We now consider the reflexive transitive closure of those relations $\sim^*_{\mathcal{SK}}$,$\sim^*_{\mathcal{PK}}$, formally defined by $\sim^* = \bigcup_{k \in \mathbb{N}} \sim^k$. The resulting relations $\sim^*_{\mathcal{SK}}$,$\sim^*_{\mathcal{PK}}$ are equivalence relations because the underlying relations $\sim_{\mathcal{SK}}, \sim_{\mathcal{PK}}$ are symmetric and the reflexive transitive closure of a symmetric relation remains symmetric and is extended to a reflexive and transitive relation . Given an element sk we denote its equivalence class under $\sim^*_{\mathcal{SK}}$ with $[\mathsf{sk}]_{\sim^*_{\mathcal{SK}}} = \{\mathsf{sk}' \in \mathcal{SK} : \mathsf{sk}' \sim^*_{\mathcal{SK}} \mathsf{sk}\}$, analogously for an element pk and the relation $\sim^*_{\mathcal{PK}}$ we define $[\mathsf{pk}]_{\sim^*_{\mathcal{PK}}} = \{\mathsf{pk}' \in \mathcal{PK} : \mathsf{pk}' \sim^*_{\mathcal{PK}} \mathsf{pk}\}$. We claim that secret and public keys related with the relation $\sim^*_{\mathcal{SK}}, \sim^*_{\mathcal{PK}}$ respectively induce the same mapping on their respective algorithm. We formally state this observation in the following claim.

polish

Claim 3.8 *For all secret keys $\widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}$ that the following property holds:*

$$\forall \mathsf{sk} \in [\widetilde{\mathsf{sk}}]_{\sim^*_{\mathcal{SK}}}, \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, \cdot) = \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widetilde{\mathsf{sk}}, \cdot)$$

and for all public keys $\widetilde{\mathsf{pk}} \in \widetilde{\mathcal{PK}}$ that the following holds

$$\forall \mathsf{pk} \in [\widetilde{\mathsf{pk}}]_{\sim^*_{\mathcal{PK}}}, \mathcal{O}_{uppc}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, \cdot, \cdot, \cdot) = \mathcal{O}_{uppc}.\mathsf{Vfy}_{\mathsf{VRF}}(\widetilde{\mathsf{pk}}, \cdot, \cdot, \cdot)$$

Proof (Claim 3.8) Let $\widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}$ be arbitrary and for a contradiction that there exists a $\mathsf{sk} \in [\widetilde{\mathsf{sk}}]_{\sim^*_{\mathcal{SK}}}$ and an arbitrary evaluation point $x \in \{0,1\}^\lambda$ such that $\mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x) = y$ and $\mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widetilde{\mathsf{sk}}, x) = \tilde{y}$ with $y \neq \tilde{y}$. Note that

the following holds:

$$\begin{aligned}
\mathsf{sk} \in [\widetilde{\mathsf{sk}}]_{\sim^*_{\mathcal{SK}}} &\iff \mathsf{sk} \in \left\{\mathsf{sk}' \in \mathcal{SK} : \mathsf{sk}' \sim^*_{\mathcal{SK}} \widetilde{\mathsf{sk}}\right\} && (3.7)\\
&\iff \mathsf{sk} \in \left\{\mathsf{sk}' \in \mathcal{SK} : \exists k \in \mathbb{N}, \mathsf{sk}' \sim^k_{\mathcal{SK}} \widetilde{\mathsf{sk}}\right\} && (3.8)\\
&\iff \mathsf{sk} \in \bigcup_{k\in\mathbb{N}} \left\{\mathsf{sk}' \in \mathcal{SK} : \mathsf{sk}' \sim^k_{\mathcal{SK}} \widetilde{\mathsf{sk}}\right\} && (3.9)\\
&\iff \mathsf{sk} \in \bigcup_{k\in\mathbb{N}} [\widetilde{\mathsf{sk}}]_{\sim^k_{\mathcal{SK}}} && (3.10)
\end{aligned}$$

□

Which is why we can establish the claim by induction on $k \in \mathbb{N}$. For the base case note that $\mathsf{sk} \in [\widetilde{\mathsf{sk}}]_{\sim^0_{\mathcal{SK}}}$ if and only if $\mathsf{sk} = \widetilde{\mathsf{sk}}$, which directly results in a contradiction since then we would break either unique provability or perfect correctness immediately. For the inductive step assume that the claim holds for $k \in \mathbb{N}$, we show that it also holds for $k+1$. Let $\mathsf{sk} \in [\widetilde{\mathsf{sk}}]_{\sim^{k+1}_{\mathcal{SK}}}$ and let $\widehat{\mathsf{sk}} \in [\widetilde{\mathsf{sk}}]_{\sim^k_{\mathcal{SK}}}$ be arbitrary, then we know that $\mathsf{sk} \sim_{\mathcal{SK}} \widehat{\mathsf{sk}}$ and therefore $\mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk},\cdot) = \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widehat{\mathsf{sk}},\cdot)$. By the induction hypothesis we know that $\mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widehat{\mathsf{sk}},\cdot) = \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widetilde{\mathsf{sk}},\cdot)$ and therefore we finally arrive at $\mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk},\cdot) = \mathcal{O}_{uppc}.\mathsf{Eval}_{\mathsf{VRF}}(\widetilde{\mathsf{sk}},\cdot)$. The argument for the public key version of that statement is analogous.

polish

Additionally, for secret and public keys we define the function $R_{\mathcal{SK}}$ and $R_{\mathcal{PK}}$ respectively. R maps a key to all counterparts with are sampled with that key with non-negligible probability.

$$R_{\mathcal{PK}}(\mathsf{pk}) = \left\{\mathsf{sk} \in \mathcal{SK} : \Pr\left[(\mathsf{sk},\mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)\right] > 0\right\} \tag{3.11}$$

$$R_{\mathcal{SK}}(\mathsf{sk}) = \left\{\mathsf{pk} \in \mathcal{PK} : \Pr\left[(\mathsf{sk},\mathsf{pk}) \leftarrow_{\$} \mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)\right] > 0\right\} \tag{3.12}$$

Next we define the notion of the closure of a set. Given a subset of secret $\widetilde{\mathcal{SK}}$ or public keys $\widetilde{\mathcal{PK}}$ we define its closure $\mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})$ and $\mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}})$ which are just the union over the equivalence classes of all keys in the subsets. We formally define the functions as follows:

$$\mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}) = \bigcup_{\widetilde{\mathsf{sk}}\in\widetilde{\mathcal{SK}}} [\widetilde{\mathsf{sk}}]_{\sim^*_{\mathcal{SK}}} \tag{3.13}$$

$$\mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}}) = \bigcup_{\widetilde{\mathsf{pk}}\in\widetilde{\mathcal{PK}}} [\widetilde{\mathsf{pk}}]_{\sim^*_{\mathcal{PK}}} \tag{3.14}$$

Observe that the secret key closure $\mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})$ for a subset $\widetilde{\mathcal{SK}} \subseteq \mathcal{SK}$ is the set of secret keys that need to be remapped if we want to remap all of the evaluations on the secret keys $\widetilde{\mathcal{SK}}$ to preserve unique provability and correctness. The same holds for the public key closure. Now we define the

closure for subsets $\widetilde{\mathcal{SK}} \subseteq \mathcal{SK}$ and $\widetilde{\mathcal{PK}} \subseteq \mathcal{PK}$ at the same time.

$$\mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}}) = \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}) \cup \bigcup_{\widetilde{\mathsf{pk}} \in \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widetilde{\mathsf{pk}}) \tag{3.15}$$

$$\mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}}) = \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}}) \cup \bigcup_{\widetilde{\mathsf{sk}} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})} R_{\mathcal{SK}}(\widetilde{\mathsf{sk}}) \tag{3.16}$$

We now constuct an oracle $\widetilde{\mathcal{O}}_{up}$ that interpolates between $\mathcal{O}_{up}$ and $\mathcal{O}_{\mathbf{VRF}}$. To be precise we define all of the algorithms of $\widetilde{\mathcal{O}}_{up}$: The key generation algorithm is defined to be the function for key generation of $\mathcal{O}_{\mathbf{VRF}}$ while the function for evaluation and verification are defined as follows.

$$\widetilde{\mathcal{O}}_{up}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x) = \begin{cases} \mathcal{O}_{up}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x) & \text{if } \mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}}) \\ \mathcal{O}_{\mathbf{VRF}}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x) & \text{otherwise} \end{cases} \tag{3.17}$$

$$\widetilde{\mathcal{O}}_{up}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y, \pi) = \begin{cases} \mathcal{O}_{up}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y, \pi) & \text{if } \mathsf{pk} \in \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}}) \\ \mathcal{O}_{\mathbf{VRF}}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y, \pi) & \text{otherwise} \end{cases} \tag{3.18}$$

Note that the properties 1. and 2. of Lemma 3.7 hold by definition of the oracle since by reflexivity of $\sim^*_{\mathcal{SK}}$ and $\sim^*_{\mathcal{PK}}$ we have $\widetilde{\mathcal{SK}} \subseteq \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}})$ and $\widetilde{\mathcal{PK}} \subseteq \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}})$. We show that 3. holds by showing the $\widetilde{\mathcal{O}}_{up}$ is uniquely provable and perfectly correct and pseudorandom seperately.

Claim 3.9 *Let $\mathcal{O}_{up}, \mathcal{O}_{vrf}$ be oracles implementing a uniquely provable VF in the sense of Definition 2.5 and a VRF in the sense of Definition 2.9 respectively. The oracle $\mathcal{O}_{mix}$ constructed from $\mathcal{O}_{up}$ and $\mathcal{O}_{vrf}$ is perfectly correct in the sense of Definition 2.4 and uniquely provable in the sense of Definition 2.5.*

Let $\lambda \in \mathbb{N}$ be arbitrary. For perfect correctness let $(\mathsf{sk}, \mathsf{pk}) \leftarrow_\$ \mathcal{O}_{mix}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$, let $x \in \{0,1\}^\lambda$ be arbitrary and let $(y, \pi) \leftarrow \mathcal{O}_{mix}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x)$. We show that $\mathsf{sk} \in \mathcal{SK}_{map}$ if and only if $\mathsf{pk} \in \mathcal{PK}_{map}$, following that, if $\mathsf{sk} \in \mathcal{SK}_{map}$ then (y, π) verifies by perfect correctness of $\mathcal{O}_{up}$ and if $\mathsf{sk} \notin \mathcal{SK}_{map}$ then (y, π) verifies by perfect correctness of $\mathcal{O}_{vrf}$.

We show only $\mathsf{sk} \in \mathcal{SK}_{map} \implies \mathsf{pk} \in \mathcal{PK}_{map}$, the other direction follows from a symmetric argument. Assume $\mathsf{sk} \in \mathcal{SK}_{map}$, by definition of $\mathcal{SK}_{map}$ we distinguish the cases $\mathsf{sk} \in \mathsf{cl}(\widetilde{\mathcal{SK}})$ and $\mathsf{sk} \in \bigcup_{\widetilde{\mathsf{pk}} \in \mathsf{cl}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widetilde{\mathsf{pk}})$. If $\mathsf{sk} \in \mathsf{cl}(\widetilde{\mathcal{SK}})$ then together with $\mathsf{pk} \in R_{\mathcal{PK}}(\mathsf{sk})$ we get $\mathsf{pk} \in \bigcup_{\widetilde{\mathsf{sk}} \in \mathsf{cl}(\widetilde{\mathcal{SK}})} R_{\mathcal{SK}}(\widetilde{\mathsf{sk}})$ and therefore $\mathsf{pk} \in \mathcal{PK}_{map}$. On the other hand if $\mathsf{sk} \in \bigcup_{\widetilde{\mathsf{pk}} \in \mathsf{cl}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widetilde{\mathsf{pk}})$ then for some $\widetilde{\mathsf{pk}} \in \mathsf{cl}(\widetilde{\mathcal{PK}})$ we have $\mathsf{sk} \in R_{\mathcal{PK}}(\widetilde{\mathsf{pk}})$ but since $\widetilde{\mathsf{pk}} \sim_{\mathcal{PK}} \mathsf{pk}$ and therefore in particular $\widetilde{\mathsf{pk}} \sim^*_{\mathcal{PK}} \mathsf{pk}$ we have $\mathsf{pk} \in \mathsf{cl}(\widetilde{\mathsf{pk}})$, implying $\mathsf{pk} \in \mathcal{PK}_{map}$.

For unique provability, suppose for a contradiction, that there exist two distinct images $y_0 \neq y_1$ with corresponding proofs π_0, π_1 such that $\mathcal{O}_{mix}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y_0, \pi_0) = \mathcal{O}_{mix}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y_1, \pi_1) = 1$. Now, if $\mathsf{pk} \in \mathcal{PK}_{map}$ then we break the assumed unique provability of $\mathcal{O}_{up}$ and if $\mathsf{pk} \notin \mathcal{PK}_{map}$ then we break the assumed unique provability of $\mathcal{O}_{vrf}$. We conclude that the constructed oracle $\mathcal{O}_{mix}$ must indeed be perfectly correct and uniquely provable.

Next we show that if $\mathcal{O}_{\mathbf{VRF}}$ is pseudorandom then $\mathcal{O}_{mix}$ is also pseudorandom. We formulate this statement precisely in the following claim.

Claim 3.10 *Let $\mathcal{O}_{up}, \mathcal{O}_{vrf}$ be oracles implementing a uniquely provable VF in the sense of Definition 2.5 and a VRF in the sense of Definition 2.9 respectively that is (t, ε)-pseudorandom. Let $\widetilde{\mathcal{SK}} \subseteq \mathcal{SK}, \widetilde{\mathcal{PK}} \subseteq \mathcal{PK}$ be polynomially bounded subsets of the secret and public key space respectively, i.e. $|\widetilde{\mathcal{SK}}|, |\widetilde{\mathcal{PK}}| \in \mathsf{poly}(\lambda)$. Then $\widetilde{\mathcal{O}}_{mix}^{\widetilde{\mathcal{SK}},\widetilde{\mathcal{PK}},\mathcal{O}_{up},\mathcal{O}_{vrf}}$ which is constructed from $\mathcal{O}_{up}$ and $\mathcal{O}_{vrf}$ using the above procedure is (t, ε)-pseudorandom for $\varepsilon_{mix}^{prf} = \varepsilon_{vrf}^{prf} + \mu_1(\lambda) + \mu_2(\lambda)$ where both $\mu_1(\lambda)$ and $\mu_2(\lambda)$ are negligible functions depending on the size of the closure of $\widetilde{\mathcal{SK}}$ and $\widetilde{\mathcal{PK}}$ respectively.*

Assume, towards a contradiction, that $\mathcal{O}_{mix}$ is not pseudorandom, i.e. that there exists an efficient (ppt.) adversary $\mathcal{A}$ such that $\mathcal{A}$ wins the pseudorandomness experiment against $\mathcal{O}_{mix}$ with non-negligible advantage. We now show that the pseudorandomness game against $\mathcal{O}_{mix}$ and $\mathcal{O}_{\mathbf{VRF}}$ are statistically close, i.e. we bound the probability that the hidden secret key $\mathsf{sk} \in \mathcal{SK}_{map}$ and apply the difference lemma. We define the following games $H_1(\lambda, \mathcal{A}), H_2(\lambda, \mathcal{A})$ and $H_3(\lambda, \mathcal{A})$ corresponding to the pseudorandomness security experiment for hidden bit $b = 0$ against $\mathcal{O}_{\mathbf{VRF}}$, the pseudorandomness security experiment for hidden bit $b = 1$ against $\mathcal{O}_{\mathbf{VRF}}$ and the pseudorandomness security experiment for hidden bit $b = 1$ against $\mathcal{O}_{mix}$ respectively as defined in Figure 2.1.

We use $H_i^{prf}(\lambda, \mathcal{A}) = 1$ to denote the event that adversary $\mathcal{A}$ wins the game H_i for $i \in [3]$.

define games of the hybrid formally

$$\mathbf{Adv}^{\text{prf}}_{\mathsf{VRF}}(\mathcal{A}, \mathcal{O}_{mix}) = \left|\Pr\left[H_0^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_1^{prf}(\lambda, \mathcal{A}) = 1\right]\right| \tag{3.19}$$

$$= \Big|\Pr\left[H_0^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_2^{prf}(\lambda, \mathcal{A}) = 1\right] \tag{3.20}$$

$$+ \Pr\left[H_2^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_1^{prf}(\lambda, \mathcal{A}) = 1\right]\Big| \tag{3.21}$$

$$\leq \left|\Pr\left[H_0^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_2^{prf}(\lambda, \mathcal{A}) = 1\right]\right| \tag{3.22}$$

$$+ \left|\Pr\left[H_2^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_1^{prf}(\lambda, \mathcal{A}) = 1\right]\right| \tag{3.23}$$

$$\leq \varepsilon^{prf}_{VRF,mix} + \left|\Pr\left[H_2^{prf}(\lambda, \mathcal{A}) = 1\right] - \Pr\left[H_1^{prf}(\lambda, \mathcal{A}) = 1\right]\right| \tag{3.24}$$

Let $\mathcal{E}$ be the event that $\mathsf{sk} \in \mathcal{SK}_{map}$ for $(\mathsf{sk}, \mathsf{pk}) \leftarrow_{\$} \mathcal{O}_{mix}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$. Observe that the games H_2, H_1 are identical if the event $\mathcal{E}$ doesn't occur. The difference lemma is a classical result in cryptography and states that the difference in probability of an event happening can be bounded from above by the probability of a "bad" event happening conditioned on which the previous two events have the same probability of happening. For completeness we state the result but defer the proof to the appendix.

Lemma 3.11 (Difference Lemma) *let W_0, W_1 and B be events satisfying:*

$$\Pr[W_0 \mid \neg B] = \Pr[W_1 \mid \neg B]$$

Then we can impose the following bound:

$$|\Pr[W_0] - \Pr[W_1]| \leq \Pr[B]$$

By the above observation we can therefore bound the difference in probability over the two games by the probability of event $\mathcal{E}$ occuring. Applying a union bound and the definition of the joint closure we then arrive at the following bound of the adversary $\mathcal{A}$'s advantage.

$$\mathbf{Adv}^{\text{prf}}_{\mathsf{VRF}}(\mathcal{A}, \mathcal{O}_{mix}) \leq \varepsilon^{prf}_{VRF,mix} + \Pr\left[\mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}}, \widetilde{\mathcal{PK}})\right] \tag{3.25}$$

$$\leq \varepsilon^{prf}_{VRF,mix} + \Pr\left[\mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})\right] \tag{3.26}$$

$$+ \Pr\left[\mathsf{sk} \in \bigcup_{\widehat{\mathsf{pk}} \in \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widehat{\mathsf{pk}})\right] \tag{3.27}$$

$$\leq \varepsilon^{prf}_{\mathbf{VRF}} + |\widetilde{\mathcal{SK}}|\varepsilon^{prf}_{\mathbf{VRF}} + |\widetilde{\mathcal{PK}}|\varepsilon^{prf}_{\mathbf{VRF}} \tag{3.28}$$

We bound the probabilities and arrive at the final bound we show that if the probability were non-negligible an adversary would win the pseudorandomness security experiment against $\mathcal{O}_{\mathbf{VRF}}$ with non-negligible advantage,

which is a contradiction since we assume $\mathcal{O}_{\mathbf{VRF}}$ to be pseudorandom. For the subsequent proofs keep in mind that the probabilities are over the randomly sampled secret key. We consider both probabilities seperately,

For the bound on $\Pr[\mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})]$ note that for any value of x the set of possible images is given by $\{y \leftarrow_{\$} \mathcal{O}_{up}.\mathsf{Eval}_{\mathsf{VRF}}(\widetilde{\mathsf{sk}}, x) : \widetilde{\mathsf{sk}} \in \widetilde{\mathcal{SK}}\}$ which is bounded in cardinality from above by $\widetilde{\mathcal{SK}}$. Recall that $|\widetilde{\mathcal{SK}}| \in \mathsf{poly}(\lambda)$. Conditioned on the event that $\mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})$ there exists an adversary $\mathcal{A}$ with advantage at least $1/|\widetilde{\mathcal{SK}}|$. Hence we can bound $\Pr[\mathsf{sk} \in \mathsf{cl}_{\mathcal{SK}}(\widetilde{\mathcal{SK}})]$ from above by $\varepsilon^{prf}_{VRF,mix}|\widetilde{\mathcal{SK}}|$.

For the bound on $\Pr[\mathsf{sk} \in \bigcup_{\widetilde{\mathsf{pk}} \in \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widetilde{\mathsf{pk}})]$ by a similar argument the mappings also correspond to elements of $\widetilde{\mathcal{PK}}$. Again, following this line of argument we condition on the event that $\mathsf{sk} \in \bigcup_{\widetilde{\mathsf{pk}} \in \mathsf{cl}_{\mathcal{PK}}(\widetilde{\mathcal{PK}})} R_{\mathcal{PK}}(\widetilde{\mathsf{pk}})$ and find an adversary with advantage bounded from below by $1/|\widetilde{\mathcal{PK}}|$. We obtain the bound on the probability of $\varepsilon^{prf}_{\mathbf{VRF}}|\widetilde{\mathcal{PK}}|$. □

Using this result we claim that for a fixed oracle $\mathcal{O}_i$ and any subset of queries made during the evaluation algorithm which are not reflected in the trace of the verification execution, we call such queries *hidden*, the output of the evaluation algorithm doesn't change for all possible outputs of the oracles. That is, if we execute the evaluation algorithm and replace every oracle query to an algorithm of $\mathcal{O}_i$ with the output in the transcript or any other random output in the support if it doesnt occur in the transcript we arrive at the same value for the right secret key sk.

Claim 3.12 *Let $\mathcal{O}_1, \mathcal{O}_2$ be uniquely provable and perfectly correct VF oracles and let S be a set of hidden vertices in G_{eval} with queries made to only one oracle. Then they are jointly irrelevant to the output of the combiners evaluation algorithm. Specifically we can simulate the output of the individual oracle queries by choosing arbitrary elements in the support of the oracles algorithm.*

Proof of Claim 3.12 Assume this were not the case, we follow the topological ordering and initialize the oracle responses to those queries with arbitrary outputs in the support. If at one point the output of the combiner changes then simply remap the corresponding oracle and make the other oracle a VRF. Subsequently the combiner needs to be uniquely provable, perfectly correct and pseudorandom. By perfect correctness we have

$$\Pi^{\hat{\mathcal{O}}_1, \mathcal{O}_2^{\mathbf{VRF}}}_{\mathsf{VRF}}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, \hat{y}, \hat{\pi}) = 1 \tag{3.29}$$

$$\Pi^{\tilde{\mathcal{O}}_1, \mathcal{O}_2^{\mathbf{VRF}}}_{\mathsf{VRF}}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, \tilde{y}, \tilde{\pi}) = 1 \tag{3.30}$$

And by unique provability and $\hat{y} \neq \tilde{y}$ we have that

$$\Pi_{\mathsf{VRF}}^{\hat{\mathcal{O}}_1,\mathcal{O}_2^{\mathbf{VRF}}}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, \tilde{y}, \tilde{\pi}) = 0 \tag{3.31}$$

$$\Pi_{\mathsf{VRF}}^{\tilde{\mathcal{O}}_1,\mathcal{O}_2^{\mathbf{VRF}}}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, \hat{y}, \hat{\pi}) = 0 \tag{3.32}$$

Now since the oracle $\tilde{\mathcal{O}}_1$ and $\hat{\mathcal{O}}_1$ only differ in the evaluations not covered by the verification algorithm the execution of the algorithm will be identical, given the input is the same. This fundamentally contradicts (3.30) and (**??**), we conclude that the resulting combiner is either not perfectly correct or uniquely provable.

We define the evaluation simulation $\mathsf{EvalSim}_{\mathsf{VRF}}$ that simulates the evaluation without invoking any oracle queries. The simulation will simply traverse the evaluation algorithm of the DAG combiner. For any oracle query it checks the corresponding transcript τ_i. If the query is either to oracle $\mathcal{O}_1$ we can honestly answer it with 0 or in the transcript, then we can answer it hoenstly as well. If the query is *obscure* then we branch once for every possible assignment of the oracle response which fits the given format, e.g. for a query to eval we branch for every answer $(y, \pi) \in \mathcal{Y} \times \mathcal{P}$. The pseudocode for $\mathsf{EvalSim}_{\mathsf{VRF}}$ is shown in **??**. In the following we show that this algorithm satisfies a few properties.

Claim 3.13 *Let* $\mathsf{EvalSim}_{\mathsf{VRF}}$ *be the algorithm as described above and in* **??** *taking as input a tuple* $(\mathsf{sk}, x, y, \pi, \tau)$ *containing a secret key, evaluation point, image, proof and a trace of the combiners verification algorithm on* (pk, x, y, π) *where* pk *is the true public key. Then* $\mathsf{EvalSim}_{\mathsf{VRF}}$ *satisfies the following properties.*

1. $\mathsf{EvalSim}_{\mathsf{VRF}}$ *makes no oracle queries*
2. $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x, y, \pi, \tau) = \top$ *if* $\mathsf{sk} = \mathsf{sk}^*$
3. $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x, y, \pi, \tau) = \bot$ *if* $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}^{y}(\mathsf{sk}, x) \neq y$

Informally this means that the evaluation simulation will return with $\top$ on a *non-empty* subset of secret keys which agrees with the true secret key sk^* on the evaluation of x.

The first property holds by construction of $\mathsf{EvalSim}_{\mathsf{VRF}}$ the third property also holds by construction and the fact that if the evaluation of $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}^{y}(\mathsf{sk}, x) \neq y$ then there exists an assignment of the obscure queries such that every oracle query is answered exactly the same as in the execution of the combiner, hence the combiner outputs $\bot$. If $\mathsf{sk} = \mathsf{sk}^*$ we need to argue that for every format adhering assignment of the oracle responses to the obscure queries, the output doesn't change. Assume towards a contradiction for two assignments of the obscure queries the output of the combiner changes from y_0 to $y_1 \neq y_0$. Now we can apply Lemma 3.7 to construct a secure VRF from $\mathcal{O}_1$ which agrees with the old candidate on all points queried in evaluation

and verification, and reassign obscure queries. By perfect correctness both outputs y_0, y_1 must verify in their respective world, however on all oracle queries done by the verification combiner in the two worlds the queries agree exactly (since the queries are obscure) and we break unique provability.

Using this simulator $\mathsf{EvalSim}_{\mathsf{VRF}}$ we can describe the set of iteratively filtered candidate secret keys as follows. Let $\{(x_i, y_i, \pi_i, \tau_i)\}_{i\in[2s(\lambda)]}$ be a set of $2s(\lambda)$ tuples containing a uniformly random evaluation point $x_i \in \{0,1\}^\lambda$, the evaluation of x_i resulting in the tuple (y_i, π_i) and the transcript of the combiners verification algorithm on (x_i, y_i, π_i). The set of candidate keys is defined as:

$$\mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i) := \{\mathsf{sk} \in \mathcal{SK} : \mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i)\}$$

We claim that for any secret key $\mathsf{sk}_{cand} \in \mathcal{SK}_{cand}$, the probability that the secret key evaluates to the same output as the evaluation algorithm of the combiner does on a uniformly random value $x \in \{0,1\}^\lambda$ is overwhelming. We state this result formally in the following claim.

Claim 3.14 *Let $\mathcal{SK}_{cand}$ be defined as above and let $\{(x_i, y_i, \pi_i, \tau_i)\}_{i\in[2s(\lambda)]}$ then we have that for any secret key sk^* sampled uniformly at random from the intersection of all filtered candidate sets, i.e. sampled from*

$$\mathsf{sk}^* \leftarrow_\$ \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)$$

The probability that for a uniformly random challenge $x^* \leftarrow_\$ \{0,1\}^\lambda \setminus \{x_1, \ldots, x_{2s(\lambda)}\}$ the black-box combiner instanciated with the correct oracles evaluates to the same image as for the true secret key is bounded from below by

$$\Pr\left[\Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}^y_{\mathsf{VRF}}(\mathsf{sk}^*, x) = \Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}^y_{\mathsf{VRF}}(\mathsf{sk}, x)\right] \geq \frac{1}{p(\lambda)}$$

For p a polynomial in λ.

Proof (Claim 3.14) For a secret key $\mathsf{sk} \in \mathcal{SK}$ we define the number of secret keys $\mathsf{sk} \in \mathcal{SK}$ for which the evaluation algorithm under sk on x agrees with the evaluation algorithm under sk^* on x.

$$\mathcal{X}(\mathsf{sk}) = \left|\left\{x \in \{0,1\}^\lambda : \Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}^y_{\mathsf{VRF}}(\mathsf{sk}, x) = \Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}^*, x)\right\}\right|$$

We say that a secret key is *unfavorable* if the probability of a uniformly random evaluation point differing in the output is at least $1/2$ and let $\mathcal{SK}_{unfav} \subseteq \mathcal{SK}$ be the set of unfavorable keys. Since we sample the evaluation points x uniformly at random from $\{0,1\}^\lambda$ the probability of the key surviving the filtering step is given by the following:

$$\Pr[\mathsf{sk} \in \mathcal{SK}_{cand}(x, y, \pi, \tau)] = \frac{\mathcal{X}(\mathsf{sk})}{2^\lambda}$$

Since the $2s(\lambda)$ evaluation points x are furthermore sampled i.i.d. we can bound the probability the a fixed secret key $\mathsf{sk} \in \mathcal{SK}$ is in the intersection of all $2s(\lambda)$ tuples by the following expression:

$$\Pr\left[\mathsf{sk} \in \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right] = \left(\frac{\mathcal{X}(\mathsf{sk})}{2^\lambda}\right)^{2s(\lambda)}$$

We can bound the expected number of unfavorable secret keys that survive $2s(\lambda)$ rounds of secret key filtering over the randomness of $x_1, \ldots, x_{2s(\lambda)}$ by applying the union bound:

$$\mathbb{E}\left[\left|\mathcal{SK}_{unfav} \cap \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right|\right] \tag{3.33}$$

$$\leq \sum_{\mathsf{sk}_{unvaf}\in\mathcal{SK}_{unfav}} \Pr\left[\mathsf{sk}_{unfav} \in \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right] \tag{3.34}$$

$$\leq \sum_{\mathsf{sk}_{unvaf}\in\mathcal{SK}_{unfav}} \prod_{i\in[2s(\lambda)]} \Pr\left[\mathsf{sk}_{unfav} \in \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right] \tag{3.35}$$

$$\leq \sum_{\mathsf{sk}_{unvaf}\in\mathcal{SK}_{unfav}} \prod_{i\in[2s(\lambda)]} \frac{\mathcal{X}(\mathsf{sk})}{2^\lambda} \tag{3.36}$$

$$\leq \sum_{\mathsf{sk}_{unvaf}\in\mathcal{SK}_{unfav}} \prod_{i\in[2s(\lambda)]} \frac{1}{2} \tag{3.37}$$

$$\leq \frac{2^\lambda}{2^{2s(\lambda)}} \tag{3.38}$$

Which for general polynomials $s(\lambda) > \lambda$ is negligibly small. We can now use a simple Markov bound to show that the probability of a bad key surviving the filtering is negligibly small. Note that the expected number of surviving unfavorable secret keys is by definition non-negative and therefore we have that the probability of all keys filtered is given by the following expression:

add assumption?

$$\Pr\left[\left|\mathcal{SK}_{unfav} \cap \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{card}(x_i, y_i, \pi_i, \tau_i)\right| \geq 1\right] \leq \frac{2^\lambda}{2^{2s(\lambda)}}$$

To bound the final probability simply condition on the event that no bad key survives. Let $\mathcal{E}$ be the event that $|\mathcal{SK}_{unfav} \cap \bigcap_{i\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)| = 0$ and let $\mathcal{F}$ be the event that $\Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}^y_{\mathsf{VRF}}(\mathsf{sk}^*, x^*) = \Pi^{\mathcal{O}_1,\mathcal{O}_2}_{\mathsf{VRF}}.\mathsf{Eval}^y_{\mathsf{VRF}}(\mathsf{sk}, x^*)$. Note that if $\neg\mathcal{E}$ holds we know that only *favorable* keys survive and therefore

the probability of the same image is at least $1/2$.

$$\begin{aligned}
\Pr[\mathcal{F}] &= 1 - \Pr[\neg\mathcal{F} \mid \mathcal{E}]\Pr[\mathcal{E}] - \Pr[\neg\mathcal{F} \mid \neg\mathcal{E}]\Pr[\neg\mathcal{E}] && (3.39)\\
&\geq 1 - \Pr[\neg\mathcal{F} \mid \mathcal{E}] - \Pr[\neg\mathcal{E}] && (3.40)\\
&\geq 1 - \tfrac{1}{2} - \tfrac{2^\lambda}{2^{2s(\lambda)}} && (3.41)\\
&\geq \tfrac{1}{2} - \tfrac{2^\lambda}{2^{2s(\lambda)}} && (3.42)
\end{aligned}$$

Which concludes this proof. □

Now we define the following two languages $\mathcal{L}_{cand}, \mathcal{L}_{size}$ as follows.

$$\mathcal{L}_{cand} := \left\{ \left(\rho, i, b, \{(x_i, y_i, \pi_i, \tau_i)\}_{i\in[2s(\lambda)]}\right) : \mathrm{rk}_\rho\left(\bigcap_{j\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right)_i = b \right\} \tag{3.43}$$

$$\mathcal{L}_{size} := \left\{ \left(m, \{(x_i, y_i, \pi_i, \tau_i)\}_{i\in[2s(\lambda)]}\right) : \left|\bigcap_{j\in[2s(\lambda)]} \mathcal{SK}_{cand}(x_i, y_i, \pi_i, \tau_i)\right| \leq m \right\} \tag{3.44}$$

We show that $\mathcal{L}_{cand}$ and $\mathcal{L}_{size}$ are in PSPACE and can therefore be decided by the PSPACE complete oracle. The adversary will first use binary search over m to recover the size of the candidate set $\mathcal{SK}_{cand}$ and then pass use the language $\mathcal{L}_{cand}$ to recover a uniformly random candidate secret key sk_{cand}. Formally stated in the following two claims.

Claim 3.15 *$\mathcal{L}_{cand} \in$ PSPACE and $\mathcal{L}_{size} \in$ PSPACE.*

To proof Claim 3.15 we need to provide Turing machines $\mathcal{M}_{cand}, \mathcal{M}_{size}$ that decide whether an arbitrary element is member of the language $\mathcal{L}_{cand}$ and $\mathcal{L}_{size}$ respectively such that space used by $\mathcal{M}_{cand}$ and $\mathcal{M}_{size}$ is bounded from above by functions polynomial in their input size. $\mathcal{M}_{cand}$ iterates over the keys in canonical ordering, for every secret key $\mathsf{sk} \in \mathcal{SK}$ iterate over all $i \in [2s(\lambda)]$ and for every i verify whether $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i) = \top$. If that holds for every i then increment a counter. If we would increment the counter but the value of the counter is ρ then check the i'th bit of the candidate is equal to b.

The algorithm $\mathcal{M}_{size}$ requires works similarly. We iterate over all secret keys $\mathsf{sk} \in \mathcal{SK}$ and keep a counter to count the number of secret keys that pass every filter. For every secret key candidate sk we iterate over all $i \in [2s(\lambda)]$ and increment the counter if for all values $\mathsf{EvalSim}_{\mathsf{VRF}}(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i) = \top$. The algorithm only needs space for the counter in $\mathcal{O}(s(\lambda))$ and the execution of $\mathsf{EvalSim}_(\mathsf{sk}, x_i, y_i, \pi_i, \tau_i)$ which is also polynomial. This concludes the proof of Claim 3.15.

We can now describe the distinguisher $\mathcal{D}$ for the pseudorandomness game as follows: $\mathcal{D}$ first samples $2s(\lambda)$ evaluation points x_i uniformly at random from $\{0,1\}^\lambda$, then he uses the evaluation oracle of the pseudorandomness security experiment $\mathcal{O}_{eval}$ to evaluate the points and obtain $(y_1, \pi_1), \ldots, (y_{2s(\lambda)}, \pi_{2s(\lambda)})$. Subsequently he computes the trace of the combiners verification algorithm τ_i on (x_i, y_i, π_i). Using binary search and at most $2s(\lambda)$ many queries to its PSPACE complete oracle it can recover the size of the set of candidate secret keys $\mathcal{SK}_{cand}$ using the language $\mathcal{L}_{size}$. He then samples a uniformly random number $\rho \in [|\mathcal{SK}_{cand}|]$ then then bit-for-bit, again using $2s(\lambda)$ many queries recovers a the ρ'th candidate key in canonical ordering from $\mathcal{SK}_{cand}^{\{(x_i,y_i,\pi_i,\tau_i)\}_{i\in 2s(\lambda)}}$. He then samples a uniformly random challenge $x^* \leftarrow_\$ \{0,1\}$, checking that $x^* \neq x_i$ and returns the secret key candidate sk_{cand} in the state and x^*.

In the second stage then then gets sk_{cand}, x^* and y^*. He simply recomputes $y' \leftarrow \Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}_{cand}, x)$ and returns 0 if $y^* = y'$ and 1 otherwise. We illustrate the distinguisher in Figure 3.2.

Finally, using what we proved before, we show that the distinguisher $\mathcal{D}^{\mathsf{PSPACE},\mathcal{O}_1,\mathcal{O}_2}$ has non-negligible advantage in the pseudorandomness game against $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$. We state this result formally in the final claim.

Claim 3.16 *The advantage of the adversary $(\mathcal{D}_1^{\mathsf{PSPACE},\mathcal{O}_1,\mathcal{O}_2}, \mathcal{D}_2^{\mathsf{PSPACE},\mathcal{O}_1,\mathcal{O}_2})$ in the pseudorandomness game against the combiner $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ is overwhelming, i.e.*

$$\mathbf{Adv}_{\mathsf{VRF}}^{\mathrm{prf}}(\mathcal{A}, \lambda) \geq 1 - 3\varepsilon_{VRF,mix}^{prf}$$

Proof (Claim 3.16) The claim is established by applying the claims proven before. □

lots of arguing to do

While robust $(2;1)$ black-box combiners are generally sufficient to construct robust $(n;1)$ black-box combiners, non-existence of a robust $(2;1)$ black-box combiner only allows one to deduce the impossibility of a robust $(n;\lfloor n/2 \rfloor)$ black-box combiner. This holds since we can easily construct a robust $(2;1)$ black-box combiner from a robust $(n;\lfloor n/2 \rfloor)$ black-box combiner by running the robust $(n;\lfloor n/2 \rfloor)$ black-box combiner and for every query made to the first $\lfloor n/2 \rfloor$ oracle candidates we answer with the first oracle candidate given to $\Pi_{\mathsf{VRF}}{}^{(2;1)}$ and for the upper $n - \lfloor n/2 \rfloor$ candidate we simply query the other oracle. If at least one oracle given to $\Pi_{\mathsf{VRF}}{}^{(2;1)}$ implements a secure VRF, then at least $\lfloor n/2 \rfloor$ candidates correspond to a VRF oracle. We can derive the following corollary.

change title to lemma maybe

Lemma 3.17 (Robust $(n;\lfloor n/2 \rfloor)$ Black-Box VRF Combiner) *There exists no robust $(n;\lfloor n/2 \rfloor)$ black-box combiner in the sense of Definition 2.12 for the VRF primitive defined in Definition 2.9 for all $n \in \mathbb{N}^+$.*

Distinguisher $\mathcal{D}_1^{\mathsf{PSPACE},\mathcal{O}_{eval},\mathcal{O}_1,\mathcal{O}_2}(\mathsf{pk})$

// Obtain $\{(x_i, y_i, \pi_i, \tau_i)\}_{i\in[2s(\lambda)]}$:
$\mathcal{X} \leftarrow \varnothing$
for $i \in [2s(\lambda)]$ **do**
  $x_i \leftarrow_{\$} \{0,1\}^\lambda$
  $\mathcal{X} \leftarrow \mathcal{X} \cup \{x_i\}$
  $(y_i, \pi_i) \leftarrow \mathcal{O}_{eval}(x_i)$
  $\tau_i \leftarrow \mathsf{trace}(\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x_i, y_i, \pi_i))$
// Obtain $|\mathcal{SK}_{cand}|$ using binary search:
$\rho \leftarrow_{\$} [k]$
// Obtain $\mathsf{sk}_{cand} \in \mathcal{SK}_{cand}$:
$\mathsf{sk}_{cand} \leftarrow \varepsilon$
for $i \in [s(\lambda)]$ **do**
  $b \leftarrow \mathsf{PSPACE}((0, \rho, i, \{x_i, y_i, \pi_i, \tau_i\}_{i\in[2s(\lambda)]}) \in \mathcal{L}_{cand})$
  if $b = \top$ **then**
    $\mathsf{sk}_{cand} \leftarrow \mathsf{sk}_{cand} \| 0$
  else if $b = \bot$ **then**
    $\mathsf{sk}_{cand} \leftarrow \mathsf{sk}_{cand} \| 1$
$x^* \leftarrow_{\$} \{0,1\}^\lambda \setminus \mathcal{X}$
return $(\mathsf{sk}_{cand}, x^*)$

Distringuisher $\mathcal{D}_2^{\mathsf{PSPACE},\mathcal{O}_{eval},\mathcal{O}_1,\mathcal{O}_2}(\mathsf{pk}, \mathsf{sk}_{cand}, x^*, y^*)$

$y' \leftarrow \Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}_{cand}, x^*)$
return $y' = y^*$

Figure 3.2: Distinguisher.

Extending this result to an impossibility of robust $(n; n-1)$ seems difficult. We elaborate on the reason why the proof for **??** cannot easily be extended to general robust $(n; n-1)$ black-box VRF-combiners. We still believe that robust $(n; n-1)$ black-box VRF-combiners are not possible and therefore pose the following conjecture. We dedicate a brief paragraph in the appendix to show why the proof for result Theorem 3.19 cannot easily be extended to cover this more general result. Briefly, the issue is that the hidden queries, which we show are candidate-wise jointly irrelevant to the combiner output are not jointly irrelevant over multiple candidates if we increase the number of candidates. This means that we cannot simply exhaust every possible output of the hidden oracle queries and guarantee that for the correct secret key the output is always y.

Conjecture 3.18 *There exists no robust $(n; n-1)$ black-box combiner in the sense of Definition 2.12 for the VRF primitive as defined in Definition 2.9 for all natural numbers $n > 1$.*

Instead of extending the impossibility of robust $(2; 1)$ black-box VRF-combiners to an impossibility of more general robust $(n; n-1)$ black-box VRF-combiners, we show that the impossibility still holds if we lower the requirements on the combiner. Specifically we show that even if we only require the combiner to be weakly pseudorandom or unpredictable and statistically correct, there still exists no robust $(2; 1)$ black-box VRF-combiner.

Theorem 3.19 (Weak Robust $(n; \lfloor n/2 \rfloor)$ Black-Box VRF Combiners) *There exist no robust $(n; \lfloor n/2 \rfloor)$ black-box combiner in the sense of Definition 2.12 that implements a VF in Definition 2.3 that is statistically correct in the sense of Definition 2.4, uniquely provable in the sense of Definition 2.5 and weakly pseudorandom in the sense of Definition 2.7, even if at least $n-1$ candidates implement a secure VRF in the sense of Definition 2.9.*

Intuition. The proof works similar to the proof for Theorem 3.5, we note that the current adversary already has the capability to break the weak pseudorandomness of the combiner. Additionally, even if the combiner is only required to satisfy statistical correctness, we argue that over a random secret key sk and a polynomial number of uniformly random evaluation points x we can still expect the combiner to be correct with high probability. The proof works by additionally conditioning on the probability that the combiner is correct on all evaluations x sampled during the pseudorandomness game.

Proof (Theorem 3.19) Again we fix a robust $(2; 1)$ black-box VRF-combiner Π_{VRF} that is only ε-correct for some $\varepsilon \in \mathsf{negl}(\lambda)$. Let $\mathcal{E}$ be the event that under the true secret key sk^* the combiner is not correct on at least one evaluation point x_i. We now redo the analysis of the adversary in the proof of Theorem 3.5, specifically Claim 3.16. Additionally we now condition on the event $\mathcal{E}$, to obtain the following bound. todo

Finally we want to note that the distinguisher constructed in the proof of Theorem 3.5 can predict the image of any arbitrary pre-image $x \in \{0,1\}^\lambda$. This means that the adversary is strong enough win the weak pseudorandomness and unpredictability security experiment with significant advantage. As a corollary of Theorem 3.5 we get the impossibility of robust $(n; \lfloor n/2 \rfloor)$ black-box combiners for the VUF and WVRF primitive.

Corollary 3.20 (Robust $(n; \lfloor n/2 \rfloor)$ Black-Box VUF-combiner) *There exists no robust $(n; \lfloor n/2 \rfloor)$ black-box combiner in the sense of Definition 2.12 for the VUF primitive as defined in Definition 2.11.*

Corollary 3.21 (Robust $(n; \lfloor n/2 \rfloor)$ Black-Box WVRF-combiner) *There exists no robust $(n; \lfloor n/2 \rfloor)$ black-box combiner in the sense of Definition 2.12 for the WVRF primitive as defined in Definition 2.10.*

3.3 Strong Robust Black-Box Combiners

Having ruled out the possibility of combining VRFs, VUFs, wVRFs even for statistical notions of correctness and unique provability and all oracles pseudorandomness we need to make an even stronger assumption to allow for combiners to exist. We will assume that all candidates satisfy unique provability. This is a strong assumption since unique provability is one of the main properties of VRFs which distinguishes VRFs from PRFs which admit simple robust $(n;1)$ black-box combiner constructions. We note that unique provability is generally required to be perfect for good constructions, meaning that most existing constructions come with rigorous mathematical proofs that assert their unique provability. Examples of this are ECVRF and Lattice VRFs, which are the most famous constructions of VRFs.

change

As previously mentioned, PRFs admit a simple robust $(n;1)$ black-box combiner which simply xors the outputs of all PRF candidates. We show that this construction can be extended to VRFs by simply computing the trace of the evaluation algorithms trace and providing this as a proof. The existence of such combiners is formalized in the following lemma.

Lemma 3.22 (Strong Robust $(n;1)$ Black-Box VRF Combiners) *There exist robust $(n;1)$ black-box combiners in the sense of Definition 2.12 for the VRF primitive Definition 2.9 if we assume that all candidates are uniquely provable and perfectly correct.*

Proof of Lemma 3.22. We show the existence of a robust $(2;1)$ black-box VRF-combiner under the assumption that all candidates are perfectly correct and uniquely provable. A robust $(n;n-1)$ black-box VRF-combiner can be constructed by iteratively applying the construction on the previous combiner and a new candidate instance until all candidates are combined. We provide a construction which is very similar to PRF combiners shown in Section 1.2, the key generation function samples a key pair for both candidates and returns a secret key $\mathsf{sk} = (\mathsf{sk}_1, \mathsf{sk}_2)$ and public key $\mathsf{pk} = (\mathsf{pk}_1, \mathsf{pk}_2)$. The evaluation algorithm computes the image by computing the XOR of the individual outputs $y = y_1 \oplus y_2$ and the proof by collecting all intermediate results $\pi = (y_1, \pi_1, y_2, \pi_2)$. The verification then works by first checking whether both the values y_1, y_2 have been correctly computed with $\mathcal{O}_1.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}_1, x_1, y_1, \pi_1)$ and $\mathcal{O}_2.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}_2, x_2, y_2, \pi_2)$ and then subsequently checks whether $y = y_1 \oplus y_2$. The combiner construction is shown in Figure 3.3.

Claim 3.23 *The combiner in* **??** *is perfectly correct in the sense of Definition 2.4 and uniquely provable in the sense of Definition 2.5 if all candidates are perfectly correct Definition 2.4 and uniquely provable Definition 2.5.*

The proof of this claim follows essentially by definition of the combiner construction and the assumed unique provability and pseudorandomness of

Algorithm $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$

1 : $(\mathsf{sk}_1, \mathsf{pk}_1) \leftarrow_\$ \mathcal{O}_1.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$
2 : $(\mathsf{sk}_2, \mathsf{pk}_2) \leftarrow_\$ \mathcal{O}_2.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$
3 : **return** $((\mathsf{sk}_1, \mathsf{sk}_2), (\mathsf{pk}_1, \mathsf{pk}_2))$

Algorithm $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}, x)$

1 : $(\mathsf{sk}_1, \mathsf{sk}_2) \leftarrow \mathsf{sk}$
2 : $(y_1, \pi_1) \leftarrow \mathcal{O}_1.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}_1, x)$
3 : $(y_2, \pi_2) \leftarrow \mathcal{O}_2.\mathsf{Eval}_{\mathsf{VRF}}(\mathsf{sk}_2, x)$
4 : $y \leftarrow y_1 \oplus y_2$
5 : $\pi \leftarrow (y_1, \pi_1, y_2, \pi_2)$
6 : **return** (y, π)

Algorithm $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}, x, y, \pi)$

1 : $(\mathsf{pk}_1, \mathsf{pk}_2) \leftarrow \mathsf{pk}$
2 : $(y_1, \pi_1, y_2, \pi_2) \leftarrow \pi$
3 : **req** $y = y_1 \oplus y_2$
4 : **req** $\mathcal{O}_1.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}_1, x, y_1, \pi_1) = 1$
5 : **req** $\mathcal{O}_2.\mathsf{Vfy}_{\mathsf{VRF}}(\mathsf{pk}_2, x, y_2, \pi_2) = 1$

Figure 3.3: Combiner for VRFs if all candidate schemes are uniquely provable.

all candidates. We lead the detailed argument in the appendix but believe that its easy to see why the claim holds. We only need to show that the combiner is pseudorandom, we employ a reductionist approach to show the following claim.

Claim 3.24 *The combiner in* **??** *is* (t, ε)*-pseudorandom in the sense of Definition 2.6 if at least one candidates are* (t, ε)*-pseudorandom. In particular if at least one candidate is pseudorandom then the combiner is pseudorandom.*

Assume, towards a contradiction, that there exists an adversary $\mathcal{A}$ running in time t that breaks pseudorandomness of the combiner $\Pi_{\mathsf{VRF}}^{\mathcal{O}_1,\mathcal{O}_2}$ with advantage ε, we show that we can construct an adversary $\mathcal{R}_i$ running in time t_i that wins the prf security experiment of every candidate with advantage ε_i. The reduction $\mathcal{R}_i$ simulates all the remaining candidates queries and uses adversary $\mathcal{A}$ to break that one candidate. We show the reduction $\mathcal{R}_i$ in Figure 3.4.

The reduction works as follows: We

The runtime of the reduction is given by

The advantage of the reduction is given by

describe reduction here

todo

todo

finish the reduction

Reduction $\mathcal{R}_i^{\mathcal{O}^{prf}_{eval,i}}(\mathsf{pk}_i)$

$b \leftarrow_{\$} \{0,1\}$

$(\mathsf{sk}_{1-i}, \mathsf{pk}_{1-i}) \leftarrow_{\$} \mathcal{O}^{prf}_{eval,1-i}.\mathsf{Gen}_{\mathsf{VRF}}(1^\lambda)$

$\mathsf{sk} \leftarrow (\mathsf{sk}_0, \mathsf{sk}_1)$

$\mathsf{pk} \leftarrow (\mathsf{pk}_0, \mathsf{pk}_1)$

Figure 3.4: Reduction.

3.4 Discussion

There are different ways to combine VRFs, for both unique provability and key-homomorphism they cannot be combined in a black-box fashion if we want to preserve properties such as unpredictability and therefore also randomness. On the other hand we manage to construct a robust black-box combiner that combines unbiasabile VRFs under guaranteed unique provability for all candidates. We find that the black-box combination of information theoretic properties generally seems hard if other properties such as unpredictability need to be preserved. While the class of all robust black-box combiners initially seems to be very broad we show that we can capture all polynomially bounded combiners using the notion of a robust black-box DAG combiner, which allows a more systematic analysis of possible constructions by abstracting a graph structure in the computation executed by the implemented algorithms. We have not considered possible combiner constructions for stronger relaxations, such as computational unique provability or correctness with error, this is mainly because the resulting construction only offer weak guarantees that are insufficient for practical applications.

Extensions. We show that there exists no robust $(n; \lfloor n/2 \rfloor)$ black-box combiner for the VRF primitive, naturally we wonder whether an impossibility can be shown for robust $(n; n-1)$ black-box VRF-combiners which eliminates the possibility of combining VRFs if even one candidate is not guaranteed to be secure. We believe this statement to be true. Additionally it would be interesting to study how to strongly combine the notion of unbiasable VRFs, another advanced notion of VRFs introduced in [**?**].

Having shown that general notion of combiners on VRFs even with relaxed requirements on the security properties of the combiner are impossibile and the combiners on VRFs with guaranteed unique provability are easy we want to strengthen the result by considering combiners for VRFs (assuming all candidates are uniquely provable) with advanced additional properties, namely constrainability as in **??**, key-homomorphism as in **??**, aggregability as in **??** and finally unbiasability as in **??**. In the section in the appendix we

extend the combiner in Figure 3.3 to those notions except for unbiasability.

Chapter 4

Conclusion

Bibliography

[GGM86] Oded Goldreich, Shafi Goldwasser, and Silvio Micali. How to construct random functions. *Journal of the ACM*, 33(4):792–807, October 1986.

[MRV99] Silvio Micali, Michael O. Rabin, and Salil P. Vadhan. Verifiable random functions. pages 120–130, 1999.

Appendix

The Difference Lemma

We present the proof of the difference lemma, formally:

Lemma .1 (Difference Lemma) *Let $\mathcal{W}_0, \mathcal{W}_1, \mathcal{E}$ be events with*

$$\Pr[\mathcal{W}_0 \wedge \neg\mathcal{E}] = \Pr[\mathcal{W}_1 \wedge \neg\mathcal{E}]$$

Then we can bound the difference in probability of $\mathcal{W}_0$ and $\mathcal{W}_1$ with

$$|\Pr[\mathcal{W}_0] - \Pr[\mathcal{W}_1]| \leq \Pr[\mathcal{E}]$$

Proof of Lemma .1. Let $\mathcal{W}_0, \mathcal{W}_1, \mathcal{E}$ be events and assume $\Pr[\mathcal{W}_0 \wedge \neg\mathcal{E}] = \Pr[\mathcal{W}_1 \wedge \neg\mathcal{E}]$. Then we can deduce the following:

$$\begin{aligned}
&|\Pr[\mathcal{W}_0] - \Pr[\mathcal{W}_1]| && (.1)\\
=&|\Pr[\mathcal{W}_0 \wedge \mathcal{E}] + \Pr[\mathcal{W}_0 \wedge \neg\mathcal{E}] - \Pr[\mathcal{W}_1 \wedge \mathcal{E}] - \Pr[\mathcal{W}_1 \wedge \neg\mathcal{E}]| && (.2)\\
=&|\Pr[\mathcal{W}_0 \wedge \mathcal{E}] - \Pr[\mathcal{W}_1 \wedge \mathcal{E}]| && (.3)\\
=&|\Pr[\mathcal{W}_0 \mid \mathcal{E}]\Pr[\mathcal{E}] - \Pr[\mathcal{W}_1 \mid \mathcal{E}]\Pr[\mathcal{E}]| && (.4)\\
=&|\Pr[\mathcal{W}_0 \mid \mathcal{E}] - \Pr[\mathcal{W}_1 \mid \mathcal{E}]|\Pr[\mathcal{E}] && (.5)\\
\leq&\Pr[\mathcal{E}] && (.6)
\end{aligned}$$

Conjecture

We quickly want to make a few remarks towards the idea of extending the proof of **??** to the more general case of **??**. The direct proof fails because of the subtle reason that the hidden oracle queries need to be candidate-wide irrelevant but not jointly irrelevant over queries to many distinct candidate schemes. In the proof of **??** we argue that for oracle $\mathcal{O}_2$ all hidden oracle queries, i.e. all oracle queries not contained in the transcript of the combiners verification algorithm are exactly the queries that would influence the combiner output if changes. On the other hand, for any arbitrary assignment of

the hidden queries, the output of the combiner stays constant as long as the non-hidden queries and the queries to $\mathcal{O}_1$ are honestly answered.

This idea gives rise to the attack of iteratively filtering the secret key space on a polynomial number of points by keeping in every round $(1.)$ at least the true secret key, $(2.)$ only secret keys for which the output of the combiner is the same as for the true secret key. We argue that after a sufficient number of filtering steps, any remaining candidate has sufficiently high chance of evaluating to the same output as the combiner does with the true secret key on a uniformly random evaluation point.

However, since the hidden queries must not necessarily be jointly-irrelevant this argument cannot be applied if we have more candidates, of which still $n - 1$ need to be secure for the combiner to be required to implement unique provability and pseudorandomness.

TODO example of axis-constant function

Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Declaration of originality

The signed declaration of originality is a component of every written paper or thesis authored during the course of studies. **In consultation with the supervisor**, one of the following two options must be selected:

☐ I hereby declare that I authored the work in question independently, i.e. that no one helped me to author it. Suggestions from the supervisor regarding language and content are excepted. I used no generative artificial intelligence technologies[1].

☐ I hereby declare that I authored the work in question independently. In doing so I only used the authorised aids, which included suggestions from the supervisor regarding language and content and generative artificial intelligence technologies. The use of the latter and the respective source declarations proceeded in consultation with the supervisor.

Title of paper or thesis:

Authored by:
If the work was compiled in a group, the names of all authors are required.

Last name(s):	**First name(s):**

With my signature I confirm the following:
- I have adhered to the rules set out in the Citation Guidelines.
- I have documented all methods, data and processes truthfully and fully.
- I have mentioned all persons who were significant facilitators of the work.

I am aware that the work may be screened electronically for originality.

Place, date	**Signature(s)**

If the work was compiled in a group, the names of all authors are required. Through their signatures they vouch jointly for the entire content of the written work.

[1] For further information please consult the ETH Zurich websites, e.g. https://ethz.ch/en/the-eth-zurich/education/ai-in-education.html and https://library.ethz.ch/en/researching-and-publishing/scientific-writing-at-eth-zurich.html (subject to change).