


# Dual Timer (PDL\_DT)

## 1.0

## Features

- Programmable 32/16-bit down counter
- Three operating modes
  - Free-Running
  - Periodic
  - One-Shot



## General Description

The Peripheral Driver Library (PDL) Dual Timer (PDL\_DT) component allows you to configure the Dual Timer peripheral block, which contains a pair of programmable 32/16-bit down counters that generate an interrupt when the counter reaches zero.

This component uses a firmware driver from the PDL\_DT module, which is automatically added to your project after a successful build.

## When to Use a PDL\_DT Component

Use this to implement different timeouts, timing delays, system ticks, software timers and other timed activities.

## Quick Start

Follow this quick start steps below to configure and start a Dual Timer.

1. Drag a PDL\_DT component from the Component Catalog FMx/Digital folder onto your schematic. The placed instance takes the name DT\_1.
2. Double-click to open the component's Configure dialog. See Components Parameters.
3. On the **Basic** tab, to meet your timing requirements set the following parameters:
  - timer mode
  - counter size
  - clock prescaler
4. Initialize needed interrupts and their callback functions.

- Build the project to verify the correctness of your design. This will add the required PDL modules to the Workspace Explorer and generate configuration data for the DT\_1 instance.
- In the *main.c* file, initialize the peripheral and start the application.

```
Dt_Init(&DT_1_Chn_Config, DT_1_CHANNELn);
Dt_WriteLoadVal(val, DT_1_CHANNELn);
Dt_EnableCount(DT_1_CHANNELn);
n = 0,1 - timer channel number.
```

- Build and program the device.

## Component Parameters

The PDL\_DT component Configure dialog allows you to edit the configuration parameters for the component instance.

### Timer Tab

This tab contains the component parameters used in the general peripheral initialization settings.

Parameter Name	Description
u8ChnMode	Configures the DT to one of the following modes: <ul style="list-style-type: none"> <li>Free Run: The counter operates continuously and wraps around to its maximum value each time that it reaches zero.</li> <li>Periodic: The counter is reloaded from Load Register and operates continuously each time that it reaches zero.</li> <li>One Shot: Writing to the Load Register (TimerXLoad) loads the counter with a new value. The counter halts until it is reprogrammed when the counter reaches zero.</li> </ul> <i>n</i> - number of the channel to configure.
u8ChnCounterSize	Sets the counter size to 16 or 32 bits, where <i>n</i> – is the number of the channel to configure.
u8ChnPrescalerDiv	Sets the clock prescaler to divide the timer source (PCLK) by 1, 16 or 256, where <i>n</i> – is the number of the channel to configure

### Interrupt Tab

This tab contains the Interrupt configuration settings.

Parameter Name	Description
bChnIrqEnable	Enables Dual Timer interrupt, where <i>n</i> – is the number of the channel to configure.
pfnChnIrqCb	Callback function for Dual Timer interrupt, where <i>n</i> – is the number of the channel to configure. This generates a declaration only. The user is required to provide the callback handler.

Parameter Name	Description
bChnTouchNvic	Updates the NVIC with the timer channel interrupt, where $n$ – is the number of the channel to configure.

## Component Usage

After a successful build, firmware drivers from the PDL\_DT module will be added to your project in the pdl/driver/dt folder. Pass the generated data structures to the associated PDL functions in your application initialization code to configure the peripheral.

## Generated Data

The PDL\_DT component populates the following peripheral initialization data structure(s). The generated code is placed in C source and header files that are named after the instance of the component (e.g. *DT\_1\_config.c*). Each variable is also prefixed with the instance name of the component.

Data Structure Type	Name	Description
stc_dt_channel_config_t	DT_1_Ch $n$ _Config	The configuration structure to initialize the DT, where $n$ – is the number of the channel. This should be passed to Dt_Init().

Once the component is initialized, the application code should use the peripheral functions provided in the referenced PDL files. Refer to the PDL API Reference Manual for the list of provided API functions. To access this document, right-click on the component symbol on the schematic and choose “**Open API Documentation...**” in the drop-down menu.

## Data in RAM

The generated data may be placed in flash memory (const) or RAM. The former is the more memory-efficient choice if you do not wish to modify the configuration data at run-time. Under the Built-In tab of the Configure dialog set the parameter CONST\_CONFIG to make your selection. The default option is to place the data in flash.

## Interrupt Support

If the DT component is specified to trigger interrupts, it will generate the callback function declaration that will be called from the DT ISR. The user is then required to provide the actual callback code. If a null string is provided the struct is populated with zeroes and the callback declaration is not generated. Thus, it is the user’s responsibility to modify the struct in firmware.

The component generates the following function declarations.



Function Callback	Description
DT_1_Ch <i>n</i> _IrqCb	This will be called from the DT ISR, triggered when the counter reaches zero, where <i>n</i> – is the number of the channel intended to call the callback. Note: this generates a declaration only - USER must implement the function.

## Code Examples and Application Notes

There are numerous code examples that include schematics and example code available online at the [Cypress Code Examples web page](#).

Cypress also provides a number of application notes describing how FMx devices can be integrated into your design. You can access the Cypress Application Notes search web page at [www.cypress.com/appnotes](http://www.cypress.com/appnotes).

## Resources

The PDL\_DT component uses the one channel of the Dual Timer peripheral block.

## References

- [FM0+ Family of 32-bit ARM® Cortex®-M0+ Microcontrollers Peripheral Manuals](#)
- [Cypress FM0+ Family of 32-bit ARM® Cortex®-M0+ Microcontrollers](#)

## Component Errata

This section lists known problems with the component.

Cypress ID	Component Version	Problem	Workaround
251737	1.0	The PDL dual timer driver does not configure Channel 1 correctly. This limits the dual timer peripheral usage to Channel 0 only	None. The problem will be corrected in the next PDL release.

## Component Changes

This section lists the major changes in the component from the previous version.

Version	Description of Changes	Reason for Changes / Impact
1.0.a	Minor datasheet edits.	
1.0	Initial Version	

© Cypress Semiconductor Corporation, 2016-2017. This document is the property of Cypress Semiconductor Corporation and its subsidiaries, including Spansion LLC ("Cypress"). This document, including any software or firmware included or referenced in this document ("Software"), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress's patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. Cypress products are not designed, intended, or authorized for use as critical components in systems designed or intended for the operation of weapons, weapons systems, nuclear installations, life-support devices or systems, other medical devices or systems (including resuscitation equipment and surgical implants), pollution control or hazardous substances management, or other uses where the failure of the device or system could cause personal injury, death, or property damage ("Unintended Uses"). A critical component is any component of a device or system whose failure to perform can be reasonably expected to cause the failure of the device or system, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from or related to all Unintended Uses of Cypress products. You shall indemnify and hold Cypress harmless from and against all claims, costs, damages, and other liabilities, including claims for personal injury or death, arising from or related to any Unintended Uses of Cypress products.

Cypress, the Cypress logo, Spansion, the Spansion logo, and combinations thereof, WICED, PSoC, CapSense, EZ-USB, F-RAM, and Traveo are trademarks or registered trademarks of Cypress in the United States and other countries. For a more complete list of Cypress trademarks, visit [cypress.com](http://cypress.com). Other names and brands may be claimed as property of their respective owners.

