LINKWARE™ PC
CABLE TEST MANAGEMENT SOFTWARE

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
001	PASS	TIA Cat 6A Channel	80 ft	5.3 dB (NEXT)	12/13/2022 07:11 PM

Total Length:	80 ft
Number of Reports:	1
Number of Passing Reports:	1
Number of Failing Reports:	0
Number of Warning Reports:	0
Documentation Only:	0

LINKWARE™ PC
CABLE TEST MANAGEMENT SOFTWARE

Cable ID: 001

Test Summary: PASS

Test Limit: TIA Cat 6A Channel
Limits Version: V7.6
Date / Time: 12/13/2022 07:11:59 PM
Operator: RAHILOU DIALLO
Headroom 5.3 dB (NEXT 3,6-4,5)
Cable Type: Cat 6A U/FTP
NVP: 78.0%

Main: Versiv
S/N: 21140824
Software Version: V6.7 Build 1
Calibration Date: 10/20/2021
Adapter: DSX-602 (DSX-PLA004)
S/N: 21330979

Remote: Versiv
S/N: 21140728
Software Version: V6.7 Build 1
Calibration Date: 10/20/2021
Adapter: DSX-602R (DSX-PLA004)
S/N: 21331016

Length (ft), Limit 328	[Pair 3,6]	80
Prop. Delay (ns), Limit 555	[Pair 1,2]	109
Delay Skew (ns), Limit 50	[Pair 1,2]	5
Resistance (ohms)	[Pair 4,5]	3.91
Insertion Loss Margin (dB)	[Pair 3,6]	37.7
Frequency (MHz)	[Pair 3,6]	500.0
Limit (dB)	[Pair 3,6]	49.3

	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
NEXT (dB)	5.3	5.4	5.3	5.4
Freq. (MHz)	499.0	499.0	499.0	499.0
Limit (dB)	26.1	26.1	26.1	26.1
Worst Pair	4,5	4,5	4,5	4,5
PS NEXT (dB)	6.8	7.0	6.8	7.0
Freq. (MHz)	499.0	499.0	499.0	499.0
Limit (dB)	23.3	23.3	23.3	23.3
PASS	MAIN	SR	MAIN	SR
Worst Pair	7,8-4,5	7,8-4,5	7,8-4,5	4,5-7,8
ACR-F (dB)	15.8	15.8	18.7	18.7
Freq. (MHz)	5.0	3.1	499.0	498.0
Limit (dB)	49.3	53.4	9.3	9.3
Worst Pair	4,5	4,5	4,5	7,8
PS ACR-F (dB)	17.3	17.3	21.4	21.5
Freq. (MHz)	2.3	2.0	498.0	498.0
Limit (dB)	53.2	54.2	6.3	6.3
N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
ACR-N (dB)	17.1	17.6	44.0	44.1
Freq. (MHz)	5.0	5.1	499.0	499.0
Limit (dB)	56.9	56.6	-23.1	-23.1
Worst Pair	4,5	4,5	3,6	3,6
PS ACR-N (dB)	17.9	18.4	44.8	45.5
Freq. (MHz)	5.1	5.1	499.0	499.0
Limit (dB)	54.1	54.1	-26.0	-26.0
PASS	MAIN	SR	MAIN	SR
Worst Pair	4,5	4,5	3,6	3,6
RL (dB)	8.2	8.7	9.1	10.7
Freq. (MHz)	154.5	139.0	475.0	475.0
Limit (dB)	10.1	10.6	6.0	6.0

Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
10GBASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	























LinkWare™ PC Version 10.9