

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26052636-PE
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -20 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 32.0 dBm

EIRP : 45.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -25.8 dBm
ODU Output Power : 31.9 dBm
EIRP : 44.9 dBW
Es/No : 13.5 dB
Header Compression : Disabled

Timing correction : -152 us (262127 us)

Frequency correction: -120 Hz

dvb rx show

Satellite (DVB) RX Configuration _____ Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

9.320000 12.055825 DVB-S2 102 0 0.0 E * 0 0

Yes

Satellite (DVB) Receiver Status _____

Rx State : On
DVB State : Forward link up : 1326, T14R Beam Network Frequency Frequency : 12.055787 GHz Symbol Rate : 9.320048 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 16 8PSK-8/9

: On Pilot Frame length : Short DVB S2 Mode : ACM : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 : 12.6 dB SNR Input Power : -27 dBm

IP DVB 172.18.131.61 /32