


# **TERMO DE ACEITE TÉCNICO**

**VSAT** 

Solicitante: VIVO- Projeto Escolas Rurais NOC/Operador: Wallace Teixeira Cliente: Vivo **Empresa** VSAT-ID Link kbps Plataforma EMC Brasil 256K/128K

VIVO-PER-23179538-CE



# dvb tx show

#### Satellite (DVB) TX Configuration

: Enabled Auto start IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm : 47.0 dBW EIRP Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

#### Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -14.8 dBm : 34.1 dBm ODU Output Power EIRP : 47.4 dBW : 11.0 dB Es/No

Header Compression : Disabled

Timing correction : -56 us (249451 us)

Frequency correction: -200 Hz

dvb rx show

## Satellite (DVB) RX Configuration

\_\_\_\_\_

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						

Name Enable \* 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E

Yes

7 7 30.000000 12.050000 DVB-S2 102 0 0.0 E

Yes

### Satellite (DVB) Receiver Status

\_\_\_\_\_

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.050126 GHz

Symbol Rate : 25.333116 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.9 dB

Input Power : -25 dBm

