


TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25078062-PB
 256k/128k
 VSAT





dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -24 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -23.4 dBm
ODU Output Power : 33.5 dBm
EIRP : 46.8 dBW
Es/No : 14.0 dB
Header Compression : Disabled

Timing correction : -156 us (262209 us)

Frequency correction: 90 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

```
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                                   Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
                   : On
Rx State
                   : Forward link up
: 1326, GlobalIP@Telstar-14R
: 12.055966 GHz
: 9.320053 Msps
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
     - receiving : 1 QPSK-1/4
- current max : 16 8PSK-8/9
Pilot
                : On
: Short
Frame length : Shoot DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.5 dB
Input Power : -28 dBm
IP DVB 10.50.1.166/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=1110 ms
64 bytes from 8.8.8.8: time=880 ms
64 bytes from 8.8.8.8: time=1080 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 710/890/1110 ms
```