

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

> VSAT-ID Link kbps **Empresa** Plataforma **EMC** Brasil VIVO-PER-31020788-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable

* 0 0 9.320000 12.055825 DVB-S2 4 Yes 0.000000 0.000000 DVB-S2 2 1 1 No

Satellite (DVB) Receiver Status

: On Rx State

DVB State : Forward link up
Network : 1326, GloballP@Telstar-14R Symbol Rate S2 ModCod : 0.20, GlobalIP@ : 12.056028 GHz : 9.319890 : 9.319889 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On

Frame length : Short DVB S2 Mode : ACM Roll off : 0.20 SNR : 13.7 dB Input Power : -28 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -35 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -19.9 dBm
ODU Output Power : 32.0 dBm

EIRP : 46.3 dBW Es/No : 14.5 dB

Header Compression: Disabled Timing correction: -232 us (262445 us)

Frequency correction: 30 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=830 ms 64 bytes from 8.8.8.8: time=880 ms 64 bytes from 8.8.8.8: time=570 ms 64 bytes from 8.8.8.8: time=620 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 570/710/880 ms