

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Jefferson de Souza Marques

> **Empresa** VSAT-ID Link kbps Plataforma **EMC Brasil** VIVO-PER-3118150-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

: Enabled Auto start

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

: 12.055783 GHz Frequency : 9.320125 Msps Symbol Rate

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 15.0 dB Input Power : -26 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -23.5 dBm

ODU Output Power : 33.6 dBm

EIRP
Es/No
                   : 14.0 dB
Header Compression : Disabled
Timing correction : -104 us (261496 us)
Frequency correction: -370 Hz
IP DVB 10.53.0.121/32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=2210 ms
64 bytes from 8.8.8.8: time=900 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=1510 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 900/1280/2210 ms
```