


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Guilherme Cunha

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-24075523-RN 256k/128k **VSAT**



Satellite (DVB) TX Configuration

: Enabled Auto start : -20 dBm IDU Output Power IDU Max Output Power: 0.0 dBm : 34.0 dBm ODU Output Power EIRP : 47.0 dBW Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State

: On (DVB-RCS2) IDU Output Power : -12.1 dBm ODU Output Power : 33.9 dBm EIRP : 46.9 dBW Es/No : 11.5 dB Header Compression : Disabled

Timing correction : -32 us (251058 us)

Frequency correction: -100 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E

Yes

1 1 30.000000 12.050000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050148 GHz
Symbol Rate : 25.333096 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short

DVB S2 Mode : ACM

DVB S2 Stream type : MPEG-TS

Roll off : 0.20

SNR : 15.5 dB

Input Power : -27 dBm

