


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23084227-CE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm EIRP : 47.0 dBW

```
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
______
State : On (TDMA)

IDU Output Power : -20.9 dBm

ODU Output Power : 33.9 dBm
EIRP
Eb/No
                    : 47.2 dBW
                    : 14.0 dB
Header Compression : Disabled
Timing correction : -85 us (261018 us)
Frequency correction: -310 Hz
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5
dB)
                   : 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055466 GHz

Symbol Rate : 9.319924 Msps
S2 ModCod
   - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Mode
Roll off
                   : 0.25
SNR
                   : 15.1 dB
Input Power : -27 dBm
IP DVB 10.50.0.204/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=830 ms
64 bytes from 8.8.8.8: time=800 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=620 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/680/830 ms
```