

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Jefferson de Souza Marques Cliente: VIVO

> VSAT-ID **Empresa** Link kbps Plataforma **EMC** Brasil VIVO-PER-23142154-CE 256k/128k **VSAT**



Satellite (DVB) RX Configuration

: Enabled

Max Signalling MODCOD: 23 16APSK-9/10 Max Traffic MODCOD : 28 32APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable 9.320000 12.055825 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State

DVB State : Forward link up Network : 1326. T14R Beam : 12.055987 GHz Frequency Symbol Rate : 9.319928 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max: 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.2 dB : -33 dBm Input Power

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled
BUPC status : Disabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode
               : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
State : On (DVB-RCS)
IDU Output Power : -20.1 dBm
Es/No : 14.5 dB
Header Compression: Disabled
Timing correction: -180 us (261081 us)
Frequency correction: -30 Hz
# 64 bytes from 8.8.8.8: time=670 ms
64 bytes from 8.8.8.8: time=630 ms
64 bytes from 8.8.8.8: time=1000 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=650 ms
64 bytes from 8.8.8.8: time=630 ms
64 bytes from 8.8.8.8: time=610 ms
--- ping statistics ---
10 packets transmitted, 10 received, 0.00 percent packet loss
rtt min/avg/max = 610/670/1000 ms
```