


# TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

> Plataforma **Empresa VSAT-ID** Link kbps **EMC** Brasil VIVO-PER-26150794-MG 256/128 **VSAT**



# Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable \* 0 0 9.320000 12.055825 DVB-S2 4

### Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency Symbol Rate : 9.319912 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

Pilot : On : Short Frame length DVB S2 Mode : ACM Roll off : 0.25 : 14.6 dB SNR Input Power : -32 dBm

```
Satellite (DVB) TX Configuration
```

-----

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.9 dBm

EIRP : 47.2 dBW

Default CW Frequency: 14.125500 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

-----

State : On (TDMA)
IDU Output Power : -19.8 dBm
ODU Output Power : 34.0 dBm

EIRP : 47.3 dBW Eb/No : 14.5 dB

Header Compression: Disabled

Timing correction : -103 us (262434 us)

Frequency correction: -330 Hz

## Pinging 10.53.0.48 with 32 bytes of data:

Reply from 10.53.0.48: bytes=32 time=1675ms TTL=61 Reply from 10.53.0.48: bytes=32 time=621ms TTL=61 Reply from 10.53.0.48: bytes=32 time=652ms TTL=61

Reply from 10.53.0.48: bytes=32 time=573ms TTL=61

Ping statistics for 10.53.0.48:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 573ms, Maximum = 1675ms, Average = 880ms

### Pinging 10.29.0.49 with 32 bytes of data:

Reply from 10.29.0.49: bytes=32 time=603ms TTL=61 Reply from 10.29.0.49: bytes=32 time=556ms TTL=61 Reply from 10.29.0.49: bytes=32 time=1201ms TTL=61 Reply from 10.29.0.49: bytes=32 time=547ms TTL=61

Ping statistics for 10.29.0.49:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 547ms, Maximum = 1201ms, Average = 726ms

# ping 8.8.8.8

64 bytes from 8.8.8.8: time=1490 ms 64 bytes from 8.8.8.8: time=1330 ms 64 bytes from 8.8.8.8: time=530 ms 64 bytes from 8.8.8.8: time=620 ms 64 bytes from 8.8.8.8: time=630 ms

#### --- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 530/910/1490 ms