

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23050330-CE256/128VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable

* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GloballP@Telstar-14R

Frequency: 12.055947 GHz Symbol Rate: 9.320021 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short

DVB S2 Mode : ACM
Roll off : 0.25
SNR : 15.3 dB
Input Power : -21 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -22.5 dBm
ODU Output Power : 34.0 dBm

EIRP : 47.3 dBW Es/No : 14.5 dB

Header Compression: Disabled

Timing correction : -127 us (260664 us)

Frequency correction: -360 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=580 ms 64 bytes from 8.8.8.8: time=540 ms 64 bytes from 8.8.8.8: time=550 ms 64 bytes from 8.8.8.8: time=580 ms 64 bytes from 8.8.8.8: time=670 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 540/580/670 ms