

TERMO DE ACEITE TÉCNICO

Solicitante: ATI - Agência de Tecnologia da Informação do Estado do Piauí

NOC/Operadora: Leonardo Martins Silva

Técnico Instalador: Osvaldo Oliveira

Contato: 86 9802-4522

Email: costa-osvaldo@hotmail.com

Responsável/cliente: Cícero Evangelista Dias

Orgão: SEDUC

Unidade:

Data Instalação

09/10/2018

Data Ativação

09/10/2018

Operadora
Global Eagle

VSAT-ID
ATI-PB-0070-OUT

Porta kbps
4024/256

Tipo
Outdoor

Piauí, 09 de Outubro de 2018

1 – Local da Instalação



2 – Configurações do Modem

device show

System Information:

Name : ATI-PB-0070-OUT
Location : Piripiri - PI
Contact :
System Up time : 0 days, 00:02:26
CPU Load : 38%
System time(UTC) : 09 October 2018 12:39:27
Broadcast Message : not set

HW:

Model : SatLink 2000
HW ID : 120033
Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:87:4b
Satellite (DVB) : 00:20:0e:10:87:4b

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -19 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -19.2 dBm
Es/No : 13.0 dB
Header Compression : Disabled
Timing correction : -311 us (249700 us)
Frequency correction: 220 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	25.000000	11.628079	DVB-S2	105	0	0.0 E		Yes	

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, ATI-PI
Frequency : 11.628101 GHz
Symbol Rate : 24.999888 Msps
S2 ModCod
- receiving : 1 QPSK-1/4
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.25
SNR : 13.5 dB
Input Power : -38 dBm
odu show

Antenna

Type ASC/Andrew/Channel Master Type 123 - 1.2m
Antenna controller None
Tx Gain at 14.25 GHz 43.3dB

Transmitter (BUC)

Type Invacom TUL-204 (14.0-14.5 GHz)
Local oscillator 13.050000 GHz
DC supply 24V On

Receiver (LNB)

Type Zinwell ZK-VJ1 (10.70-12.75 GHz)
Local oscillator - LO1 9.750000 GHz
Local oscillator - LO2 10.600000 GHz
Oscillator switching frequency 1-2 11.700000 GHz
LO Switching mode 22kHz
13/18V DC supply 13V

ip show

Interfaces

If	IPAddress	SubnetMask	BroadCastAddr	MTU	Alias	AdminStatus
1	10.225.0.209	255.255.255.252	10.225.0.211	1500	eth0	1
3	172.18.192.141	255.255.255.255	N/A	1500	dvb0	1
4	N/A	N/A	N/A	1500	air0	1

DNS Client Configuration

Primary DNS Server: 209.244.0.3, Secondary DNS Server: 209.244.0.4

Interface Statistics

----- Input ----- Output -----
If UCast NUCast Disc Octets UCast NUCast Disc Octets
1 137 336 223 73760 92 27 1 40310
3 140 0 0 34914 174 0 0 15238

4	0	0	0	0	0	0	0	0	0
IP	Receive	Deliver	Errors	Discards	Forward	Request	NoRoute	Discards	
	577	418	0	0	119	225	16	72	

Interface Directed Routing Table

In If Out If

-----IP LAC Statistics-----


RPF	Src eq dest	RPF HitCount	Src eq dest HitCount	MfcHitCount (-1/drop classified)
Disabled	Enabled	0	0	0

Routing Table

DestMask	RouteMask	NextHop	If	RtType
0.0.0.0	0.0.0.0	0.0.0.0	3	STATIC
10.225.0.208	255.255.255.252	0.0.0.0	1	LOCAL
10.225.62.0	255.255.255.0	10.225.0.210	1	STATIC
172.18.192.141	255.255.255.255	0.0.0.0	3	LOCAL

#

3 – Configurações dos Equipamentos



Configurações de Rede

[Configurações](#)[Interfaces](#)[Roteamento Estático](#)[Roteamento Dinâmico](#)[Configurações IPv6](#)[Controle de Banda](#)[H.A.](#)

Status	Interface	Endereço	Gateway	Tipo	Zona	Ação
	eth0	10.225.0.210/30	-	Física	WAN	
	eth1	10.225.62.1/24	-	Física	LAN	
	eth2	-	-	Física	-	
	eth3	-	-	Física	-	

```
admin >ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.0.210 netmask 255.255.255.252 broadcast 10.225.0.211
    ether 00:90:27:ef:70:5c txqueuelen 10000 (Ethernet)
    RX packets 24990 bytes 15699852 (14.9 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 24819 bytes 14483953 (13.8 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 16 memory 0xfe8e0000-fe900000

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.62.1 netmask 255.255.255.0 broadcast 10.225.62.255
    ether 00:90:27:ef:70:5d txqueuelen 10000 (Ethernet)
    RX packets 27454 bytes 14938702 (14.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 29705 bytes 22286104 (21.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 17 memory 0xfe9e0000-fea00000

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1 (Local Loopback)
    RX packets 38478 bytes 24905582 (23.7 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 38478 bytes 24905582 (23.7 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

admin >
```

4 – Teste de Velocidade

Download/Uploand

