

# TERMO DE ACEITE TÉCNICO

**Solicitante:** VIVO- Projeto Escolas Rurais

**NOC/Operador:** Wallace Teixeira

**Cliente:** Vivo

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-25104527-PB

**Link kbps**  
256K/128K

**Plataforma**  
VSAT



SatLink VSAT

10.29.61.89/wmi/dwp/index\_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

SatLink 2000

16.0.1.57

00:20:0e:10:49:da

00:20:0e:10:49:da

0 days, 00:07:57

17%

VIVO-PER-25104527-PB

Pitimbu - PB

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

Telnet 10.29.61.89

State : On <DVB-RCS2>  
IDU Output Power : -19.9 dBm  
Es/No : 10.5 dB  
Header Compression : Disabled  
Timing correction : -44 us <251466 us>  
Frequency correction: 50 Hz  
#  
Satellite <DVB> TX Configuration  
Auto start : Enabled  
IDU Output Power : -20 dBm  
IDU Max Output Power: 0.0 dBm  
Default CW Frequency: 0.000000 GHz  
RTM mode : UC-Mux  
Header Compression : None  
Satellite <DVB> Transmitter Status  
State : On <DVB-RCS2>  
IDU Output Power : -19.9 dBm  
Es/No : 12.0 dB  
Header Compression : Disabled  
Timing correction : -44 us <251466 us>  
Frequency correction: 50 Hz  
#  
Satellite <DVB> RX Configuration  
Auto start : Enabled  
Max Traffic MODCOD : 23 16APSK-9/10  
RX watchdog : 15 minute  
Idx Pri SynbRate[Mbps] Enable Freq[GHz] Mode PopId SatId Pos SatName  
\* 0 0 25.333333 Yes 12.050000 DVB-S2 102 0 0.0 E  
1 1 30.000000 Yes 12.050000 DVB-S2 102 0 0.0 E  
Satellite <DVB> Receiver Status  
Rx State : On  
DVB State : Forward link up  
Network : 1326, 114R Beam  
Frequency : 12.050028 GHz  
Symbol Rate : 25.333071 Msps  
S2 ModCod :  
- receiving : 21 16APSK-5/6  
- current max : 22 16APSK-8/9  
Pilot : On  
Frame length : Short  
DVB S2 Mode : ACM  
DVB S2 Stream type : MPEG-TS  
Roll off : 0.20  
SNR : 14.6 dB  
Input Power : -31 dBm  
#

SatLink VSAT

10.29.61.89/wmi/dwp/index\_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

SatLink 2000

16.0.1.57

00:20:0e:10:49:da

00:20:0e:10:49:da

0 days, 00:09:53

20%

VIVO-PER-25104527-PB

Pitimbu - PB

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=899ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=607ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=663ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=718ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1149ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=724ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=880ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=899ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1009ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1031ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=706ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=892ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=918ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=619ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=860ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=892ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=918ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=806ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1984ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=758ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=627ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1504ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=796ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=927ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=628ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=667ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1113ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=716ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=769ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=863ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=580ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=648ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=724ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=827ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=901ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=632ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=692ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=778ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=839ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=911ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=628ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=710ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=777ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1277ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=658ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=736ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1177ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1061ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=748ms TTL=44  
Estatísticas do Ping para 8.8.8.8:  
Pacotes: Enviados = 67, Recebidos = 67, Perdidos = 0 (0% de perda).  
Aproximar um número redondo de vezes em milissegundos:  
Mínimo = 580ms, Máximo = 1984ms, Média = 844ms  
Control-C  
C:\Windows\System32\_