

# TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais Cliente: VIVO NOC/Operador: Rogério Momi Frias **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-23096292-CE 256/128 **VSAT** SpeedOf.Me, HTML5 Spee... × ▼ C Q Pesquisar ☆自♥↓♠♥≡ SpeedOf.Me is an HTML5 Internet speed test. No Flash or Java needed! It is the smartest and most accurate online bandwidth test. It works well on iPhone, iPad, Android, Windows 8 and other mobile devices, as well as desktop computers. XWX 0× CUPOM DE Download: 240 kbps **DIRECIONAL** Upload: 30 kbps
Latency: 6617 ms | Max Download: 0.24 | Max Upload: 0.03
11-06-2015 | Test Server: Miami 2
IP: 200.143.6.142 CRIE APÊS COM DESCONTOS - DE ATÉ 370 MIL PRÓPRIO Speed: 0 kbps Time: 19:11:58.254 PARTICIPE WEBSITE 19:11:30 19:12:00 - E X sexta-feira, 6 de novembro de 2015 Sem título - Bloco de notas Download Speed: 240 kl Arquivo Editar Formatar Exibir Ajudi Upload Speed: 30 kbps VIVO-PER-23096292-CE-Boa Viagem-CE D S T Q Q S S 25 26 27 28 29 30 31 1 2 3 4 5 6 7 8 9 10 11 12 13 14 Click 'Share' to share thi 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 1 2 3 4 5 Test Again Share Test Complete. 19:21:20

8

#### Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

ldx Pri SymbRate[Msps] Freq[GHz] Mode Popld Enable \* 0 0 9.320000 12.055825 DVB-S2 4 Yes

## Satellite (DVB) Receiver Status

Rx State : On

DVD Otata . On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency: 12.055863 GHz Symbol Rate: 9.319926 Msps

S2 ModCod

- receiving : 1 QPSK-1/4

- current max : 23 16APSK-9/10

Pilot : On

Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.7 dB
Input Power : -18 dBm

## Satellite (DVB) TX Configuration

-----

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

### Satellite (DVB) Transmitter Status

-----

State : On (TDMA)
IDU Output Power : -17.9 dBm
ODU Output Power : 35.1 dBm

EIRP : 48.4 dBW Eb/No : 14.5 dB

Header Compression: Disabled Timing correction: -188 us (260655 us)

Frequency correction: -60 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=640 ms 64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=630 ms 64 bytes from 8.8.8.8: time=620 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 620/640/660 ms