

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26021684-PE

Link kbps
256/128

Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
* 0	0	9.320000	12.055825	DVB-S2 102	0	0.0	E	

Yes

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.056128 GHz
Symbol Rate : 9.320166 Msp/s
S2 ModCod
- receiving : 15 8PSK-5/6
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.1 dB
Input Power : -23 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -18 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.0 dBm
EIRP : 48.0 dBW
Default CW Frequency: 14.125750 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -17.7 dBm
ODU Output Power : 34.7 dBm
EIRP : 47.7 dBW
Es/No : 13.0 dB
Header Compression : Disabled
Timing correction : -227 us (261395 us)
Frequency correction: -20 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=1400 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=1140 ms
64 bytes from 8.8.8.8: time=840 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 710/960/1400 ms