

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Jefferson de Souza Marques

> **Empresa VSAT-ID** Link kbps **Plataforma EMC Brasil** VIVO-PER-31094048-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 9.320000 12.055825 DVB-S2 4 0.000000 0.000000 DVB-S2 2

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

: 12.055393 GHz Frequency Symbol Rate : 9.319932 Msps

S2 ModCod

QPSK-2/3 - receiving : 6 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.6 dB : -31 d<u>Bm</u> Input Power

```
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
                   : 48.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)
IDU Output Power : -16.0 dBm
ODU Output Power : 34.6 dBm
EIRP
                   : 47.9 dBW
Eb/No
                   : 14.0 dB
Header Compression : Disabled
Timing correction : -196 us (260912 us)
Frequency correction: -260 Hz
IP DVB 10.53.0.196/32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=1550 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=770 ms
64 bytes from 8.8.8.8: time=900 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 770/1000/1550 ms
```