

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-22068872-PI256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm

IDU Max Output Power: 0.0 dBm Default CW Frequency: 14.125850 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.2 dBm
Es/No : 15.5 dB
Header Compression : Disabled

Timing correction : -115 us (253249 us)

Frequency correction: -100 Hz

dvb rx show

Satellite (DVB) RX Configuration ______

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

1 1 12.055825 DVB-S2 4 0 0.0 E 9.320000

Yes

Satellite (DVB) Receiver Status _____

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.059103 GHz

Symbol Rate : 15.000245 Msps

S2 ModCod

- receiving : 20 16APSK-4/5 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 15.3 dB Input Power : -36 dBm



