TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias

Cliente: VIVO

Empresa	VSAT-ID	Link kbps	Plataforma
EMC Brasil	VIVO-PER-31251038-MG	256/128	VSAT

Satellite (DVB) RX Configuration

Auto start   : Enabled
Max Traffic MODCOD   : 23   16APSK-9/10
RX watchdog   : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode   PopId SatId Pos SatName   Name   Enable
* 0 0   9.320000   12.055825 DVB-S2 102   0   0.0 E   Yes

Satellite (DVB) Receiver Status

Rx State   : On
DVB State   : Forward link up
Network   : 1326, GlobalIP@Telstar-14R
Frequency   : 12.055838 GHz
Symbol Rate   : 9.319984 Msps
S2 ModCod
    - receiving   : 14   8PSK-3/4
    - current max : 15   8PSK-5/6
Pilot   : On
Frame length   : Short
DVB S2 Mode   : ACM
DVB S2 Stream type : MPEG-TS
Roll off   : 0.20
SNR   : 12.3 dB
Input Power   : -29 dBm

```
Satellite (DVB) TX Configuration
-------------------------------
Auto start         : Enabled
IDU Output Power    : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power    : 34.7 dBm
EIRP              : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode          : VC-Mux
Header Compression  : None


Satellite (DVB) Transmitter Status
--------------------------------
State            : On  (DVB-RCS)
IDU Output Power    : -18.4 dBm
ODU Output Power    : 34.8 dBm
EIRP              : 48.1 dBW
Es/No            : 13.5 dB
Header Compression  : Disabled
Timing correction    : -199 us (261442 us)
Frequency correction: 250 Hz




 ping 8.8.8.8
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=730 ms

---  ping statistics ---
5 packets transmitted, 5 received,  0.00 percent packet loss
rtt min/avg/max = 710/720/760 ms
```