

## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-31086541-MG 256/128 **VSAT**



## Satellite (DVB) RX Configuration

Auto start : Enabled

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable \* 0 0 9.320000 12.055825 DVB-S2 4

Satellite (DVB) Receiver Status

Rx State

: Forward link up **DVB State** 

Network : 1326, GlobalIP@Telstar-14R

: 12.055768 GHz Frequency Symbol Rate : 9.319972 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 23 16APSK-9/10

Pilot : On : Short Frame length DVB S2 Mode : ACM Roll off : 0.25 SNR : 15.2 dB Input Power : -19 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP
            : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
State : On (TDMA)
IDU Output Power : -19.9 dBm
ODU Output Power : 34.5 dBm
EIRP
             : 47.8 dBW
Eb/No
              : 16.0 dB
Header Compression: Disabled
Timing correction : -250 us (260843 us)
Frequency correction: -150 Hz
Pinging 10.53.0.246 with 32 bytes of data:
Reply from 10.53.0.246: bytes=32 time=2184ms TTL=61
Reply from 10.53.0.246: bytes=32 time=1847ms TTL=61
Reply from 10.53.0.246: bytes=32 time=679ms TTL=61
Reply from 10.53.0.246: bytes=32 time=656ms TTL=61
Ping statistics for 10.53.0.246:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 656ms, Maximum = 2184ms, Average = 1341ms
Pinging 10.29.5.81 with 32 bytes of data:
Reply from 10.29.5.81: bytes=32 time=2682ms TTL=61
Reply from 10.29.5.81: bytes=32 time=2028ms TTL=61
Reply from 10.29.5.81: bytes=32 time=516ms TTL=61
Reply from 10.29.5.81: bytes=32 time=832ms TTL=61
Ping statistics for 10.29.5.81:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 516ms, Maximum = 2682ms, Average = 1514ms
ping 8.8.8.8
64 bytes from 8.8.8.8: time=1330 ms
64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=1170 ms
64 bytes from 8.8.8.8: time=1900 ms
64 bytes from 8.8.8.8: time=1540 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 730/1330/1900 ms
```