



Ciente: VIVO

Plataforma VSAT

```
Rx State           : On
DVB State          : Forward link up
Network            : 1326, GlobalIP@Telstar-14R
Frequency          : 12.056018 GHz
Symbol Rate       : 9.319889 Msps
S2 ModCod
- receiving        : 1  QPSK-1/4
- current max     : 23  16APSK-9/10
Pilot              : On
Frame length       : Short
DVB S2 Mode        : ACM
Roll off           : 0.25
SNR                : 15.3 dB
Input Power        : -24 dBm
```

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -24.1 dBm
ODU Output Power : 33.6 dBm
EIRP : 47.3 dBW
Eb/No : 15.0 dB
Header Compression : Disabled
Timing correction : -154 us (260666 us)
Frequency correction: -350 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=780 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=610 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 580/670/780 ms