

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26113139-PE

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```

Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 32.7 dBm
EIRP                 : 46.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
  
```

Satellite (DVB) Transmitter Status

```

State                : On   (DVB-RCS2)
IDU Output Power     : -19.6 dBm
ODU Output Power     : 32.8 dBm
EIRP                 : 46.1 dBW
Es/No                : 12.5 dB
  
```

Header Compression : Disabled
Timing correction : -78 us (251499 us)
Frequency correction: -80 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	30.000000	12.050000	DVB-S2	4	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050092 GHz
Symbol Rate : 25.332575 Msps
S2 ModCod
- receiving : 7 QPSK-3/4
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.2 dB
Input Power : -32 dBm
#

SatLink VSAT

10.29.64.209/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:58:4a

00:20:0e:10:58:4a

0 days, 00:29:44

21%

VIVO-PER-26113139-PE

OLINDA- PE

104804040203090703780000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=665ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=772ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=687ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=948ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=639ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=701ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=766ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=836ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=907ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=638ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=615ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=746ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=815ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=885ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=570ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=705ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=705ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=859ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=570ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=642ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=730ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=708ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=875ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=500ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=672ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=724ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=815ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=890ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=608ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=665ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=849ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=929ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=676ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=743ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=807ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=894ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=583ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=695ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=767ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=883ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=633ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=714ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=882ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=596ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=600ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 51, Recebidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 570ms, Máximo = 948ms, Média = 731ms
Control-C
^C
C:\Windows\System32>

PT

17:06

09/09/2017