

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26022311-PE
 256/128
 VSAT



# dvb tx show

## Satellite (DVB) TX Configuration

-----

Auto start : Enabled

IDU Output Power : -30 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125850 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -17.6 dBm
ODU Output Power : 35.2 dBm
EIRP : 48.2 dBW
Es/No : 14.0 dB

Header Compression : Disabled
Timing correction : -234 us (261448 us)

Frequency correction: -10 Hz

```
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                          Name
Enable
          9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
           : On
: Forward link up
Rx State
              : 1326, GlobalIP@Telstar-14R
: 12.055980 GHz
: 9 320150
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
   - receiving : 1 QPSK-1/4
- current max : 16 8PSK-8/9
              : On
Pilot
Frame length : Short DVB S2 Mode : ACM
                   : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR
                   : 14.5 dB
                   : -22 dBm
Input Power
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=680 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=990 ms
64 bytes from 8.8.8.8: time=820 ms
64 bytes from 8.8.8.8: time=610 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 680/1020/1610 ms
```

