

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais


NOC/Operador: Wallace Teixeira

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID VIVO-PER35660887-SP

Link kbps 256k/128k
Plataforma VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -16 dBm

IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -16.1 dBm

Es/No : 13.0 dB

Header Compression: Disabled

Timing correction: 14 us (248732 us)

Frequency correction: 0 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

* 0 0 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes 1 1 25.333000 11.592000 DVB-S2 4 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 11.591994 GHz
Symbol Rate : 30.000171 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 21 16APSK-5/6

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 15.4 dB Input Power : -29 dBm

