


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: VIVO

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-22020195-PI 256k/128k **VSAT**



dvb tx show

Satellite (DVB) TX Configuration

: Enabled Auto start IDU Output Power : -21 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm EIRP : 47.0 dBW Default CW Frequency: 0.000000 GHz

: VC-Mux ATM mode Header Compression : None

Satellite (DVB) Transmitter Status

: On (DVB-RCS2) State IDU Output Power : -12.7 dBm : 32.4 dBm ODU Output Power ETRP : 45.7 dBW Es/No : 12.5 dB Header Compression : Disabled

Timing correction : -39 us (248557 us)

Frequency correction: -30 Hz

dvb rx show

Satellite (DVB) RX Configuration ______ : Enabled Auto start

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 0 0.0 E 12.050000 DVB-S2 102 25.333333

Yes

0 0.0 E 7 7 12.050000 DVB-S2 102 30.000000

Yes

Satellite (DVB) Receiver Status -----

Rx State : On

: Forward link up DVB State : 1326, T14R Beam Network : 12.050069 GHz : 25.332629 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 20 16APSK-4/5 - current max : 20 16APSK-4/5

Pilot : On Frame length : Short : ACM DVB S2 Stream type : MPEG-TS : 0.20 Roll off SNR : 14.2 dB : -25 dBm Input Power

