


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31170054-MG
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -18 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.2 dBm
EIRP : 47.5 dBW
Default CW Frequency: 14.162500 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -17.7 dBm

ODU Output Power : 34.0 dBm

EIRP : 47.3 dBW

Eb/No : 14.0 dB

```
Header Compression : Disabled
Timing correction : -141 us (260633 us)
Frequency correction: -390 Hz
# dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
 1 1
                         0.000000 DVB-S2 2
                                                      No
          0.000000
Satellite (DVB) Receiver Status
_____
           : On : Forward link up
Rx State
DVB State
                   : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055850 GHz
Symbol Rate : 9.319835 Msps
S2 ModCod
   - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
rilot : On
Frame length : Sho
DVB S2 Mode : ACM
                   : Short
                   : ACM
Roll off
                   : 0.25
SNR : 14.6 dB Input Power : -28 dBm
IP DVB 10.53.0.245/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=530 ms
64 bytes from 8.8.8.8: time=1150 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 530/750/1150 ms
```