


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

Empresa VSAT-ID VIVO-PER-23167645-CE Link kbps 256/128 VSAT VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Auto Start . Eriableu

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode Popld Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

1 1 0.000000 0.000000 DVB-S2 2 No

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326. GlobalIP@Telstar-14R

Frequency : 12.055507 GHz Symbol Rate : 9.319862 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.8 dB
Input Power : -31 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -20.2 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Eb/No : 15.5 dB
Header Compression : Disabled
Timing correction : -298 us (261027 us)

Frequency correction: -50 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=830 ms 64 bytes from 8.8.8.8: time=960 ms 64 bytes from 8.8.8.8: time=880 ms 64 bytes from 8.8.8.8: time=820 ms 64 bytes from 8.8.8.8: time=940 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 820/880/960 ms