

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-35912906-SP

Link kbps
256k/128k

Plataforma
VSAT



SatLink VSAT

10.47.8.105/wmi/dwp/index_page.dwp

STM SatLink VSAT

Status

- Satellite
- Statistics
- Device
- DHCP
- Eventlog
- Configuration
- Satellite
- IP
- Static NAT
- Lineup
- Device
- Help
- Introduction
- Status
- Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:5e:99
DVB MAC Address	00:20:0e:10:5e:99
System Up Time	0 days, 00:50:44
CPU Load	14%
System Name	VIVO-PER-35912906-SP
System Contact	
System Location	SOCORRO
ODU Serial Number	104804040203090403590000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved

Satellite <DUB> Receiver Status

Rx State : On
DUB State : Forward link up
Network : 1326, T14R Bean
Frequency : 12.059127 GHz
Symbol Rate : 14.999979 Msps
S2 ModCod :
- receiving : ? QPSK-3/4
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DUB S2 Mode : ACM
DUB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.3 dB
Input Power : -19 dBm

Satellite <DUB> TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power : 32.7 dBm
EIRP : 46.0 dBW
Default CW Frequency : 14.092600 GHz
AIM mode : UC-Mux
Header Compression : None

Satellite <DUB> Transmitter Status

State : On (DUB-RCS2)
IDU Output Power : -17.1 dBm
ODU Output Power : 32.5 dBm
EIRP : 45.8 dBW
Es/No : 15.0 dB
Header Compression : Disabled
Timing correction : -452 us (255800 us)
Frequency correction : 40 Hz

PT 19:44 19/05/2017

SatLink VSAT

10.47.8.105/wmi/dwp/index_page.dwp

STM SatLink VSAT

Status

- Satellite
- Statistics
- Device
- DHCP
- Eventlog
- Configuration
- Satellite
- IP
- Static NAT
- Lineup
- Device
- Help
- Introduction
- Status
- Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:5e:99
DVB MAC Address	00:20:0e:10:5e:99
System Up Time	0 days, 00:50:44
CPU Load	14%
System Name	VIVO-PER-35912906-SP
System Contact	
System Location	SOCORRO
ODU Serial Number	104804040203090403590000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved

cmd - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=505ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1754ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=508ms TTL=55

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 66, Recebidos = 65, Perdidos = 1 (1% perda),
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 505ms, Máximo = 2744ms, Média = 1126ms

Control-C
C:\Windows\System32>arp -a

Interface: 192.168.0.100 --- 0xc	Endereço IP	Endereço físico	Tipo
192.168.0.1	08-94-f6-2d-0d-e1	dinâmico	
192.168.0.255	ff-fd-ff-ff-ff-ff	estático	
224.0.0.2	01-00-5e-00-00-02	estático	
224.0.0.251	01-00-5e-00-00-fb	estático	
224.0.0.252	01-00-5e-00-00-fc	estático	
239.255.255.250	01-00-5e-7f-ff-fa	estático	
239.255.255.253	01-00-5e-7f-ff-fd	estático	
255.255.255.255	ff-fd-ff-ff-ff-ff	estático	

Interface: 10.47.8.106 --- 0xd

Endereço IP	Endereço físico	Tipo
10.47.8.105	08-20-0e-10-5e-99	dinâmico
10.47.8.111	ff-fd-ff-ff-ff-ff	estático
224.0.0.2	01-00-5e-00-00-02	estático
224.0.0.22	01-00-5e-00-00-16	estático
224.0.0.251	01-00-5e-00-00-fb	estático
224.0.0.252	01-00-5e-00-00-fc	estático
239.255.255.250	01-00-5e-7f-ff-fa	estático
239.255.255.253	01-00-5e-7f-ff-fd	estático
255.255.255.255	ff-fd-ff-ff-ff-ff	estático

C:\Windows\System32>>vivo-per-35912906-sp_

PT 19:37 19/05/2017