

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Rogerio Momi Frias

> **Empresa** VSAT-ID Link kbps **Plataforma EMC** Brasil VIVO-PER-25029177-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes 1 1 0.000000 0.000000 DVB-S2 2 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.055771 GHz Symbol Rate : 9.319998 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 23 16APSK-9/10

Pilot Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.6 dB Input Power : -26 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
           : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
State : On (TDMA)
IDU Output Power : -20.9 dBm
ODU Output Power : 33.6 dBm
EIRP
           : 46.9 dBW
Eb/No
             : 15.0 dB
Header Compression: Disabled
Timing correction : -266 us (261196 us)
Frequency correction: -100 Hz
Pinging 10.50.0.3 with 32 bytes of data:
Reply from 10.50.0.3: bytes=32 time=1321ms TTL=61
Reply from 10.50.0.3: bytes=32 time=560ms TTL=61
Reply from 10.50.0.3: bytes=32 time=658ms TTL=61
Reply from 10.50.0.3: bytes=32 time=769ms TTL=61
Ping statistics for 10.50.0.3:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 560ms, Maximum = 1321ms, Average = 827ms
Pinging 10.29.6.41 with 32 bytes of data:
Reply from 10.29.6.41: bytes=32 time=884ms TTL=61
Reply from 10.29.6.41: bytes=32 time=633ms TTL=61
Reply from 10.29.6.41: bytes=32 time=552ms TTL=61
Reply from 10.29.6.41: bytes=32 time=650ms TTL=61
Ping statistics for 10.29.6.41:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 552ms, Maximum = 884ms, Average = 679ms
ping 8.8.8.8
64 bytes from 8.8.8.8: time=1490 ms
64 bytes from 8.8.8.8: time=1340 ms
64 bytes from 8.8.8.8: time=790 ms
64 bytes from 8.8.8.8: time=1510 ms
64 bytes from 8.8.8.8: time=700 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 700/1160/1510 ms