


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26081024-PE
 256k/128k
 VSAT



Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 32.7 dBm
EIRP : 46.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -22.7 dBm
ODU Output Power : 32.5 dBm
EIRP : 45.8 dBW
Es/No : 9.5 dB
Header Compression : Disabled

Timing correction : -43 us (251027 us)

Frequency correction: -80 Hz

#

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable * 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E Yes 1 1 15.000000 12.059000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State

: On : Forward link up : 1326, T14R Beam DVB State Network : 12.049820 GHz Frequency : 25.333071 Msps Symbol Rate

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

: On Pilot : Short Frame length DVB S2 Stream type : MPEG-TS Roll off SNR : 15.0 dB Input Power : -22 dBm

