



TERMO DE ACEITE TÉCNICO

Solicitante: ATI - Agência de Tecnologia da Informação do Estado do Piauí

NOC/Operadora: Leonardo Martins Silva

Técnico Instalador: Jean Polini

Contato: 11 97701-2709

Email: jeanpolinitelecom@gmail.com

Responsável/cliente: Francisco de Sousa Santos

Orgão: SEDUC

Unidade: Professor João Alfredo de Carvalho

Data Instalação

27/10/2018

Data Ativação

27/10/2018

Operadora
Global Eagle

VSAT-ID
ATI-ES-0142-IND

Porta kbps
4M/256k

Tipo
Indoor

Piauí, 27 de Outubro de 2018

1 – Local da Instalação



2 – Configurações do Modem

device show

System Information:

Name : ATI-ES-0142-IND
Location : Campo Largo do Piaui - PI
Contact :
System Up time : 0 days, 01:17:04
CPU Load : 38%
System time(UTC) : 27 October 2018 13:00:34
Broadcast Message : not set

HW:

Model : SatLink 2000
HW ID : 120033
Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:88:1d
Satellite (DVB) : 00:20:0e:10:88:1d

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -18 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -18.0 dBm
Es/No : 14.0 dB
Header Compression : Disabled
Timing correction : -340 us (250049 us)
Frequency correction: 190 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	25.000000	11.628079	DVB-S2	105	0	0.0 E		Yes	

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, ATI-PI
Frequency : 11.628147 GHz
Symbol Rate : 25.000104 Msps
S2 ModCod
- receiving : 1 QPSK-1/4
- current max : 21 16APSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.25
SNR : 17.4 dB
Input Power : -26 dBm
odu show

Antenna

Type ASC/Andrew/Channel Master Type 123 - 1.2m
Antenna controller None
Tx Gain at 14.25 GHz 43.3dB

Transmitter (BUC)

Type JRC NJT5017 (14.0-14.5 GHz)
Local oscillator 13.050000 GHz
DC supply 24V On

Receiver (LNB)

Type SatLink 403x (10.70-12.75 GHz)
Local oscillator - LO1 9.750000 GHz
Local oscillator - LO2 10.600000 GHz
Oscillator switching frequency 1-2 11.700000 GHz
LO Switching mode 22kHz
13/18V DC supply 13V

ip show

Interfaces

If	IPAddress	SubnetMask	BroadCastAddr	MTU	Alias	AdminStatus
1	10.225.2.65	255.255.255.252	10.225.2.67	1500	eth0	1
3	172.18.192.217	255.255.255.255	N/A	1500	dvb0	1
4	N/A	N/A	N/A	1500	air0	1

DNS Client Configuration

Primary DNS Server: 209.244.0.3, Secondary DNS Server: 209.244.0.4

Interface Statistics

----- Input ----- Output -----

If	UCast	NUCast	Disc	Octets	UCast	NUCast	Disc	Octets
1	113734	719	392	8243881	229088	49	0	313702909
3	228942	0	0	314116542	16379	0	0	1943641
4	0	0	0	0	0	0	0	0

IP Receive Deliver Errors Discards Forward Request NoRoute Discards
343277 447 0 0 245234 213 293 293

Interface Directed Routing Table

In If	Out If
-------	--------

-----IP LAC Statistics-----

RPF	Src eq dest	RPF HitCount	Src eq dest HitCount	MfcHitCount (-1/drop classified)
Disabled	Enabled	0	0	0

Routing Table

DestMask	RouteMask	NextHop	If	RtType
0.0.0.0	0.0.0.0	0.0.0.0	3	STATIC
10.225.2.64	255.255.255.252	0.0.0.0	1	LOCAL
10.225.154.0	255.255.255.0	10.225.2.66	1	STATIC
172.18.192.217	255.255.255.255	0.0.0.0	3	LOCAL

#

3 – Configurações dos Equipamentos

```
admin >ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.2.66 netmask 255.255.255.252 broadcast 10.225.2.67
    ether 00:90:27:f0:8c:60 txqueuelen 1000 (Ethernet)
    RX packets 1169 bytes 353947 (345.6 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1279 bytes 477039 (465.8 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 16 memory 0xfe8e0000-fe900000

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.154.1 netmask 255.255.255.0 broadcast 10.225.154.255
    ether 00:90:27:f0:8c:61 txqueuelen 1000 (Ethernet)
    RX packets 2131 bytes 555816 (542.7 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1419 bytes 377235 (368.3 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 17 memory 0xfe9e0000-fea00000

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1 (Local Loopback)
    RX packets 727 bytes 59703 (58.3 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 727 bytes 59703 (58.3 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

admin >
```

Configurações de Rede

Configurações Interfaces Roteamento Estático Roteamento Dinâmico Configurações IPv6 Controle de Banda H.A.

Status	Interface	Endereço	Gateway	Tipo	Zona	Ação
	eth0	10.225.2.66/30	-	Física	WAN	
	eth1	10.225.154.1/24	10.225.154.1	Física	LAN	
	eth2	-	-	Física	-	
	eth3	-	-	Física	-	

4 – Teste de Velocidade

Download / Upload

