

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-28001923-SE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 14.125500 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -14.1 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Es/No : 11.0 dB
Header Compression : Disabled

Timing correction : -11 us (249796 us)

Frequency correction: -200 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes 5 5 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes 0 0.0 E 7 12.050000 DVB-S2 102 7 30.000000 Yes 0 0.0 E 9 9 25.333000 11.592000 DVB-S2 102

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 11.592295 GHz
Symbol Rate : 30.000324 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 21 16APSK-5/6

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.9 dB
Input Power : -22 dBm



