


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26078554-PE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -17 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -14.6 dBm

```
ODU Output Power : 34.9 dBm
EIRP : 47.9 dBW Es/No : 13.5 dB
Header Compression : Disabled
Timing correction : -229 us (262189 us)
Frequency correction: -180 Hz
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Auto start
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                                 Name
Enable
          9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
-----
Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.056248 GHz

Symbol Rate : 9.320113 Msps
S2 ModCod
   - receiving : 14 8PSK-3/4
     - current max: 16 8PSK-8/9
Pilot
             : On
Frame length : Short DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                   : 13.3 dB
SNR
Input Power : -27 dBm
IP DVB 10.50.1.227/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=690 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=710 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 610/680/730 ms
```