

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-27216730-AL
 256/128
 VSAT



#

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055977 GHz Symbol Rate : 9.320001 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short

DVB S2 Mode : ACM

Roll off : 0.25

SNR : 15.1 dB

Input Power : -26 dBm

```
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -26 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 14.125900 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -21.5 dBm

ODU Output Power : 32.3 dBm

EIRP
EIRP
                   : 45.6 dBW
Es/No
                   : 15.0 dB
Header Compression : Disabled
Timing correction : -279 us (262109 us)
Frequency correction: -140 Hz
IP DVB 10.50.0.237/32
#ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=1240 ms
64 bytes from 8.8.8.8: time=1670 ms
64 bytes from 8.8.8.8: time=1050 ms
64 bytes from 8.8.8.8: time=1500 ms
64 bytes from 8.8.8.8: time=570 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 570/1200/1670 ms
```