


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: Vivo

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23053658-CE256K/128KVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -15 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 34.0 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -20.7 dBm

ODU Output Power : 35.2 dBm EIRP : 48.2 dBW Es/No : 14.5 dB : 48.2 dBW Header Compression : Disabled

Timing correction : -53 us (249737 us)

Frequency correction: -170 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	<pre>SymbRate[Msps]</pre>	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.050146 GHz

Symbol Rate : 25.332987 Msps

S2 ModCod

- receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 16.2 : 16.2 dB Input Power : -24 dBm

